

Antenna specification

Part Description	Vendor : 点滴 Product Name : pcb antenna-B Part NO : 			Description : Project : E1000WT Version : A1 		
Attachments	☒ Spec ☐ Cpk Report ☐ QC Flow Chart ☒ Packing Content	☒ Drawing ☐ FAI Report ☐ Molding conditions 3C Certificate	☐ Sample ☒ Reliability Report ☒ Material Verification Sheet ☐ Material inspection standard	☒ ROHS Repot ☐ Safety Report		
Vendor	Design:胥万芳 Check:郑翠兰 Approval:彭发辉					
Technology check	Mechanical: ID: DQE/SQE: Hardware: Market:					
Final check	ROHS: Quality plannin					
Approval condition	☐ Approved ☐ Reject ☐ Condition approved Temporary approved					
Approval by	RD Leader(Technology Director)			Quality Director		
Distribute						

Content

1	Content	2
2	Instructions	3
3	Product specifications.....	3
4	Reliability test	4
5	Electrical performance test	5
6.1	Test equipment and environment.....	5
6.2	Antenna Return Loss (RL) and SWR.....	5
6.3	Antenna passive test data.....	6

2 instructions

This report includes several equipment, test environment and test results for the electrical performance of the antenna, as well as structural drawings and inspection reports of the antenna. Below is a picture of the antenna.




Figure 1: Antenna Dimensions

L1	4.73 mm
L2	10.96 mm
L3	1.90 mm
L4	6.14 mm
L5	2.01 mm
W1	0.50 mm
W2	1.00 mm
D1	3.00 mm
D2	0.26 mm

3 Product specifications

Electrical Specifications	
Frequency Range (MHz)	2400-2500
Gain (dBi)	0.8
VSWR	≤3
Input Impedance (Ω)	50
Polarization	Vertical
Maximum input power (W)	2
Input connector type	
Dimensions (mm)	10.5*3
Antenna weight (kg)	
Antenna color	

4 Reliability test

1	SAIT SPRAY TEST	Brine spray test: distilled water according to GB1266-86 standard: single distillationPH6.5~7 Spray volume: 1.4me80cm 7 H compressed air pressure: 1kgf / cm ² Test Relativity: 98 ° Temperature: 45 °~ 47 ° Pressure temperature: 35 ° Test time: 24hr	All characteristic range is 30% of the initial value
2	HEAT TEST	85+2℃ for 96 hours, after keep in normal condition for 30mim the to test.	
3	HUMIDITY TEST	40+2℃ 90-95%RH for 96hours, after keep in normal condition for 30mim the to test.	
4	COLD TEST	-40+2℃ for 96hours, after keep in normal condition for 30mim the to test.	

5 Electrical performance test

5.1 Test equipment and environment

测试设备



SATIMO-24



ETS



模拟人头手



安捷伦8960



安利MT8820C



CMW500



安捷伦E5071C

测试系统

SATIMO—24

ETS

测试环境

温度: $22^{\circ}\text{C} \pm 3^{\circ}\text{C}$

湿度: $50\% \pm 15\%$

有源测试


支持2G/3G/4G


BT/WIFI/GPS

无源测试

400MHZ—6G

5.2 Antenna Return Loss(RL) and SWR





6.3 Antenna passive test data

Test Point ID	Freq. (MHz)	Gain (dBi)	Efficiency (%)
1	2410.0	0.6	34.8%
2	2420.0	0.6	34.2%
3	2430.0	0.7	34.1%
4	2440.0	0.7	33.6%
5	2450.0	0.7	33.5%
6	2460.0	0.8	32.3%
7	2470.0	0.8	32%
8	2480.0	0.8	32.2%
9	2490.0	0.8	31.9%

2D CHART

Freq:2460M Gain(dBi)

