

# FCC RF Exposure

EUT Description: Smart Light Pro Dual

Model No.: SMPDV1

FCC ID: 2A25ESMPDV1

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

Where:

Result =  $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

| Frequency (MHz) | Output power (dBm) | Tune Up Power (dBm) | Max Tune Up power (dBm/mW) | Min test separation distance (mm) | Result | Limit (mW/cm <sup>2</sup> ) | SAR Test Exclusion |
|-----------------|--------------------|---------------------|----------------------------|-----------------------------------|--------|-----------------------------|--------------------|
| 2480            | 1.55               | 1±1(2)              | 1.585                      | 5                                 | 0.499  | 3.0                         | Pass               |

Note:

PK Output power = conducted power.

Conducted power see the test report HK2503201345-E, antenna gain = -12.86dBi

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.499 which is  $\leq 3$ , RF Exposure testing is not required.

Note: Exclusion Thresholds Results =  $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance = 5mm