



## Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V05

Report Template Revision Date: 2021-11-03

# Test Report

**Report No.:** CQASZ20240801801E-01  
**Applicant:** REESTAR INTERNATIONAL LIMITED  
**Address of Applicant:** FLAT/RM 16 18/F SEAPOWERTOWER CONCORDIA PLAZA 1 SCIENCE MUSEUM ROAD TSIM SHA TSUI KL  
**Equipment Under Test (EUT):**  
**Product:** Body Composition Scale  
**Model No.:** ES-CS20M, ES-CS20M-W, ES-32MD, ES-26M, FT-26BB-B, R-A005, FT-24D, FT-26R-B, ES-24M, R-A019, ES-26P3  
**Test Model No.:** ES-CS20M  
**Brand Name:** RENPHO, Fitindex  
**FCC ID:** 2A26P-ESCS20MA2  
**Standards:** 47 CFR Part 15, Subpart C  
KDB558074 D01 15.247 Meas Guidance v05r02  
ANSI C63.10:2013  
**Date of Receipt:** 2024-08-22  
**Date of Test:** 2024-08-22 to 2024-11-06  
**Date of Issue:** 2024-11-06  
**Test Result:** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above.

**Tested By:** Lewis Zhou  
( Lewis Zhou )

**Reviewed By:** Timo Lei  
( Timo Lei )

**Approved By:** Alex  
( Alex Wang )



## 1 Version

### Revision History Of Report

| Report No.           | Version | Description    | Issue Date |
|----------------------|---------|----------------|------------|
| CQASZ20240801801E-01 | Rev.01  | Initial report | 2024-11-06 |

## 2 Test Summary

| Test Item                                                         | Test Requirement                                    | Test method      | Result |
|-------------------------------------------------------------------|-----------------------------------------------------|------------------|--------|
| Antenna Requirement                                               | 47 CFR Part 15, Subpart C Section 15.203/15.247 (c) | ANSI C63.10 2013 | PASS   |
| AC Power Line Conducted Emission                                  | 47 CFR Part 15, Subpart C Section 15.207            | ANSI C63.10 2013 | N/A    |
| Conducted Peak Output Power                                       | 47 CFR Part 15, Subpart C Section 15.247 (b)(3)     | ANSI C63.10 2013 | PASS   |
| 6dB Occupied Bandwidth                                            | 47 CFR Part 15, Subpart C Section 15.247 (a)(2)     | ANSI C63.10 2013 | PASS   |
| Power Spectral Density                                            | 47 CFR Part 15, Subpart C Section 15.247 (e)        | ANSI C63.10 2013 | PASS   |
| Band-edge for RF Conducted Emissions                              | 47 CFR Part 15, Subpart C Section 15.247(d)         | ANSI C63.10 2013 | PASS   |
| RF Conducted Spurious Emissions                                   | 47 CFR Part 15, Subpart C Section 15.247(d)         | ANSI C63.10 2013 | PASS   |
| Radiated Spurious Emissions                                       | 47 CFR Part 15, Subpart C Section 15.205/15.209     | ANSI C63.10 2013 | PASS   |
| Restricted bands around fundamental frequency (Radiated Emission) | 47 CFR Part 15, Subpart C Section 15.205/15.209     | ANSI C63.10 2013 | PASS   |

### 3 Contents

|                                                         | Page      |
|---------------------------------------------------------|-----------|
| <b>1 VERSION .....</b>                                  | <b>2</b>  |
| <b>2 TEST SUMMARY .....</b>                             | <b>3</b>  |
| <b>3 CONTENTS .....</b>                                 | <b>4</b>  |
| <b>4 GENERAL INFORMATION .....</b>                      | <b>5</b>  |
| 4.1 CLIENT INFORMATION .....                            | 5         |
| 4.2 GENERAL DESCRIPTION OF EUT .....                    | 5         |
| 4.3 ADDITIONAL INSTRUCTIONS .....                       | 7         |
| 4.4 TEST ENVIRONMENT .....                              | 8         |
| 4.5 DESCRIPTION OF SUPPORT UNITS .....                  | 8         |
| 4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY .....      | 9         |
| 4.7 TEST LOCATION .....                                 | 10        |
| 4.8 TEST FACILITY .....                                 | 10        |
| 4.9 DEVIATION FROM STANDARDS .....                      | 10        |
| 4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....  | 10        |
| 4.11 EQUIPMENT LIST .....                               | 11        |
| <b>5 TEST RESULTS AND MEASUREMENT DATA .....</b>        | <b>12</b> |
| 5.1 ANTENNA REQUIREMENT .....                           | 12        |
| 5.2 CONDUCTED PEAK OUTPUT POWER .....                   | 13        |
| 5.3 6dB OCCUPY BANDWIDTH .....                          | 17        |
| 5.4 POWER SPECTRAL DENSITY .....                        | 21        |
| 5.5 BAND-EDGE FOR RF CONDUCTED EMISSIONS .....          | 25        |
| 5.6 SPURIOUS RF CONDUCTED EMISSIONS .....               | 28        |
| 5.7 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS ..... | 37        |
| 5.7.1 <i>Spurious Emissions</i> .....                   | 37        |
| <b>6 PHOTOGRAPHS - EUT TEST SETUP .....</b>             | <b>44</b> |
| 6.1 RADIATED SPURIOUS EMISSION .....                    | 44        |
| <b>7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS .....</b> | <b>46</b> |

## 4 General Information

### 4.1 Client Information

|                          |                                                                                                                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Applicant:               | REESTAR INTERNATIONAL LIMITED                                                                                                                                                         |
| Address of Applicant:    | FLAT/RM 16 18/F SEAPOWERTOWER CONCORDIA PLAZA 1 SCIENCE MUSEUM ROAD TSIM SHA TSUI KL                                                                                                  |
| Manufacturer:            | Shenzhen Ruiyi Business Technology Co., Ltd.                                                                                                                                          |
| Address of Manufacturer: | No. 810-C063, 8th Floor, Xiangbin International Financial Centre, No.18, West Free Trade Street, China Special Economic Zone, Qianhai Bay, Shenzhen, Guangdong Province, 518000 China |

### 4.2 General Description of EUT

|                           |                                                                                                                                                              |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:             | Body Composition Scale                                                                                                                                       |
| Model No.:                | ES-CS20M, ES-CS20M-W, ES-32MD, ES-26M, FT-26BB-B, R-A005, FT-24D, FT-26R-B, ES-24M, R-A019, ES-26P3                                                          |
| Test Model No.:           | ES-CS20M                                                                                                                                                     |
| Trade Mark:               | RENPHO, Fitindex                                                                                                                                             |
| Software Version:         | V1.0                                                                                                                                                         |
| Hardware Version:         | V1.0                                                                                                                                                         |
| Operation Frequency:      | 2402MHz~2480MHz                                                                                                                                              |
| Bluetooth Version:        | V5.0                                                                                                                                                         |
| Modulation Type:          | GFSK                                                                                                                                                         |
| Transfer Rate:            | 1Mbps, 2Mbps                                                                                                                                                 |
| Number of Channel:        | 40                                                                                                                                                           |
| Product Type:             | <input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable                                                                                 |
| Test Software of EUT:     | FCC_assist_1.0.2.2                                                                                                                                           |
| Antenna Type:             | PCB antenna                                                                                                                                                  |
| Antenna Gain:             | 0.5 dBi                                                                                                                                                      |
| EUT Power Supply:         | AAA*3 battery                                                                                                                                                |
| Simultaneous Transmission | <input type="checkbox"/> Simultaneous TX is supported and evaluated in this report.<br><input checked="" type="checkbox"/> Simultaneous TX is not supported. |

| Operation Frequency each of channel |           |         |           |         |           |         |           |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                             | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 0                                   | 2402MHz   | 10      | 2422MHz   | 20      | 2442MHz   | 30      | 2462MHz   |
| 1                                   | 2404MHz   | 11      | 2424MHz   | 21      | 2444MHz   | 31      | 2464MHz   |
| 2                                   | 2406MHz   | 12      | 2426MHz   | 22      | 2446MHz   | 32      | 2466MHz   |
| 3                                   | 2408MHz   | 13      | 2428MHz   | 23      | 2448MHz   | 33      | 2468MHz   |
| 4                                   | 2410MHz   | 14      | 2430MHz   | 24      | 2450MHz   | 34      | 2470MHz   |
| 5                                   | 2412MHz   | 15      | 2432MHz   | 25      | 2452MHz   | 35      | 2472MHz   |
| 6                                   | 2414MHz   | 16      | 2434MHz   | 26      | 2454MHz   | 36      | 2474MHz   |
| 7                                   | 2416MHz   | 17      | 2436MHz   | 27      | 2456MHz   | 37      | 2476MHz   |
| 8                                   | 2418MHz   | 18      | 2438MHz   | 28      | 2458MHz   | 38      | 2478MHz   |
| 9                                   | 2420MHz   | 19      | 2440MHz   | 29      | 2460MHz   | 39      | 2480MHz   |

Note:


In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel                    | Frequency |
|----------------------------|-----------|
| The lowest channel (CH0)   | 2402MHz   |
| The middle channel (CH19)  | 2440MHz   |
| The highest channel (CH39) | 2480MHz   |

### 4.3 Additional Instructions

| EUT Test Software Settings:                                                                                                 |                                                                                                                                                                                        |                |
|-----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| Mode:                                                                                                                       | <input checked="" type="checkbox"/> Special software is used.<br><input type="checkbox"/> Through engineering command into the engineering mode.<br>engineering command: *##3646633#** |                |
| EUT Power level:                                                                                                            | Class2 (Power level is built-in set parameters and cannot be changed and selected)                                                                                                     |                |
| Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT. |                                                                                                                                                                                        |                |
| Mode                                                                                                                        | Channel                                                                                                                                                                                | Frequency(MHz) |
| GFSK                                                                                                                        | CH0                                                                                                                                                                                    | 2402           |
|                                                                                                                             | CH19                                                                                                                                                                                   | 2440           |
|                                                                                                                             | CH39                                                                                                                                                                                   | 2480           |

#### Run Software:



The screenshot shows the FCC Assist 1.0.2.2 software interface. It features a '串口设置' (Serial Port Settings) section with dropdowns for '串 口' (COM port), '波特率' (Baud rate: 115200), '数据位' (Data bits: 8), '校验位' (Parity: None), '停止位' (Stop bits: 1), and '流 控' (Flow control: NoFlow). A '打开' (Open) button is below these settings. Below this is a section for 'BR/EDR' and 'BLE' with fields for 'Command\_Type' (EN\_TX\_TEST\_CMD), 'ch\_index' (0 ~ 2402), 'len\_of\_test\_data' (0x0), 'Package\_Payload' (FRRS9), 'PHY' (LE 1M PHY), and 'Modulation\_Index' (standard). A 'Send configuration' button is at the bottom of this section. A large empty text area is on the right, and a '清除日志' (Clear log) button is at the bottom right.

## 4.4 Test Environment

| Operating Environment: |                                                                                                                             |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Temperature:           | 24.5°C                                                                                                                      |
| Humidity:              | 59% RH                                                                                                                      |
| Atmospheric Pressure:  | 1009mbar                                                                                                                    |
| Test Mode:             | Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT. |

## 4.5 Description of Support Units

The EUT has been tested with associated equipment below.

### 1) Support equipment

| Description | Manufacturer | Model No. | Certification | Supplied by |
|-------------|--------------|-----------|---------------|-------------|
| /           | /            | /         | /             | /           |

### 2) Cable

| Cable No. | Description | Manufacturer | Cable Type/Length | Supplied by |
|-----------|-------------|--------------|-------------------|-------------|
| /         | /           | /            | /                 | /           |

## 4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

| No. | Item                               | Uncertainty        |
|-----|------------------------------------|--------------------|
| 1   | Radiated Emission (Below 1GHz)     | 5.12dB             |
| 2   | Radiated Emission (Above 1GHz)     | 4.60dB             |
| 3   | Conducted Disturbance (0.15~30MHz) | 3.34dB             |
| 4   | Radio Frequency                    | $3 \times 10^{-8}$ |
| 5   | Duty cycle                         | 0.6 %              |
| 6   | Occupied Bandwidth                 | 1.1%               |
| 7   | RF conducted power                 | 0.86dB             |
| 8   | RF power density                   | 0.74               |
| 9   | Conducted Spurious emissions       | 0.86dB             |
| 10  | Temperature test                   | 0.8°C              |
| 11  | Humidity test                      | 2.0%               |
| 12  | Supply voltages                    | 0.5 %              |
| 13  | Frequency Error                    | 5.5 Hz             |

## 4.7 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

## 4.8 Test Facility

- **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

## 4.9 Deviation from Standards

None.

## 4.10 Other Information Requested by the Customer

None.

## 4.11 Equipment List


| Test Equipment                                         | Manufacturer | Model No.              | Instrument No. | Calibration Date         | Calibration Due Date     |
|--------------------------------------------------------|--------------|------------------------|----------------|--------------------------|--------------------------|
| EMI Test Receiver                                      | R&S          | ESR7                   | CQA-005        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Spectrum analyzer                                      | R&S          | FSU26                  | CQA-038        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Spectrum analyzer                                      | R&S          | FSU40                  | CQA-075        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Preamplifier                                           | MITEQ        | AFS4-00010300-18-10P-4 | CQA-035        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Preamplifier                                           | MITEQ        | AMF-6D-02001800-29-20P | CQA-036        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Preamplifier                                           | EMCI         | EMC184055SE            | CQA-089        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Loop antenna                                           | Schwarzbeck  | FMZB1516               | CQA-060        | 2023/9/8                 | 2026/9/7                 |
| Bilog Antenna                                          | R&S          | HL562                  | CQA-011        | 2023/11/01               | 2026/10/31               |
| Horn Antenna                                           | R&S          | HF906                  | CQA-012        | 2023/11/01               | 2026/10/31               |
| Horn Antenna                                           | Schwarzbeck  | BBHA 9170              | CQA-088        | 2023/9/7                 | 2026/9/6                 |
| Coaxial Cable (Above 1GHz)                             | CQA          | N/A                    | C007           | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Coaxial Cable (Below 1GHz)                             | CQA          | N/A                    | C013           | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| RF cable(9KHz~40GHz)                                   | CQA          | RF-01                  | CQA-079        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Antenna Connector                                      | CQA          | RFC-01                 | CQA-080        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Power Sensor N1918A Power Analysis Manager Power Panel | KEYSIGHT     | U2021XA                | CQA-30         | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Power meter                                            | Agilent      | N1918A                 | CQA-074        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Power meter                                            | R&S          | NRVD                   | CQA-029        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Power divider                                          | MIDWEST      | PWD-2533-02-SMA-79     | CQA-067        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| EMI Test Receiver                                      | R&S          | ESR7                   | CQA-005        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| LISN                                                   | R&S          | ENV216                 | CQA-003        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| Coaxial cable                                          | CQA          | N/A                    | CQA-C009       | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |
| DC power                                               | KEYSIGHT     | E3631A                 | CQA-028        | 2023/09/08<br>2024/09/02 | 2024/09/07<br>2025/09/01 |

Note:


The temporary antenna connector is soldered on the pcb board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

## 5 Test results and Measurement Data

### 5.1 Antenna Requirement

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Standard requirement:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 47 CFR Part 15C Section 15.203 /247(c)                                              |
| <p>15.203 requirement:<br/> An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement:<br/> The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> |                                                                                     |
| <b>EUT Antenna:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |  |
| <p>The antenna is PCB antenna.</p> <p>The connection/connection type between the antenna to the EUT's antenna port is: permanently attachment</p> <p>This is either permanently attachment or a unique coupling that satisfies the requirement.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                     |


## 5.2 Conducted Peak Output Power

|                   |                                                                                                                                          |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (b)(3)                                                                                                    |
| Test Method:      | ANSI C63.10 2013                                                                                                                         |
| Test Setup:       |  <p>Remark: Offset=Cable loss+ attenuation factor.</p> |
| Limit:            | 30dBm                                                                                                                                    |
| Test Mode:        | Transmitting with GFSK modulation.                                                                                                       |
| Test Results:     | Pass                                                                                                                                     |

### Measurement Data


| GFSK mode (1Mbps) |                         |             |        |
|-------------------|-------------------------|-------------|--------|
| Test channel      | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest            | 1.34                    | 30.00       | Pass   |
| Middle            | 0.21                    | 30.00       | Pass   |
| Highest           | 0.54                    | 30.00       | Pass   |
| GFSK mode (2Mbps) |                         |             |        |
| Test channel      | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest            | 1.51                    | 30.00       | Pass   |
| Middle            | 0.42                    | 30.00       | Pass   |
| Highest           | 0.67                    | 30.00       | Pass   |

BLE\_1M\_Ant1\_2402



Date: 6 NOV.2024 14:11:36

BLE\_1M\_Ant1\_2440




Date: 6 NOV.2024 14:12:19

BLE\_1M\_Ant1\_2480




Date: 6 NOV.2024 14:12:33

### BLE\_2M\_Ant1\_2402




Date: 6 NOV.2024 14:12:52

### BLE\_2M\_Ant1\_2440




Date: 6 NOV.2024 14:13:05

BLE 2M Ant1 2480



Date: 6 NOV.2024 14:13:18


### 5.3 6dB Occupy Bandwidth

|                   |                                                                                                                                          |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (a)(2)                                                                                                    |
| Test Method:      | ANSI C63.10 2013                                                                                                                         |
| Test Setup:       |  <p>Remark: Offset=Cable loss+ attenuation factor.</p> |
| Limit:            | ≥ 500 kHz                                                                                                                                |
| Instruments Used: | Refer to section 4.11 for details.                                                                                                       |
| Test Results:     | Pass                                                                                                                                     |

#### Measurement Data


| GFSK mode (1Mbps) |                            |             |        |
|-------------------|----------------------------|-------------|--------|
| Test channel      | 6dB Occupy Bandwidth (MHz) | Limit (kHz) | Result |
| Lowest            | 0.65                       | ≥500        | Pass   |
| Middle            | 0.65                       | ≥500        | Pass   |
| Highest           | 0.65                       | ≥500        | Pass   |
| GFSK mode (2Mbps) |                            |             |        |
| Test channel      | 6dB Occupy Bandwidth (MHz) | Limit (kHz) | Result |
| Lowest            | 1.14                       | ≥500        | Pass   |
| Middle            | 1.14                       | ≥500        | Pass   |
| Highest           | 1.14                       | ≥500        | Pass   |

BLE\_1M\_Ant1\_2402




Date: 29.AUG.2024 17:58:20

BLE\_1M\_Ant1\_2440




Date: 29.AUG.2024 18:01:20

BLE\_1M\_Ant1\_2480




Date: 29.AUG.2024 18:03:08

### BLE\_2M\_Ant1\_2402




Date: 29.AUG.2024 18:05:55

### BLE\_2M\_Ant1\_2440




Date: 29.AUG.2024 18:18:02

BLE 2M Ant1 2480



Date: 29 AUG 2024 18:19:24


## 5.4 Power Spectral Density


|                   |                                                                                                                                           |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (e)                                                                                                        |
| Test Method:      | ANSI C63.10 2013                                                                                                                          |
| Test Setup:       |  <p>Remark: Offset=Cable loss+ attenuation factor.</p> |
| Limit:            | $\leq 8.00 \text{ dBm/3kHz}$                                                                                                              |
| Test Mode:        | Transmitting with GFSK modulation.                                                                                                        |
| Test Results:     | Pass                                                                                                                                      |

### Measurement Data

| GFSK mode (1Mbps) |                                   |                  |        |
|-------------------|-----------------------------------|------------------|--------|
| Test channel      | Power Spectral Density (dBm/3kHz) | Limit (dBm/3kHz) | Result |
| Lowest            | -20.89                            | $\leq 8.00$      | Pass   |
| Middle            | -20.94                            | $\leq 8.00$      | Pass   |
| Highest           | -20.45                            | $\leq 8.00$      | Pass   |
| GFSK mode (2Mbps) |                                   |                  |        |
| Test channel      | Power Spectral Density (dBm/3kHz) | Limit (dBm/3kHz) | Result |
| Lowest            | -22.8                             | $\leq 8.00$      | Pass   |
| Middle            | -23                               | $\leq 8.00$      | Pass   |
| Highest           | -22.63                            | $\leq 8.00$      | Pass   |


Test plot as follows:






Date: 29.AUG.2024 18:03:28

### BLE\_2M\_Ant1\_2402




Date: 29.AUG.2024 18:06:15

### BLE\_2M\_Ant1\_2440




Date: 29.AUG.2024 18:18:23

BLE 2M Ant1 2480




Date: 29.AUG.2024 18:19:45


## 5.5 Band-edge for RF Conducted Emissions

|                   |                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                      |
| Test Method:      | ANSI C63.10 2013                                                                                                                                                                                                                                                                                                                                                                        |
| Test Setup:       |  <p>Remark: Offset=Cable loss+ attenuation factor.</p>                                                                                                                                                                                                                                                |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test Mode:        | Transmitting with GFSK modulation.                                                                                                                                                                                                                                                                                                                                                      |
| Test Results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                    |

| TestMode | ChName | Freq(MHz) | RefLevel[dBm] | Result[dBm] | Limit[dBm] | Verdict |
|----------|--------|-----------|---------------|-------------|------------|---------|
| BLE_1M   | Low    | 2402      | -5.49         | -43.97      | ≤-25.49    | PASS    |
|          | High   | 2480      | -5.34         | -42.35      | ≤-25.34    | PASS    |
| BLE_2M   | Low    | 2402      | -5.46         | -40.11      | ≤-25.46    | PASS    |
|          | High   | 2480      | -5.52         | -43.11      | ≤-25.52    | PASS    |

Test plot as follows:






Date: 29.AUG.2024 18:06:26

BLE 2M Ant1\_High\_2480





Date: 29.AUG.2024 18:19:55

## 5.6 Spurious RF Conducted Emissions

|                   |                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                      |
| Test Method:      | ANSI C63.10 2013                                                                                                                                                                                                                                                                                                                                                                        |
| Test Setup:       |  <p><i>Remark: Offset=Cable loss+ attenuation factor.</i></p>                                                                                                                                                                                                                                         |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test Mode:        | Transmitting with GFSK modulation.                                                                                                                                                                                                                                                                                                                                                      |
| Test Results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                    |

Test plot as follows:






Date: 29.AUG.2024 18:00:57

BLE\_1M\_Ant1\_2440\_0~Reference




Date: 29.AUG.2024 18:01:49

BLE\_1M\_Ant1\_2440\_30~1000



Date: 29.AUG.2024 18:01:56

BLE\_1M\_Ant1\_2440\_1000~26500




Date: 29.AUG.2024 18:02:18

BLE\_1M\_Ant1\_2480\_0~Reference




Date: 29.AUG.2024 18:05:08

BLE\_1M\_Ant1\_2480\_30~1000




Date: 29.AUG.2024 18:05:14

BLE\_1M\_Ant1\_2480\_1000~26500




Date: 29.AUG.2024 18:05:36

BLE\_2M\_Ant1\_2402\_0~Reference




Date: 29.AUG.2024 18:08:19

BLE\_2M\_Ant1\_2402\_30~1000



Date: 29.AUG.2024 18:08:26

BLE\_2M\_Ant1\_2402\_1000~26500




Date: 29.AUG.2024 18:08:48

BLE\_2M\_Ant1\_2440\_0~Reference




Date: 29.AUG.2024 18:18:31

BLE\_2M\_Ant1\_2440\_30~1000



Date: 29.AUG.2024 18:18:38

BLE\_2M\_Ant1\_2440\_1000~26500




Date: 29.AUG.2024 18:19:00

BLE\_2M\_Ant1\_2480\_0~Reference




Date: 29.AUG.2024 18:21:36

BLE\_2M\_Ant1\_2480\_30~1000



Date: 29.AUG.2024 18:21:42

BLE\_2M\_Ant1\_2480\_1000~26500



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o), The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

## 5.7 Radiated Spurious Emission & Restricted bands

### 5.7.1 Spurious Emissions

|                                                                                                                                                                                                                                                                             |                                                  |                                     |                   |            |                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|-------------------------------------|-------------------|------------|-----------------------------|
| Test Requirement:                                                                                                                                                                                                                                                           | 47 CFR Part 15C Section 15.209 and 15.205        |                                     |                   |            |                             |
| Test Method:                                                                                                                                                                                                                                                                | ANSI C63.10 2013                                 |                                     |                   |            |                             |
| Test Site:                                                                                                                                                                                                                                                                  | Measurement Distance: 3m (Semi-Anechoic Chamber) |                                     |                   |            |                             |
| Receiver Setup:                                                                                                                                                                                                                                                             | Frequency                                        | Detector                            | RBW               | VBW        | Remark                      |
|                                                                                                                                                                                                                                                                             | 0.009MHz-0.090MHz                                | Peak                                | 10kHz             | 30kHz      | Peak                        |
|                                                                                                                                                                                                                                                                             | 0.009MHz-0.090MHz                                | Average                             | 10kHz             | 30kHz      | Average                     |
|                                                                                                                                                                                                                                                                             | 0.090MHz-0.110MHz                                | Quasi-peak                          | 10kHz             | 30kHz      | Quasi-peak                  |
|                                                                                                                                                                                                                                                                             | 0.110MHz-0.490MHz                                | Peak                                | 10kHz             | 30kHz      | Peak                        |
|                                                                                                                                                                                                                                                                             | 0.110MHz-0.490MHz                                | Average                             | 10kHz             | 30kHz      | Average                     |
|                                                                                                                                                                                                                                                                             | 0.490MHz -30MHz                                  | Quasi-peak                          | 10kHz             | 30kHz      | Quasi-peak                  |
|                                                                                                                                                                                                                                                                             | 30MHz-1GHz                                       | Quasi-peak                          | 100 kHz           | 300kHz     | Quasi-peak                  |
|                                                                                                                                                                                                                                                                             | Above 1GHz                                       | Peak                                | 1MHz              | 3MHz       | Peak                        |
|                                                                                                                                                                                                                                                                             |                                                  | Peak                                | 1MHz              | 10Hz       | Average                     |
| Limit:                                                                                                                                                                                                                                                                      | Frequency                                        | Field strength<br>(microvolt/meter) | Limit<br>(dBuV/m) | Remark     | Measurement<br>distance (m) |
|                                                                                                                                                                                                                                                                             | 0.009MHz-0.490MHz                                | 2400/F(kHz)                         | -                 | -          | 300                         |
|                                                                                                                                                                                                                                                                             | 0.490MHz-1.705MHz                                | 24000/F(kHz)                        | -                 | -          | 30                          |
|                                                                                                                                                                                                                                                                             | 1.705MHz-30MHz                                   | 30                                  | -                 | -          | 30                          |
|                                                                                                                                                                                                                                                                             | 30MHz-88MHz                                      | 100                                 | 40.0              | Quasi-peak | 3                           |
|                                                                                                                                                                                                                                                                             | 88MHz-216MHz                                     | 150                                 | 43.5              | Quasi-peak | 3                           |
|                                                                                                                                                                                                                                                                             | 216MHz-960MHz                                    | 200                                 | 46.0              | Quasi-peak | 3                           |
|                                                                                                                                                                                                                                                                             | 960MHz-1GHz                                      | 500                                 | 54.0              | Quasi-peak | 3                           |
|                                                                                                                                                                                                                                                                             | Above 1GHz                                       | 500                                 | 54.0              | Average    | 3                           |
| Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device. |                                                  |                                     |                   |            |                             |

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:


- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.  
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.  
Note: For the radiated emission test above 1GHz:  
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                        | <p>horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz)</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> |
| Exploratory Test Mode: | <p>Transmitting with GFSK modulation.</p> <p>Transmitting mode.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Final Test Mode:       | <p>Through Pre-scan, find the 1Mbps of data type and GFSK modulation is the worst case.</p> <p>For below 1GHz part, through pre-scan, the worst case is the highest channel.</p> <p>Only the worst case is recorded in the report.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Results:          | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

Radiated Emission below 1GHz

30MHz~1GHz, the worst case

Test mode: Transmitting mode Horizontal



|      | Freq    | Read Level | Factor | Level  | Limit Line | Over Limit | Remark | Pol/Phase  |
|------|---------|------------|--------|--------|------------|------------|--------|------------|
|      | MHz     | dBuV       | dB/m   | dBuV/m | dBuV/m     | dB         |        |            |
| 1    | 31.73   | 9.18       | 15.71  | 24.89  | 40.00      | -15.11     | Peak   | HORIZONTAL |
| 2    | 35.62   | 8.89       | 14.84  | 23.73  | 40.00      | -16.27     | Peak   | HORIZONTAL |
| 3    | 101.64  | 10.16      | 11.69  | 21.85  | 43.50      | -21.65     | Peak   | HORIZONTAL |
| 4    | 556.77  | 10.23      | 21.04  | 31.27  | 46.00      | -14.73     | Peak   | HORIZONTAL |
| 5 pp | 878.32  | 8.63       | 26.76  | 35.39  | 46.00      | -10.61     | Peak   | HORIZONTAL |
| 6    | 1000.00 | 9.26       | 27.71  | 36.97  | 54.00      | -17.03     | Peak   | HORIZONTAL |