

RF Exposure Estimation

1. Introduction

Applicant:	Markisol USA Inc
Address:	700 Pinnacle Ct Suite 170 Norcross GEORGIA 30071 USA
Product:	Five-channel transmitter
FCC ID:	2A27U251H
Model No.:	DD251H
Reference RF report #	709502301626-00A

2. B.2 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance. The 1 mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph § 1.1307(b)(3)(ii)(A). The 1 mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

3. RF Exposure Evaluation

Per the test report included herein, for 433.92MHz

According to C63.10 Annex G

$$EIRP = pt \times gt = (E \times d)^2 / 30, \text{ so } pt = (E \times d)^2 / 30 \times gt$$

where

pt is the transmitter output power in watts

gt is the numeric gain of the transmitting antenna (dimensionless)

E is the electric field strength in V/m

d is the measurement distance in meters (m)

transmitter output power for 433.92MHz Function

Field strength (E):	88.03 (dBuV/m) = 0.0252 (V/m)
Measurement distance (D):	3 (m)
Antenna Gain, typical (dBi):	-3
Numerical gain of the transmit antenna (gt):	0.50
Transmitter output power (TP):	0.000380(W)
Transmitter output power (TP):	0.380(mW)

We used the maximum ERP/EIRP to perform RF exposure exemption evaluation.

	Evaluation method	Exempt Limit (mW)	Verdict
☒	Blanket 1 mW Blanket Exemption	1mW	Yes
☐	MPE-based Exemption (ERP)	7mW (ERP)	N/A
☐	SAR-based Exemption (Pth)	3060mW	N/A

So, the device is qualified for SAR test exemption, the exemption report is in lieu of the SAR report.


- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:

Hui Tong



Hui TONG

Jiaxi Xu

Jiaxi XU

Cheng Huali

Cheng Huali

EMC Section Manager

Date: April 17, 2023

EMC Project Engineer

Date: April 17, 2023

EMC Test Engineer

Date: April 17, 2023

-----End of Test Report-----