

Test Report

Report No.: MTI230629016-11E3

Date of issue: 2023-08-25

Applicant: DONGGUAN CITY SITENG ELECTRONICS CO., LTD

Product: Photo Printer

Model(s): DHP511, DHP512, DHP513, DHP514, DHP515, DHP516,
DHP517, DHP518, DHP519, DHP520

FCC ID: 2A288-DHP511

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

The test report is only used for customer scientific research, teaching, internal quality control and other purposes, and is for internal reference only.



Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Table of contents

1	General Description	5
1.1	Description of the EUT	5
1.2	Description of test modes	5
1.3	Environmental Conditions	7
1.4	Description of support units	7
1.5	Measurement uncertainty	7
2	Summary of Test Result	8
3	Test Facilities and accreditations	9
3.1	Test laboratory	9
4	List of test equipment.....	10
5	Evaluation Results (Evaluation).....	11
5.1	Antenna requirement	11
6	Radio Spectrum Matter Test Results (RF)	11
6.1	Conducted Emission at AC power line	11
6.2	Occupied Bandwidth	16
6.3	Maximum Conducted Output Power.....	17
6.4	Power Spectral Density	18
6.5	Emissions in frequency bands.....	19
6.6	Band edge emissions (Radiated)	20
6.7	Emissions in frequency bands (below 1GHz).....	25
6.8	Emissions in frequency bands (above 1GHz)	29
	Photographs of the test setup	36
	Photographs of the EUT.....	37
	Appendix A: DTS Bandwidth	39
	Appendix B: Maximum conducted output power.....	44
	Appendix C: Maximum power spectral density.....	45
	Appendix D: Band edge measurements	50
	Appendix E: Conducted Spurious Emission	53
	Appendix F: Duty Cycle	65

Test Result Certification	
Applicant:	DONGGUAN CITY SITENG ELECTRONICS CO., LTD
Address:	Block A, Jingbo Industrial Park, Buxin Industrial Area, Yan Tian Village, Fenggang Town, Dongguan, Guangdong, China
Manufacturer:	SITENG ELECTRONICS CO.,LTD
Address:	A Building,jingbo Industrial Park,Zhentian West Roat,Buxin Industrial zone,YanTian Village,Fenggang Town,Dongguan City,Guangdong Province,China
Product description	
Product name:	Photo Printer
Trademark:	N/A
Model name:	DHP511
Series Model:	DHP512, DHP513, DHP514, DHP515, DHP516, DHP517, DHP518, DHP519, DHP520
Standards:	47 CFR Part 15.247
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02
Date of Test	
Date of test:	2023-07-13 to 2023-08-10
Test result:	Pass

Test Engineer	:	
		(Maleah Deng)
Reviewed By	:	
		(Leon Chen)
Approved By	:	
		(Tom Xue)

1 General Description

1.1 Description of the EUT

Product name:	Photo Printer
Model name:	DHP511
Series Model:	DHP512,DHP513,DHP514,DHP515,DHP516,DHP517,DHP518,DHP519,DHP520
Model difference:	All the models are the same circuit and module, except the model name.
Electrical rating:	Input: DC 24V 1.6A
Accessories:	Adapter: Model: DSA-38PFE-24FCH240160 Input: AC 100-240V 50/60Hz, 1.0A Output: DC 24V 1.6A
Hardware version:	RevC.1
Software version:	0.0.1_0005
Test sample(s) number:	MTI230629016-11S1001
RF specification	
Operating frequency range:	802.11b/g/n20:2412~2462 MHz 802.11n40:2422~2452 MHz
Modulation type:	IEEE 802.11b: DSSS (DBPSK, DQPSK, CCK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna(s) type:	PCB Antenna
Antenna(s) gain:	-7.13dBi

1.2 Description of test modes

No.	Emission test modes
Mode1	TX-802.11b
Mode2	TX-802.11g
Mode3	TX-802.11n(HT20)
Mode4	TX-802.11n(HT40)

1.2.1 Operation channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

Note: The test software provided by manufacturer is used to control EUT for working in engineering mode, that enables selectable channel, and capable of continuous transmitting mode.

Test Software:

For power setting, refer to below table.

Test Software:		Realtek MP Test	
802.11b		802.11g	
Channel	Power setting	Channel	Power setting
1	Default	1	Default
6	Default	6	Default
11	Default	11	Default
802.11n (HT20)		802.11n (HT40)	
Channel	Power setting	Channel	Power setting
1	Default	3	Default
6	Default	6	Default
11	Default	9	Default

```

-v, --verbose: display the power settings
for every
rate even when every rate in a rate group
has the same power.
wl [pkteng_stop]
stop packet engine; usage: wl pkteng_stop
<tx|rx>
wl [pkteng_stats]
packet engine stats; usage: wl pkteng_stat
s
wl [rdvar]
Read a named variable to the srom
wl [wrvar]
Write a named variable to the srom
NOTE: Must use single quotes around the na
me=value clause:
wl wrvar 'macaddr=11:22:33:44:55:66'
NOTE: Must use hex form for numeric values
:
wl wrvar 'boardnum=0xaaaa'
wl [revinfo]
Get hardware revision information
wl [clmver]
Get version information for CLM data and t
ools
Sending wl command...done
Sending wl command...done
Sending wl command...done
packet engine started
>
  
```

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

Support equipment list			
Description	Model	Serial No.	Manufacturer
/	/	/	/
Support cable list			
Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.1dB
Occupied channel bandwidth	±3 %
RF output power, conducted	±1 dB
Power Spectral Density, conducted	±1 dB
Unwanted Emissions, conducted	±1 dB
Radiated spurious emissions (1GHz~25GHz)	5.3dB
Radiated spurious emissions (9kHz~30MHz)	4.3dB
Radiated spurious emissions (30MHz~1GHz)	4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Antenna requirement	47 CFR Part 15.247	47 CFR 15.203	Pass
2	Conducted Emission at AC power line	47 CFR Part 15.247	47 CFR 15.207(a)	Pass
3	Occupied Bandwidth	47 CFR Part 15.247	47 CFR 15.247(a)(2)	Pass
4	Maximum Conducted Output Power	47 CFR Part 15.247	47 CFR 15.247(b)(3)	Pass
5	Power Spectral Density	47 CFR Part 15.247	47 CFR 15.247(e)	Pass
6	Emissions in frequency bands	47 CFR Part 15.247	47 CFR 15.247(d) 15.209, 15.205	Pass
7	Band edge emissions (Radiated)	47 CFR Part 15.247	47 CFR 15.247(d) 15.209, 15.205	Pass
8	Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d) 15.209, 15.205	Pass
9	Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d) 15.209, 15.205	Pass

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
Conducted Emission at AC power line						
1	EMI Test Receiver	Rohde&schwarz	ESCI3	101368	2023-04-26	2024-04-25
2	Artificial mains network	Schwarzbeck	NSLK 8127	183	2023-05-05	2024-05-04
3	Artificial Mains Network	Schwarzbeck	NSLK 8127	1001	2023-05-06	2024-05-05
Occupied Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in frequency bands						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2023-04-26	2024-04-25
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2023-04-25	2024-04-24
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2023-04-25	2024-04-24
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2023-04-25	2024-04-24
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2023-04-26	2024-04-25
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2023-04-26	2024-04-25
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2023-05-05	2024-05-04
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2023-04-25	2024-04-24
9	DC Power Supply	Agilent	E3632A	MY40027695	2023-05-05	2024-05-04
Band edge emissions (Radiated) Emissions in frequency bands (above 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2023-04-26	2024-04-25
2	Double Ridged Broadband Horn Antenna	schwarabeck	BBHA 9120 D	2278	2023-05-26	2024-05-25
3	Amplifier	Agilent	8449B	3008A01120	2023-05-26	2024-05-25
4	Multi-device Controller	TuoPu	TPMDC	/	2023-05-04	2024-05-03
5	MXA signal analyzer	Agilent	N9020A	MY54440859	2023-05-05	2024-05-04
Emissions in frequency bands (below 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2023-04-26	2024-04-25
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2023-06-11	2025-06-10
3	Amplifier	Hewlett-Packard	8447F	3113A06184	2023-04-26	2024-04-25
4	Multi-device Controller	TuoPu	TPMDC	/	2023-05-04	2024-05-03
5	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2023-06-11	2025-06-10

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Description of the antenna of EUT:	The antenna of the EUT is permanently attached.
Conclusion:	The EUT complies with the requirement of FCC PART 15.203.

6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2013 section 6.2		
Procedure:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

6.1.1 E.U.T. Operation:


Operating Environment:					
Temperature:	22.7 °C	Humidity:	52.9 %	Atmospheric Pressure:	98.8 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				
Note: All modes of operation of the EUT were investigated, and only the worst-case results are reported					

6.1.2 Test Setup Diagram:




6.1.3 Test Data:

Mode1(AC 120/60Hz) / Line: Line / Band: 2.4G / BW: 20




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dB	Over dB	Detector	Comment
1	*	0.1500	40.23	10.29	50.52	66.00	-15.48	QP	
2		0.1500	13.75	10.29	24.04	56.00	-31.96	AVG	
3		0.3660	19.49	10.98	30.47	58.59	-28.12	QP	
4		0.4100	5.95	11.07	17.02	47.65	-30.63	AVG	
5		1.1060	12.49	12.57	25.06	56.00	-30.94	QP	
6		1.1300	-1.85	12.60	10.75	46.00	-35.25	AVG	
7		2.1820	16.43	10.44	26.87	56.00	-29.13	QP	
8		2.2180	1.24	10.44	11.68	46.00	-34.32	AVG	
9		10.7018	8.04	10.34	18.38	50.00	-31.62	AVG	
10		10.7418	19.92	10.34	30.26	60.00	-29.74	QP	
11		27.7900	24.57	10.83	35.40	60.00	-24.60	QP	
12		27.7900	13.47	10.83	24.30	50.00	-25.70	AVG	

Mode1(AC 120/60Hz) / Line: Neutral / Band: 2.4G / BW: 20




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1580	13.09	10.28	23.37	55.57	-32.20	AVG	
2	*	0.1620	39.66	10.28	49.94	65.36	-15.42	QP	
3		0.4100	17.55	11.12	28.67	57.65	-28.98	QP	
4		0.4140	6.32	11.12	17.44	47.57	-30.13	AVG	
5		2.1460	17.01	10.04	27.05	56.00	-28.95	QP	
6		2.2220	2.54	10.06	12.60	46.00	-33.40	AVG	
7		4.4740	2.43	10.26	12.69	46.00	-33.31	AVG	
8		4.5939	18.97	10.27	29.24	56.00	-26.76	QP	
9		11.0580	20.62	10.43	31.05	60.00	-28.95	QP	
10		11.0580	9.95	10.43	20.38	50.00	-29.62	AVG	
11		27.5260	23.72	10.83	34.55	60.00	-25.45	QP	
12		28.0060	13.51	10.84	24.35	50.00	-25.65	AVG	

Mode1(AC 240/60Hz) / Line: Line / Band: 2.4G / BW: 20



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1580	7.59	10.28	17.87	55.57	-37.70	AVG	
2	*	0.1620	34.16	10.28	44.44	65.36	-20.92	QP	
3		0.2779	23.03	10.83	33.86	60.88	-27.02	QP	
4		0.4138	8.32	11.12	19.44	47.57	-28.13	AVG	
5		1.0500	14.25	12.49	26.74	56.00	-29.26	QP	
6		1.5859	1.67	13.35	15.02	46.00	-30.98	AVG	
7		2.1459	20.01	10.04	30.05	56.00	-25.95	QP	
8		2.2219	6.54	10.06	16.60	46.00	-29.40	AVG	
9		4.3859	5.29	10.26	15.55	46.00	-30.45	AVG	
10		4.5937	19.47	10.27	29.74	56.00	-26.26	QP	
11		19.3018	24.42	10.63	35.05	60.00	-24.95	QP	
12		26.8218	16.43	10.82	27.25	50.00	-22.75	AVG	

Mode1(AC 240/60Hz) / Line: Neutral / Band: 2.4G / BW: 20



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	31.73	10.29	42.02	66.00	-23.98	QP	
2		0.1500	5.25	10.29	15.54	56.00	-40.46	AVG	
3		0.2977	23.10	10.84	33.94	60.31	-26.37	QP	
4		0.4100	3.95	11.07	15.02	47.65	-32.63	AVG	
5		0.7419	14.91	11.86	26.77	56.00	-29.23	QP	
6		0.9140	-0.47	12.16	11.69	46.00	-34.31	AVG	
7		2.2058	16.46	10.44	26.90	56.00	-29.10	QP	
8		2.2179	2.24	10.44	12.68	46.00	-33.32	AVG	
9		4.3978	19.26	10.28	29.54	56.00	-26.46	QP	
10		4.5457	3.16	10.28	13.44	46.00	-32.56	AVG	
11		10.6500	6.90	10.34	17.24	50.00	-32.76	AVG	
12		11.5656	17.68	10.37	28.05	60.00	-31.95	QP	


6.2 Occupied Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2013, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	a) Set RBW = 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	30.5 °C	Humidity:	22.2 %	Atmospheric Pressure:	100 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

Please Refer to Appendix for Details.


6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2013, section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013, section 11.9.1 Maximum peak conducted output power

6.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	30.5 °C	Humidity:	22.2 %	Atmospheric Pressure:	100 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				

6.3.2 Test Setup Diagram:



6.3.3 Test Data:

Please Refer to Appendix for Details.


6.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2013, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013, section 11.10, Maximum power spectral density level in the fundamental emission

6.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	30.5 °C	Humidity:	22.2 %	Atmospheric Pressure:	100 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				

6.4.2 Test Setup Diagram:



6.4.3 Test Data:

Please Refer to Appendix for Details.


6.5 Emissions in frequency bands

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2013 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013 Section 11.11.1, Section 11.11.2, Section 11.11.3

6.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	30.5 °C	Humidity:	22.2 %	Atmospheric Pressure:	100 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

Please Refer to Appendix for Details.


6.6 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.		
Test Method:	ANSI C63.10-2013 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.10.5.2		

6.6.1 E.U.T. Operation:

Operating Environment:					
Temperature:	29.7 °C	Humidity:	42.2 %	Atmospheric Pressure:	99 kPa
Test mode:		Mode1, Mode2, Mode3, Mode4			
Note: All modes of operation of the EUT were investigated, and only the worst-case results are reported					
All other emissions are attenuated 20dB below the limit, so does not recorded.					

6.6.2 Test Setup Diagram:



6.6.3 Test Data:

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 1

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	46.41	-8.08	38.33	74.00	-35.67	peak
2		2310.000	35.18	-8.08	27.10	54.00	-26.90	AVG
3		2390.000	56.07	-7.71	48.36	74.00	-25.64	peak
4	*	2390.000	42.42	-7.71	34.71	54.00	-19.29	AVG

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 1

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	44.48	-8.08	36.40	74.00	-37.60	peak
2		2310.000	33.88	-8.08	25.80	54.00	-28.20	AVG
3		2390.000	51.71	-7.71	44.00	74.00	-30.00	peak
4	*	2390.000	38.17	-7.71	30.46	54.00	-23.54	AVG

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	53.81	-7.24	46.57	74.00	-27.43	peak
2	*	2483.500	44.69	-7.24	37.45	54.00	-16.55	AVG
3		2500.000	50.58	-7.17	43.41	74.00	-30.59	peak
4		2500.000	39.73	-7.17	32.56	54.00	-21.44	AVG

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	50.34	-7.24	43.10	74.00	-30.90	peak
2	*	2483.500	40.67	-7.24	33.43	54.00	-20.57	AVG
3		2500.000	49.48	-7.17	42.31	74.00	-31.69	peak
4		2500.000	38.25	-7.17	31.08	54.00	-22.92	AVG


6.7 Emissions in frequency bands (below 1GHz)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.			
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.7.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	55 %	Atmospheric Pressure:	101 kPa
Test mode:	Mode1, Mode2, Mode3, Mode4				
Note: The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported. There were no emissions found below 30MHz within 20dB of the limit.					


6.7.2 Test Setup Diagram:






6.7.3 Test Data:

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 11



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		59.4405	34.29	-6.77	27.52	40.00	-12.48	QP	
2		90.2205	45.29	-9.44	35.85	43.50	-7.65	QP	
3	*	113.7143	45.93	-9.29	36.64	43.50	-6.86	QP	
4		216.0240	35.86	-6.62	29.24	46.00	-16.76	QP	
5		455.9058	40.29	-5.55	34.74	46.00	-11.26	QP	
6		597.2234	36.74	-2.16	34.58	46.00	-11.42	QP	

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 11



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		44.2752	35.18	-6.39	28.79	40.00	-11.21	QP	
2		59.6493	38.85	-6.76	32.09	40.00	-7.91	QP	
3		91.8163	43.31	-9.08	34.23	43.50	-9.27	QP	
4		103.4421	37.97	-7.77	30.20	43.50	-13.30	QP	
5		279.0436	43.56	-7.39	36.17	46.00	-9.83	QP	
6	*	497.6765	41.56	-2.68	38.88	46.00	-7.12	QP	


6.8 Emissions in frequency bands (above 1GHz)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.			
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.8.1 E.U.T. Operation:

Operating Environment:						
Temperature:	25 °C		Humidity:	57 %	Atmospheric Pressure:	101 kPa
Test mode:		Mode1, Mode2, Mode3, Mode4				
Note: Test frequency are from 1GHz to 25GHz, the amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported.						

6.8.2 Test Setup Diagram:



6.8.3 Test Data:

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 1

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4824.000	45.71	0.82	46.53	74.00	-27.47	peak
2		4824.000	39.44	0.82	40.26	54.00	-13.74	AVG
3		7236.000	40.69	6.00	46.69	74.00	-27.31	peak
4		7236.000	34.33	6.00	40.33	54.00	-13.67	AVG
5		9648.000	40.81	6.17	46.98	74.00	-27.02	peak
6	*	9648.000	34.32	6.17	40.49	54.00	-13.51	AVG

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 1

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4824.000	42.03	0.82	42.85	74.00	-31.15	peak
2		4824.000	35.60	0.82	36.42	54.00	-17.58	AVG
3		7236.000	39.43	6.00	45.43	74.00	-28.57	peak
4		7236.000	33.22	6.00	39.22	54.00	-14.78	AVG
5		9648.000	41.37	6.17	47.54	74.00	-26.46	peak
6	*	9648.000	35.12	6.17	41.29	54.00	-12.71	AVG

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 6

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4874.000	46.36	1.01	47.37	74.00	-26.63	peak
2	*	4874.000	40.25	1.01	41.26	54.00	-12.74	AVG
3		7311.000	40.00	5.94	45.94	74.00	-28.06	peak
4		7311.000	33.39	5.94	39.33	54.00	-14.67	AVG
5		9748.000	40.60	6.54	47.14	74.00	-26.86	peak
6		9748.000	34.56	6.54	41.10	54.00	-12.90	AVG

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 6

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4874.000	42.54	1.01	43.55	74.00	-30.45	peak
2		4874.000	36.28	1.01	37.29	54.00	-16.71	AVG
3		7311.000	40.11	5.94	46.05	74.00	-27.95	peak
4		7311.000	34.16	5.94	40.10	54.00	-13.90	AVG
5		9748.000	40.69	6.54	47.23	74.00	-26.77	peak
6	*	9748.000	34.61	6.54	41.15	54.00	-12.85	AVG

Mode1 / Polarization: Horizontal / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4924.000	46.57	1.27	47.84	74.00	-26.16	peak
2	*	4924.000	40.11	1.27	41.38	54.00	-12.62	AVG
3		7386.000	40.95	5.86	46.81	74.00	-27.19	peak
4		7386.000	34.47	5.86	40.33	54.00	-13.67	AVG
5		9848.000	41.35	6.31	47.66	74.00	-26.34	peak
6		9848.000	34.97	6.31	41.28	54.00	-12.72	AVG

Mode1 / Polarization: Vertical / Band: 2.4G / BW: 20 / CH: 11

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4924.000	42.31	1.27	43.58	74.00	-30.42	peak
2		4924.000	35.95	1.27	37.22	54.00	-16.78	AVG
3		7386.000	40.62	5.86	46.48	74.00	-27.52	peak
4		7386.000	34.37	5.86	40.23	54.00	-13.77	AVG
5		9848.000	41.12	6.31	47.43	74.00	-26.57	peak
6	*	9848.000	35.05	6.31	41.36	54.00	-12.64	AVG

Photographs of the test setup

Refer to Appendix - Test Setup Photos

Photographs of the EUT

Refer to Appendix - EUT Photos

Appendix

Appendix A: DTS Bandwidth

Test Result

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	8.040	0.5	PASS
		2437	8.080	0.5	PASS
		2462	8.520	0.5	PASS
11G	Ant1	2412	15.440	0.5	PASS
		2437	15.720	0.5	PASS
		2462	15.640	0.5	PASS
11N20SISO	Ant1	2412	15.160	0.5	PASS
		2437	15.080	0.5	PASS
		2462	15.880	0.5	PASS
11N40SISO	Ant1	2422	35.280	0.5	PASS
		2437	35.280	0.5	PASS
		2452	35.200	0.5	PASS

Test Graphs



11G Ant1 2412




11G Ant1 2437




11G Ant1 2462




11N20SISO Ant1 2412




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437



11N40SISO_Ant1_2452



Appendix B: Maximum conducted output power

Test Result Peak


Test Mode	Antenna	Frequency [MHz]	Peak Power [dBm]	Conducted Limit [dBm]	Verdict
11B	Ant1	2412	16.28	≤30.00	PASS
		2437	15.80	≤30.00	PASS
		2462	16.08	≤30.00	PASS
11G	Ant1	2412	21.79	≤30.00	PASS
		2437	20.86	≤30.00	PASS
		2462	21.29	≤30.00	PASS
11N20SISO	Ant1	2412	20.05	≤30.00	PASS
		2437	19.26	≤30.00	PASS
		2462	19.62	≤30.00	PASS
11N40SISO	Ant1	2422	20.02	≤30.00	PASS
		2437	19.75	≤30.00	PASS
		2452	19.31	≤30.00	PASS

Appendix C: Maximum power spectral density


Test Result

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3-100kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-7.54	≤8.00	PASS
		2437	-8.5	≤8.00	PASS
		2462	-8.31	≤8.00	PASS
11G	Ant1	2412	-8.2	≤8.00	PASS
		2437	-8.98	≤8.00	PASS
		2462	-8.77	≤8.00	PASS
11N20SISO	Ant1	2412	-10.25	≤8.00	PASS
		2437	-9.22	≤8.00	PASS
		2462	-9.3	≤8.00	PASS
11N40SISO	Ant1	2422	-13.82	≤8.00	PASS
		2437	-14.18	≤8.00	PASS
		2452	-13.89	≤8.00	PASS


Test Graphs




11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437




11N40SISO_Ant1_2452




Appendix D: Band edge measurements

11B Ant1 Low 2412



11B Ant1 High 2462



11G Ant1 Low 2412

