



FCC 47 CFR PART 15 SUBPART C
CERTIFICATION TEST REPORT

For

Round Sublimated Wireless Charger

MODEL NUMBER: #GY68

FCC ID: 2A28GGY68

REPORT NUMBER: 4790090016.1-1

ISSUE DATE: September 16, 2021

Prepared for

PlanetArt, LLC
23801 Calabasas Road | Calabasas, California 91302

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	09/16/2021	Initial Issue	



Summary of Test Results		
Description of Test Item	Standard	Results
Power Line Conducted Emission Test	FCC 15.207	PASS
Radiated Emission Test	FCC 15.209	PASS
20dB Bandwidth	FCC 15.215	PASS
This test report is only published to and used by the applicant, and it is not for evidence purpose in China.		



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY.....	5
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY</i>	<i>7</i>
5. EQUIPMENT UNDER TEST	8
5.1. <i>DESCRIPTION OF EUT</i>	<i>8</i>
5.2. <i>TEST MODE.....</i>	<i>8</i>
5.3. <i>ACCESSORY</i>	<i>9</i>
5.4. <i>MEASURING INSTRUMENT LIST.....</i>	<i>10</i>
6. 20dB BANDWIDTH TEST	11
7. RADIATED EMISSION TEST	14
7.1. <i>SPURIOUS EMISSIONS BELOW 30 MHz.....</i>	<i>18</i>
7.2. <i>SPURIOUS EMISSIONS 30 MHz ~ 1 GHz</i>	<i>21</i>
8. AC POWER LINE CONDUCTED EMISSIONS	23



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: PlanetArt, LLC
Address: 23801 Calabasas Road | Calabasas, California 91302

Manufacturer Information

Company Name: Shenzhen Yuncheng Technology Co.,Ltd
Address: 6 / F, Building C, Jinxiongda Science park, South Huanguan Road, Guanhu Street, Longhua District, Shenzhen

EUT Information

EUT Name: Round Sublimated Wireless Charger
Model: #GY68
Brand: /
Sample Received Date: September 06, 2021
Sample Status: Normal
Sample ID: 4203959
Date of Tested: September 08, 2021 ~ September 15, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Gary Zhang
Project Engineer

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

All tests were performed in accordance with the standard FCC CFR 47 Part 2, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 15, ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction Emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
DTS and 99% Occupied Bandwidth	±0.0196%
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Round Sublimated Wireless Charger	
Model	#GY68	
Product Description	Operation Frequency	110 ~ 205 kHz
Rated Output Power	15 W	
Antenna type	Coil	
Ratings	Input: DC 9V 2A Output: 15W Max.	

5.2. TEST MODE

Test Mode	Description
Mode 1	Charging with 15 W wireless charging load (Full Load)
Mode 2	Charging with 15 W wireless charging load (Half Load)
Mode 3	Charging with 15 W wireless charging load (No Load)

Note:

All the modes had been tested, but only the worst data (Mode 1) was recorded in the report.



5.3. ACCESSORY

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Series No.
1	Wireless charger RX artificial load	/	/	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	USB Type-C	USB type-A to Type-C	1.0m	/


ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	Power Adapter	HUAWEI	HW-100225C00	Input: 100-240V~50/60Hz, 0.75A Output: 9V2A

TEST SETUP

The EUT support wireless charging.

SETUP DIAGRAM FOR TEST



5.4. MEASURING INSTRUMENT LIST

Conducted Emissions						
Equipment		Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver		R&S	ESR3	101961	Nov. 12, 2020	Nov. 11, 2021
Two-Line V-Network		R&S	ENV216	101983	Nov. 12, 2020	Nov. 11, 2021
Software						
Description			Manufacturer	Name	Version	
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1	
Radiated Emissions						
Equipment		Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver		KESIGHT	N9038A	MY56400036	Nov. 12, 2020	Nov. 11, 2021
Hybrid Log Periodic Antenna		TDK	HLP-3003C	130959	April 24, 2020	April 23, 2023
Preamplifier		HP	8447D	2944A09099	Nov. 12, 2020	Nov. 11, 2021
Loop antenna		Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17,2022
Preamplifier		TDK	PA-02-001-3000	TRS-305-00067	Nov.12,2020	Nov.11,2021
Software						
Description			Manufacturer	Name	Version	
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1	
Other Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
☒	Spectrum Analyzer	Keysight	N9030A	MY55410512	Nov.20,2020	Nov.19,2021



6. 20dB BANDWIDTH TEST

LIMITS

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.215, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	1% to 5% of the occupied bandwidth
VBW	approximately 3×RBW
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 99%/20 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP




TEST ENVIRONMENT


Temperature	25.8 °C	Relative Humidity	59.5%
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

Frequency (KHz)	20dB Bandwidth (Hz)
128.8	267.7



Frequency (KHz)	99% Bandwidth (Hz)
128.8	250.1





7. RADIATED EMISSION TEST

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.


Radiated emissions limits for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit ($\mu\text{V/m}$) at 3 m	Field Strength Limit ($\text{dB}\mu\text{V/m}$) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	$2400/F(\text{kHz})$	300
0.490-1.705	$24000/F(\text{kHz})$	30
1.705-30.0	30	30

TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1 GHz and above 30 MHz



The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.



TEST ENVIRONMENT

Temperature	24.3 °C	Relative Humidity	59.0 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS



7.1. SPURIOUS EMISSIONS BELOW 30 MHz

FCC PART 15C BELOW 30MHz SPURIOUS EMISSIONS (LOOP ANTENNA FACE ON TO THE EUT)

9 kHz ~ 150 kHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0090	72.03	-101.13	-29.10	48.43	-77.53	peak
2	0.0672	63.55	-101.03	-37.48	31.05	-68.53	peak
3	0.0895	75.82	-101.11	-25.29	28.57	-53.86	peak
4	0.0920	75.28	-101.15	-25.87	28.33	-54.20	peak
5	0.1218	52.95	-101.55	-48.60	25.89	-74.49	peak
6	0.1355	81.70	-101.72	-20.02	24.97	-44.99	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

4. The test was performed at 3 m test site, but we added the corresponding factor to extrapolated the result to the specified distance according to FCC 15.31(f)(2).

5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}(120\pi) = \text{dBuV/m} - 51.5$.

150 kHz ~ 490 kHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1826	69.39	-101.86	-32.47	22.38	-54.85	peak
2	0.2516	62.68	-101.79	-39.11	19.59	-58.70	peak
3	0.2727	70.70	-101.78	-31.08	18.89	-49.97	peak
4	0.3520	64.49	-101.76	-37.27	16.67	-53.94	peak
5	0.4108	68.18	-101.74	-33.56	15.33	-48.89	peak
6	0.4482	60.96	-101.72	-40.76	14.57	-55.33	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

4. The test was performed at 3 m test site, but we added the corresponding factor to extrapolated the result to the specified distance according to FCC 15.31(f)(2).

5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}(120\pi) = \text{dBuV/m} - 51.5$.

490 kHz ~ 30 MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6.6576	53.50	-61.68	-8.18	29.54	-37.72	peak
2	13.4449	48.28	-61.40	-13.12	29.54	-42.66	peak
3	21.5306	65.10	-61.05	4.05	29.54	-25.49	peak
4	21.7962	63.68	-61.04	2.64	29.54	-26.90	peak
5	26.4588	57.41	-60.88	-3.47	29.54	-33.01	peak
6	26.7244	58.52	-60.87	-2.35	29.54	-31.89	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.


3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

4. The test was performed at 3 m test site, but we added the corresponding factor to extrapolated the result to the specified distance according to FCC 15.31(f)(2).

5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}(120\pi) = \text{dBuV/m} - 51.5$.

7.2. SPURIOUS EMISSIONS 30 MHz ~ 1 GHz

FCC PART15C SPURIOUS EMISSIONS (HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	57.1600	43.74	-20.58	23.16	40.00	-16.84	QP
2	87.2300	38.49	-21.80	16.69	40.00	-23.31	QP
3	157.0700	35.14	-17.92	17.22	43.50	-26.28	QP
4	250.1900	33.99	-18.91	15.08	46.00	-30.92	QP
5	446.1300	27.92	-12.52	15.40	46.00	-30.60	QP
6	909.7900	26.96	-4.98	21.98	46.00	-24.02	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

4. All the noise are created from the digital circuit. It is not created by wireless charging circuit.

**FCC PART15C SPURIOUS EMISSIONS (VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	50.3700	51.33	-20.76	30.57	40.00	-9.43	peak
2	59.1000	55.83	-20.52	35.31	40.00	-4.69	peak
3	157.0700	51.96	-17.92	34.04	43.50	-9.46	peak
4	177.4400	41.37	-16.97	24.40	43.50	-19.10	peak
5	436.4300	28.53	-12.63	15.90	46.00	-30.10	peak
6	903.0000	27.80	-5.15	22.65	46.00	-23.35	peak

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

4. All the noise are created from the digital circuit. It is not created by wireless charging circuit.

8. AC POWER LINE CONDUCTED EMISSIONS


LIMITS

Please refer to CFR 47 FCC §15.207 (a)

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.




The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST ENVIRONMENT

Temperature	25.9 °C	Relative Humidity	67.7 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

**RESULTS****LINE L1 RESULTS**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1941	36.27	9.59	45.86	63.86	-18.00	QP
2	0.1941	19.64	9.59	29.23	53.86	-24.63	AVG
3	0.2910	31.55	9.59	41.14	60.50	-19.36	QP
4	0.2910	15.52	9.59	25.11	50.50	-25.39	AVG
5	0.4187	24.11	9.60	33.71	57.47	-23.76	QP
6	0.4187	9.46	9.60	19.06	47.47	-28.41	AVG
7	0.5456	21.55	9.60	31.15	56.00	-24.85	QP
8	0.5456	11.45	9.60	21.05	46.00	-24.95	AVG
9	2.1101	22.10	9.63	31.73	56.00	-24.27	QP
10	2.1101	16.23	9.63	25.86	46.00	-20.14	AVG
11	21.6222	23.89	9.75	33.64	60.00	-26.36	QP
12	21.6222	16.39	9.75	26.14	50.00	-23.86	AVG

Note: 1. Result = Reading +Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz-150 kHz), 9 kHz (150 kHz-30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

**LINE N RESULTS**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1978	34.69	9.59	44.28	63.70	-19.42	QP
2	0.1978	17.36	9.59	26.95	53.70	-26.75	AVG
3	0.2662	30.15	9.59	39.74	61.24	-21.50	QP
4	0.2662	18.78	9.59	28.37	51.24	-22.87	AVG
5	0.3933	28.59	9.59	38.18	57.99	-19.81	QP
6	0.3933	16.87	9.59	26.46	47.99	-21.53	AVG
7	2.6352	28.08	9.62	37.70	56.00	-18.30	QP
8	2.6352	19.96	9.62	29.58	46.00	-16.42	AVG
9	3.9525	28.38	9.60	37.98	56.00	-18.02	QP
10	3.9525	20.24	9.60	29.84	46.00	-16.16	AVG
11	19.7700	27.51	9.73	37.24	60.00	-22.76	QP
12	19.7700	18.91	9.73	28.64	50.00	-21.36	AVG

Note: 1. Result = Reading +Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz-150 kHz), 9 kHz (150 kHz-30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

END OF REPORT