



FCC RF Test Report

APPLICANT : COOSEA GROUP (HK) COMPANY LIMITED
EQUIPMENT : Feature Phone
BRAND NAME : Consumer Cellular
MODEL NAME : SN331CC
FCC ID : 2A28USN331CC
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Jan. 04, 2026 ~ Jan. 08, 2026

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System.....	8
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	9
3 TEST RESULT	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	15
3.5 Radiated Band Edges and Spurious Emission Measurement	28
3.6 AC Conducted Emission Measurement.....	32
3.7 Antenna Requirements.....	34
4 LIST OF MEASURING EQUIPMENT	35
5 MEASUREMENT UNCERTAINTY	36
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5N2009C	Rev. 01	Initial issue of report	Mar. 09, 2026

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)	Conducted Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.51 dB at 2483.77 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 9.78 dB at 0.20 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

COOSEA GROUP (HK) COMPANY LIMITED

UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE TSIMSHATSUI KL

1.2 Manufacturer

COOSEA GROUP (HK) COMPANY LIMITED

UNIT 5-6 16/F MULTIFIELD PLAZA 3-7A PRAT AVENUE TSIMSHATSUI KL

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Feature Phone
Brand Name	Consumer Cellular
Model Name	SN331CC
FCC ID	2A28USN331CC
IMEI Code	Conducted: 351341590003730/351341590003748 Conduction: 351341590006790/351341590006808 Radiation: 351341590004639/351341590004647
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 20.52 dBm (0.1127 W) 802.11g : 24.26 dBm (0.2667 W) 802.11n HT20 : 24.41 dBm (0.2761 W) 802.11n HT40 : 23.64 dBm (0.2312 W) 802.11ac VHT20 : 24.20 dBm (0.2630 W) 802.11ac VHT40 : 23.19 dBm (0.2084 W)
99% Occupied Bandwidth	802.11b : 13.12MHz 802.11g : 16.97MHz 802.11n HT20 : 17.98MHz 802.11n HT40 : 36.88MHz
Antenna Type / Gain	IFA Antenna type with gain 0.39 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

Note: For 802.11n HT20 /ac VHT20 and 802.11n HT40 /ac VHT40 mode, the whole testing have assessed only 802.11n HT20/HT40 by referring to the higher output power.



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ CO02-SZ; 03CH04-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-SZ	AUDIX	E3	6.2009-8-24
2.	CO02-SZ	AUDIX	E3	6.120613b

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2020
- ♦

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z and the EUT in both open and folded states. The worst cases (X/Y plane with open states) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1 :LTE Band 5 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable (Charging from Adapter1) + Earphon
Remark: For Radiated Test Cases, The tests were performance with Adapter, Earphone and USB Cable.	

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station(LTE)	Anritsu	MT8820C	N/A	N/A	N/A
2.	Earphone	apple	N/A	N/A	N/A	N/A
3.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A
4.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 1.30 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 1.30 + 10 = 11.30 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 11.8.1 for 6dB BW and 6.9.3 for 99% occupied bandwidth measurements
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth (VBW) $\geq 3 \times \text{RBW}$. Detector = Peak. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) approximately three times the RBW.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 clause 11.9.1.2 PKPM1 Peak power meter or ANSI C63.10-2020 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure of ANSI C63.10-2020 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 11.11.3
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission


Test Engineer :	Ken Hsu	Temperature :	19~21°C
		Relative Humidity :	44~46%

Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----






Test Mode : 802.11g Test Channel : 01


100kHz PSD reference Level




Channel Plot



Spurious Emission Plot-1




Spurious Emission Plot-2






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11n HT20	Test Channel :	01
-------------	--------------	----------------	----






Test Mode :	802.11n HT20	Test Channel :	06
-------------	--------------	----------------	----





Test Mode :	802.11n HT20	Test Channel :	11
-------------	--------------	----------------	----







Test Mode : 802.11n HT40

Test Channel : 03


100kHz PSD reference Level




Channel Plot



Spurious Emission Plot-1




Spurious Emission Plot-2





Test Mode :	802.11n HT40	Test Channel :	06
-------------	--------------	----------------	----







Test Mode : 802.11n HT40

Test Channel : 09


100kHz PSD reference Level




Channel Plot



Spurious Emission Plot-1



Spurious Emission Plot-2



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2020 clause 6.3, 6.5, 6.6, 11.11 and 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 02, 2025	Jan. 04, 2026	Apr. 01, 2026	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 24, 2025	Jan. 04, 2026	Dec. 23, 2026	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Oct. 14, 2025	Jan. 04, 2026	Oct. 13, 2026	Conducted (TH01-SZ)
EMI Receiver	R&S	ESR7	102297	9kHz~7GHz;	Jul. 03, 2025	Jan. 08, 2026	Jul. 02, 2026	Conduction (CO02-SZ)
AC LISN	R&S	ENV216	101499	9kHz~30MHz	Jul. 03, 2025	Jan. 08, 2026	Jul. 02, 2026	Conduction (CO02-SZ)
AC Power Source	CHROMA	61601	616010002470	100Vac~250Vac	Dec.25, 2025	Jan. 08, 2026	Dec. 24, 2026	Conduction (CO02-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Oct. 15, 2025	Jan. 06, 2026~Jan. 07, 2026	Oct. 14, 2026	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2025	Jan. 06, 2026~Jan. 07, 2026	Jul. 02, 2026	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 25, 2025	Jan. 06, 2026~Jan. 07, 2026	Dec. 24, 2026	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	Apr. 21, 2025	Jan. 06, 2026~Jan. 07, 2026	Apr. 20, 2026	Radiation (03CH04-SZ)
Double Ridge Guide Antenna	ETS-Lindgren	Burgeon-3117	00240057	1GHz~18GHz	Jun. 26, 2025	Jan. 06, 2026~Jan. 07, 2026	Jun. 25, 2026	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	Jul. 04, 2025	Jan. 06, 2026~Jan. 07, 2026	Jul. 03, 2026	Radiation (03CH04-SZ)
LF Amplifier	EM Electronics	EM330	060773	20MHz~3GHz	Apr. 02, 2025	Jan. 06, 2026~Jan. 07, 2026	Apr. 01, 2026	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 13, 2025	Jan. 06, 2026~Jan. 07, 2026	Oct. 12, 2026	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 02, 2025	Jan. 06, 2026~Jan. 07, 2026	Jul. 01, 2026	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY57280136	500MHz~26.5GHz	Jul. 03, 2025	Jan. 06, 2026~Jan. 07, 2026	Jul. 02, 2026	Radiation (03CH04-SZ)
AC Power Source	APC	AFV-S-600B	F119050019	N/A	Oct. 14, 2025	Jan. 06, 2026~Jan. 07, 2026	Oct. 13, 2026	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jan. 06, 2026~Jan. 07, 2026	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jan. 06, 2026~Jan. 07, 2026	NCR	Radiation (03CH04-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	± 1.34 dB
Occupied Channel Bandwidth	± 0.012 MHz
Conducted Power	± 1.34 dB
Conducted Power Spectral Density	± 1.32 dB
Frequency	± 1.3 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------

----- THE END -----



Appendix A. Conducted Test Results

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Haydn Chen	Temperature:	21~25	°C
Test Date:	2026/1/4	Relative Humidity:	51~54	%

TEST RESULTS DATA
Peak Output Power

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
					Ant 1	Ant 1	Ant 1	Ant 1	Ant 1	
11b	1Mbps	1	1	2412	18.56	30.00	0.39	18.95	36.00	Pass
11b	1Mbps	1	6	2437	20.52	30.00	0.39	20.91	36.00	Pass
11b	1Mbps	1	11	2462	17.56	30.00	0.39	17.95	36.00	Pass
11g	6Mbps	1	1	2412	23.11	30.00	0.39	23.50	36.00	Pass
11g	6Mbps	1	6	2437	24.26	30.00	0.39	24.65	36.00	Pass
11g	6Mbps	1	11	2462	23.71	30.00	0.39	24.10	36.00	Pass
HT20	MCS0	1	1	2412	23.21	30.00	0.39	23.60	36.00	Pass
HT20	MCS0	1	6	2437	24.41	30.00	0.39	24.80	36.00	Pass
HT20	MCS0	1	11	2462	23.89	30.00	0.39	24.28	36.00	Pass
HT40	MCS0	1	3	2422	22.40	30.00	0.39	22.79	36.00	Pass
HT40	MCS0	1	6	2437	23.64	30.00	0.39	24.03	36.00	Pass
HT40	MCS0	1	9	2452	23.23	30.00	0.39	23.62	36.00	Pass
VHT20	MCS0	1	1	2412	23.12	30.00	0.39	23.51	36.00	Pass
VHT20	MCS0	1	6	2437	24.20	30.00	0.39	24.59	36.00	Pass
VHT20	MCS0	1	11	2462	23.63	30.00	0.39	24.02	36.00	Pass
VHT40	MCS0	1	3	2422	21.07	30.00	0.39	21.46	36.00	Pass
VHT40	MCS0	1	6	2437	23.19	30.00	0.39	23.58	36.00	Pass
VHT40	MCS0	1	9	2452	22.49	30.00	0.39	22.88	36.00	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Average Output Power

2.4GHz Band											
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail	Setting
					Ant 1	Ant 1	Ant 1	Ant 1	Ant 1		Ant 1
11b	1Mbps	1	1	2412	16.60	30.00	0.39	16.99	36.00	Pass	17.00
11b	1Mbps	1	6	2437	18.00	30.00	0.39	18.39	36.00	Pass	18.00
11b	1Mbps	1	11	2462	15.50	30.00	0.39	15.89	36.00	Pass	15.00
11g	6Mbps	1	1	2412	15.10	30.00	0.39	15.49	36.00	Pass	15.50
11g	6Mbps	1	6	2437	17.00	30.00	0.39	17.39	36.00	Pass	17.00
11g	6Mbps	1	11	2462	15.60	30.00	0.39	15.99	36.00	Pass	15.50
HT20	MCS0	1	1	2412	14.50	30.00	0.39	14.89	36.00	Pass	15.00
HT20	MCS0	1	6	2437	16.90	30.00	0.39	17.29	36.00	Pass	17.00
HT20	MCS0	1	11	2462	14.90	30.00	0.39	15.29	36.00	Pass	15.00
HT40	MCS0	1	3	2422	11.90	30.00	0.39	12.29	36.00	Pass	12.00
HT40	MCS0	1	6	2437	14.60	30.00	0.39	14.99	36.00	Pass	14.50
HT40	MCS0	1	9	2452	12.70	30.00	0.39	13.09	36.00	Pass	12.50
VHT20	MCS0	1	1	2412	14.40	30.00	0.39	14.79	36.00	Pass	15.00
VHT20	MCS0	1	6	2437	16.80	30.00	0.39	17.19	36.00	Pass	17.00
VHT20	MCS0	1	11	2462	14.80	30.00	0.39	15.19	36.00	Pass	15.00
VHT40	MCS0	1	3	2422	11.80	30.00	0.39	12.19	36.00	Pass	12.00
VHT40	MCS0	1	6	2437	14.50	30.00	0.39	14.89	36.00	Pass	14.50
VHT40	MCS0	1	9	2452	12.60	30.00	0.39	12.99	36.00	Pass	12.50

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 1		
11b	1Mbps	1	1	2412	13.01	8.36	0.50	Pass
11b	1Mbps	1	6	2437	13.10	8.38	0.50	Pass
11b	1Mbps	1	11	2462	13.12	8.38	0.50	Pass
11g	6Mbps	1	1	2412	16.91	16.22	0.50	Pass
11g	6Mbps	1	6	2437	16.97	16.18	0.50	Pass
11g	6Mbps	1	11	2462	16.85	16.22	0.50	Pass
HT20	MCS0	1	1	2412	17.96	17.58	0.50	Pass
HT20	MCS0	1	6	2437	17.98	17.36	0.50	Pass
HT20	MCS0	1	11	2462	17.88	17.40	0.50	Pass
HT40	MCS0	1	3	2422	36.56	35.44	0.50	Pass
HT40	MCS0	1	6	2437	36.72	35.40	0.50	Pass
HT40	MCS0	1	9	2452	36.88	36.24	0.50	Pass


TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)	DG (dBi)	Peak PSD Limit (dBm/3kHz)	Pass/Fail
					Ant 1	Ant 1	Ant 1	
11b	1Mbps	1	1	2412	-3.37	0.39	8.00	Pass
11b	1Mbps	1	6	2437	-3.59	0.39	8.00	Pass
11b	1Mbps	1	11	2462	-3.21	0.39	8.00	Pass
11g	6Mbps	1	1	2412	-8.00	0.39	8.00	Pass
11g	6Mbps	1	6	2437	-7.60	0.39	8.00	Pass
11g	6Mbps	1	11	2462	-7.57	0.39	8.00	Pass
HT20	MCS0	1	1	2412	-7.93	0.39	8.00	Pass
HT20	MCS0	1	6	2437	-7.47	0.39	8.00	Pass
HT20	MCS0	1	11	2462	-6.89	0.39	8.00	Pass
HT40	MCS0	1	3	2422	-11.59	0.39	8.00	Pass
HT40	MCS0	1	6	2437	-11.95	0.39	8.00	Pass
HT40	MCS0	1	9	2452	-12.10	0.39	8.00	Pass

Measured power density (dBm) has offset with cable loss.




Appendix B. AC Conducted Emission Test Results





Test Engineer :	Nathon	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO02-SZ
Condition : FCC 15C_QP LISN-N_2026 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.51	26.86	-19.14	46.00	7.00	9.72	10.14	Average
2	0.51	43.16	-12.84	56.00	23.30	9.72	10.14	QP
3	0.70	24.69	-21.31	46.00	4.80	9.76	10.13	Average
4	0.70	41.49	-14.51	56.00	21.60	9.76	10.13	QP
5	0.90	25.19	-20.81	46.00	5.30	9.77	10.12	Average
6	0.90	45.09	-10.91	56.00	25.20	9.77	10.12	QP
7	1.03	30.89	-15.11	46.00	11.00	9.77	10.12	Average
8 *	1.03	45.99	-10.01	56.00	26.10	9.77	10.12	QP
9	2.05	26.01	-19.99	46.00	6.10	9.76	10.15	Average
10	2.05	42.11	-13.89	56.00	22.20	9.76	10.15	QP
11	14.75	26.89	-23.11	50.00	6.80	9.78	10.31	Average
12	14.75	41.79	-18.21	60.00	21.70	9.78	10.31	QP

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C Radiated Spurious Emission Test Data

Test Engineer :	HuaCong Liang	Relative Humidity :	48~49%
		Temperature :	24~25℃

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	4	802.11b	01	2412	1Mbps	-	-
Mode 2	2400-2483.5	4	802.11b	06	2437	1Mbps	-	-
Mode 3	2400-2483.5	4	802.11b	11	2462	1Mbps	-	-
Mode 4	2400-2483.5	4	802.11g	01	2412	6Mbps	-	-
Mode 5	2400-2483.5	4	802.11g	06	2437	6Mbps	-	-
Mode 6	2400-2483.5	4	802.11g	11	2462	6Mbps	-	-
Mode 7	2400-2483.5	4	802.11n HT20	01	2412	MCS0	-	-
Mode 8	2400-2483.5	4	802.11n HT20	06	2437	MCS0	-	-
Mode 9	2400-2483.5	4	802.11n HT20	11	2462	MCS0	-	-
Mode 10	2400-2483.5	4	802.11n HT40	03	2422	MCS0	-	-
Mode 11	2400-2483.5	4	802.11n HT40	06	2437	MCS0	-	-
Mode 12	2400-2483.5	4	802.11n HT40	09	2452	MCS0	-	-
Mode 13	2400-2483.5	4	802.11n HT20-LF	11	2462	MCS0	-	-





Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	802.11b	01	2387.61	41.46	54.00	-12.54	H	AVERAGE	Pass	Band Edge
1	802.11b	01	4824.00	53.10	54.00	-0.90	V	Average	Pass	Harmonic
2	802.11b	06	2483.56	36.87	54.00	-17.13	H	AVERAGE	Pass	Band Edge
2	802.11b	06	4874.00	45.36	54.00	-8.64	V	Average	Pass	Harmonic
3	802.11b	11	2488.30	42.63	54.00	-11.37	H	AVERAGE	Pass	Band Edge
3	802.11b	11	4924.00	53.37	54.00	-0.63	V	Average	Pass	Harmonic
4	802.11g	01	2389.95	53.41	54.00	-0.59	H	AVERAGE	Pass	Band Edge
4	802.11g	01	4824.00	40.29	54.00	-13.71	V	Average	Pass	Harmonic
5	802.11g	06	2483.56	38.96	54.00	-15.04	H	AVERAGE	Pass	Band Edge
5	802.11g	06	4874.00	38.21	54.00	-15.79	V	Average	Pass	Harmonic
6	802.11g	11	2483.58	52.70	54.00	-1.30	H	AVERAGE	Pass	Band Edge
6	802.11g	11	4924.00	41.92	54.00	-12.08	V	Average	Pass	Harmonic
7	802.11n HT20	01	2389.95	53.37	54.00	-0.63	H	AVERAGE	Pass	Band Edge
7	802.11n HT20	01	4824.00	39.96	54.00	-14.04	V	Average	Pass	Harmonic
8	802.11n HT20	06	2483.56	39.61	54.00	-14.39	H	AVERAGE	Pass	Band Edge
8	802.11n HT20	06	4874.00	38.07	54.00	-15.93	V	Average	Pass	Harmonic
9	802.11n HT20	11	2483.77	53.49	54.00	-0.51	H	AVERAGE	Pass	Band Edge
9	802.11n HT20	11	4924.00	40.27	54.00	-13.73	V	Average	Pass	Harmonic
10	802.11n HT40	03	2389.97	51.37	54.00	-2.63	H	AVERAGE	Pass	Band Edge
10	802.11n HT40	03	7266.00	46.29	74.00	-27.71	H	Peak	Pass	Harmonic
11	802.11n HT40	06	2389.76	52.24	54.00	-1.76	H	AVERAGE	Pass	Band Edge
11	802.11n HT40	06	7311.00	46.11	74.00	-27.89	V	Peak	Pass	Harmonic
12	802.11n HT40	09	2484.16	52.59	54.00	-1.41	H	AVERAGE	Pass	Band Edge
12	802.11n HT40	09	4904.00	46.35	74.00	-27.65	V	Peak	Pass	Harmonic
13	802.11n HT20-LF	11	862.26	30.21	46.00	-15.79	V	Peak	Pass	LF





Mode	1																																																																																	
	Band Edge																																																																																	
	2400-2483.5_802.11b_CH01_2412MHz																																																																																	
ANT	4																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2026-01-07 Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2386.96</td><td>49.53</td><td>74.00</td><td>-24.47</td><td>44.91</td><td>30.41</td><td>6.86</td><td>32.65</td><td>117</td><td>90</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2386.96	49.53	74.00	-24.47	44.91	30.41	6.86	32.65	117	90	PEAK	Level (dBuV/m) Date: 2026-01-07 Frequency (MHz) PEAK_74 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>105.80</td><td>-----</td><td>-----</td><td>101.12</td><td>30.43</td><td>6.89</td><td>32.64</td><td>117</td><td>90</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2412.00	105.80	-----	-----	101.12	30.43	6.89	32.64	117	90	PEAK
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2386.96	49.53	74.00	-24.47	44.91	30.41	6.86	32.65	117	90	PEAK																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2412.00	105.80	-----	-----	101.12	30.43	6.89	32.64	117	90	PEAK																																																																							
Avg	Level (dBuV/m) Date: 2026-01-07 Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2387.61</td><td>41.46</td><td>54.00</td><td>-12.54</td><td>36.83</td><td>30.41</td><td>6.86</td><td>32.64</td><td>117</td><td>90</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2387.61	41.46	54.00	-12.54	36.83	30.41	6.86	32.64	117	90	AVERAGE	Level (dBuV/m) Date: 2026-01-07 Frequency (MHz) AVG_54 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>103.68</td><td>-----</td><td>-----</td><td>99.00</td><td>30.43</td><td>6.89</td><td>32.64</td><td>117</td><td>90</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2412.00	103.68	-----	-----	99.00	30.43	6.89	32.64	117	90	AVERAGE
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2387.61	41.46	54.00	-12.54	36.83	30.41	6.86	32.64	117	90	AVERAGE																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2412.00	103.68	-----	-----	99.00	30.43	6.89	32.64	117	90	AVERAGE																																																																							



Mode	1																																																																																	
	Band Edge																																																																																	
	2400-2483.5_802.11b_CH01_2412MHz																																																																																	
ANT	4																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	Date: 2026-01-07 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2387.48</td><td>45.55</td><td>74.00</td><td>-28.45</td><td>40.93</td><td>30.41</td><td>6.86</td><td>32.65</td><td>400</td><td>80</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2387.48	45.55	74.00	-28.45	40.93	30.41	6.86	32.65	400	80	PEAK	Date: 2026-01-07 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>97.14</td><td>-----</td><td>-----</td><td>92.45</td><td>30.43</td><td>6.89</td><td>32.63</td><td>400</td><td>80</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2412.00	97.14	-----	-----	92.45	30.43	6.89	32.63	400	80	PEAK
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2387.48	45.55	74.00	-28.45	40.93	30.41	6.86	32.65	400	80	PEAK																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2412.00	97.14	-----	-----	92.45	30.43	6.89	32.63	400	80	PEAK																																																																							
Avg	Date: 2026-01-07 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2386.83</td><td>36.72</td><td>54.00</td><td>-17.28</td><td>32.10</td><td>30.41</td><td>6.86</td><td>32.65</td><td>400</td><td>80</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2386.83	36.72	54.00	-17.28	32.10	30.41	6.86	32.65	400	80	AVERAGE	Date: 2026-01-07 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>94.89</td><td>-----</td><td>-----</td><td>90.21</td><td>30.43</td><td>6.89</td><td>32.64</td><td>400</td><td>80</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2412.00	94.89	-----	-----	90.21	30.43	6.89	32.64	400	80	AVERAGE
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2386.83	36.72	54.00	-17.28	32.10	30.41	6.86	32.65	400	80	AVERAGE																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2412.00	94.89	-----	-----	90.21	30.43	6.89	32.64	400	80	AVERAGE																																																																							



Mode	1																																																																																															
	Harmonic																																																																																															
	2400-2483.5_802.11b_CH01_2412MHz																																																																																															
ANT	4																																																																																															
Pol.	Horizontal						Vertical																																																																																									
Peak Avg																																																																																																
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr></thead><tbody><tr><td>1</td><td>4824.00</td><td>53.02</td><td>74.00</td><td>-20.98</td><td>60.04</td><td>35.41</td><td>10.16</td><td>52.59</td><td>176</td><td>163</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>49.53</td><td>54.00</td><td>-4.47</td><td>56.55</td><td>35.41</td><td>10.16</td><td>52.59</td><td>176</td><td>163</td><td>Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	1	4824.00	53.02	74.00	-20.98	60.04	35.41	10.16	52.59	176	163	Peak	2	4824.00	49.53	54.00	-4.47	56.55	35.41	10.16	52.59	176	163	Average	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr></thead><tbody><tr><td>1</td><td>4824.00</td><td>55.73</td><td>74.00</td><td>-18.27</td><td>62.75</td><td>35.41</td><td>10.16</td><td>52.59</td><td>122</td><td>313</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>53.10</td><td>54.00</td><td>-0.90</td><td>60.12</td><td>35.41</td><td>10.16</td><td>52.59</td><td>122</td><td>313</td><td>Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	1	4824.00	55.73	74.00	-18.27	62.75	35.41	10.16	52.59	122	313	Peak	2	4824.00	53.10	54.00	-0.90	60.12	35.41	10.16	52.59	122	313	Average
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																								
1	4824.00	53.02	74.00	-20.98	60.04	35.41	10.16	52.59	176	163	Peak																																																																																					
2	4824.00	49.53	54.00	-4.47	56.55	35.41	10.16	52.59	176	163	Average																																																																																					
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																								
1	4824.00	55.73	74.00	-18.27	62.75	35.41	10.16	52.59	122	313	Peak																																																																																					
2	4824.00	53.10	54.00	-0.90	60.12	35.41	10.16	52.59	122	313	Average																																																																																					
	<table><thead><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4824.00</td><td>53.02</td><td>74.00</td><td>-20.98</td><td>60.04</td><td>35.41</td><td>10.16</td><td>52.59</td><td>176</td><td>163</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>49.53</td><td>54.00</td><td>-4.47</td><td>56.55</td><td>35.41</td><td>10.16</td><td>52.59</td><td>176</td><td>163</td><td>Average</td></tr></tbody></table>							MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4824.00	53.02	74.00	-20.98	60.04	35.41	10.16	52.59	176	163	Peak	2	4824.00	49.53	54.00	-4.47	56.55	35.41	10.16	52.59	176	163	Average	<table><thead><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4824.00</td><td>55.73</td><td>74.00</td><td>-18.27</td><td>62.75</td><td>35.41</td><td>10.16</td><td>52.59</td><td>122</td><td>313</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>53.10</td><td>54.00</td><td>-0.90</td><td>60.12</td><td>35.41</td><td>10.16</td><td>52.59</td><td>122</td><td>313</td><td>Average</td></tr></tbody></table>							MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4824.00	55.73	74.00	-18.27	62.75	35.41	10.16	52.59	122	313	Peak	2	4824.00	53.10	54.00	-0.90	60.12	35.41	10.16	52.59	122	313	Average												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	4824.00	53.02	74.00	-20.98	60.04	35.41	10.16	52.59	176	163	Peak																																																																																					
2	4824.00	49.53	54.00	-4.47	56.55	35.41	10.16	52.59	176	163	Average																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	4824.00	55.73	74.00	-18.27	62.75	35.41	10.16	52.59	122	313	Peak																																																																																					
2	4824.00	53.10	54.00	-0.90	60.12	35.41	10.16	52.59	122	313	Average																																																																																					



Mode	2																																																																																	
	Band Edge - L																																																																																	
	2400-2483.5_802.11b_CH06_2437MHz																																																																																	
ANT	4																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	Date: 2026-01-07 Level (dBuV/m) Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2387.60</td><td>46.88</td><td>74.00</td><td>-27.12</td><td>42.25</td><td>30.41</td><td>6.86</td><td>32.64</td><td>100</td><td>267</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2387.60	46.88	74.00	-27.12	42.25	30.41	6.86	32.64	100	267	PEAK	Date: 2026-01-07 Level (dBuV/m) Frequency (MHz) PEAK_74 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2437.00</td><td>106.60</td><td>-----</td><td>-----</td><td>101.86</td><td>30.45</td><td>6.92</td><td>32.63</td><td>100</td><td>267</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2437.00	106.60	-----	-----	101.86	30.45	6.92	32.63	100	267	PEAK
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2387.60	46.88	74.00	-27.12	42.25	30.41	6.86	32.64	100	267	PEAK																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2437.00	106.60	-----	-----	101.86	30.45	6.92	32.63	100	267	PEAK																																																																							
Avg	Date: 2026-01-07 Level (dBuV/m) Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.76</td><td>36.78</td><td>54.00</td><td>-17.22</td><td>32.14</td><td>30.41</td><td>6.87</td><td>32.64</td><td>100</td><td>267</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.76	36.78	54.00	-17.22	32.14	30.41	6.87	32.64	100	267	AVERAGE	Date: 2026-01-07 Level (dBuV/m) Frequency (MHz) AVG_54 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2437.00</td><td>104.14</td><td>-----</td><td>-----</td><td>99.40</td><td>30.45</td><td>6.92</td><td>32.63</td><td>100</td><td>267</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2437.00	104.14	-----	-----	99.40	30.45	6.92	32.63	100	267	AVERAGE
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.76	36.78	54.00	-17.22	32.14	30.41	6.87	32.64	100	267	AVERAGE																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2437.00	104.14	-----	-----	99.40	30.45	6.92	32.63	100	267	AVERAGE																																																																							



Mode	2																																																																	
	Band Edge - R																																																																	
	2400-2483.5_802.11b_CH06_2437MHz																																																																	
ANT	4																																																																	
Pol.	Horizontal	Fundamental																																																																
Peak	Date: 2026-01-07 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr></thead><tbody><tr><td>1</td><td>2488.35</td><td>47.45</td><td>74.00</td><td>-26.55</td><td>42.58</td><td>30.49</td><td>6.98</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>32.60</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>100</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>267</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	1	2488.35	47.45	74.00	-26.55	42.58	30.49	6.98								32.60								100								267								PEAK	Blank
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																											
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB																																																											
1	2488.35	47.45	74.00	-26.55	42.58	30.49	6.98																																																											
							32.60																																																											
							100																																																											
							267																																																											
							PEAK																																																											
Avg	Date: 2026-01-07 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr></thead><tbody><tr><td>1</td><td>2483.56</td><td>36.87</td><td>54.00</td><td>-17.13</td><td>32.01</td><td>30.49</td><td>6.98</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>32.61</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>100</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>267</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	1	2483.56	36.87	54.00	-17.13	32.01	30.49	6.98								32.61								100								267								AVERAGE	Blank
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																											
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB																																																											
1	2483.56	36.87	54.00	-17.13	32.01	30.49	6.98																																																											
							32.61																																																											
							100																																																											
							267																																																											
							AVERAGE																																																											



Mode	2	
	Band Edge - L	
	2400-2483.5_802.11b_CH06_2437MHz	
ANT	4	
Pol.	Vertical	Fundamental
Peak		







Mode	2																																																	
	Band Edge - R																																																	
	2400-2483.5_802.11b_CH06_2437MHz																																																	
ANT	4																																																	
Pol.	Vertical					Fundamental																																												
Peak	Date: 2026-01-07 <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2486.71</td><td>44.92</td><td>74.00</td><td>-29.08</td><td>40.06</td><td>30.49</td><td>6.98</td><td>32.61</td><td>383</td><td>264</td><td>PEAK</td></tr></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2486.71	44.92	74.00	-29.08	40.06	30.49	6.98	32.61	383	264	PEAK	Blank				
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																									
1	2486.71	44.92	74.00	-29.08	40.06	30.49	6.98	32.61	383	264	PEAK																																							
Avg	Date: 2026-01-07 <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2485.32</td><td>35.01</td><td>54.00</td><td>-18.99</td><td>30.15</td><td>30.49</td><td>6.98</td><td>32.61</td><td>383</td><td>264</td><td>AVERAGE</td></tr></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2485.32	35.01	54.00	-18.99	30.15	30.49	6.98	32.61	383	264	AVERAGE	Blank				
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																									
1	2485.32	35.01	54.00	-18.99	30.15	30.49	6.98	32.61	383	264	AVERAGE																																							







Mode	2																																																																																																																																												
	Harmonic																																																																																																																																												
	2400-2483.5_802.11b_CH06_2437MHz																																																																																																																																												
ANT	4																																																																																																																																												
Pol.	Horizontal										Vertical																																																																																																																																		
Peak Avg																																																																																																																																													
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4874.00</td><td>47.66</td><td>74.00</td><td>-26.34</td><td>54.49</td><td>35.52</td><td>10.27</td><td>52.62</td><td>209</td><td>218</td><td>Peak</td></tr><tr><td>2</td><td>4874.00</td><td>42.07</td><td>54.00</td><td>-11.93</td><td>48.90</td><td>35.52</td><td>10.27</td><td>52.62</td><td>209</td><td>218</td><td>Average</td></tr><tr><td>3</td><td>7311.00</td><td>45.70</td><td>74.00</td><td>-28.30</td><td>49.44</td><td>36.47</td><td>12.01</td><td>52.22</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	47.66	74.00	-26.34	54.49	35.52	10.27	52.62	209	218	Peak	2	4874.00	42.07	54.00	-11.93	48.90	35.52	10.27	52.62	209	218	Average	3	7311.00	45.70	74.00	-28.30	49.44	36.47	12.01	52.22	---	---	Peak	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4874.00</td><td>50.62</td><td>74.00</td><td>-23.38</td><td>57.45</td><td>35.52</td><td>10.27</td><td>52.62</td><td>156</td><td>315</td><td>Peak</td></tr><tr><td>2</td><td>4874.00</td><td>45.36</td><td>54.00</td><td>-8.64</td><td>52.19</td><td>35.52</td><td>10.27</td><td>52.62</td><td>156</td><td>315</td><td>Average</td></tr><tr><td>3</td><td>7311.00</td><td>45.37</td><td>74.00</td><td>-28.63</td><td>49.11</td><td>36.47</td><td>12.01</td><td>52.22</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	50.62	74.00	-23.38	57.45	35.52	10.27	52.62	156	315	Peak	2	4874.00	45.36	54.00	-8.64	52.19	35.52	10.27	52.62	156	315	Average	3	7311.00	45.37	74.00	-28.63	49.11	36.47	12.01	52.22	---	---	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																					
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																			
1	4874.00	47.66	74.00	-26.34	54.49	35.52	10.27	52.62	209	218	Peak																																																																																																																																		
2	4874.00	42.07	54.00	-11.93	48.90	35.52	10.27	52.62	209	218	Average																																																																																																																																		
3	7311.00	45.70	74.00	-28.30	49.44	36.47	12.01	52.22	---	---	Peak																																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																			
1	4874.00	50.62	74.00	-23.38	57.45	35.52	10.27	52.62	156	315	Peak																																																																																																																																		
2	4874.00	45.36	54.00	-8.64	52.19	35.52	10.27	52.62	156	315	Average																																																																																																																																		
3	7311.00	45.37	74.00	-28.63	49.11	36.47	12.01	52.22	---	---	Peak																																																																																																																																		





Mode	3																																																																																																	
	Band Edge																																																																																																	
	2400-2483.5_802.11b_CH11_2462MHz																																																																																																	
ANT	4																																																																																																	
Pol.	Horizontal						Fundamental																																																																																											
Peak																																																																																																		
	<table><tr><th colspan="2"></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2488.14</td><td>50.15</td><td>74.00</td><td>-23.85</td><td>45.28</td><td>30.49</td><td>6.98</td><td>32.60</td><td>100</td><td>264 PEAK</td></tr></table>								Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg		1	2488.14	50.15	74.00	-23.85	45.28	30.49	6.98	32.60	100	264 PEAK	<table><tr><th colspan="2"></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2462.00</td><td>106.71</td><td>-----</td><td>-----</td><td>101.91</td><td>30.47</td><td>6.95</td><td>32.62</td><td>100</td><td>264 PEAK</td></tr></table>							Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg		1	2462.00	106.71	-----	-----	101.91	30.47	6.95	32.62	100
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor			Remark																																																																																								
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2488.14	50.15	74.00	-23.85	45.28	30.49	6.98	32.60	100	264 PEAK																																																																																								
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor			Remark																																																																																								
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2462.00	106.71	-----	-----	101.91	30.47	6.95	32.62	100	264 PEAK																																																																																								
Avg																																																																																																		
	<table><tr><th colspan="2"></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2488.30</td><td>42.63</td><td>54.00</td><td>-11.37</td><td>37.76</td><td>30.49</td><td>6.98</td><td>32.60</td><td>100</td><td>264 AVERAGE</td></tr></table>								Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg		1	2488.30	42.63	54.00	-11.37	37.76	30.49	6.98	32.60	100	264 AVERAGE	<table><tr><th colspan="2"></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2462.00</td><td>104.51</td><td>-----</td><td>-----</td><td>99.71</td><td>30.47</td><td>6.95</td><td>32.62</td><td>100</td><td>264 AVERAGE</td></tr></table>							Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg		1	2462.00	104.51	-----	-----	99.71	30.47	6.95	32.62	100
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor			Remark																																																																																								
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2488.30	42.63	54.00	-11.37	37.76	30.49	6.98	32.60	100	264 AVERAGE																																																																																								
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor			Remark																																																																																								
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2462.00	104.51	-----	-----	99.71	30.47	6.95	32.62	100	264 AVERAGE																																																																																								







Mode	3																																																																																	
	Band Edge																																																																																	
	2400-2483.5_802.11b_CH11_2462MHz																																																																																	
ANT	4																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2026-01-07  <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2486.81</td><td>47.77</td><td>74.00</td><td>-26.23</td><td>42.91</td><td>30.49</td><td>6.98</td><td>32.61</td><td>369 261 PEAK</td></tr></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark		MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	2486.81	47.77	74.00	-26.23	42.91	30.49	6.98	32.61	369 261 PEAK	Level (dBuV/m) Date: 2026-01-07  <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>101.92</td><td>-----</td><td>97.12</td><td>30.47</td><td>6.95</td><td>32.62</td><td>369</td><td>261 PEAK</td></tr></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark		MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	2462.00	101.92	-----	97.12	30.47	6.95	32.62	369	261 PEAK
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
	MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2486.81	47.77	74.00	-26.23	42.91	30.49	6.98	32.61	369 261 PEAK																																																																									
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
	MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2462.00	101.92	-----	97.12	30.47	6.95	32.62	369	261 PEAK																																																																									
Avg	Level (dBuV/m) Date: 2026-01-07  <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.88</td><td>39.20</td><td>54.00</td><td>-14.80</td><td>34.33</td><td>30.49</td><td>6.98</td><td>32.60</td><td>369 261 AVERAGE</td></tr></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark		MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	2487.88	39.20	54.00	-14.80	34.33	30.49	6.98	32.60	369 261 AVERAGE	Level (dBuV/m) Date: 2026-01-07  <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>99.68</td><td>-----</td><td>94.88</td><td>30.47</td><td>6.95</td><td>32.62</td><td>369</td><td>261 AVERAGE</td></tr></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark		MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	2462.00	99.68	-----	94.88	30.47	6.95	32.62	369	261 AVERAGE
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
	MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2487.88	39.20	54.00	-14.80	34.33	30.49	6.98	32.60	369 261 AVERAGE																																																																									
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
	MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2462.00	99.68	-----	94.88	30.47	6.95	32.62	369	261 AVERAGE																																																																									







Mode	3																																																																																																																																															
	Harmonic																																																																																																																																															
	2400-2483.5_802.11b_CH11_2462MHz																																																																																																																																															
ANT	4																																																																																																																																															
Pol.	Horizontal						Vertical																																																																																																																																									
Peak Avg																																																																																																																																																
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4924.00</td><td>51.85</td><td>74.00</td><td>-22.15</td><td>58.55</td><td>35.63</td><td>10.32</td><td>52.65</td><td>273</td><td>142</td><td>Peak</td></tr><tr><td>2</td><td>4924.00</td><td>46.87</td><td>54.00</td><td>-7.13</td><td>53.57</td><td>35.63</td><td>10.32</td><td>52.65</td><td>273</td><td>142</td><td>Average</td></tr><tr><td>3</td><td>7386.00</td><td>46.06</td><td>74.00</td><td>-27.94</td><td>49.77</td><td>36.56</td><td>11.98</td><td>52.25</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4924.00	51.85	74.00	-22.15	58.55	35.63	10.32	52.65	273	142	Peak	2	4924.00	46.87	54.00	-7.13	53.57	35.63	10.32	52.65	273	142	Average	3	7386.00	46.06	74.00	-27.94	49.77	36.56	11.98	52.25	---	---	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4924.00</td><td>55.60</td><td>74.00</td><td>-18.40</td><td>62.30</td><td>35.63</td><td>10.32</td><td>52.65</td><td>174</td><td>313</td><td>Peak</td></tr><tr><td>2</td><td>4924.00</td><td>53.37</td><td>54.00</td><td>-0.63</td><td>60.07</td><td>35.63</td><td>10.32</td><td>52.65</td><td>174</td><td>313</td><td>Average</td></tr><tr><td>3</td><td>7386.00</td><td>45.67</td><td>74.00</td><td>-28.33</td><td>49.38</td><td>36.56</td><td>11.98</td><td>52.25</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4924.00	55.60	74.00	-18.40	62.30	35.63	10.32	52.65	174	313	Peak	2	4924.00	53.37	54.00	-0.63	60.07	35.63	10.32	52.65	174	313	Average	3	7386.00	45.67	74.00	-28.33	49.38	36.56	11.98	52.25	---	---	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																								
	Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																						
1	4924.00	51.85	74.00	-22.15	58.55	35.63	10.32	52.65	273	142	Peak																																																																																																																																					
2	4924.00	46.87	54.00	-7.13	53.57	35.63	10.32	52.65	273	142	Average																																																																																																																																					
3	7386.00	46.06	74.00	-27.94	49.77	36.56	11.98	52.25	---	---	Peak																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																						
1	4924.00	55.60	74.00	-18.40	62.30	35.63	10.32	52.65	174	313	Peak																																																																																																																																					
2	4924.00	53.37	54.00	-0.63	60.07	35.63	10.32	52.65	174	313	Average																																																																																																																																					
3	7386.00	45.67	74.00	-28.33	49.38	36.56	11.98	52.25	---	---	Peak																																																																																																																																					





Mode	4																																																																																								
	Band Edge																																																																																								
	2400-2483.5_802.11g_CH01_2412MHz																																																																																								
ANT	4																																																																																								
Pol.	Horizontal					Fundamental																																																																																			
Peak																																																																																									
	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.69</td><td>64.87</td><td>74.00</td><td>-9.13</td><td>60.23</td><td>30.41</td><td>6.87</td><td>32.64</td><td>342 281 PEAK</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.69	64.87	74.00	-9.13	60.23	30.41	6.87	32.64	342 281 PEAK	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>105.85</td><td>-----</td><td>101.17</td><td>30.43</td><td>6.89</td><td>32.64</td><td>342</td><td>281 PEAK</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2412.00	105.85	-----	101.17	30.43	6.89	32.64	342
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2389.69	64.87	74.00	-9.13	60.23	30.41	6.87	32.64	342 281 PEAK																																																																																
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2412.00	105.85	-----	101.17	30.43	6.89	32.64	342	281 PEAK																																																																																
Avg																																																																																									
	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>53.41</td><td>54.00</td><td>-0.59</td><td>48.77</td><td>30.41</td><td>6.87</td><td>32.64</td><td>342 281 AVERAGE</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.95	53.41	54.00	-0.59	48.77	30.41	6.87	32.64	342 281 AVERAGE	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>98.39</td><td>-----</td><td>93.71</td><td>30.43</td><td>6.89</td><td>32.64</td><td>342</td><td>281 AVERAGE</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2412.00	98.39	-----	93.71	30.43	6.89	32.64	342
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2389.95	53.41	54.00	-0.59	48.77	30.41	6.87	32.64	342 281 AVERAGE																																																																																
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2412.00	98.39	-----	93.71	30.43	6.89	32.64	342	281 AVERAGE																																																																																



Mode	4																																																																																																																																																																				
	Band Edge																																																																																																																																																																				
	2400-2483.5_802.11g_CH01_2412MHz																																																																																																																																																																				
ANT	4																																																																																																																																																																				
Pol.	Vertical	Fundamental																																																																																																																																																																			
Peak	Level (dBuV/m) Date: 2026-01-06  231023362362238824142440 017.535.052.570.087.5105.0122.5140 <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.69</td><td>61.06</td><td>74.00</td><td>-12.94</td><td>56.42</td><td>30.41</td><td>6.87</td><td>32.64</td><td>345</td><td>221 PEAK</td></tr></tbody></table> Level (dBuV/m) Date: 2026-01-06  100014001800220026003000 017.535.052.570.087.5105.0122.5140 <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>100.43</td><td>-----</td><td>95.75</td><td>30.43</td><td>6.89</td><td>32.64</td><td>345</td><td>221 PEAK</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.69	61.06	74.00	-12.94	56.42	30.41	6.87	32.64	345	221 PEAK		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2412.00	100.43	-----	95.75	30.43	6.89	32.64	345	221 PEAK	Avg	Level (dBuV/m) Date: 2026-01-06  231023362362238824142440 017.535.052.570.087.5105.0122.5140 <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.95</td><td>48.89</td><td>54.00</td><td>-5.11</td><td>44.25</td><td>30.41</td><td>6.87</td><td>32.64</td><td>345</td><td>221 AVERAGE</td></tr></tbody></table> Level (dBuV/m) Date: 2026-01-06  100014001800220026003000 017.535.052.570.087.5105.0122.5140 <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>93.00</td><td>-----</td><td>88.32</td><td>30.43</td><td>6.89</td><td>32.64</td><td>345</td><td>221 AVERAGE</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.95	48.89	54.00	-5.11	44.25	30.41	6.87	32.64	345	221 AVERAGE		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2412.00	93.00	-----	88.32	30.43	6.89	32.64	345	221 AVERAGE
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																												
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																																																																																												
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																												
1	2389.69	61.06	74.00	-12.94	56.42	30.41	6.87	32.64	345	221 PEAK																																																																																																																																																											
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																													
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																																																																																												
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																												
1	2412.00	100.43	-----	95.75	30.43	6.89	32.64	345	221 PEAK																																																																																																																																																												
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																													
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																																																																																												
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																												
1	2389.95	48.89	54.00	-5.11	44.25	30.41	6.87	32.64	345	221 AVERAGE																																																																																																																																																											
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																													
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																																																																																												
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																												
1	2412.00	93.00	-----	88.32	30.43	6.89	32.64	345	221 AVERAGE																																																																																																																																																												



Mode	4																																																																																																							
	Harmonic																																																																																																							
	2400-2483.5_802.11g_CH01_2412MHz																																																																																																							
ANT	4																																																																																																							
Pol.	Horizontal						Vertical																																																																																																	
Peak Avg																																																																																																								
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4824.00</td><td>45.36</td><td>74.00</td><td>-28.64</td><td>52.38</td><td>35.41</td><td>10.16</td><td>52.59</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	45.36	74.00	-28.64	52.38	35.41	10.16	52.59	---	---	Peak	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4824.00</td><td>51.37</td><td>74.00</td><td>-22.63</td><td>58.39</td><td>35.41</td><td>10.16</td><td>52.59</td><td>147</td><td>313</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>40.29</td><td>54.00</td><td>-13.71</td><td>47.31</td><td>35.41</td><td>10.16</td><td>52.59</td><td>147</td><td>313</td><td>Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	51.37	74.00	-22.63	58.39	35.41	10.16	52.59	147	313	Peak	2	4824.00	40.29	54.00	-13.71	47.31	35.41	10.16	52.59	147	313	Average
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																															
1	4824.00	45.36	74.00	-28.64	52.38	35.41	10.16	52.59	---	---	Peak																																																																																													
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																															
1	4824.00	51.37	74.00	-22.63	58.39	35.41	10.16	52.59	147	313	Peak																																																																																													
2	4824.00	40.29	54.00	-13.71	47.31	35.41	10.16	52.59	147	313	Average																																																																																													







Mode	5																																																																																	
	Band Edge - L																																																																																	
	2400-2483.5_802.11g_CH06_2437MHz																																																																																	
ANT	4																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 2389.63</td><td>51.25</td><td>74.00</td><td>-22.75</td><td>46.61</td><td>30.41</td><td>6.87</td><td>32.64</td><td>367</td><td>287 PEAK</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1 2389.63	51.25	74.00	-22.75	46.61	30.41	6.87	32.64	367	287 PEAK	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) PEAK_74 <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 2437.00</td><td>107.94</td><td>-----</td><td>-----</td><td>103.19</td><td>30.45</td><td>6.92</td><td>32.62</td><td>367</td><td>287 PEAK</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1 2437.00	107.94	-----	-----	103.19	30.45	6.92	32.62	367	287 PEAK
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1 2389.63	51.25	74.00	-22.75	46.61	30.41	6.87	32.64	367	287 PEAK																																																																									
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1 2437.00	107.94	-----	-----	103.19	30.45	6.92	32.62	367	287 PEAK																																																																									
Avg	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 2389.76</td><td>37.17</td><td>54.00</td><td>-16.83</td><td>32.53</td><td>30.41</td><td>6.87</td><td>32.64</td><td>367</td><td>287 AVERAGE</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1 2389.76	37.17	54.00	-16.83	32.53	30.41	6.87	32.64	367	287 AVERAGE	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) AVG_54 <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 2437.00</td><td>100.61</td><td>-----</td><td>-----</td><td>95.86</td><td>30.45</td><td>6.92</td><td>32.62</td><td>367</td><td>287 AVERAGE</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1 2437.00	100.61	-----	-----	95.86	30.45	6.92	32.62	367	287 AVERAGE
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1 2389.76	37.17	54.00	-16.83	32.53	30.41	6.87	32.64	367	287 AVERAGE																																																																									
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1 2437.00	100.61	-----	-----	95.86	30.45	6.92	32.62	367	287 AVERAGE																																																																									



Mode	5																																																	
	Band Edge - R																																																	
	2400-2483.5_802.11g_CH06_2437MHz																																																	
ANT	4																																																	
Pol.	Horizontal					Fundamental																																												
Peak	Date: 2026-01-06 PEAK_BE_74 <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.19</td><td>51.08</td><td>74.00</td><td>-22.92</td><td>46.22</td><td>30.49</td><td>6.98</td><td>32.61</td><td>367</td><td>287</td><td>PEAK</td></tr></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2484.19	51.08	74.00	-22.92	46.22	30.49	6.98	32.61	367	287	PEAK	Blank				
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																									
1	2484.19	51.08	74.00	-22.92	46.22	30.49	6.98	32.61	367	287	PEAK																																							
Avg	Date: 2026-01-06 AVG_BE_54 <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.56</td><td>38.96</td><td>54.00</td><td>-15.04</td><td>34.10</td><td>30.49</td><td>6.98</td><td>32.61</td><td>367</td><td>287</td><td>AVERAGE</td></tr></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.56	38.96	54.00	-15.04	34.10	30.49	6.98	32.61	367	287	AVERAGE	Blank				
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																									
1	2483.56	38.96	54.00	-15.04	34.10	30.49	6.98	32.61	367	287	AVERAGE																																							



Mode	5																																																																																								
	Band Edge - L																																																																																								
	2400-2483.5_802.11g_CH06_2437MHz																																																																																								
ANT	4																																																																																								
Pol.	Vertical					Fundamental																																																																																			
Peak																																																																																									
	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.50</td><td>47.10</td><td>74.00</td><td>-26.90</td><td>42.46</td><td>30.41</td><td>6.87</td><td>32.64</td><td>374 243 PEAK</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.50	47.10	74.00	-26.90	42.46	30.41	6.87	32.64	374 243 PEAK	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>106.64</td><td>-----</td><td>-----</td><td>101.90</td><td>30.45</td><td>6.92</td><td>32.63</td><td>374 243 PEAK</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2437.00	106.64	-----	-----	101.90	30.45	6.92	32.63
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2389.50	47.10	74.00	-26.90	42.46	30.41	6.87	32.64	374 243 PEAK																																																																																
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2437.00	106.64	-----	-----	101.90	30.45	6.92	32.63	374 243 PEAK																																																																																
Avg																																																																																									
	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.76</td><td>36.22</td><td>54.00</td><td>-17.78</td><td>31.58</td><td>30.41</td><td>6.87</td><td>32.64</td><td>374 243 AVERAGE</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.76	36.22	54.00	-17.78	31.58	30.41	6.87	32.64	374 243 AVERAGE	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>99.07</td><td>-----</td><td>-----</td><td>94.32</td><td>30.45</td><td>6.92</td><td>32.62</td><td>374 243 AVERAGE</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2437.00	99.07	-----	-----	94.32	30.45	6.92	32.62
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2389.76	36.22	54.00	-17.78	31.58	30.41	6.87	32.64	374 243 AVERAGE																																																																																
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2437.00	99.07	-----	-----	94.32	30.45	6.92	32.62	374 243 AVERAGE																																																																																







Mode	5																																																	
	Band Edge - R																																																	
	2400-2483.5_802.11g_CH06_2437MHz																																																	
ANT	4																																																	
Pol.	Vertical					Fundamental																																												
Peak	Date: 2026-01-06 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2484.75</td><td>47.84</td><td>74.00</td><td>-26.16</td><td>42.98</td><td>30.49</td><td>6.98</td><td>32.61</td><td>374</td><td>243</td><td>PEAK</td></tr></tbody></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2484.75	47.84	74.00	-26.16	42.98	30.49	6.98	32.61	374	243	PEAK	Blank				
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																									
1	2484.75	47.84	74.00	-26.16	42.98	30.49	6.98	32.61	374	243	PEAK																																							
Avg	Date: 2026-01-06 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.75</td><td>37.17</td><td>54.00</td><td>-16.83</td><td>32.31</td><td>30.49</td><td>6.98</td><td>32.61</td><td>374</td><td>243</td><td>AVERAGE</td></tr></tbody></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.75	37.17	54.00	-16.83	32.31	30.49	6.98	32.61	374	243	AVERAGE	Blank				
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																									
1	2483.75	37.17	54.00	-16.83	32.31	30.49	6.98	32.61	374	243	AVERAGE																																							







Mode	5																																																																																																																															
	Harmonic																																																																																																																															
	2400-2483.5_802.11g_CH06_2437MHz																																																																																																																															
ANT	4																																																																																																																															
Pol.	Horizontal						Vertical																																																																																																																									
Peak Avg																																																																																																																																
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>45.21</td><td>74.00</td><td>-28.79</td><td>52.04</td><td>35.52</td><td>10.27</td><td>52.62</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>7311.00</td><td>45.85</td><td>74.00</td><td>-28.15</td><td>49.59</td><td>36.47</td><td>12.01</td><td>52.22</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	45.21	74.00	-28.79	52.04	35.52	10.27	52.62	---	---	Peak	2	7311.00	45.85	74.00	-28.15	49.59	36.47	12.01	52.22	---	---	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>48.53</td><td>74.00</td><td>-25.47</td><td>55.36</td><td>35.52</td><td>10.27</td><td>52.62</td><td>148</td><td>313</td><td>Peak</td></tr><tr><td>2</td><td>4874.00</td><td>38.21</td><td>54.00</td><td>-15.79</td><td>45.04</td><td>35.52</td><td>10.27</td><td>52.62</td><td>148</td><td>313</td><td>Average</td></tr><tr><td>3</td><td>7311.00</td><td>45.79</td><td>74.00</td><td>-28.21</td><td>49.53</td><td>36.47</td><td>12.01</td><td>52.22</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	48.53	74.00	-25.47	55.36	35.52	10.27	52.62	148	313	Peak	2	4874.00	38.21	54.00	-15.79	45.04	35.52	10.27	52.62	148	313	Average	3	7311.00	45.79	74.00	-28.21	49.53	36.47	12.01	52.22	---	---	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																						
1	4874.00	45.21	74.00	-28.79	52.04	35.52	10.27	52.62	---	---	Peak																																																																																																																					
2	7311.00	45.85	74.00	-28.15	49.59	36.47	12.01	52.22	---	---	Peak																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																						
1	4874.00	48.53	74.00	-25.47	55.36	35.52	10.27	52.62	148	313	Peak																																																																																																																					
2	4874.00	38.21	54.00	-15.79	45.04	35.52	10.27	52.62	148	313	Average																																																																																																																					
3	7311.00	45.79	74.00	-28.21	49.53	36.47	12.01	52.22	---	---	Peak																																																																																																																					



Mode	6																																																																																										
	Band Edge																																																																																										
	2400-2483.5_802.11g_CH11_2462MHz																																																																																										
ANT	4																																																																																										
Pol.	Horizontal					Fundamental																																																																																					
Peak	 Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The plot shows a signal level starting at approximately 105 dBuV/m at 2462 MHz, decreasing to about 70 dBuV/m at 2483.5 MHz, and then dropping to around 40 dBuV/m at 2500 MHz. A red vertical line is at 2483.5 MHz, and a red horizontal line labeled 'PEAK_BE_74' is at approximately 70 dBuV/m. The date is 2026-01-06. <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.58</td><td>68.27</td><td>74.00</td><td>-5.73</td><td>63.41</td><td>30.49</td><td>6.98</td><td>32.61</td><td>316</td><td>271 PEAK</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.58	68.27	74.00	-5.73	63.41	30.49	6.98	32.61	316	271 PEAK	 Level (dBuV/m) vs Frequency (MHz) plot for Fundamental polarization. The plot shows a signal level starting at approximately 105 dBuV/m at 2462 MHz, decreasing to about 70 dBuV/m at 2483.5 MHz, and then dropping to around 40 dBuV/m at 2500 MHz. A red vertical line is at 2483.5 MHz, and a red horizontal line labeled 'PEAK_74' is at approximately 70 dBuV/m. The date is 2026-01-06. <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>106.59</td><td>-----</td><td>101.79</td><td>30.47</td><td>6.95</td><td>32.62</td><td>316</td><td>271 PEAK</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2462.00	106.59	-----	101.79	30.47	6.95	32.62	316	271 PEAK
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																		
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																		
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																		
1	2483.58	68.27	74.00	-5.73	63.41	30.49	6.98	32.61	316	271 PEAK																																																																																	
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																		
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																		
1	2462.00	106.59	-----	101.79	30.47	6.95	32.62	316	271 PEAK																																																																																		
Avg	 Level (dBuV/m) vs Frequency (MHz) plot for Horizontal polarization. The plot shows a signal level starting at approximately 105 dBuV/m at 2462 MHz, decreasing to about 70 dBuV/m at 2483.5 MHz, and then dropping to around 40 dBuV/m at 2500 MHz. A red vertical line is at 2483.5 MHz, and a red horizontal line labeled 'AVG_BE_54' is at approximately 54 dBuV/m. The date is 2026-01-06. <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.58</td><td>52.70</td><td>54.00</td><td>-1.30</td><td>47.84</td><td>30.49</td><td>6.98</td><td>32.61</td><td>316</td><td>271 AVERAGE</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.58	52.70	54.00	-1.30	47.84	30.49	6.98	32.61	316	271 AVERAGE	 Level (dBuV/m) vs Frequency (MHz) plot for Fundamental polarization. The plot shows a signal level starting at approximately 105 dBuV/m at 2462 MHz, decreasing to about 70 dBuV/m at 2483.5 MHz, and then dropping to around 40 dBuV/m at 2500 MHz. A red vertical line is at 2483.5 MHz, and a red horizontal line labeled 'AVG_54' is at approximately 54 dBuV/m. The date is 2026-01-06. <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>99.49</td><td>-----</td><td>94.69</td><td>30.47</td><td>6.95</td><td>32.62</td><td>316</td><td>271 AVERAGE</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2462.00	99.49	-----	94.69	30.47	6.95	32.62	316	271 AVERAGE
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																		
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																		
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																		
1	2483.58	52.70	54.00	-1.30	47.84	30.49	6.98	32.61	316	271 AVERAGE																																																																																	
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																		
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																		
1	2462.00	99.49	-----	94.69	30.47	6.95	32.62	316	271 AVERAGE																																																																																		



Mode	6																																																																																								
	Band Edge																																																																																								
	2400-2483.5_802.11g_CH11_2462MHz																																																																																								
ANT	4																																																																																								
Pol.	Vertical					Fundamental																																																																																			
Peak	 Level (dBuV/m) vs Frequency (MHz). Date: 2026-01-06. Peak at 2483.62 MHz, 64.18 dBuV/m. Limit line at 74.00 dB. Label: PEAK_BE_74.					 Level (dBuV/m) vs Frequency (MHz). Date: 2026-01-06. Peak at 2462.00 MHz, 103.44 dBuV/m. Limit line at 74.00 dB. Label: PEAK_74.																																																																																			
	<table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.62</td><td>64.18</td><td>74.00</td><td>-9.82</td><td>59.32</td><td>30.49</td><td>6.98</td><td>32.61</td><td>362 252 PEAK</td></tr></tbody></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.62	64.18	74.00	-9.82	59.32	30.49	6.98	32.61	362 252 PEAK	<table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2462.00</td><td>103.44</td><td>-----</td><td>98.64</td><td>30.47</td><td>6.95</td><td>32.62</td><td>362</td><td>252 PEAK</td></tr></tbody></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2462.00	103.44	-----	98.64	30.47	6.95	32.62	362
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2483.62	64.18	74.00	-9.82	59.32	30.49	6.98	32.61	362 252 PEAK																																																																																
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2462.00	103.44	-----	98.64	30.47	6.95	32.62	362	252 PEAK																																																																																
Avg	 Level (dBuV/m) vs Frequency (MHz). Date: 2026-01-06. Average at 2483.51 MHz, 49.00 dBuV/m. Limit line at 54.00 dB. Label: AVG_BE_54.					 Level (dBuV/m) vs Frequency (MHz). Date: 2026-01-06. Average at 2462.00 MHz, 96.22 dBuV/m. Limit line at 54.00 dB. Label: AVG_54.																																																																																			
	<table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.51</td><td>49.00</td><td>54.00</td><td>-5.00</td><td>44.14</td><td>30.49</td><td>6.98</td><td>32.61</td><td>362 252 AVERAGE</td></tr></tbody></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.51	49.00	54.00	-5.00	44.14	30.49	6.98	32.61	362 252 AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2462.00</td><td>96.22</td><td>-----</td><td>91.42</td><td>30.47</td><td>6.95</td><td>32.62</td><td>362</td><td>252 AVERAGE</td></tr></tbody></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2462.00	96.22	-----	91.42	30.47	6.95	32.62	362
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2483.51	49.00	54.00	-5.00	44.14	30.49	6.98	32.61	362 252 AVERAGE																																																																																
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																																
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																
1	2462.00	96.22	-----	91.42	30.47	6.95	32.62	362	252 AVERAGE																																																																																







Mode	6																																																																																																																														
	Harmonic																																																																																																																														
	2400-2483.5_802.11g_CH11_2462MHz																																																																																																																														
ANT	4																																																																																																																														
Pol.	Horizontal						Vertical																																																																																																																								
Peak Avg																																																																																																																															
	<table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th></th><th>dB</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4924.00</td><td>45.09</td><td>74.00</td><td>-28.91</td><td></td><td>51.79</td><td>35.63</td><td>10.32</td><td>52.65</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>7386.00</td><td>46.23</td><td>74.00</td><td>-27.77</td><td></td><td>49.94</td><td>36.56</td><td>11.98</td><td>52.25</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB		dB	deg		1	4924.00	45.09	74.00	-28.91		51.79	35.63	10.32	52.65	---	---	Peak	2	7386.00	46.23	74.00	-27.77		49.94	36.56	11.98	52.25	---	---	Peak	<table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th></th><th>dB</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4924.00</td><td>52.19</td><td>74.00</td><td>-21.81</td><td></td><td>58.89</td><td>35.63</td><td>10.32</td><td>52.65</td><td>143</td><td>314</td><td>Peak</td></tr><tr><td>2</td><td>4924.00</td><td>41.92</td><td>54.00</td><td>-12.08</td><td></td><td>48.62</td><td>35.63</td><td>10.32</td><td>52.65</td><td>143</td><td>314</td><td>Average</td></tr><tr><td>3</td><td>7386.00</td><td>45.29</td><td>74.00</td><td>-28.71</td><td></td><td>49.00</td><td>36.56</td><td>11.98</td><td>52.25</td><td>---</td><td>---</td><td>Peak</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB		dB	deg		1	4924.00	52.19	74.00	-21.81		58.89	35.63	10.32	52.65	143	314	Peak	2	4924.00	41.92	54.00	-12.08		48.62	35.63	10.32	52.65	143	314	Average	3	7386.00	45.29	74.00	-28.71		49.00	36.56	11.98	52.25	---	---
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB		dB	deg																																																																																																																				
1	4924.00	45.09	74.00	-28.91		51.79	35.63	10.32	52.65	---	---	Peak																																																																																																																			
2	7386.00	46.23	74.00	-27.77		49.94	36.56	11.98	52.25	---	---	Peak																																																																																																																			
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB		dB	deg																																																																																																																				
1	4924.00	52.19	74.00	-21.81		58.89	35.63	10.32	52.65	143	314	Peak																																																																																																																			
2	4924.00	41.92	54.00	-12.08		48.62	35.63	10.32	52.65	143	314	Average																																																																																																																			
3	7386.00	45.29	74.00	-28.71		49.00	36.56	11.98	52.25	---	---	Peak																																																																																																																			



Mode	7																																																																																	
	Band Edge																																																																																	
	2400-2483.5_802.11n HT20_CH01_2412MHz																																																																																	
ANT	4																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.95</td><td>67.93</td><td>74.00</td><td>-6.07</td><td>63.29</td><td>30.41</td><td>6.87</td><td>32.64</td><td>341</td><td>283</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.95	67.93	74.00	-6.07	63.29	30.41	6.87	32.64	341	283	PEAK	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) PEAK_74 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>104.85</td><td>-----</td><td>-----</td><td>100.17</td><td>30.43</td><td>6.89</td><td>32.64</td><td>341</td><td>283</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2412.00	104.85	-----	-----	100.17	30.43	6.89	32.64	341	283	PEAK
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.95	67.93	74.00	-6.07	63.29	30.41	6.87	32.64	341	283	PEAK																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2412.00	104.85	-----	-----	100.17	30.43	6.89	32.64	341	283	PEAK																																																																							
Avg	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.95</td><td>53.37</td><td>54.00</td><td>-0.63</td><td>48.73</td><td>30.41</td><td>6.87</td><td>32.64</td><td>341</td><td>283</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.95	53.37	54.00	-0.63	48.73	30.41	6.87	32.64	341	283	AVERAGE	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) AVG_54 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>97.49</td><td>-----</td><td>-----</td><td>92.81</td><td>30.43</td><td>6.89</td><td>32.64</td><td>341</td><td>283</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2412.00	97.49	-----	-----	92.81	30.43	6.89	32.64	341	283	AVERAGE
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.95	53.37	54.00	-0.63	48.73	30.41	6.87	32.64	341	283	AVERAGE																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2412.00	97.49	-----	-----	92.81	30.43	6.89	32.64	341	283	AVERAGE																																																																							



Mode	7																																																																																	
	Band Edge																																																																																	
	2400-2483.5_802.11n HT20_CH01_2412MHz																																																																																	
ANT	4																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2026-01-06  Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.82</td><td>63.40</td><td>74.00</td><td>-10.60</td><td>58.76</td><td>30.41</td><td>6.87</td><td>32.64</td><td>342 221 PEAK</td></tr></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark		MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	2389.82	63.40	74.00	-10.60	58.76	30.41	6.87	32.64	342 221 PEAK	Level (dBuV/m) Date: 2026-01-06  Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>100.13</td><td>-----</td><td>95.45</td><td>30.43</td><td>6.89</td><td>32.64</td><td>342</td><td>221 PEAK</td></tr></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark		MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	2412.00	100.13	-----	95.45	30.43	6.89	32.64	342	221 PEAK
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
	MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.82	63.40	74.00	-10.60	58.76	30.41	6.87	32.64	342 221 PEAK																																																																									
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
	MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2412.00	100.13	-----	95.45	30.43	6.89	32.64	342	221 PEAK																																																																									
Avg	Level (dBuV/m) Date: 2026-01-06  Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>49.60</td><td>54.00</td><td>-4.40</td><td>44.96</td><td>30.41</td><td>6.87</td><td>32.64</td><td>342 221 AVERAGE</td></tr></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark		MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	2389.95	49.60	54.00	-4.40	44.96	30.41	6.87	32.64	342 221 AVERAGE	Level (dBuV/m) Date: 2026-01-06  Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>92.91</td><td>-----</td><td>88.23</td><td>30.43</td><td>6.89</td><td>32.64</td><td>342</td><td>221 AVERAGE</td></tr></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark		MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	2412.00	92.91	-----	88.23	30.43	6.89	32.64	342	221 AVERAGE
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
	MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.95	49.60	54.00	-4.40	44.96	30.41	6.87	32.64	342 221 AVERAGE																																																																									
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
	MHz	dBuV/m	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2412.00	92.91	-----	88.23	30.43	6.89	32.64	342	221 AVERAGE																																																																									



Mode	7																																																																																																																																	
	Harmonic																																																																																																																																	
	2400-2483.5_802.11n HT20_CH01_2412MHz																																																																																																																																	
ANT	4																																																																																																																																	
Pol.	Horizontal						Vertical																																																																																																																											
Peak Avg	Horizontal Polarization Spectrum Plot showing Level (dBuV/m) vs Frequency (MHz). The plot includes a blue signal line, a red limit line at 74.00 dBuV/m (PEAK_74), and a red average line at 54.00 dBuV/m (AVG_54). The signal level is approximately 47.74 dBuV/m at 4824.00 MHz.						Vertical Polarization Spectrum Plot showing Level (dBuV/m) vs Frequency (MHz). The plot includes a blue signal line, a red limit line at 74.00 dBuV/m (PEAK_74), and a red average line at 54.00 dBuV/m (AVG_54). The signal level is approximately 50.10 dBuV/m at 4824.00 MHz.																																																																																																																											
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4824.00</td><td>47.74</td><td>74.00</td><td>-26.26</td><td>54.76</td><td>35.41</td><td>10.16</td><td>52.59</td><td>225</td><td>156</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>38.10</td><td>54.00</td><td>-15.90</td><td>45.12</td><td>35.41</td><td>10.16</td><td>52.59</td><td>225</td><td>156</td><td>Average</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	4824.00	47.74	74.00	-26.26	54.76	35.41	10.16	52.59	225	156	Peak	2	4824.00	38.10	54.00	-15.90	45.12	35.41	10.16	52.59	225	156	Average	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4824.00</td><td>50.10</td><td>74.00</td><td>-23.90</td><td>57.12</td><td>35.41</td><td>10.16</td><td>52.59</td><td>150</td><td>311</td><td>Peak</td></tr><tr><td>2</td><td>4824.00</td><td>39.96</td><td>54.00</td><td>-14.04</td><td>46.98</td><td>35.41</td><td>10.16</td><td>52.59</td><td>150</td><td>311</td><td>Average</td></tr></table>								Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	4824.00	50.10	74.00	-23.90	57.12	35.41	10.16	52.59	150	311	Peak	2	4824.00	39.96	54.00	-14.04	46.98	35.41	10.16	52.59	150	311	Average
			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																									
1	4824.00	47.74	74.00	-26.26	54.76	35.41	10.16	52.59	225	156	Peak																																																																																																																							
2	4824.00	38.10	54.00	-15.90	45.12	35.41	10.16	52.59	225	156	Average																																																																																																																							
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																									
1	4824.00	50.10	74.00	-23.90	57.12	35.41	10.16	52.59	150	311	Peak																																																																																																																							
2	4824.00	39.96	54.00	-14.04	46.98	35.41	10.16	52.59	150	311	Average																																																																																																																							







Mode	8																																																																																	
	Band Edge - L																																																																																	
	2400-2483.5_802.11n HT20_CH06_2437MHz																																																																																	
ANT	4																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.76</td><td>55.61</td><td>74.00</td><td>-18.39</td><td>50.97</td><td>30.41</td><td>6.87</td><td>32.64</td><td>373</td><td>280</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.76	55.61	74.00	-18.39	50.97	30.41	6.87	32.64	373	280	PEAK	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) PEAK_74 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2437.00</td><td>106.94</td><td>-----</td><td>-----</td><td>102.20</td><td>30.45</td><td>6.92</td><td>32.63</td><td>373</td><td>280</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	106.94	-----	-----	102.20	30.45	6.92	32.63	373	280	PEAK
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.76	55.61	74.00	-18.39	50.97	30.41	6.87	32.64	373	280	PEAK																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2437.00	106.94	-----	-----	102.20	30.45	6.92	32.63	373	280	PEAK																																																																							
Avg	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.76</td><td>38.57</td><td>54.00</td><td>-15.43</td><td>33.93</td><td>30.41</td><td>6.87</td><td>32.64</td><td>373</td><td>280</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.76	38.57	54.00	-15.43	33.93	30.41	6.87	32.64	373	280	AVERAGE	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) AVG_54 <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2437.00</td><td>100.06</td><td>-----</td><td>-----</td><td>95.32</td><td>30.45</td><td>6.92</td><td>32.63</td><td>373</td><td>280</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	100.06	-----	-----	95.32	30.45	6.92	32.63	373	280	AVERAGE
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.76	38.57	54.00	-15.43	33.93	30.41	6.87	32.64	373	280	AVERAGE																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2437.00	100.06	-----	-----	95.32	30.45	6.92	32.63	373	280	AVERAGE																																																																							



Mode	8																																																	
	Band Edge - R																																																	
	2400-2483.5_802.11n HT20_CH06_2437MHz																																																	
ANT	4																																																	
Pol.	Horizontal					Fundamental																																												
Peak	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.75</td><td>50.72</td><td>74.00</td><td>-23.28</td><td>45.86</td><td>30.49</td><td>6.98</td><td>32.61</td><td>373</td><td>280</td><td>PEAK</td></tr></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.75	50.72	74.00	-23.28	45.86	30.49	6.98	32.61	373	280	PEAK	Blank				
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																									
1	2483.75	50.72	74.00	-23.28	45.86	30.49	6.98	32.61	373	280	PEAK																																							
Avg	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.56</td><td>39.61</td><td>54.00</td><td>-14.39</td><td>34.75</td><td>30.49</td><td>6.98</td><td>32.61</td><td>373</td><td>280</td><td>AVERAGE</td></tr></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.56	39.61	54.00	-14.39	34.75	30.49	6.98	32.61	373	280	AVERAGE	Blank				
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																									
1	2483.56	39.61	54.00	-14.39	34.75	30.49	6.98	32.61	373	280	AVERAGE																																							





Mode	8																																																																																	
	Band Edge - L																																																																																	
	2400-2483.5_802.11n HT20_CH06_2437MHz																																																																																	
ANT	4																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2026-01-06  23102335.42360.82386.22411.62437 017.535.052.570.087.5105.0122.5140 <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.12</td><td>52.96</td><td>74.00</td><td>-21.04</td><td>48.33</td><td>30.41</td><td>6.86</td><td>32.64</td><td>339 254 PEAK</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.12	52.96	74.00	-21.04	48.33	30.41	6.86	32.64	339 254 PEAK	Level (dBuV/m) Date: 2026-01-06  10001400.1800.2200.2600.3000 017.535.052.570.087.5105.0122.5140 <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2437.00</td><td>105.18</td><td>-----</td><td>-----</td><td>100.43</td><td>30.45</td><td>6.92</td><td>32.62</td><td>339 254 PEAK</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2437.00	105.18	-----	-----	100.43	30.45	6.92	32.62	339 254 PEAK
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.12	52.96	74.00	-21.04	48.33	30.41	6.86	32.64	339 254 PEAK																																																																									
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2437.00	105.18	-----	-----	100.43	30.45	6.92	32.62	339 254 PEAK																																																																									
Avg	Level (dBuV/m) Date: 2026-01-06  23102335.42360.82386.22411.62437 017.535.052.570.087.5105.0122.5140 <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.88</td><td>39.59</td><td>54.00</td><td>-14.41</td><td>34.95</td><td>30.41</td><td>6.87</td><td>32.64</td><td>339 254 AVERAGE</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.88	39.59	54.00	-14.41	34.95	30.41	6.87	32.64	339 254 AVERAGE	Level (dBuV/m) Date: 2026-01-06  10001400.1800.2200.2600.3000 017.535.052.570.087.5105.0122.5140 <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2437.00</td><td>98.11</td><td>-----</td><td>-----</td><td>93.36</td><td>30.45</td><td>6.92</td><td>32.62</td><td>339 254 AVERAGE</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2437.00	98.11	-----	-----	93.36	30.45	6.92	32.62	339 254 AVERAGE
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.88	39.59	54.00	-14.41	34.95	30.41	6.87	32.64	339 254 AVERAGE																																																																									
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2437.00	98.11	-----	-----	93.36	30.45	6.92	32.62	339 254 AVERAGE																																																																									



Mode	8									
	Band Edge - R									
	2400-2483.5_802.11n HT20_CH06_2437MHz									
ANT	4									
Pol.	Vertical					Fundamental				
Peak	</									







Mode	8																																																																																																																																																																																
	Harmonic																																																																																																																																																																																
	2400-2483.5_802.11n_HT20_CH06_2437MHz																																																																																																																																																																																
ANT	4																																																																																																																																																																																
Pol.	Horizontal							Vertical																																																																																																																																																																									
Peak Avg																																																																																																																																																																																	
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th colspan="2">Ant</th><th colspan="2">Cable Preamp</th><th colspan="2">APos</th><th colspan="2">TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th><th></th></tr><tr><td>1</td><td>4874.00</td><td>44.52</td><td>74.00</td><td>-29.48</td><td>51.35</td><td>35.52</td><td>10.27</td><td>52.62</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td><td></td></tr><tr><td>2</td><td>7311.00</td><td>45.66</td><td>74.00</td><td>-28.34</td><td>49.40</td><td>36.47</td><td>12.01</td><td>52.22</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td><td></td></tr></table>									Limit		Read		Ant		Cable Preamp		APos		TPos		Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor								MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg				1	4874.00	44.52	74.00	-29.48	51.35	35.52	10.27	52.62	---	---	---	---	Peak		2	7311.00	45.66	74.00	-28.34	49.40	36.47	12.01	52.22	---	---	---	---	Peak		<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th colspan="2">Ant</th><th colspan="2">Cable Preamp</th><th colspan="2">APos</th><th colspan="2">TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th><th></th></tr><tr><td>1</td><td>4874.00</td><td>49.07</td><td>74.00</td><td>-24.93</td><td>55.90</td><td>35.52</td><td>10.27</td><td>52.62</td><td>150</td><td>353</td><td>Peak</td><td></td><td></td><td></td></tr><tr><td>2</td><td>4874.00</td><td>38.07</td><td>54.00</td><td>-15.93</td><td>44.90</td><td>35.52</td><td>10.27</td><td>52.62</td><td>150</td><td>353</td><td>Average</td><td></td><td></td><td></td></tr><tr><td>3</td><td>7311.00</td><td>45.28</td><td>74.00</td><td>-28.72</td><td>49.02</td><td>36.47</td><td>12.01</td><td>52.22</td><td>---</td><td>---</td><td>---</td><td>---</td><td>Peak</td><td></td></tr></table>									Limit		Read		Ant		Cable Preamp		APos		TPos		Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor								MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg				1	4874.00	49.07	74.00	-24.93	55.90	35.52	10.27	52.62	150	353	Peak				2	4874.00	38.07	54.00	-15.93	44.90	35.52	10.27	52.62	150	353	Average				3	7311.00	45.28	74.00	-28.72	49.02	36.47	12.01	52.22	---	---	---	---	Peak	
			Limit		Read		Ant		Cable Preamp		APos		TPos		Remark																																																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																						
1	4874.00	44.52	74.00	-29.48	51.35	35.52	10.27	52.62	---	---	---	---	Peak																																																																																																																																																																				
2	7311.00	45.66	74.00	-28.34	49.40	36.47	12.01	52.22	---	---	---	---	Peak																																																																																																																																																																				
		Limit		Read		Ant		Cable Preamp		APos		TPos		Remark																																																																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																						
1	4874.00	49.07	74.00	-24.93	55.90	35.52	10.27	52.62	150	353	Peak																																																																																																																																																																						
2	4874.00	38.07	54.00	-15.93	44.90	35.52	10.27	52.62	150	353	Average																																																																																																																																																																						
3	7311.00	45.28	74.00	-28.72	49.02	36.47	12.01	52.22	---	---	---	---	Peak																																																																																																																																																																				





Mode	9																																																																																																					
	Band Edge																																																																																																					
	2400-2483.5_802.11n HT20_CH11_2462MHz																																																																																																					
ANT	4																																																																																																					
Pol.	Horizontal																																																																																																					
Peak	Fundamental																																																																																																					
	Level (dBuV/m) Date: 2026-01-06 PEAK_BE_74 Frequency (MHz)											Level (dBuV/m) Date: 2026-01-06 PEAK_74 Frequency (MHz)																																																																																										
	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.51</td><td>69.65</td><td>74.00</td><td>-4.35</td><td>64.79</td><td>30.49</td><td>6.98</td><td>32.61</td><td>324 280 PEAK</td></tr></table>												Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.51	69.65	74.00	-4.35	64.79	30.49	6.98	32.61	324 280 PEAK	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>107.44</td><td>-----</td><td>-----</td><td>102.63</td><td>30.47</td><td>6.95</td><td>32.61</td><td>324 280 PEAK</td></tr></table>												Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2462.00	107.44	-----	-----	102.63	30.47	6.95	32.61	324 280 PEAK
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																														
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark																																																																																													
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																													
1	2483.51	69.65	74.00	-4.35	64.79	30.49	6.98	32.61	324 280 PEAK																																																																																													
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																														
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark																																																																																													
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																													
1	2462.00	107.44	-----	-----	102.63	30.47	6.95	32.61	324 280 PEAK																																																																																													
Avg	Level (dBuV/m) Date: 2026-01-07 AVG_BE_54 Frequency (MHz)											Level (dBuV/m) Date: 2026-01-06 AVG_54 Frequency (MHz)																																																																																										
	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.77</td><td>53.49</td><td>54.00</td><td>-0.51</td><td>48.63</td><td>30.49</td><td>6.98</td><td>32.61</td><td>324 280 AVERAGE</td></tr></table>												Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.77	53.49	54.00	-0.51	48.63	30.49	6.98	32.61	324 280 AVERAGE	<table><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>100.53</td><td>-----</td><td>-----</td><td>95.73</td><td>30.47</td><td>6.95</td><td>32.62</td><td>324 280 AVERAGE</td></tr></table>												Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2462.00	100.53	-----	-----	95.73	30.47	6.95	32.62	324 280 AVERAGE
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																													
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark																																																																																													
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																													
1	2483.77	53.49	54.00	-0.51	48.63	30.49	6.98	32.61	324 280 AVERAGE																																																																																													
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																														
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		Remark																																																																																													
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																													
1	2462.00	100.53	-----	-----	95.73	30.47	6.95	32.62	324 280 AVERAGE																																																																																													



Mode	9																																																																																	
	Band Edge																																																																																	
	2400-2483.5_802.11n HT20_CH11_2462MHz																																																																																	
ANT	4																																																																																	
Pol.	Vertical	Fundamental																																																																																
Peak	Date: 2026-01-06  Level (dBuV/m) Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.74</td><td>65.61</td><td>74.00</td><td>-8.39</td><td>60.75</td><td>30.49</td><td>6.98</td><td>32.61</td><td>362</td><td>261</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.74	65.61	74.00	-8.39	60.75	30.49	6.98	32.61	362	261	PEAK	Date: 2026-01-06  Level (dBuV/m) Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2462.00</td><td>102.81</td><td>74.00</td><td>-28.19</td><td>98.00</td><td>30.47</td><td>6.95</td><td>32.61</td><td>362</td><td>261</td><td>PEAK</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2462.00	102.81	74.00	-28.19	98.00	30.47	6.95	32.61	362	261	PEAK
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2483.74	65.61	74.00	-8.39	60.75	30.49	6.98	32.61	362	261	PEAK																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2462.00	102.81	74.00	-28.19	98.00	30.47	6.95	32.61	362	261	PEAK																																																																							
Avg	Date: 2026-01-06  Level (dBuV/m) Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.55</td><td>50.00</td><td>54.00</td><td>-4.00</td><td>45.14</td><td>30.49</td><td>6.98</td><td>32.61</td><td>362</td><td>261</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.55	50.00	54.00	-4.00	45.14	30.49	6.98	32.61	362	261	AVERAGE	Date: 2026-01-06  Level (dBuV/m) Frequency (MHz) <table><thead><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2462.00</td><td>95.71</td><td>54.00</td><td>-41.71</td><td>90.91</td><td>30.47</td><td>6.95</td><td>32.62</td><td>362</td><td>261</td><td>AVERAGE</td></tr></tbody></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2462.00	95.71	54.00	-41.71	90.91	30.47	6.95	32.62	362	261	AVERAGE
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2483.55	50.00	54.00	-4.00	45.14	30.49	6.98	32.61	362	261	AVERAGE																																																																							
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2462.00	95.71	54.00	-41.71	90.91	30.47	6.95	32.62	362	261	AVERAGE																																																																							



Mode	9																																																																																																																																				
	Harmonic																																																																																																																																				
	2400-2483.5_802.11n HT20_CH11_2462MHz																																																																																																																																				
ANT	4																																																																																																																																				
Pol.	Horizontal								Vertical																																																																																																																												
Peak Avg																																																																																																																																					
	<table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4924.00</td><td>45.22</td><td>74.00</td><td>-28.78</td><td>51.92</td><td>35.63</td><td>10.32</td><td>52.65</td><td>---</td><td>---</td><td>Peak</td><td></td></tr><tr><td>2</td><td>7386.00</td><td>45.09</td><td>74.00</td><td>-28.91</td><td>48.80</td><td>36.56</td><td>11.98</td><td>52.25</td><td>---</td><td>---</td><td>Peak</td><td></td></tr></tbody></table>									Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4924.00	45.22	74.00	-28.78	51.92	35.63	10.32	52.65	---	---	Peak		2	7386.00	45.09	74.00	-28.91	48.80	36.56	11.98	52.25	---	---	Peak		<table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4924.00</td><td>50.86</td><td>74.00</td><td>-23.14</td><td>57.56</td><td>35.63</td><td>10.32</td><td>52.65</td><td>174</td><td>313</td><td>Peak</td><td></td></tr><tr><td>2</td><td>4924.00</td><td>40.27</td><td>54.00</td><td>-13.73</td><td>46.97</td><td>35.63</td><td>10.32</td><td>52.65</td><td>174</td><td>313</td><td>Average</td><td></td></tr><tr><td>3</td><td>7386.00</td><td>45.31</td><td>74.00</td><td>-28.69</td><td>49.02</td><td>36.56</td><td>11.98</td><td>52.25</td><td>---</td><td>---</td><td>Peak</td><td></td></tr></tbody></table>									Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4924.00	50.86	74.00	-23.14	57.56	35.63	10.32	52.65	174	313	Peak		2	4924.00	40.27	54.00	-13.73	46.97	35.63	10.32	52.65	174	313	Average		3	7386.00	45.31	74.00	-28.69	49.02	36.56	11.98	52.25	---	---	Peak	
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	4924.00	45.22	74.00	-28.78	51.92	35.63	10.32	52.65	---	---	Peak																																																																																																																										
2	7386.00	45.09	74.00	-28.91	48.80	36.56	11.98	52.25	---	---	Peak																																																																																																																										
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	4924.00	50.86	74.00	-23.14	57.56	35.63	10.32	52.65	174	313	Peak																																																																																																																										
2	4924.00	40.27	54.00	-13.73	46.97	35.63	10.32	52.65	174	313	Average																																																																																																																										
3	7386.00	45.31	74.00	-28.69	49.02	36.56	11.98	52.25	---	---	Peak																																																																																																																										



Mode	10																																																																																	
	Band Edge - L																																																																																	
	2400-2483.5_802.11n HT40_CH03_2422MHz																																																																																	
ANT	4																																																																																	
Pol.	Horizontal	Fundamental																																																																																
Peak	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.86</td><td>65.78</td><td>74.00</td><td>-8.22</td><td>61.14</td><td>30.41</td><td>6.87</td><td>32.64</td><td>341 280 PEAK</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.86	65.78	74.00	-8.22	61.14	30.41	6.87	32.64	341 280 PEAK	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2422.00</td><td>101.20</td><td>-----</td><td>96.49</td><td>30.44</td><td>6.90</td><td>32.63</td><td>341</td><td>280 PEAK</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2422.00	101.20	-----	96.49	30.44	6.90	32.63	341	280 PEAK
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.86	65.78	74.00	-8.22	61.14	30.41	6.87	32.64	341 280 PEAK																																																																									
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2422.00	101.20	-----	96.49	30.44	6.90	32.63	341	280 PEAK																																																																									
Avg	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.97</td><td>51.37</td><td>54.00</td><td>-2.63</td><td>46.73</td><td>30.41</td><td>6.87</td><td>32.64</td><td>341 280 AVERAGE</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2389.97	51.37	54.00	-2.63	46.73	30.41	6.87	32.64	341 280 AVERAGE	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2422.00</td><td>93.84</td><td>-----</td><td>89.12</td><td>30.44</td><td>6.91</td><td>32.63</td><td>341</td><td>280 AVERAGE</td></tr></tbody></table>		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2422.00	93.84	-----	89.12	30.44	6.91	32.63	341	280 AVERAGE
		Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																									
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2389.97	51.37	54.00	-2.63	46.73	30.41	6.87	32.64	341 280 AVERAGE																																																																									
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss Factor			Remark																																																																									
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																									
1	2422.00	93.84	-----	89.12	30.44	6.91	32.63	341	280 AVERAGE																																																																									



Mode	10																																																	
	Band Edge - R																																																	
	2400-2483.5_802.11n HT40_CH03_2422MHz																																																	
ANT	4																																																	
Pol.	Horizontal					Fundamental																																												
Peak	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.62</td><td>51.97</td><td>74.00</td><td>-22.03</td><td>47.11</td><td>30.49</td><td>6.98</td><td>32.61</td><td>341</td><td>280</td><td>PEAK</td></tr></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.62	51.97	74.00	-22.03	47.11	30.49	6.98	32.61	341	280	PEAK	Blank				
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																									
1	2483.62	51.97	74.00	-22.03	47.11	30.49	6.98	32.61	341	280	PEAK																																							
Avg	Level (dBuV/m) Date: 2026-01-06 Frequency (MHz) <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.54</td><td>38.57</td><td>54.00</td><td>-15.43</td><td>33.71</td><td>30.49</td><td>6.98</td><td>32.61</td><td>341</td><td>280</td><td>AVERAGE</td></tr></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2483.54	38.57	54.00	-15.43	33.71	30.49	6.98	32.61	341	280	AVERAGE	Blank				
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Remark																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																									
1	2483.54	38.57	54.00	-15.43	33.71	30.49	6.98	32.61	341	280	AVERAGE																																							