



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250400032011

Rev.: 01

Page: 1 of 78

Appendix B

Detailed Test Results

1. WCDMA
WCDMA Band II
WCDMA Band IV
WCDMA Band V
2. LTE
LTE Band 2
LTE Band 5
LTE Band 7
LTE Band 12
LTE Band 14
LTE Band 30
LTE Band 66
3. NR
NR Band n2
NR Band n5
NR Band n30
NR Band n66
NR Band n77
4. WIFI
WIFI 2.4G
WIFI 5G
5. BT
BT
6. NFC
NFC

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Wireless Laboratory

South of No. 6 Plant, No. 1, RunSheng Road, Suzhou Industrial Park,
Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000

t (86-512) 6229 2980
www.sgs.com.cn


SN333A WCDMA II RMC 9538CH Right tilted

Communication System: Band 2; Frequency: 1907.600
Medium: HSL. Medium parameters used: $f=1907.600$ MHz; $\sigma=1.41$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.880 W/kg; SAR (10g) = 0.356 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.07 dB
SAR (1g) = 0.863 W/kg; SAR (10g) = 0.365 W/kg;
M2/M1 [%] 82.3
Dist 3dB Peak [mm] 6.0




SN333A WCDMA II RMC 9400CH Back side 15mm

Communication System: Band 2; Frequency: 1852.400
Medium: HSL. Medium parameters used: $f=1852.400$ MHz; $\sigma=1.39$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.544 W/kg; SAR (10g) = 0.306 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.01 dB
SAR (1g) = 0.525 W/kg; SAR (10g) = 0.225 W/kg;
M2/M1 [%] 83.4
Dist 3dB Peak [mm] 6.8




SN333A WCDMA II RMC 9538CH Top side 10mm

Communication System: Band 2; Frequency: 1907.600
Medium: HSL. Medium parameters used: $f=1907.600$ MHz; $\sigma=1.41$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.687 W/kg; SAR (10g) = 0.340 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.01 dB
SAR (1g) = 0.707 W/kg; SAR (10g) = 0.347 W/kg;
M2/M1 [%] 81.6
Dist 3dB Peak [mm] 8.4




SN333A WCDMA II RMC 9538CH Top side 0mm

Communication System: Band 2; Frequency: 1907.600
Medium: HSL. Medium parameters used: $f=1907.600$ MHz; $\sigma=1.41$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 4.96 W/kg; SAR (10g) = 1.99 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.13 dB
SAR (1g) = 5.06 W/kg; SAR (10g) = 1.88 W/kg;
M2/M1 [%] 71.0
Dist 3dB Peak [mm] 6.1



**SN333A WCDMA IV RMC 1513CH Right
tilted**

Communication System: Band 4; Frequency: 1752.600

Medium: HSL. Medium parameters used: $f=1752.600$ MHz; $\sigma=1.38$ S/m; $\epsilon_r=41.0$

DASY8 Configuration:

- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.910 W/kg; SAR (10g) = 0.404 W/kg;


Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm

Power Drift = -0.11 dB

SAR (1g) = 0.973 W/kg; SAR (10g) = 0.440 W/kg;

M2/M1 [%] 77.2

Dist 3dB Peak [mm] 6.1




SN333A WCDMA IV RMC 1412CH Front side 15mm

Communication System: Band 4; Frequency: 1732.400
Medium: HSL. Medium parameters used: $f=1732.400$ MHz; $\sigma=1.37$ S/m; $\epsilon_r=41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.434 W/kg; SAR (10g) = 0.253 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.09 dB
SAR (1g) = 0.445 W/kg; SAR (10g) = 0.265 W/kg;
M2/M1 [%] 83.7
Dist 3dB Peak [mm] 14.4




SN333A WCDMA IV RMC 1513CH Top side 10mm

Communication System: Band 4; Frequency: 1752.600
Medium: HSL. Medium parameters used: $f=1752.600$ MHz; $\sigma=1.38$ S/m; $\epsilon_r=41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.946 W/kg; SAR (10g) = 0.491 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.01 dB
SAR (1g) = 0.950 W/kg; SAR (10g) = 0.494 W/kg;
M2/M1 [%] 82.0
Dist 3dB Peak [mm] 9.6




SN333A WCDMA IV RMC 1513CH Top side 0mm

Communication System: Band 4; Frequency: 1752.600
Medium: HSL. Medium parameters used: $f=1752.600$ MHz; $\sigma=1.38$ S/m; $\epsilon_r=41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 5.35 W/kg; SAR (10g) = 2.26 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.05 dB
SAR (1g) = 5.27 W/kg; SAR (10g) = 2.07 W/kg;
M2/M1 [%] 69.9
Dist 3dB Peak [mm] 6.1




SN333A WCDMA V RMC 4182CH Right cheek

Communication System: Band 5; Frequency: 836.400
Medium: HSL. Medium parameters used: $f=836.400$ MHz; $\sigma=0.924$ S/m; $\epsilon_r=41.4$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.34, 10.34, 10.34); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.232 W/kg; SAR (10g) = 0.159 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.02 dB
SAR (1g) = 0.239 W/kg; SAR (10g) = 0.179 W/kg;
M2/M1 [%] 88.9
Dist 3dB Peak [mm] 21.4




SN333A WCDMA V RMC 4182CH Back side 15mm

Communication System: Band 5; Frequency: 836.400
Medium: HSL. Medium parameters used: $f=836.400$ MHz; $\sigma=0.924$ S/m; $\epsilon_r=41.4$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.34, 10.34, 10.34); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.219 W/kg; SAR (10g) = 0.155 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.01 dB
SAR (1g) = 0.233 W/kg; SAR (10g) = 0.174 W/kg;
M2/M1 [%] 85.5
Dist 3dB Peak [mm] > 16.0




SN333A WCDMA V RMC 4182CH Back side 10mm

Communication System: Band 5; Frequency: 836.400
Medium: HSL. Medium parameters used: $f = 836.400$ MHz; $\sigma = 0.924$ S/m; $\epsilon_r = 41.4$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.34, 10.34, 10.34); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.347 W/kg; SAR (10g) = 0.228 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.03 dB
SAR (1g) = 0.348 W/kg; SAR (10g) = 0.212 W/kg;
M2/M1 [%] 80.5
Dist 3dB Peak [mm] 14.4




SN333A LTE Band 2 20M QPSK 1RB0 19100CH Right tilted

Communication System: Band 2; Frequency: 1900.000
Medium: HSL. Medium parameters used: $f=1900.000$ MHz; $\sigma=1.40$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.854 W/kg; SAR (10g) = 0.353 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.16 dB
SAR (1g) = 0.852 W/kg; SAR (10g) = 0.361 W/kg;
M2/M1 [%] 81.6
Dist 3dB Peak [mm] 6.0




SN333A LTE Band 2 20M QPSK 1RB0 18900CH Back side 15mm

Communication System: Band 2; Frequency: 1880.000
Medium: HSL. Medium parameters used: $f=1880.000$ MHz; $\sigma=1.40$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.515 W/kg; SAR (10g) = 0.295 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.08 dB
SAR (1g) = 0.529 W/kg; SAR (10g) = 0.301 W/kg;
M2/M1 [%] 83.0
Dist 3dB Peak [mm] 13.0




SN333A LTE Band 2 20M QPSK 1RB0 19100CH Top side 10mm

Communication System: Band 2; Frequency: 1900.000
Medium: HSL. Medium parameters used: $f= 1900.000$ MHz; $\sigma= 1.40$ S/m; $\epsilon_r = 40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.798 W/kg; SAR (10g) = 0.394 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.06 dB
SAR (1g) = 0.822 W/kg; SAR (10g) = 0.404 W/kg;
M2/M1 [%] 81.4
Dist 3dB Peak [mm] 8.4




SN333A LTE Band 2 20M QPSK 1RB0 19100CH Top side 0mm

Communication System: Band 2; Frequency: 1900.000
Medium: HSL. Medium parameters used: $f=1900.000$ MHz; $\sigma=1.40$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 5.60 W/kg; SAR (10g) = 2.30 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.06 dB
SAR (1g) = 5.75 W/kg; SAR (10g) = 2.15 W/kg;
M2/M1 [%] 71.9
Dist 3dB Peak [mm] 6.9




SN333A LTE Band 5 10M QPSK 1RB0 20525CH Right cheek

Communication System: Band 5; Frequency: 836.500
Medium: HSL. Medium parameters used: $f = 836.500$ MHz; $\sigma = 0.924$ S/m; $\epsilon_r = 41.4$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.34, 10.34, 10.34); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.223 W/kg; SAR (10g) = 0.153 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.05 dB
SAR (1g) = 0.233 W/kg; SAR (10g) = 0.174 W/kg;
M2/M1 [%] 88.7
Dist 3dB Peak [mm] 22.4



SN333A LTE Band 5 10M QPSK 1RB0 20525CH Back side 15mm

Communication System: Band 5; Frequency: 836.500

Medium: HSL. Medium parameters used: $f = 836.500$ MHz; $\sigma = 0.924$ S/m; $\epsilon_r = 41.4$

DASY8 Configuration:

- Probe: EX3DV4 - SN7767; ConvF(10.34, 10.34, 10.34); Calibrated: 2024-12-31
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.210 W/kg; SAR (10g) = 0.149 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm

Power Drift = -0.03 dB


SAR (1g) = 0.222 W/kg; SAR (10g) = 0.165 W/kg;

M2/M1 [%]

85.9

Dist 3dB Peak [mm]

> 16.0



SN333A LTE Band 5 10M QPSK 1RB0 20525CH Back side 10mm

Communication System: Band 5; Frequency: 836.500

Medium: HSL. Medium parameters used: $f = 836.500$ MHz; $\sigma = 0.924$ S/m; $\epsilon_r = 41.4$

DASY8 Configuration:

- Probe: EX3DV4 - SN7767; ConvF(10.34, 10.34, 10.34); Calibrated: 2024-12-31
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm

SAR (1g) = 0.387 W/kg; SAR (10g) = 0.253 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm

Power Drift = -0.01 dB


SAR (1g) = 0.383 W/kg; SAR (10g) = 0.233 W/kg;

M2/M1 [%]

80.3

Dist 3dB Peak [mm]

14.0




SN333A LTE Band 7 20M QPSK 1RB0 21100CH Right tilted

Communication System: Band 7; Frequency: 2535.000
Medium: HSL. Medium parameters used: $f= 2535.000$ MHz; $\sigma= 1.87$ S/m; $\epsilon_r = 38.5$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.03, 8.03, 8.03); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.537 W/kg; SAR (10g) = 0.260 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = 0.03 dB
SAR (1g) = 0.634 W/kg; SAR (10g) = 0.259 W/kg;
M2/M1 [%] 75.8
Dist 3dB Peak [mm] 7.3




SN333A LTE Band 7 20M QPSK 1RB0 21100CH Back side 15mm

Communication System: Band 7; Frequency: 2535.000
Medium: HSL. Medium parameters used: $f=2535.000$ MHz; $\sigma=1.87$ S/m; $\epsilon_r=38.5$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.03, 8.03, 8.03); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.132 W/kg; SAR (10g) = 0.065 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.04 dB
SAR (1g) = 0.134 W/kg; SAR (10g) = 0.066 W/kg;
M2/M1 [%] 80.6
Dist 3dB Peak [mm] 12.4




SN333A LTE Band 7 20M QPSK 1RB0 21100CH Top side 10mm

Communication System: Band 7; Frequency: 2535.000
Medium: HSL. Medium parameters used: $f= 2535.000$ MHz; $\sigma= 1.87$ S/m; $\epsilon_r = 38.5$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.03, 8.03, 8.03); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 12.0 mm
SAR (1g) = 0.350 W/kg; SAR (10g) = 0.151 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.16 dB
SAR (1g) = 0.367 W/kg; SAR (10g) = 0.160 W/kg;
M2/M1 [%] 80.6
Dist 3dB Peak [mm] 8.0




SN333A LTE Band 12 10M QPSK 1RB0 23095CH Right cheek

Communication System: Band 12; Frequency: 707.500
Medium: HSL. Medium parameters used: $f=707.500$ MHz; $\sigma=0.904$ S/m; $\epsilon_r=42.2$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.76, 10.76, 10.76); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.191 W/kg; SAR (10g) = 0.135 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.03 dB
SAR (1g) = 0.189 W/kg; SAR (10g) = 0.145 W/kg;
M2/M1 [%] 91.1
Dist 3dB Peak [mm] 28.7




SN333A LTE Band 12 10M QPSK 1RB0 23095CH Back side 15mm

Communication System: Band 12; Frequency: 707.500
Medium: HSL. Medium parameters used: $f=707.500$ MHz; $\sigma=0.904$ S/m; $\epsilon_r=42.2$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.76, 10.76, 10.76); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.282 W/kg; SAR (10g) = 0.202 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.14 dB
SAR (1g) = 0.297 W/kg; SAR (10g) = 0.223 W/kg;
M2/M1 [%] 85.3
Dist 3dB Peak [mm] > 16.0



SN333A LTE Band 12 10M QPSK 1RB0 23095CH Right side 10mm

Communication System: Band 12; Frequency: 707.500

Medium: HSL. Medium parameters used: $f = 707.500$ MHz; $\sigma = 0.904$ S/m; $\epsilon_r = 42.2$

DASY8 Configuration:

- Probe: EX3DV4 - SN7767; ConvF(10.76, 10.76, 10.76); Calibrated: 2024-12-31
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 210.0 mm): Measurement Grid: 8.0 mm x 15.0 mm

SAR (1g) = 0.339 W/kg; SAR (10g) = 0.235 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm

Power Drift = 0.07 dB


SAR (1g) = 0.349 W/kg; SAR (10g) = 0.242 W/kg;

M2/M1 [%]

84.3

Dist 3dB Peak [mm]

> 16.0




SN333A LTE Band 14 10M QPSK 1RB0 23330CH Right cheek

Communication System: Band 14; Frequency: 793.000
Medium: HSL. Medium parameters used: $f=793.000$ MHz; $\sigma=0.923$ S/m; $\epsilon_r=41.7$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.76, 10.76, 10.76); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.161 W/kg; SAR (10g) = 0.111 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.06 dB
SAR (1g) = 0.170 W/kg; SAR (10g) = 0.129 W/kg;
M2/M1 [%] 91.2
Dist 3dB Peak [mm] 27.0




SN333A LTE Band 14 10M QPSK 1RB0 23330CH Back side 15mm

Communication System: Band 14; Frequency: 793.000
Medium: HSL. Medium parameters used: $f = 793.000$ MHz; $\sigma = 0.923$ S/m; $\epsilon_r = 41.7$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.76, 10.76, 10.76); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.192 W/kg; SAR (10g) = 0.136 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.03 dB
SAR (1g) = 0.201 W/kg; SAR (10g) = 0.150 W/kg;
M2/M1 [%] 86.9
Dist 3dB Peak [mm] > 16.0




SN333A LTE Band 14 10M QPSK 1RB0 23330CH Bottom side 10mm

Communication System: Band 14; Frequency: 793.000
Medium: HSL. Medium parameters used: $f=793.000$ MHz; $\sigma=0.923$ S/m; $\epsilon_r=41.7$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.76, 10.76, 10.76); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.268 W/kg; SAR (10g) = 0.159 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.02 dB
SAR (1g) = 0.256 W/kg; SAR (10g) = 0.139 W/kg;
M2/M1 [%] 72.6
Dist 3dB Peak [mm] 9.6




SN333A LTE Band 30 10M QPSK 1RB0 27710CH Right cheek

Communication System: Band 30; Frequency: 2310.000
Medium: HSL. Medium parameters used: $f=2310.000$ MHz; $\sigma=1.69$ S/m; $\epsilon_r=39.3$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.33, 8.33, 8.33); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.787 W/kg; SAR (10g) = 0.385 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = 0.07 dB
SAR (1g) = 0.991 W/kg; SAR (10g) = 0.402 W/kg;
M2/M1 [%] 77.7
Dist 3dB Peak [mm] 7.0




SN333A LTE Band 30 10M QPSK 1RB0 27710CH Back side 15mm

Communication System: Band 30; Frequency: 2310.000
Medium: HSL. Medium parameters used: $f=2310.000$ MHz; $\sigma=1.69$ S/m; $\epsilon_r=39.3$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.33, 8.33, 8.33); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.737 W/kg; SAR (10g) = 0.367 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.07 dB
SAR (1g) = 0.760 W/kg; SAR (10g) = 0.383 W/kg;
M2/M1 [%] 83.5
Dist 3dB Peak [mm] 10.0




SN333A LTE Band 30 10M QPSK 1RB0 27710CH Top side 10mm

Communication System: Band 30; Frequency: 2310.000
Medium: HSL. Medium parameters used: $f=2310.000$ MHz; $\sigma=1.69$ S/m; $\epsilon_r=39.3$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.33, 8.33, 8.33); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 12.0 mm
SAR (1g) = 0.840 W/kg; SAR (10g) = 0.373 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.02 dB
SAR (1g) = 0.903 W/kg; SAR (10g) = 0.403 W/kg;
M2/M1 [%] 79.9
Dist 3dB Peak [mm] 8.1




SN333A LTE Band 30 10M QPSK 1RB0 27710CH Top side 0mm

Communication System: Band 30; Frequency: 2310.000
Medium: HSL. Medium parameters used: $f=2310.000$ MHz; $\sigma=1.69$ S/m; $\epsilon_r=39.3$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.33, 8.33, 8.33); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 12.0 mm
SAR (1g) = 5.44 W/kg; SAR (10g) = 2.14 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.08 dB
SAR (1g) = 5.61 W/kg; SAR (10g) = 2.00 W/kg;
M2/M1 [%] 71.2
Dist 3dB Peak [mm] 5.0




SN333A LTE Band 66 20M QPSK 1RB0 132572CH Right tilted

Communication System: Band 66; Frequency: 1770.000
Medium: HSL. Medium parameters used: $f= 1770.000$ MHz; $\sigma= 1.39$ S/m; $\epsilon_r = 41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.763 W/kg; SAR (10g) = 0.340 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.16 dB
SAR (1g) = 0.790 W/kg; SAR (10g) = 0.355 W/kg;
M2/M1 [%] 77.1
Dist 3dB Peak [mm] 7.4




SN333A LTE Band 66 20M QPSK 1RB0 132322CH Front 15mm

Communication System: Band 66; Frequency: 1745.000
Medium: HSL. Medium parameters used: $f=1745.000$ MHz; $\sigma=1.38$ S/m; $\epsilon_r=41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.508 W/kg; SAR (10g) = 0.291 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.16 dB
SAR (1g) = 0.506 W/kg; SAR (10g) = 0.290 W/kg;
M2/M1 [%] 83.9
Dist 3dB Peak [mm] 14.1




SN333A LTE Band 66 20M QPSK 1RB0 132572CH Top side 10mm

Communication System: Band 66; Frequency: 1770.000
Medium: HSL. Medium parameters used: $f=1770.000$ MHz; $\sigma=1.39$ S/m; $\epsilon_r=41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.654 W/kg; SAR (10g) = 0.342 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.08 dB
SAR (1g) = 0.731 W/kg; SAR (10g) = 0.375 W/kg;
M2/M1 [%] 80.9
Dist 3dB Peak [mm] 9.6




SN333A LTE Band 66 20M QPSK 1RB0 132572CH Top side 0mm

Communication System: Band 66; Frequency: 1770.000
Medium: HSL. Medium parameters used: $f=1770.000$ MHz; $\sigma=1.39$ S/m; $\epsilon_r=41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 7.35 W/kg; SAR (10g) = 2.48 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.05 dB
SAR (1g) = 7.40 W/kg; SAR (10g) = 2.53 W/kg;
M2/M1 [%] 70.0
Dist 3dB Peak [mm] 6.1




SN333A 5G NR n2 20M QPSK 50RB28 380000CH Right tilted

Communication System: Band n2; Frequency: 1900.000
Medium: HSL. Medium parameters used: $f=1900.000$ MHz; $\sigma=1.40$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.846 W/kg; SAR (10g) = 0.363 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.09 dB
SAR (1g) = 0.823 W/kg; SAR (10g) = 0.353 W/kg;
M2/M1 [%] 78.1
Dist 3dB Peak [mm] 6.4




SN333A 5G NR n2 20M QPSK 50RB28 376000CH Back side 15mm

Communication System: Band n2; Frequency: 1880.000
Medium: HSL. Medium parameters used: $f=1880.000$ MHz; $\sigma=1.40$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.673 W/kg; SAR (10g) = 0.369 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.01 dB
SAR (1g) = 0.696 W/kg; SAR (10g) = 0.379 W/kg;
M2/M1 [%] 82.6
Dist 3dB Peak [mm] 10.3




SN333A 5G NR n2 20M QPSK 50RB28 380000CH Top side 10mm

Communication System: Band n2; Frequency: 1900.000
Medium: HSL. Medium parameters used: $f=1900.000$ MHz; $\sigma=1.40$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.768 W/kg; SAR (10g) = 0.379 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.03 dB
SAR (1g) = 0.810 W/kg; SAR (10g) = 0.395 W/kg;
M2/M1 [%] 81.8
Dist 3dB Peak [mm] 8.4




SN333A 5G NR n2 20M QPSK 1RB1 372000CH Top side 0mm

Communication System: Band n2; Frequency: 1860.000
Medium: HSL. Medium parameters used: $f=1860.000$ MHz; $\sigma=1.39$ S/m; $\epsilon_r=40.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.6, 8.6, 8.6); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 5.60 W/kg; SAR (10g) = 2.35 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.02 dB
SAR (1g) = 5.82 W/kg; SAR (10g) = 2.19 W/kg;
M2/M1 [%] 69.1
Dist 3dB Peak [mm] 6.9




SN333A 5G NR n5 20M QPSK 50RB28 167300CH Right cheek

Communication System: Band n5; Frequency: 836.500
Medium: HSL. Medium parameters used: $f=836.500$ MHz; $\sigma=0.924$ S/m; $\epsilon_r=41.4$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.34, 10.34, 10.34); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.148 W/kg; SAR (10g) = 0.101 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.02 dB
SAR (1g) = 0.157 W/kg; SAR (10g) = 0.122 W/kg;
M2/M1 [%] 92.1
Dist 3dB Peak [mm] 24.9




SN333A 5G NR n5 20M QPSK 50RB28 167300CH Back side 15mm

Communication System: Band n5; Frequency: 836.500
Medium: HSL. Medium parameters used: $f=836.500$ MHz; $\sigma=0.924$ S/m; $\epsilon_r=41.4$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.34, 10.34, 10.34); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.258 W/kg; SAR (10g) = 0.183 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.02 dB
SAR (1g) = 0.272 W/kg; SAR (10g) = 0.204 W/kg;
M2/M1 [%] 85.3
Dist 3dB Peak [mm] > 16.0




SN333A 5G NR n5 20M QPSK 50RB28 167300CH Back side 10mm

Communication System: Band n5; Frequency: 836.500
Medium: HSL. Medium parameters used: $f=836.500$ MHz; $\sigma=0.924$ S/m; $\epsilon_r=41.4$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(10.34, 10.34, 10.34); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.583 W/kg; SAR (10g) = 0.383 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.17 dB
SAR (1g) = 0.565 W/kg; SAR (10g) = 0.342 W/kg;
M2/M1 [%] 85.2
Dist 3dB Peak [mm] > 16.0




SN333A 5G NR n30 10M QPSK 1RB1 462000CH Right tilted

Communication System: Band n30; Frequency: 2310.000
Medium: HSL. Medium parameters used: $f= 2310.000$ MHz; $\sigma= 1.69$ S/m; $\epsilon_r = 39.3$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.33, 8.33, 8.33); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.723 W/kg; SAR (10g) = 0.335 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.17 dB
SAR (1g) = 0.908 W/kg; SAR (10g) = 0.361 W/kg;
M2/M1 [%] 80.5
Dist 3dB Peak [mm] 5.6




SN333A 5G NR n30 10M QPSK 1RB1 462000CH Back side 15mm

Communication System: Band n30; Frequency: 2310.000
Medium: HSL. Medium parameters used: $f=2310.000$ MHz; $\sigma=1.69$ S/m; $\epsilon_r=39.3$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.33, 8.33, 8.33); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.688 W/kg; SAR (10g) = 0.343 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.05 dB
SAR (1g) = 0.731 W/kg; SAR (10g) = 0.362 W/kg;
M2/M1 [%] 83.3
Dist 3dB Peak [mm] 9.0




SN333A 5G NR n30 10M QPSK 1RB1 462000CH Top side 10mm

Communication System: Band n30; Frequency: 2310.000
Medium: HSL. Medium parameters used: $f=2310.000$ MHz; $\sigma=1.69$ S/m; $\epsilon_r=39.3$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.33, 8.33, 8.33); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 12.0 mm
SAR (1g) = 0.818 W/kg; SAR (10g) = 0.357 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.07 dB
SAR (1g) = 0.829 W/kg; SAR (10g) = 0.367 W/kg;
M2/M1 [%] 80.5
Dist 3dB Peak [mm] 8.0




SN333A 5G NR n30 10M QPSK 1RB1 462000CH Top side 0mm

Communication System: Band n30; Frequency: 2310.000
Medium: HSL. Medium parameters used: $f=2310.000$ MHz; $\sigma=1.69$ S/m; $\epsilon_r=39.3$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.33, 8.33, 8.33); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 12.0 mm
SAR (1g) = 6.25 W/kg; SAR (10g) = 2.52 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.19 dB
SAR (1g) = 6.67 W/kg; SAR (10g) = 2.35 W/kg;
M2/M1 [%] 70.0
Dist 3dB Peak [mm] 5.6




SN333A 5G NR n66 40M QPSK 108RB54 349000CH Right tilted

Communication System: Band n66; Frequency: 1745.000
Medium: HSL. Medium parameters used: $f=1745.000$ MHz; $\sigma=1.38$ S/m; $\epsilon_r=41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.955 W/kg; SAR (10g) = 0.427 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.06 dB
SAR (1g) = 0.929 W/kg; SAR (10g) = 0.422 W/kg;
M2/M1 [%] 77.7
Dist 3dB Peak [mm] 6.9




SN333A 5G NR n66 40M QPSK 108RB54 349000CH Back side 15mm

Communication System: Band n66; Frequency: 1745.000
Medium: HSL. Medium parameters used: $f=1745.000$ MHz; $\sigma=1.38$ S/m; $\epsilon_r=41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.564 W/kg; SAR (10g) = 0.326 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = 0.11 dB
SAR (1g) = 0.558 W/kg; SAR (10g) = 0.315 W/kg;
M2/M1 [%] 83.2
Dist 3dB Peak [mm] 14.1




SN333A 5G NR n66 40M QPSK 108RB54 349000CH Top side 10mm

Communication System: Band n66; Frequency: 1745.000
Medium: HSL. Medium parameters used: $f=1745.000$ MHz; $\sigma=1.38$ S/m; $\epsilon_r=41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 0.899 W/kg; SAR (10g) = 0.474 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.03 dB
SAR (1g) = 0.927 W/kg; SAR (10g) = 0.491 W/kg;
M2/M1 [%] 82.4
Dist 3dB Peak [mm] 9.6




SN333A 5G NR n66 40M QPSK 108RB54 349000CH Top side 0mm

Communication System: Band n66; Frequency: 1745.000
Medium: HSL. Medium parameters used: $f=1745.000$ MHz; $\sigma=1.38$ S/m; $\epsilon_r=41.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.95, 8.95, 8.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 15.0 mm
SAR (1g) = 5.66 W/kg; SAR (10g) = 2.40 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 6.0 mm x 6.0 mm x 1.5 mm
Power Drift = -0.04 dB
SAR (1g) = 5.58 W/kg; SAR (10g) = 2.23 W/kg;
M2/M1 [%] 70.9
Dist 3dB Peak [mm] 6.6




SN333A 5G NR n77 100M QPSK 1RB1 633334CH Right tilted

Communication System: Band n77; Frequency: 3500.010
Medium: HSL. Medium parameters used: $f= 3500.010$ MHz; $\sigma= 2.96$ S/m; $\epsilon_r = 38.1$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(7.23, 7.23, 7.23); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.742 W/kg; SAR (10g) = 0.317 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = 0.07 dB
SAR (1g) = 0.734 W/kg; SAR (10g) = 0.313 W/kg;
M2/M1 [%] 78.4
Dist 3dB Peak [mm] 8.6




SN333A 5G NR n77 10M QPSK 135RB69 633334CH Front side 15mm

Communication System: Band n77; Frequency: 3500.010
Medium: HSL. Medium parameters used: $f=3500.010$ MHz; $\sigma=2.96$ S/m; $\epsilon_r=38.1$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(7.23, 7.23, 7.23); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.590 W/kg; SAR (10g) = 0.300 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = -0.07 dB
SAR (1g) = 0.551 W/kg; SAR (10g) = 0.269 W/kg;
M2/M1 [%] 73.7
Dist 3dB Peak [mm] 17.5




SN333A 5G NR n77 10M QPSK 135RB69 633334CH Left side 10mm

Communication System: Band n77; Frequency: 3500.010
Medium: HSL. Medium parameters used: $f= 3500.010$ MHz; $\sigma= 2.96$ S/m; $\epsilon_r = 38.1$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(7.23, 7.23, 7.23); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 200.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 0.599 W/kg; SAR (10g) = 0.273 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = -0.09 dB
SAR (1g) = 0.616 W/kg; SAR (10g) = 0.281 W/kg;
M2/M1 [%] 77.2
Dist 3dB Peak [mm] 11.2




SN333A 5G NR n77 10M QPSK 135RB69 633334CH Left side 0mm

Communication System: Band n77; Frequency: 3500.010
Medium: HSL. Medium parameters used: $f=3500.010$ MHz; $\sigma=2.96$ S/m; $\epsilon_r=38.1$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(7.23, 7.23, 7.23); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 200.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 4.97 W/kg; SAR (10g) = 1.53 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = -0.03 dB
SAR (1g) = 5.09 W/kg; SAR (10g) = 1.55 W/kg;
M2/M1 [%] 71.3
Dist 3dB Peak [mm] 5.1




SN333A 5G NR n77 100M QPSK 135RB69 656000CH Right tilted

Communication System: Band n77; Frequency: 3840.000
Medium: HSL. Medium parameters used: $f=3840.000$ MHz; $\sigma=3.30$ S/m; $\epsilon_r=37.2$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(6.95, 6.95, 6.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.820 W/kg; SAR (10g) = 0.333 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = 0.18 dB
SAR (1g) = 0.878 W/kg; SAR (10g) = 0.349 W/kg;
M2/M1 [%] 76.7
Dist 3dB Peak [mm] 8.0




SN333A 5G NR n77 10M QPSK 1RB1 656000CH Front 15mm

Communication System: Band n77; Frequency: 3840.000
Medium: HSL. Medium parameters used: $f=3840.000$ MHz; $\sigma=3.30$ S/m; $\epsilon_r=37.2$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(6.95, 6.95, 6.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.764 W/kg; SAR (10g) = 0.374 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = -0.01 dB
SAR (1g) = 0.701 W/kg; SAR (10g) = 0.354 W/kg;
M2/M1 [%] 79.8
Dist 3dB Peak [mm] 17.2




SN333A 5G NR n77 10M QPSK 1RB1 656000CH Left side 10mm

Communication System: Band n77; Frequency: 3840.000
Medium: HSL. Medium parameters used: $f= 3840.000$ MHz; $\sigma= 3.30$ S/m; $\epsilon_r = 37.2$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(6.95, 6.95, 6.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 200.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 0.799 W/kg; SAR (10g) = 0.356 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = -0.14 dB
SAR (1g) = 0.814 W/kg; SAR (10g) = 0.365 W/kg;
M2/M1 [%] 75.1
Dist 3dB Peak [mm] 11.5




SN333A 5G NR n77 10M QPSK 1RB1 656000CH Left side 0mm

Communication System: Band n77; Frequency: 3840.000
Medium: HSL. Medium parameters used: $f=3840.000$ MHz; $\sigma=3.30$ S/m; $\epsilon_r=37.2$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(6.95, 6.95, 6.95); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 200.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 7.18 W/kg; SAR (10g) = 2.17 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.4 mm
Power Drift = 0.06 dB
SAR (1g) = 7.70 W/kg; SAR (10g) = 2.23 W/kg;
M2/M1 [%] 69.8
Dist 3dB Peak [mm] 5.2




SN333A WIFI2.4G 802.11b 6CH Left tilted

Communication System: WLAN 2.4GHz; Frequency: 2437.000
Medium: HSL. Medium parameters used: $f= 2437.000$ MHz; $\sigma= 1.84$ S/m; $\epsilon_r = 38.8$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.03, 8.03, 8.03); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.853 W/kg; SAR (10g) = 0.423 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.01 dB
SAR (1g) = 0.881 W/kg; SAR (10g) = 0.428 W/kg;
M2/M1 [%] 77.2
Dist 3dB Peak [mm] 9.5




SN333A WIFI2.4G 802.11b 6CH Back side 15mm

Communication System: WLAN 2.4GHz; Frequency: 2437.000
Medium: HSL. Medium parameters used: $f= 2437.000$ MHz; $\sigma= 1.84$ S/m; $\epsilon_r = 38.8$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.03, 8.03, 8.03); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.148 W/kg; SAR (10g) = 0.080 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.01 dB
SAR (1g) = 0.148 W/kg; SAR (10g) = 0.080 W/kg;
M2/M1 [%] 81.2
Dist 3dB Peak [mm] 15.3




SN333A WIFI2.4G 802.11b 6CH Back side 10mm

Communication System: WLAN 2.4GHz; Frequency: 2437.000
Medium: HSL. Medium parameters used: $f= 2437.000$ MHz; $\sigma= 1.84$ S/m; $\epsilon_r = 38.8$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.03, 8.03, 8.03); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.294 W/kg; SAR (10g) = 0.157 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.08 dB
SAR (1g) = 0.306 W/kg; SAR (10g) = 0.158 W/kg;
M2/M1 [%] 80.7
Dist 3dB Peak [mm] 12.1




SN333A WIFI5G 802.11a 64CH Left cheek

Communication System: WLAN 5GHz; Frequency: 5320.000
Medium: HSL. Medium parameters used: $f= 5320.000$ MHz; $\sigma= 4.76$ S/m; $\epsilon_r = 36.3$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(5.73, 5.73, 5.73); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.765 W/kg; SAR (10g) = 0.265 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = 0.11 dB
SAR (1g) = 0.930 W/kg; SAR (10g) = 0.288 W/kg;
M2/M1 [%] 70.1
Dist 3dB Peak [mm] 5.8




SN333A WIFI5G 802.11ac 80M 106CH Left tilted

Communication System: WLAN 5GHz; Frequency: 5530.000
Medium: HSL. Medium parameters used: $f= 5530.000$ MHz; $\sigma= 4.99$ S/m; $\epsilon_r = 36.1$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(5.12, 5.12, 5.12); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.741 W/kg; SAR (10g) = 0.231 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = 0.03 dB
SAR (1g) = 0.938 W/kg; SAR (10g) = 0.247 W/kg;
M2/M1 [%] 63.3
Dist 3dB Peak [mm] 5.2




SN333A WIFI5G 802.11ac 80M 155CH Left tilted

Communication System: WLAN 5GHz; Frequency: 5775.000
Medium: HSL. Medium parameters used: $f= 5775.000$ MHz; $\sigma= 5.28$ S/m; $\epsilon_r = 35.6$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(5.21, 5.21, 5.21); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.674 W/kg; SAR (10g) = 0.199 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = 0.01 dB
SAR (1g) = 0.767 W/kg; SAR (10g) = 0.207 W/kg;
M2/M1 [%] 60.8
Dist 3dB Peak [mm] 5.7



SN333A WIFI5G 802.11a 64CH Back side 15mm

Communication System: WLAN 5GHz; Frequency: 5320.000

Medium: HSL. Medium parameters used: $f= 5320.000$ MHz; $\sigma= 4.76$ S/m; $\epsilon_r = 36.3$

DASY8 Configuration:

- Probe: EX3DV4 - SN7767; ConvF(5.73, 5.73, 5.73); Calibrated: 2024-12-31
- Sensor-Surface: 1.4 mm
- Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
- Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm

SAR (1g) = 0.302 W/kg; SAR (10g) = 0.131 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm

Power Drift = 0.09 dB


SAR (1g) = 0.310 W/kg; SAR (10g) = 0.132 W/kg;

M2/M1 [%]

64.4

Dist 3dB Peak [mm]

12.8




SN333A WIFI5G 802.11a 116CH Back side 15mm

Communication System: WLAN 5GHz; Frequency: 5580.000
Medium: HSL. Medium parameters used: $f= 5580.000$ MHz; $\sigma= 5.04$ S/m; $\epsilon_r = 35.8$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(5.12, 5.12, 5.12); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.425 W/kg; SAR (10g) = 0.172 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = 0.04 dB
SAR (1g) = 0.425 W/kg; SAR (10g) = 0.178 W/kg;
M2/M1 [%] 63.0
Dist 3dB Peak [mm] 13.7




SN333A WIFI5G 802.11a 157CH Back side 15mm

Communication System: WLAN 5GHz; Frequency: 5785.000
Medium: HSL. Medium parameters used: $f= 5785.000$ MHz; $\sigma= 5.27$ S/m; $\epsilon_r = 35.5$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(5.21, 5.21, 5.21); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.435 W/kg; SAR (10g) = 0.174 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = 0.01 dB
SAR (1g) = 0.431 W/kg; SAR (10g) = 0.171 W/kg;
M2/M1 [%] 62.6
Dist 3dB Peak [mm] 13.6




SN333A WIFI5G 802.11ac 80M 42CH Top side 10mm

Communication System: WLAN 5GHz; Frequency: 5210.000
Medium: HSL. Medium parameters used: $f= 5210.000$ MHz; $\sigma= 4.65$ S/m; $\epsilon_r = 36.6$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(5.73, 5.73, 5.73); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 0.217 W/kg; SAR (10g) = 0.067 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = -0.13 dB
SAR (1g) = 0.242 W/kg; SAR (10g) = 0.084 W/kg;
M2/M1 [%] 65.4
Dist 3dB Peak [mm] 8.2




SN333A WIFI5G 802.11ac 80M 155CH Top side 10mm

Communication System: WLAN 5GHz; Frequency: 5775.000
Medium: HSL. Medium parameters used: $f= 5775.000$ MHz; $\sigma= 5.28$ S/m; $\epsilon_r = 35.6$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(5.21, 5.21, 5.21); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 0.206 W/kg; SAR (10g) = 0.065 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = -0.19 dB
SAR (1g) = 0.231 W/kg; SAR (10g) = 0.087 W/kg;
M2/M1 [%] 61.2
Dist 3dB Peak [mm] 10.2




SN333A WIFI5G 802.11a 36CH Top side 0mm

Communication System: WLAN 5GHz; Frequency: 5180.000
Medium: HSL. Medium parameters used: $f= 5180.000$ MHz; $\sigma= 4.60$ S/m; $\epsilon_r = 35.1$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(5.73, 5.73, 5.73); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 10.5 W/kg; SAR (10g) = 1.97 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = -0.01 dB
SAR (1g) = 11.9 W/kg; SAR (10g) = 2.06 W/kg;
M2/M1 [%] 62.1
Dist 3dB Peak [mm] 4.0




SN333A WIFI5G 802.11a 52CH Top side 0mm

Communication System: WLAN 5GHz; Frequency: 5260.000
Medium: HSL. Medium parameters used: $f= 5260.000$ MHz; $\sigma= 4.71$ S/m; $\epsilon_r = 36.7$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(5.73, 5.73, 5.73); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 8.98 W/kg; SAR (10g) = 1.78 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = -0.07 dB
SAR (1g) = 11.9 W/kg; SAR (10g) = 2.08 W/kg;
M2/M1 [%] 66.5
Dist 3dB Peak [mm] 4.7




SN333A WIFI5G 802.11a 116CH Top side 0mm

Communication System: WLAN 5GHz; Frequency: 5580.000
Medium: HSL. Medium parameters used: $f= 5580.000$ MHz; $\sigma= 5.04$ S/m; $\epsilon_r = 35.8$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(5.12, 5.12, 5.12); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (48.0 mm x 120.0 mm): Measurement Grid: 8.0 mm x 10.0 mm
SAR (1g) = 6.16 W/kg; SAR (10g) = 1.38 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = 0.03 dB
SAR (1g) = 6.48 W/kg; SAR (10g) = 1.34 W/kg;
M2/M1 [%] 63.3
Dist 3dB Peak [mm] 4.4




SN333A Bluetooth DH5 Left cheek

Communication System: ISM 2.4 GHz Band; Frequency: 2402.000
Medium: HSL. Medium parameters used: $f= 2402.000$ MHz; $\sigma= 1.79$ S/m; $\epsilon_r = 39.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.03, 8.03, 8.03); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.162 W/kg; SAR (10g) = 0.078 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = 0.17 dB
SAR (1g) = 0.164 W/kg; SAR (10g) = 0.079 W/kg;
M2/M1 [%] 78.6
Dist 3dB Peak [mm] 9.4




SN333A Bluetooth DH5 Back side 15mm

Communication System: ISM 2.4 GHz Band; Frequency: 2402.000
Medium: HSL. Medium parameters used: $f= 2402.000$ MHz; $\sigma= 1.79$ S/m; $\epsilon_r = 39.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.03, 8.03, 8.03); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.019 W/kg; SAR (10g) = 0.010 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = 0.10 dB
SAR (1g) = 0.019 W/kg; SAR (10g) = 0.01 W/kg;
M2/M1 [%] 79.4
Dist 3dB Peak [mm] 14.6




SN333A Bluetooth DH5 Back side 10mm

Communication System: ISM 2.4 GHz Band; Frequency: 2402.000
Medium: HSL. Medium parameters used: $f= 2402.000$ MHz; $\sigma= 1.79$ S/m; $\epsilon_r = 39.0$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7767; ConvF(8.03, 8.03, 8.03); Calibrated: 2024-12-31
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2155
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.039 W/kg; SAR (10g) = 0.020 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm
Power Drift = -0.09 dB
SAR (1g) = 0.041 W/kg; SAR (10g) = 0.021 W/kg;
M2/M1 [%] 81.4
Dist 3dB Peak [mm] 11.5




SN333A NFC 13.56MHz Back side 0mm

Communication System: Custom Band; Frequency: 13.600
Medium: HSL. Medium parameters used: $f=13.600\text{ MHz}$; $\sigma=0.745\text{ S/m}$; $\epsilon_r=50.9$

- DASY8 Configuration:
- Probe: EX3DV4 - SN7735; ConvF(13.68, 13.51, 13.73); Calibrated: 2025-01-29
 - Sensor-Surface: 1.4 mm
 - Electronics: DAE4ip Sn1826; Calibrated: 2025-02-17
 - Phantom: ELI V8.0 (20deg probe tilt); Serial: 2217
 - Measurement Software: cDASY8 V16.4.0.5005

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.081 W/kg; SAR (10g) = 0.063 W/kg;

Zoom Scan (32.2 mm x 32.2 mm x 33.4 mm): Measurement Grid: 4.6 mm x 4.6 mm x 1.4 mm
Power Drift = 0.05 dB
SAR (1g) = 0.067 W/kg; SAR (10g) = 0.027 W/kg;
M2/M1 [%] 58.2
Dist 3dB Peak [mm] 4.7





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250400032002

Rev.: 01

Page: 78 of 78

- End of the Appendix -