



RF TEST REPORT

Product Name: Bluetooth Speaker

Model Name: TURTLEBOXG3, TURTLEBOX

FCC ID: 2A28W-TURTLEBOXG3

Issued For : Turtlebox Audio LLC

11020 Katy Freeway Suite 202 Houston, TX 77043

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT25B110RF01

Sample Received Date: Mar 06, 2025

Date of Test: Mar 06, 2025 – April 03, 2025

Date of Issue: April 03, 2025

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Turtlebox Audio LLC
Address: 11020 Katy Freeway Suite 202 Houston, TX 77043
Manufacturer: Turtlebox Audio LLC
Address: 11020 Katy Freeway Suite 202 Houston, TX 77043
Product Name: Bluetooth Speaker
Trademark: TURTLEBOX
Model Name: TURTLEBOXG3, TURTLEBOX
Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.247, Subpart C ANSI C63.10-2013	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





Table of Contents

Page

1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF THE EUT	7
2.2 DESCRIPTION OF THE TEST MODES	9
2.3 FREQUENCY HOPPING SYSTEM REQUIREMENTS	9
2.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	11
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	11
2.6 EQUIPMENTS LIST	12
3. EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.2 RADIATED EMISSION MEASUREMENT	17
APPENDIX II - MEASUREMENT PHOTOS	28
APPENDIX III - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	29



Revision History

Rev.	Issue Date	Revisions
00	April 03, 2025	Initial Issue

DRAFT



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247(a)(1)	Hopping Channel Separation	N/A	--
15.247(a)(1)&(b)(1)	Output Power	N/A	--
15.209	Radiated Spurious Emission	PASS	--
15.247(d)	Conducted Spurious & Band Edge Emission	N/A	--
15.247(a)(1)(iii)	Number of Hopping Frequency	N/A	--
15.247(a)(1)(iii)	Dwell Time	N/A	--
15.247(a)(1)	Bandwidth	N/A	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	N/A	--

NOTE:

(1) 'N/A' denotes test is not applicable in this Test Report.

(2) All tests are according to ANSI C63.10-2013.

(3) Changes of the prototype:

A、Change the Bluetooth chip memory(U14) from JL1706C8(8Mbit Flash) to JL1706C6(16Mbit Flash), Retest part 15.207Conducted Emission/part 15.209 Radiated Spurious Emission/ part 15.205 Restricted bands of operation and Part 15.247(d) Band Edge Emission.

B、MOS tube Q10/Q20/Q17/Q21 change(Pin to pin and parameters are the same), Retest part 15.207Conducted Emission/part 15.209 Radiated Spurious Emission.



1.1 TEST FACTORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	All emissions, radiated 9K-30MHz	$\pm 2.84\text{dB}$
2	All emissions, radiated 30M-1GHz	$\pm 4.39\text{dB}$
3	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
4	All emissions, radiated >6G	$\pm 5.48\text{dB}$
5	Conducted Emission (9KHz-150KHz)	$\pm 2.79\text{dB}$
6	Conducted Emission (150KHz-30MHz)	$\pm 2.80\text{dB}$

Note: The measurement uncertainty is not included in the test result.



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	Bluetooth Speaker
Trademark:	TURTLEBOX
Model Name:	TURTLEBOXG3
Series Model:	TURTLEBOX
Model Difference:	Only the model is different.
Channel List:	Please refer to the Note 3.
Bluetooth:	Frequency: 2402 – 2480 MHz Modulation: GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps), 8DPSK(3Mbps)
Antenna Type:	FPC
Antenna Gain:	3.49dBi
Adapter:	Input: AC 100-240V 50/60Hz 1.25A Output: DC 15V 3A
Battery:	Rated Capacity: 7800mAh 86.58Wh Rated Voltage: 11.1V
Hardware Version:	N/A
Software Version:	N/A
Connecting I/O Port(s):	Please refer to the Note 1.

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refers to the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.



3.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		



2.2 DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate/Modulation
Mode 1	TX CH00	1Mbps/GFSK
Mode 2	TX CH39	1Mbps/GFSK
Mode 3	TX CH78	1Mbps/GFSK
Mode 4	TX CH00	2 Mbps/ $\pi/4$ -DQPSK
Mode 5	TX CH39	2 Mbps/ $\pi/4$ -DQPSK
Mode 6	TX CH78	2 Mbps/ $\pi/4$ -DQPSK
Mode 7	TX CH00	3 Mbps/8DPSK
Mode 8	TX CH39	3 Mbps/8DPSK
Mode 9	TX CH78	3 Mbps/8DPSK
Mode 10	Hopping	GFSK
Mode 11	Hopping	$\pi/4$ -DQPSK
Mode 12	Hopping	8DPSK

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

(2) We tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V/ 60Hz is shown in the report.

(3) The battery is fully charged during the radiated and RF conducted test.

For AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 13: Keeping BT TX

2.3 FREQUENCY HOPPING SYSTEM REQUIREMENTS

(1) Standard and Limit

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

(2) The Pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th




stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones: i.e. the shift register is initialized with nine ones.

Number of shift register stages: 9


Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generator of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

(3) Frequency Hopping System

This transmitter device is frequency hopping device and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless device are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with a bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements FCC Part 15.247 rule.



2.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS.

Test software Version	Test program: Bluetooth	
FCC_assist_1.0.0.2	Mode Or Modulation type	Power setting
	1M	10
	2M	10
	3M	10

2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating
Adapter	GS-P150300E454A	GS-P150300E454A	N/A	Input: 100-240V ~ 50/60Hz 1.25A Output: 15V, 3A

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	HKF-16	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.6 EQUIPMENTS LIST

Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2025.03.06	2026.03.05
LISN	COM-POWER	LI-115	02032	2025.03.05	2026.03.04
LISN	SCHWARZBECK	NNLK 8122	00160	2025.03.05	2026.03.04
Transient Limiter	CYBERTEK	EM5010A	E2250100049	2025.03.05	2026.03.04
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2025.03.10	2026.03.09
Testing Software	EMC-I_V1.4.0.3_SKET				

Radiated Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2025.03.06	2026.03.05
Active loop Antenna	ETS	6502	00049544	2025.03.11	2028.03.10
Spectrum Analyzer	Keysight	N9010B	MY60242508	2025.03.05	2026.03.04
Trilog Broadband Antenna (30M-1G)	SCHWARZBECK	VULB 9168	2705	2024.05.17	2027.05.16
Horn Antenna(1-18G)	SCHWARZBECK	3115	10SL0060	2025.03.10	2028.03.09
Horn Antenna(18-40G)	SCHWARZBECK	BBHA 9170	685	2023.10.23	2026.10.22
Pre-amplifier(30M-1G)	EMtrace	RP01A	02019	2025.03.06	2026.03.05
Pre-amplifier(1-26.5G)	Agilent	8449B	3008A4722	2025.03.06	2026.03.05
Pre-amplifier(18-40G)	SCHWARZBECK	BBV 9721	9721-019	2024.10.21	2025.10.20
Temperature & Humidity test chamber	AISRY	LX-1000L	171200018	2024.08.05	2025.08.04
Antenna Tower	SAEMC	BK-4AT-BS-D	SK2021093008	N.A	N.A
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2025.03.10	2026.03.09
Testing Software	EMC-I_V1.4.0.3_SKET				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



- Note:**
- Support units were connected to second LISN.
 - Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.


3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.5 TEST RESULT


Project: LGT25B110	Test Engineer: LiuH
EUT: Bluetooth Speaker	Temperature: 21°C
M/N: TURTLEBOX	Humidity: 60%RH
Test Voltage: AC 120V/60Hz	Test Data: 2025-04-02
Test Mode: TX DH5 2402	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.226	30.40	10.61	41.01	62.60	-21.58	QP	L1
2*	0.586	29.05	10.57	39.62	56.00	-16.38	QP	L1
3*	0.866	25.77	10.63	36.40	56.00	-19.60	QP	L1
4*	2.106	20.29	11.01	31.30	56.00	-24.70	QP	L1
5*	4.898	17.57	11.09	28.66	56.00	-27.34	QP	L1
6*	17.906	27.24	11.53	38.77	60.00	-21.23	QP	L1
7*	0.218	18.32	10.61	28.93	52.89	-23.96	AV	L1
8*	0.586	20.83	10.57	31.40	46.00	-14.60	AV	L1
9*	0.774	17.33	10.60	27.93	46.00	-18.07	AV	L1
10*	1.710	12.15	10.90	23.05	46.00	-22.95	AV	L1
11*	7.706	5.47	11.00	16.47	50.00	-33.53	AV	L1
12*	18.242	13.26	11.55	24.81	50.00	-25.19	AV	L1



Project: LGT25B110	Test Engineer: LiuH
EUT: Bluetooth Speaker	Temperature: 21°C
M/N: TURTLEBOX	Humidity: 60%RH
Test Voltage: AC 120V/60Hz	Test Data: 2025-04-02
Test Mode: TX DH5 2402	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.238	26.76	10.57	37.33	62.17	-24.84	QP	N
2*	0.586	27.33	10.55	37.88	56.00	-18.12	QP	N
3*	1.070	22.81	10.56	33.37	56.00	-22.63	QP	N
4*	1.762	20.40	10.71	31.11	56.00	-24.89	QP	N
5*	4.874	14.91	10.84	25.75	56.00	-30.25	QP	N
6*	17.122	18.89	11.49	30.38	60.00	-29.62	QP	N
7*	0.230	17.10	10.57	27.67	52.45	-24.78	AV	N
8*	0.450	15.55	10.57	26.12	46.88	-20.76	AV	N
9*	0.778	16.84	10.56	27.40	46.00	-18.60	AV	N
10*	1.402	12.62	10.63	23.25	46.00	-22.75	AV	N
11*	5.358	1.26	10.83	12.09	50.00	-37.91	AV	N
12*	19.538	0.15	11.61	11.76	50.00	-38.24	AV	N



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205 (a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			



For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz (Peak/QP/AV)
Stop Frequency	150KHz/30MHz (Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz (Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz (Peak/AV)
Stop Frequency	10th carrier hamonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz Upper Band Edge: 2476 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

- a. The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- e. If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.3 DEVIATION FROM TEST STANDARD


No deviation.

3.2.4 TESTSETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

Please refer to section 3.1.4 of this report.



3.2.6 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



3.2.7 TEST RESULTS

Results of Radiated Emissions (9 KHz~30MHz)

No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Remark
1*	-	-	-	-	-	-	-	See Note

Note:

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.




Results of Radiated Emissions (30MHz~1000MHz)

Project: LGT25B110	Test Engineer: LiuH
EUT: Bluetooth Speaker	Temperature: 21°C
M/N: TURTLEBOX	Humidity: 60%RH
Test Voltage: Battery	Test Data: 2025-04-02
Test Mode: TX DH5 2402	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	51.098	1.75	20.64	22.39	40.00	-17.61	QP	Hor
2*	79.470	2.37	16.35	18.72	40.00	-21.28	QP	Hor
3*	159.495	2.85	21.69	24.54	43.50	-18.96	QP	Hor
4*	257.950	0.95	20.16	21.11	46.00	-24.89	QP	Hor
5*	657.105	3.05	29.82	32.87	46.00	-13.13	QP	Hor
6*	890.148	4.45	33.31	37.76	46.00	-8.24	QP	Hor



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	35.456	2.76	19.62	22.38	40.00	-17.62	QP	Ver
2*	64.799	2.72	18.82	21.54	40.00	-18.46	QP	Ver
3*	150.886	1.98	21.48	23.46	43.50	-20.04	QP	Ver
4*	280.745	2.43	20.93	23.36	46.00	-22.64	QP	Ver
5*	687.539	8.74	30.09	38.83	46.00	-7.17	QP	Ver
6*	998.181	3.80	33.90	37.70	54.00	-16.30	QP	Ver



Results of Radiated Emissions (Above 1000MHz)

Above 1000 MHz							
Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
Low Channel (2402 MHz)							
3264.69	56.24	-8.45	47.79	74.00	-26.21	PK	Vertical
3264.69	45.56	-8.45	37.11	54.00	-16.89	AV	Vertical
3264.80	55.17	-8.45	46.72	74.00	-27.28	PK	Horizontal
3264.80	45.55	-8.45	37.10	54.00	-16.90	AV	Horizontal
4804.37	54.05	-6.09	47.96	74.00	-26.04	PK	Vertical
4804.37	45.40	-6.09	39.31	54.00	-14.69	AV	Vertical
4804.55	54.83	-6.09	48.74	74.00	-25.26	PK	Horizontal
4804.55	45.52	-6.09	39.43	54.00	-14.57	AV	Horizontal
5359.77	56.99	-6.68	50.31	74.00	-23.69	PK	Vertical
5359.77	47.12	-6.68	40.44	54.00	-13.56	AV	Vertical
5359.63	57.19	-6.68	50.51	74.00	-23.49	PK	Horizontal
5359.63	47.29	-6.68	40.61	54.00	-13.39	AV	Horizontal
7205.92	60.00	-8.13	51.87	74.00	-22.13	PK	Vertical
7205.92	49.88	-8.13	41.75	54.00	-12.25	AV	Vertical
7205.83	60.35	-8.13	52.22	74.00	-21.78	PK	Horizontal
7205.83	50.07	-8.13	41.94	54.00	-12.06	AV	Horizontal
Middle Channel (2441 MHz)							
3264.60	56.26	-8.45	47.81	74.00	-26.19	PK	Vertical
3264.60	45.99	-8.45	37.54	54.00	-16.46	AV	Vertical
3264.78	55.21	-8.45	46.76	74.00	-27.24	PK	Horizontal
3264.78	46.70	-8.45	38.25	54.00	-15.75	AV	Horizontal
4882.42	54.31	-6.09	48.22	74.00	-25.78	PK	Vertical
4882.42	45.38	-6.09	39.29	54.00	-14.71	AV	Vertical
4882.48	54.51	-6.09	48.42	74.00	-25.58	PK	Horizontal
4882.48	44.34	-6.09	38.25	54.00	-15.75	AV	Horizontal
5359.77	56.94	-6.68	50.26	74.00	-23.74	PK	Vertical
5359.77	48.08	-6.68	41.40	54.00	-12.60	AV	Vertical
5359.77	56.57	-6.68	49.89	74.00	-24.11	PK	Horizontal
5359.77	46.96	-6.68	40.28	54.00	-13.72	AV	Horizontal
7313.88	60.89	-8.13	52.76	74.00	-21.24	PK	Vertical
7313.88	50.00	-8.13	41.87	54.00	-12.13	AV	Vertical
7313.80	60.45	-8.13	52.32	74.00	-21.68	PK	Horizontal
7313.80	50.85	-8.13	42.72	54.00	-11.28	AV	Horizontal



High Channel (2480 MHz)							
3264.89	55.18	-8.45	46.73	74.00	-27.27	PK	Vertical
3264.89	46.27	-8.45	37.82	54.00	-16.18	AV	Vertical
3264.72	55.90	-8.45	47.45	74.00	-26.55	PK	Horizontal
3264.72	45.75	-8.45	37.30	54.00	-16.70	AV	Horizontal
4960.49	55.18	-6.09	49.09	74.00	-24.91	PK	Vertical
4960.49	44.73	-6.09	38.64	54.00	-15.36	AV	Vertical
4960.56	55.45	-6.09	49.36	74.00	-24.64	PK	Horizontal
4960.56	44.86	-6.09	38.77	54.00	-15.23	AV	Horizontal
5359.78	56.89	-6.68	50.21	74.00	-23.79	PK	Vertical
5359.78	47.24	-6.68	40.56	54.00	-13.44	AV	Vertical
5359.72	57.14	-6.68	50.46	74.00	-23.54	PK	Horizontal
5359.72	48.26	-6.68	41.58	54.00	-12.42	AV	Horizontal
7439.90	60.17	-8.13	52.04	74.00	-21.96	PK	Vertical
7439.90	50.68	-8.13	42.55	54.00	-11.45	AV	Vertical
7439.77	60.31	-8.13	52.18	74.00	-21.82	PK	Horizontal
7439.77	50.62	-8.13	42.49	54.00	-11.51	AV	Horizontal

Remark:

In frequency ranges 18~25GHz no any other harmonic emissions detected which are tested to compliance with the limit. No recording in the test report. No any other emissions level which are attenuated less than 20dB below the limit. No recording in the test report.



3.2.8 TEST RESULTS (BAND EDGE REQUIREMENTS)

Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
GFSK							
2390.00	13.74	34.10	47.84	74.00	-26.16	PK	Vertical
2390.00	1.27	34.10	35.37	54.00	-18.63	AV	Vertical
2400.00	12.88	34.11	46.99	74.00	-27.01	PK	Vertical
2400.00	1.07	34.11	35.18	54.00	-18.82	AV	Vertical
2390.00	14.71	34.11	48.82	74.00	-25.18	PK	Horizontal
2390.00	2.97	34.11	37.08	54.00	-16.92	AV	Horizontal
2400.00	15.40	34.11	49.51	74.00	-24.49	PK	Horizontal
2400.00	2.67	34.11	36.78	54.00	-17.22	AV	Horizontal
2483.50	12.64	34.44	47.08	74.00	-26.92	PK	Vertical
2483.50	1.95	34.44	36.39	54.00	-17.61	AV	Vertical
2500.00	12.58	34.46	47.04	74.00	-26.96	PK	Vertical
2500.00	1.13	34.46	35.59	54.00	-18.41	AV	Vertical
2483.50	15.15	34.46	49.61	74.00	-24.39	PK	Horizontal
2483.50	2.01	34.46	36.47	54.00	-17.53	AV	Horizontal
2500.00	15.19	34.46	49.65	74.00	-24.35	PK	Horizontal
2500.00	1.80	34.46	36.26	54.00	-17.74	AV	Horizontal
π/4-DQPSK							
2390.00	13.59	34.10	47.69	74.00	-26.31	PK	Vertical
2390.00	1.04	34.10	35.14	54.00	-18.86	AV	Vertical
2400.00	13.37	34.11	47.48	74.00	-26.52	PK	Vertical
2400.00	2.13	34.11	36.24	54.00	-17.76	AV	Vertical
2390.00	15.53	34.11	49.64	74.00	-24.36	PK	Horizontal
2390.00	2.16	34.11	36.27	54.00	-17.73	AV	Horizontal
2400.00	15.00	34.11	49.11	74.00	-24.89	PK	Horizontal
2400.00	3.01	34.11	37.12	54.00	-16.88	AV	Horizontal
2483.50	12.27	34.44	46.71	74.00	-27.29	PK	Vertical
2483.50	1.64	34.44	36.08	54.00	-17.92	AV	Vertical
2500.00	13.01	34.46	47.47	74.00	-26.53	PK	Vertical
2500.00	0.82	34.46	35.28	54.00	-18.72	AV	Vertical
2483.50	14.18	34.46	48.64	74.00	-25.36	PK	Horizontal
2483.50	2.65	34.46	37.11	54.00	-16.89	AV	Horizontal
2500.00	14.48	34.46	48.94	74.00	-25.06	PK	Horizontal
2500.00	2.61	34.46	37.07	54.00	-16.93	AV	Horizontal
8DPSK							



2390.00	12.22	34.10	46.32	74.00	-27.68	PK	Vertical
2390.00	0.92	34.10	35.02	54.00	-18.98	AV	Vertical
2400.00	13.14	34.11	47.25	74.00	-26.75	PK	Vertical
2400.00	0.68	34.11	34.79	54.00	-19.21	AV	Vertical
2390.00	14.06	34.11	48.17	74.00	-25.83	PK	Horizontal
2390.00	3.15	34.11	37.26	54.00	-16.74	AV	Horizontal
2400.00	15.01	34.11	49.12	74.00	-24.88	PK	Horizontal
2400.00	3.24	34.11	37.35	54.00	-16.65	AV	Horizontal
2483.50	12.97	34.44	47.41	74.00	-26.59	PK	Vertical
2483.50	1.17	34.44	35.61	54.00	-18.39	AV	Vertical
2500.00	12.34	34.46	46.80	74.00	-27.20	PK	Vertical
2500.00	0.86	34.46	35.32	54.00	-18.68	AV	Vertical
2483.50	15.31	34.46	49.77	74.00	-24.23	PK	Horizontal
2483.50	3.26	34.46	37.72	54.00	-16.28	AV	Horizontal
2500.00	15.44	34.46	49.90	74.00	-24.10	PK	Horizontal
2500.00	1.78	34.46	36.24	54.00	-17.76	AV	Horizontal
Low measurement frequencies is range from 2310 to 2404 MHz, high measurement frequencies is range from 2478 to 2500 MHz.							



APPENDIX I - MEASUREMENT PHOTOS

Note: Please see the attached RF_Test Setup photos for FCC ID & IC.

DRAFT



APPENDIX II - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

Note: Please see the attached TURTLEBOX_External Photos and TURTLEBOX_Internal Photos.

※※※※※END OF THE REPORT※※※※※

DRAFT