

RF Exposure Evaluation Report

Equipment under Test: Interactive IoT Device

Model No. : NCP IOT-01

Applicant : New Century Products Co., Ltd.

Address : 1F., No. 415, Sec. 5, Nanjing E. Rd., Songshan
Dist., Taipei City

Date of Receipt : October 14, 2021

Date of Report : March 11, 2022

Prepared by

Central Research Technology Co.



EMC Test Laboratory

No.11, Lane41, Fushuen St., Jungshan Chiu, Taipei, Taiwan, 104, R.O.C.

This report shall not be reproduced, except in full, without written approval of Central Research Technology Co.. It may be duplicated completely in its entirety for legal use with the permission of the applicant. The test result in this report is based on the information provided by manufacturer and applies only to the sample tested.

1 Requirement for Compliance

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

1. For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$
3. For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

Frequency Range (MHz)	Maximum Power		Antenna distance (mm)	Calculated Result (mW)	Limit (mW)
	(dBm)	(mW)			
2402~2480	-8.4	0.1	5	0.03	3.0

2 Result

According to result, the SAR testing for this device is not required.