1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant:	Shenzhen Lancer Electronic Co.,Limited
Address of applicant:	1st Floor, 2nd Floor, 4th Floor, 5th Floor, Building B, Baifuli Industrial Zone,Tongsheng Community, Dalang Street, Longhua District, Shenzhen, China
Manufacturer:	Shenzhen Lancer Electronic Co.,Limited
Address of manufacturer:	1st Floor, 2nd Floor, 4th Floor, 5th Floor, Building B, Baifuli Industrial Zone,Tongsheng Community, Dalang Street, Longhua District, Shenzhen, China

General Description of EUT:

Product Name:	Intelligent water monitor
Trade Name:	Kemi
Model No.:	LX-001
Adding Model(s):	/
Rated Voltage:	Charging Port:DC5V Battery:DC3.7V
Battery Capacity;	4*2200mAh
Power Adapter Model:	/
FCC ID:	2A29V-LX001

Technical Characteristics of EUT:

Wi-Fi

Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20)
RF Output Power:	16.12dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Quantity of Channels:	11 for 802.11b/g/n(HT20)
Channel Separation:	5MHz
Type of Antenna:	External Antenna
Antenna Gain:	2dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm^2)	Averaging Times $\|E\|^2$, $\|H\|^2$ or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm^2)	Averaging Times $\|E\|^2$, $\|H\|^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$S = (30*P*G) / (377*R^2)$

S = power density (in appropriate units, e.g., mw/cm^2)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For Wi-Fi

Maximum Tune-Up output power: 17(dBm)

Maximum peak output power at antenna input terminal: 50.12(mW)

Prediction distance: >20(cm)

Prediction frequency: 2437 (MHz)

Antenna gain: 2 (dBi)

Directional gain (numeric gain): 1.58

The worst case is power density at prediction frequency at 20cm: 0.0158(mw/cm^2)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm^2)

Result: Pass