

**47 CFR PART 15 SUBPART C
ISED RSS-210 ISSUE 11**

TEST REPORT

For

Stripe Reader

MODEL NUMBER: S710

REPORT NUMBER: 4791861891-1-RF-5

ISSUE DATE: September 22, 2025

FCC ID: 2A2ES-STR7X

IC : 28493-STR7X

Prepared for

For FCC

Stripe Inc

354 Oyster Point Blvd, South San Francisco, CA 94080, USA

For ISED

BBPOS Limited

**15/F, Tower 2, Nina Tower, 8 Yeung Uk Road, Tsuen Wan New Territories Hong Kong 0000
China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	September 22, 2025	Initial Issue	\

Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	Transmitter 99% Emission Bandwidth / 20dB Bandwidth	RSS-Gen 6.7/ Part 15.215 (c)	PASS
2	Transmitter Frequency Stability (Temperature & Voltage Variation)	CFR 47 §15.225(e) ISED RSS-Gen Clause 6.11 ISED RSS-210 Annex B.6	PASS
3	Fundamental Field Strength	CFR 47 §15.225(a)(b)(c)(d) ISED RSS-Gen Clause 6.12 ISED RSS-210 Annex B.6	PASS
4	Radiated Emissions	CFR 47 FCC§15.209(a) CFR 47 FCC§15.225(d) ISED RSS-Gen Clause 6.13 ISED RSS-210 Annex B.6	PASS
5	Band Edge Radiated Emissions	CFR 47 §15.209(a) CFR 47 §15.225(c)(d) ISED RSS-Gen Clause 6.13 ISED RSS-210 Annex B.6	PASS
6	Conducted Emission Test for AC Power Port	CFR 47 §15.207 ISED RSS-Gen Clause 8.8	PASS
7	Antenna Requirement	CFR 47 §15.203 ISED RSS-Gen Clause 6.8	PASS
Note: - For ISED, this report is also performed according to ANSI C63.10-2020 + Cor.1-2023 standards. - This test report is only published to and used by the applicant, and it is not for evidence purpose in China. - The measurement result for the sample received is <Pass> according to <CFR 47 PART 15 SUBPART C> when <Simple Acceptance> decision rule is applied.			

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION.....	8
4.2. MEASUREMENT UNCERTAINTY	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT.....	9
5.2. MAXIMUM FIELD STRENGTH	9
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	9
5.4. TEST ENVIRONMENT.....	10
5.5. DESCRIPTION OF TEST SETUP	11
6. MEASURING INSTRUMENT AND SOFTWARE USED	12
7. ANTENNA PORT TEST RESULTS	13
7.1. 99% & 20dB BANDWIDTH.....	13
7.2. TRANSMITTER FREQUENCY STABILITY.....	15
8. RADIATED EMISSION TEST RESULTS	17
8.1. FIELD STRENGTH OF INTENTIONAL EMISSIONS.....	23
8.2. SPURIOUS EMISSIONS BELOW 1GHz AND ABOVE 30MHz	24
9. AC POWER LINE CONDUCTED EMISSIONS	29
10. ANTENNA REQUIREMENTS.....	35

1. ATTESTATION OF TEST RESULTS

Applicant Information (FCC)

Company Name: Stripe Inc
Address: 354 Oyster Point Blvd, South San Francisco, CA 94080, USA

Manufacturer Information (FCC)

Company Name: Stripe Inc
Address: 354 Oyster Point Blvd, South San Francisco, CA 94080, USA

Applicant Information (ISED)

Company Name: BBPOS Limited
Address: 15/F, Tower 2, Nina Tower, 8 Yeung Uk Road, Tsuen Wan New Territories Hong Kong 0000 China

Manufacturer Information (ISED)


Company Name: BBPOS Limited
Address: 15/F, Tower 2, Nina Tower, 8 Yeung Uk Road, Tsuen Wan New Territories Hong Kong 0000 China

EUT Information

EUT Name: Stripe Reader
Model: S710
Series Model: \
Model Difference: \
Sample Received Date: July 9, 2025
Sample Status: Normal
Sample ID: 8694498
Date of Tested: July 19, 2025 to September 19, 2025

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 PART 15 SUBPART C	PASS
ISED RSS-210 ISSUE 11	PASS
ISED RSS-GEN Issue 5	PASS


Prepared By:



James Qin

Project Engineer

Checked By:



Kebo Zhang

Operations Leader

Approved By:



Stephen Guo

Operations Manager

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 414788 D01 Radiated Test Site v01r01, CFR 47 Part 2, CFR 47 Part 15, ANSI C63.10-2013, ISED RSS-210 ISSUE 11 and RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the membership No. is 3793. Facility Name: Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202
---------------------------	--

Note:

1. All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field site and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. Measurements have been performed in an anechoic chamber for below 30 MHz and compared with the measurement result that obtained in an open field site and the measurements result have been corrected to represent the result collected in an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiation Emission test (include Fundamental emission) (9KHz-30MHz)	2.2 dB
Radiation Emission test (include Fundamental emission) (30MHz-1GHz)	4.00 dB
Radiation Emission test (1GHz to 26GHz) (include Fundamental emission)	5.78 dB (1 GHz-18 GHz)
	5.23 dB (18 GHz-26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Stripe Reader
Model	S710
Series Model	\
Model Difference	\
Operation Frequency	13.56 MHz
Modulation	ASK
Battery	Nominal Voltage: DC 3.87 V Rated capacity: 4920 mAh

Note: both ISO/IEC 14443A and ISO/IEC 14443B supported. All lowest and highest data rates as per the standards are supported - 106 kbps, 212 kbps, 424 kbps and 848 kbps. Only the worst data of ISO/IEC 14443A with 848 kbps is reported.

5.2. MAXIMUM FIELD STRENGTH

Frequency (MHz)	Max Peak field strength (dB μ V/m)
13.56	19.54

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
13.56	Coil	0

5.4. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	101 kPa	
Temperature	TN	20 ~ 28°C
Voltage:	VL	DC 3.29 V
	VN	DC 3.87 V
	VH	DC 4.26 V

Note:

1. VL= Lower Extreme Test Voltage
2. VN = Nominal Voltage
3. VH = Upper Extreme Test Voltage
4. TN = Normal Temperature

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	Specification
1	Adapter	/	FC69U	Input: 100-240 V ~ 50/60 Hz 0.6A Max Output: QC 5 V, 3 A; 9 V, 3 A; 12 V, 2.5 A; PD 5 V, 3 A; 9 V, 3 A; 12 V, 2.5 A; 15 V, 2 A;
2	Charging dock	/	STR7D	/

I/O CABLES

Item	Type of cable	Shielded Type	Ferrite Core	Length
/	/	/	/	/

ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	USB-C to USB-C cable	/	/	1m length


TEST SETUP

the NFC signal induced by engineering mode.

The EUT can transmit the NFC signal through Swiping card (NFC)

NFC support both ISO /IEC 14443A and ISO /IEC 14443B. All lowest and highest data rates as per the standards are supported - 106 kbps, 212 kbps, 424 kbps and 848 kbps, all the modes had been tested, but only the worst data (ISO 14443A 106 kbps) was recorded in the report.

SETUP DIAGRAM FOR TESTS



Note: Test was performed with tag and without tag, but only the worst-case data (with tag) was recorded in the report.

6. MEASURING INSTRUMENT AND SOFTWARE USED

Test Equipment of Conducted emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESR3	101961	Sep. 28, 2024	Sep. 27, 2025
Two-Line V-Network	ROHDE & SCHWARZ	ENV216	101983	Sep. 28, 2024	Sep. 27, 2025
Test Software for Conducted Emission	Farad	EZ-EMC	Ver.UL-3A1	N/A	N/A

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep. 28, 2024	Sep. 27, 2025
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Jun. 27, 2024	Jun. 28, 2027
Preamplifier	HP	8447D	2944A09099	Sep. 28, 2024	Sep. 27, 2025
Loop antenna	Schwarzbeck	1519B	00008	Dec.9, 2024	Dec.8, 2027
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Sep. 28, 2024	Sep. 27, 2025
Software					
Description		Manufacturer		Name	Version
Test Software for Radiated Emissions		Farad		EZ-EMC	Ver. UL-3A1

Other Instruments					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep. 28, 2024	Sep. 27, 2025

7. ANTENNA PORT TEST RESULTS

7.1. 99% & 20dB BANDWIDTH

LIMITS


Section	Test Item	Limit
ANSI C63.10 Section 6.9.2	20dB% Bandwidth	For reporting purposes only.
ISED RSS-Gen Clause 6.7 Issue 5	99 % Occupied Bandwidth	For reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 300 kHz. The VBW is set to larger than 3 times of RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

Note: Because the measured signal is CW or CW-like adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW. The type of band for the signal is narrowband.

TEST SETUP




TEST ENVIRONMENT

Temperature	22.1 °C	Relative Humidity	62 %
Atmosphere Pressure	101 kPa	Test Voltage	120V~, 60HZ

RESULTS

Frequency (MHz)	99% Occupied Bandwidth (kHz)	20dB bandwidth (kHz)
13.56	646.88	748.9

99%&20dB bandwidth



7.2. TRANSMITTER FREQUENCY STABILITY

LIMITS

CFR 47 §15.225(e)

ISED RSS-210 Annex B B.6

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+ 50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.


TEST SETUP AND PROCEDURE

Connect the UUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	PEAK
RBW	10KHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

Allow the trace to stabilize, find the peak value of the power envelope and record the frequency, then calculate the frequency drift.

TEST SETUP



Note: The manufacturer claims that the normal operating voltage range of the battery is 3.4 ~ 4.3 Vdc, the sample will not work properly beyond this range.

TEST RESULTS

Maximum frequency error of the EUT with variations in ambient temperature.

Temperature (°C)	Time after Start-up			
	0 minutes	2 minutes	5 minutes	10 minutes
-20	13.5625	13.5643	13.5552	13.5646
-10	13.5577	13.5577	13.5587	13.5584
0	13.5620	13.5551	13.5579	13.5624
10	13.5600	13.5639	13.5565	13.5650
20	13.5638	13.5569	13.5614	13.5595
30	13.5593	13.5571	13.5600	13.5584
40	13.5574	13.5555	13.5604	13.5569
50	13.5558	13.5571	13.5619	13.5556
Maximum frequency error	0.0038%	0.0043%	0.0019%	0.0050%
Limit	0.01%			
Result	Pass	Pass	Pass	Pass

Maximum frequency error of the EUT with declared battery operation voltage at a temperature of 20 degrees.

Supply Voltage by Battery	Time after Start-up			
	0 minutes	2 minutes	5 minutes	10 minutes
4.2 Vdc	13.5629	13.5620	13.5626	13.5649
3.7 Vdc	13.5594	13.5582	13.5553	13.5568
3.4 Vdc	13.5566	13.5649	13.5610	13.5605
Maximum frequency error	0.0029%	0.0049%	0.0026%	0.0049%
Limit	0.01%			
Result	Pass	Pass	Pass	Pass

Maximum frequency error of the EUT with 85% to 115% of the rated supply voltage at a temperature of 20 degrees.

Supply Voltage by adapter	Time after Start-up			
	0 minutes	2 minutes	5 minutes	10 minutes
138 Vac, 60Hz	13.5620	13.5603	13.5556	13.5641
120 Vac, 60Hz	13.5626	13.5585	13.5580	13.5601
102 Vac, 60Hz	13.5596	13.5595	13.5616	13.5554
Maximum frequency error	0.0026%	0.0003%	0.0016%	0.0041%
Limit	0.01%			
Result	Pass	Pass	Pass	Pass

8. RADIATED EMISSION TEST RESULTS

LIMITS

Fundamental field strength

FCC Reference:	Part 15.225(a)(b)(c)(d) & 15.209(a)
ISED Canada Reference:	RSS-Gen 6.13 & RSS-210 B.6 & RSS-GEN Clause 8.9
Test Method Used:	ANSI C63.10 Sections 6.3, 6.4 and 6.5

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength (dB $\mu\text{V}/\text{m}$)	Measured Distance (Meters)
13.553-13.567	15848	84	30
13.410-13.553/13.567-13.710	334	50.47	30
13.110-13.410/13.710-14.010	106	40.51	30

Note:

1. The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.
2. The limit is specified at a test distance of 30 meters. However, as specified by FCC Section 15.31 (f)(2), measurements may be performed at a closer distance and the measured level corrected to the specified measurement distance by using the square of an inverse linear distance extrapolation factor (40dB/decade).

Radiation Disturbance Test Limit for FCC (Class B) (9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30MHz.

Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.


²Above 38.6c

Table 7 – Restricted frequency bands ^{Note 1}		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ω ; For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y - 51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1G




The setting of the spectrum analyzer

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
7. The initial step of collecting radiated emission data is to set a spectrum analyzer peak detector mode, pre-scanning the measurement frequency range. Significant peaks then be marked and each peak mark is checked to be highest by slowing down the sweep time, rotated speed of turntable and lifting speed of receive antenna, then switch to receiver mode to read QP value for the marker whose margin is less than 3dB.

X axis, Y axis, Z axis orientations:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.


TEST ENVIRONMENT

Temperature	23.4 °C	Relative Humidity	61 %
Atmosphere Pressure	101kPa	Test Voltage	120V~, 60HZ

RESULTS

8.1. FIELD STRENGTH OF INTENTIONAL EMISSIONS

FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOOP ANTENNA FACE ON TO THE EUT)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	13.2691	35.71	-50.73	-15.02	40.51	-55.53	peak
2	13.3574	35.86	-50.73	-14.87	40.51	-55.38	peak
3	13.4817	35.64	-50.73	-15.09	50.47	-65.56	peak
4	13.5591	70.26	-50.72	19.54	84.00	-64.46	peak
5	13.7787	35.89	-50.71	-14.82	40.51	-55.33	peak
6	13.9596	35.68	-50.70	-15.02	40.51	-55.53	peak

Note:

1. Result Level = Read Level + Correct Factor.
2. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

8.2. SPURIOUS EMISSIONS BELOW 1GHz AND ABOVE 30MHz


SPURIOUS EMISSIONS (HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	44.5500	32.87	-15.28	17.59	40.00	-22.41	PK
2	190.0500	42.50	-12.76	29.74	43.50	-13.76	PK
3	366.5900	53.13	-10.76	42.37	46.00	-3.63	PK
4	392.7800	53.17	-10.87	42.30	46.00	-3.70	PK
5	419.9400	52.51	-10.32	42.19	46.00	-3.81	PK
6	854.5000	41.95	-3.08	38.87	46.00	-7.13	PK

Note:

1. Result Level = Read Level + Correct Factor.
2. The peak value is compliant with the QP limit, and the margin is greater than 3dB, QP value is not captured.


HARMONICS AND SPURIOUS EMISSIONS (VERTICAL)

Note:

1. Result Level = Read Level + Correct Factor.
2. The peak value is compliant with the QP limit, and the margin is greater than 3dB, QP value is not captured.

SPURIOUS EMISSIONS BELOW 30MHz

SPURIOUS EMISSIONS (LOOP ANTENNA FACE ON TO THE EUT)

9 kHz~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0097	59.28	-90.32	-31.04	47.82	-82.54	-3.68	-78.86	peak
2	0.0363	72.39	-91.23	-18.84	36.4	-70.34	-15.1	-55.24	peak
3	0.072	68.2	-92.6	-24.4	30.45	-75.9	-21.05	-54.85	peak
4	0.1084	61.82	-92.54	-30.72	26.91	-82.22	-24.59	-57.63	peak
5	0.134	41.86	-92.38	-50.52	25.06	-102.02	-26.44	-75.58	peak
6	0.1471	56.92	-92.29	-35.37	24.25	-86.87	-27.25	-59.62	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

150 kHz ~ 490 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1822	59.53	-92.06	-32.53	22.39	-84.03	-29.11	-54.92	peak
2	0.2567	56.06	-92.21	-36.15	19.41	-87.65	-32.09	-55.56	peak
3	0.3288	52.79	-92.46	-39.67	17.26	-91.17	-34.24	-56.93	peak
4	0.4022	49.81	-92.6	-42.79	15.51	-94.29	-35.99	-58.3	peak
5	0.4491	49.61	-92.7	-43.09	14.56	-94.59	-36.94	-57.65	peak
6	0.4743	51.16	-92.75	-41.59	14.08	-93.09	-37.42	-55.67	peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

490 kHz ~ 30 MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.549	47.23	-52.75	-5.52	32.81	-57.02	-18.69	-38.33	peak
2	3.7066	39.78	-51.43	-11.65	29.54	-63.15	-21.96	-41.19	peak
3	8.9299	38.13	-51	-12.87	29.54	-64.37	-21.96	-42.41	peak
4	13.5629	70.26	-50.72	19.54	\	\	\	\	fundamental
5	20.4978	37.32	-49.85	-12.53	29.54	-64.03	-21.96	-42.07	peak
6	26.5473	34.75	-49.62	-14.87	29.54	-66.37	-21.96	-44.41	peak

Note:

- Measurement = Reading Level + Correct Factor.
- If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
- All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
- About the Fundamental emission test result please refer to section 7.1.

9. AC POWER LINE CONDUCTED EMISSIONS

LIMITS


Please refer to CFR 47 §15.207 (a).

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

1. The tighter limit applies at the band edges.
2. The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

TEST SETUP AND PROCEDURE



The following table is the setting of the receiver


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was placed on the top of a rotating table 0.8 meters above the horizontal ground plane and being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
3. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
4. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
5. LISN at least 80 cm from nearest part of EUT chassis.
6. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.
7. The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST ENVIRONMENT

Temperature	21.6 °C	Relative Humidity	60.1 %
Atmosphere Pressure	101kPa	Test Voltage	AC 120V_60Hz

LINE N RESULTS with modified sample (transmitter terminated into a dummy load)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1604	24.76	9.72	34.48	65.44	-30.96	QP
2	0.1604	10.81	9.72	20.53	55.44	-34.91	AVG
3	0.4565	17.20	9.64	26.84	56.76	-29.92	QP
4	0.4565	11.01	9.64	20.65	46.76	-26.11	AVG
5	1.0580	2.83	9.64	12.47	56.00	-43.53	QP
6	1.0580	-2.69	9.64	6.95	46.00	-39.05	AVG
7	13.5500	30.11	9.74	39.85	60.00	-20.15	QP
8	13.5500	15.74	9.74	25.48	50.00	-24.52	AVG
9	19.6594	6.75	9.74	16.49	60.00	-43.51	QP
10	19.6594	1.38	9.74	11.12	50.00	-38.88	AVG
11	29.7179	3.48	9.64	13.12	60.00	-46.88	QP
12	29.7179	-0.39	9.64	9.25	50.00	-40.75	AVG

Note:

1. Result = Reading +Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

LINE L RESULTS with modified sample (transmitter terminated into a dummy load)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1604	21.12	9.64	30.76	65.44	-34.68	QP
2	0.1604	7.40	9.64	17.04	55.44	-38.40	AVG
3	0.4605	18.70	9.64	28.34	56.68	-28.34	QP
4	0.4605	12.10	9.64	21.74	46.68	-24.94	AVG
5	4.9618	9.87	9.66	19.53	56.00	-36.47	QP
6	4.9618	-0.11	9.66	9.55	46.00	-36.45	AVG
7	13.7900	27.55	9.74	37.29	60.00	-22.71	QP
8	13.7900	18.47	9.74	28.21	50.00	-21.79	AVG
9	20.2718	5.14	9.74	14.88	60.00	-45.12	QP
10	20.2718	-0.38	9.74	9.36	50.00	-40.64	AVG
11	29.2099	2.26	9.65	11.91	60.00	-48.09	QP
12	29.2099	-1.22	9.65	8.43	50.00	-41.57	AVG

Note:

1. Result = Reading +Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

LINE N RESULTS with unmodified sample (antenna present)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1857	20.04	9.67	29.71	64.23	-34.52	QP
2	0.1857	5.23	9.67	14.90	54.23	-39.33	AVG
3	0.4632	25.98	9.64	35.62	56.63	-21.01	QP
4	0.4632	17.46	9.64	27.10	46.63	-19.53	AVG
5	1.0561	18.63	9.64	28.27	56.00	-27.73	QP
6	1.0561	13.10	9.64	22.74	46.00	-23.26	AVG
7	2.7831	16.80	9.73	26.53	56.00	-29.47	QP
8	2.7831	5.47	9.73	15.20	46.00	-30.80	AVG
9	13.5595	50.08	9.74	59.82	60.00	-0.18	QP
10	13.5595	47.09	9.74	56.83	50.00	6.83	AVG
11	20.1086	7.35	9.74	17.09	60.00	-42.91	QP
12	20.1086	1.13	9.74	10.87	50.00	-39.13	AVG

Note:

1. Result = Reading +Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

LINE L RESULTS with unmodified sample (antenna present)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1502	27.14	9.64	36.78	65.99	-29.21	QP
2	0.1502	11.23	9.64	20.87	55.99	-35.12	AVG
3	0.4170	24.14	9.64	33.78	57.51	-23.73	QP
4	0.4170	15.58	9.64	25.22	47.51	-22.29	AVG
5	1.0575	18.24	9.63	27.87	56.00	-28.13	QP
6	1.0575	12.50	9.63	22.13	46.00	-23.87	AVG
7	4.0686	17.59	9.63	27.22	56.00	-28.78	QP
8	4.0686	3.44	9.63	13.07	46.00	-32.93	AVG
9	13.5595	50.35	9.74	60.09	60.00	0.09	QP
10	13.5595	47.27	9.74	57.01	50.00	7.01	AVG
11	19.7695	10.36	9.74	20.10	60.00	-39.90	QP
12	19.7695	2.09	9.74	11.83	50.00	-38.17	AVG

Note:

1. Result = Reading +Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

10. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to 47CFR §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies

END OF REPORT