

10 Appendix A - General Product Information

Radiofrequency radiation exposure evaluation

This exposure evaluation is intended for **FCC ID: 2A2F6BUC**

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances ≤ 50 mm, the Numeric threshold is determined as:

Step a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

>> The fundamental frequency of the EUT is 2402-2480MHz,
the test separation distance is $\leq 50\text{mm}$.
(Here calculated it as the worst-case, define the distance is 5mm)

Step b)

>> Numeric threshold (2402MHz), $\text{mW} / 5\text{mm} \cdot \sqrt{2.402\text{GHz}} \leq 3.0$
Numeric threshold (2402MHz) $\leq 9.678\text{mW}$

>> Numeric threshold (2440MHz), $\text{mW} / 5\text{mm} \cdot \sqrt{2.440\text{GHz}} \leq 3.0$
Numeric threshold (2440MHz) $\leq 9.602\text{mW}$

>> Numeric threshold (2480MHz), $\text{mW} / 5\text{mm} \cdot \sqrt{2.480\text{GHz}} \leq 3.0$
Numeric threshold (2480MHz) $\leq 9.525\text{mW}$

>> The power (measured + tune up tolerance) of EUT at 2402MHz is: $-1.72\text{dBm} = 0.673\text{mW}$
The power (measured + tune up tolerance) of EUT at 2440MHz is: $-2.06\text{dBm} = 0.622\text{mW}$
The power (measured + tune up tolerance) of EUT at 2480MHz is: $-2.99\text{dBm} = 0.502\text{mW}$

Which is smaller than the Numeric threshold.

Therefore, the device is exempt from stand-alone SAR test requirements.


Reviewed by:



Eric LI
EMC Project Manager



Prepared by:



Hosea CHAN
EMC Project Engineer