



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20251002411E-02
Applicant: ShenZhen New Brightness Technology Co., Ltd
Address of Applicant: Rm1511 F building baitian Internatinal Center HuanCheng Road Baitian street, Longgang District ShenZhen
Equipment Under Test (EUT):
EUT Name: TUYA BT Smart thin Down Light
Model No.: BT 6 INCH , XLD-DLBT-Th6, XLD-DLBT-Th4
Test Model No.: BT 6 INCH
Brand Name: N/A
FCC ID: 2A2GV-BT6INCH
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt: 2025-10-17
Date of Test: 2025-10-17 to 2025-10-31
Date of Issue: 2026-05-11
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20251002411E-02	Rev.01	Initial report	2026-05-11

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BLE	4
4 MPE EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 Limits	5
4.1.2 Test Procedure	5
4.1.3 EUT RF Exposure	6

3 General Information

3.1 Client Information

Applicant:	ShenZhen New Brightness Technology Co., Ltd
Address of Applicant:	Rm1511 F building baitian Internatinal Center HuanCheng Road Baitian street, Longgang District ShenZhen
Manufacturer:	ShenZhen New Brightness Technology Co., Ltd
Address of Manufacturer:	Rm1511 F building baitian Internatinal Center HuanCheng Road Baitian street, Longgang District ShenZhen
Factory:	ShenZhen New Brightness Technology Co., Ltd
Address of Factory:	No1 Yin' an 2 nd road Jun' an town ShunDe district Foshan city GuangDong

3.2 General Description of EUT

Product Name:	TUYA BT Smart thin Down Light
Model No.:	BT 6 INCH , XLD-DLBT-Th6, XLD-DLBT-Th4
Test Model No.:	BT 6 INCH
Trade Mark:	N/A
Software Version:	V1.0
Hardware Version:	V1.0
EUT Power Supply:	Power supply AC 120V

3.3 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.4
Modulation Type:	GFSK
Number of Channel:	40
Transfer Rate:	1Mbps/2Mbps
Sample Type:	☐ Mobile ☒ Portable ☐ Fix Location
Antenna Type:	PhyPlusKit
Antenna Gain:	PCB antenna
Cable loss:	1.54dBi

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave Dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

For BLE

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode(1Mbps)					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	3.18	1.03	1±1	2	1.585
Middle(2440MHz)	4.25	2.1	2±1	3	1.995
Highest(2480MHz)	3.92	1.77	2±1	3	1.995
GFSK mode(2Mbps)					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	3.27	1.12	1±1	2	1.585
Middle(2440MHz)	4.26	2.11	2±1	3	1.995
Highest(2480MHz)	3.71	1.56	1.5±1	2.5	1.778

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20251002411E-01 for EUT test Max Conducted Peak Output Power value.

2) EUT's module is more than 20cm away from the human body.

*** END OF REPORT ***