



# MPE ESTIMATION

FCC ID: 2A2GV-WIFIBLE-A19

## 1, Limit for General Population/ Uncontrolled Exposures

| Frequency        | Power density (mW/ cm <sup>2</sup> ) | Averaging time(minutes) |
|------------------|--------------------------------------|-------------------------|
| 300MHz----1.5GHz | F/1500                               | 30                      |
| 1.5GHz---100GHz  | 1.0                                  | 30                      |

Note: F= Frequency in MHz

## 2, Estimation Result

### WIFI

| Mode      | Max PK Output power(dBm) | Tune Up Power(dBm) | Max Tune Up power(mW) | Antenna Gain(dBi) | Antenna Gain (numerical) | MPE (mW/cm <sup>2</sup> ) |
|-----------|--------------------------|--------------------|-----------------------|-------------------|--------------------------|---------------------------|
| 2.4G WIFI | 16.85                    | 16±1(17)           | 50.119                | 1                 | 1.2589                   | 0.01256                   |

$$Pd = \frac{Pout * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2106081821-E**, antenna gain=1dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01256 mW/cm<sup>2</sup> which is < 1.0mW/cm<sup>2</sup>, RF Exposure testing is not required.

-----The End-----