

RF Exposure Evaluation Report

Product : Harry Potter Wireless Headphones
Trade mark : MINISO
Model/Type reference : P23
Serial Number : N/A
Report Number : EED32S813574
FCC ID : 2A2H6-P23
Date of Issue : July 23, 2026
Test Standards : 47 CFR Part 1.1307
47 CFR Part 1.1310
47 CFR Part 2.1093
KDB 447498 D04 Interim General RF
Exposure Guidance v01
Test result : PASS

Prepared for:

Shenzhen Bao Tianhua Technology Co., Ltd.
301, Building Plant No.5 Anliang Road, Xi Keng Community, Longgang
District, Shenzhen, Guangdong, China

Prepared by:

Centre Testing International Group Co., Ltd.
Building C, Hongwei Industrial Park Block 70, Bao'an District,
Shenzhen, China

TEL: +86-755-3368 3668**FAX: +86-755-3368 3385**

Compiled by:

Frazer Li

Frazer Li

Reviewed by:

Keven Tan

Keven Tan

Approved by:

Aaron Ma

Aaron Ma

Date:

July 23, 2026



Check No.:4808150626

1 Contents

	Page
1 CONTENTS	2
2 GENERAL INFORMATION	3
2.1 CLIENT INFORMATION	3
2.2 GENERAL DESCRIPTION OF EUT	3
2.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	3
2.4 TEST LOCATION	4
2.5 DEVIATION FROM STANDARDS	4
2.6 ABNORMALITIES FROM STANDARD CONDITIONS	4
2.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
3 SAR EVALUATION	5
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
3.1.1 Limits	5
3.1.2 Test Procedure	5
3.1.3 EUT RF Exposure Evaluation	6

2 General Information

2.1 Client Information

Applicant:	Shenzhen Bao Tianhua Technology Co., Ltd.
Address of Applicant:	301, Building Plant No.5 Anliang Road, Xi Keng Community, Longgang District, Shenzhen, Guangdong, China
Manufacturer:	Shenzhen Bao Tianhua Technology Co., Ltd.
Address of Manufacturer:	301, Building Plant No.5 Anliang Road, Xi Keng Community, Longgang District, Shenzhen, Guangdong, China
Factory:	Shenzhen Bao Tianhua Technology Co., Ltd.
Address of Factory:	301, Building Plant No.5 Anliang Road, Xi Keng Community, Longgang District, Shenzhen, Guangdong, China

2.2 General Description of EUT

Product Name:	Harry Potter Wireless Headphones
Model No.:	P23
Test Model No.:	P23
Trade Mark:	MINISO

2.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz	
Modulation Type:	GFSK, $\pi/4$ DQPSK	
Test Power Grade:	Default	
Test Software of EUT:	FCC_assist_1.0.2.2	
Antenna Type:	PCB Antenna	
Antenna Gain:	0.58dBi	
Power Supply:	Battery:	DC 3.7V
	USB Port:	USB 5V
Sample Received Date:	Jun. 30, 2026	
Sample tested Date:	Jun. 30, 2026 to Jul. 09, 2026	

2.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164, Test Firm Registration No.: 260439

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.1.3 EUT RF Exposure Evaluation**For Stand alone:**

Band	Frequency (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
BT	2480	0.5	-0.17	0.5800	-1.74	0.67	2.717	0.2465	Pass

Note:

① EIRP=conducted power+antenna gain;

② ERP=EIRP-2.15;

③ EIRP(dBm) = Field strength of the fundamental signal(dBuV/m@3m) – 95.23;

④ $ERP(mW) = 10^{(ERP(dBm)/10)}$;

⑤ The estimation distance is 0.5cm;

⑥ The test data please refer to the report of EED32S813580 and only the worst case data was recorded in the report.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;
2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;
3. The result(s) shown in this report refer(s) only to the sample(s) tested;
4. Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;
5. Without written approval of CTI, this report can't be reproduced except in full;

*** End of Report ***