



SAR TEST REPORT

Product Name: Tablet PC

Model Number: L1108

FCC ID: 2A2J4-L1108

Issued For : Shenzhen Pretech Industrial Co., Ltd

808,8F, Qiancheng Commercial center,5 Haicheng
Road,Bao'an District, Shenzhen, China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street,
Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT25J192HA01

Sample Received Date: Oct. 30, 2025

Date of Test Oct. 30, 2025 ~Nov. 24, 2025

Date of Issue Nov. 24, 2025

Max. SAR (1g) Body: 1.190 W/kg

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



Table of Contents

1. General Information	5
1.1 EUT Description	5
1.2 Test Environment	7
1.3 Test Factory	7
2. Test Standards and Limits	8
3. SAR Measurement System	9
3.1 Definition of Specific Absorption Rate (SAR)	9
3.2 SAR System	9
4. Tissue Simulating Liquids	12
4.1 Simulating Liquids Parameter Check	12
5. SAR System Validation	14
5.1 Validation System	14
5.2 Validation Result	15
6. SAR Evaluation Procedures	16
7. EUT Antenna Location Sketch	17
7.1 SAR test exclusion consider table	18
8. EUT Test Position	23
8.1 Body-worn Position Conditions	23
9. Uncertainty	24
9.1 Measurement Uncertainty	24
9.2 System validation Uncertainty	25
10. Conducted Power Measurement	26
10.1 Test Result	26
10.2 Tune up Power	61
11. EUT and Test Setup Photo	65
11.1 EUT Photos	65
11.2 Setup Photos	68
12. SAR Result Summary	71
12.2 Body-worn and Hotspot SAR	71
12.3 Repeated SAR	74
12.4 Repeated SAR measurement	75
12.5 Simultaneous Multi-band Transmission Evaluation	77
13. Equipment List	79
Appendix A. System Validation Plots	80



Appendix B. SAR Test Plots

98

Appendix C. Probe Calibration and Dipole Calibration Report

118

Revision History

Rev.	Issue Date	Contents
00	Nov. 24, 2025	Initial Issue



TEST REPORT CERTIFICATION

Applicant Shenzhen Pretech Industrial Co., Ltd
Address 808,8F, Qiancheng Commercial center,5 Haicheng Road,Bao'an District, Shenzhen, China
Manufacture Shenzhen Pretech Industrial Co., Ltd
Address 808,8F, Qiancheng Commercial center,5 Haicheng Road,Bao'an District, Shenzhen, China
Product Name Tablet PC
Trademark Pretech
Model Number L1108
Sample number LGT2510234-1

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
ANSI/IEEE Std. C95.1-2019 FCC 47 CFR Part 2 (2.1093) IEEE 1528: 2013	PASS

Prepared by:

Deng Deng

Deng Deng
Engineer

Approved by:

Vita Li

Vita Li
Manager





1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	Tablet PC	
Test Model Name	L1108	
Series Model	N/A	
Model Difference	N/A	
Device Category	Portable	
Product stage	Production unit	
RF Exposure Environment	General Population / Uncontrolled	
Hardware Version	P301-MB-V1.0.1	
Software Version	N/A	
Frequency Range	GSM 850: 824 ~ 849 MHz PCS 1900: 1850 ~ 1910 MHz WCDMA Band II: 1850 ~ 1910 MHz WCDMA Band IV: 1710 ~ 1755 MHz WCDMA Band V: 824 ~ 849 MHz LTE Band 2: 1850 ~ 1910 MHz LTE Band 4: 1710 ~ 1755 MHz LTE Band 5: 824 ~ 849 MHz LTE Band 7: 2500 ~ 2570 MHz LTE Band 12: 699 ~ 716 MHz LTE Band 25: 1850 ~ 1915 MHz LTE Band 26: 814 ~ 824 MHz / 824 ~ 849 MHz LTE Band 38: 2570 ~ 2620 MHz LTE Band 40: 2305 ~ 2315 MHz / 2350 ~ 2360 MHz LTE Band 41: 2496 ~ 2690 MHz LTE Band 66: 1710 ~ 1780 MHz WLAN 802.11b/g/n20: 2412 MHz ~ 2462 MHz WLAN 802.11n40: 2422 MHz ~ 2452 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5150 ~ 5250 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5250 ~ 5350 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5725 ~ 5850 MHz Bluetooth: 2402 ~ 2480 MHz NFC: 13.56 MHz	
Max. Reported SAR(1g): (Limit: 1.6W/kg) Test distance: Body: 0mm	Mode	Body Worn and Hotspot (W/ kg)
	GSM 850	0.582
	PCS 1900	1.161
	WCDMA Band II	0.864
	WCDMA Band IV	0.679
	WCDMA Band V	0.785
	LTE Band 2	0.908
	LTE Band 4	0.216
	LTE Band 5	0.850
	LTE Band 7	1.095
	LTE Band 12	0.477
	LTE Band 25	0.820
	LTE Band 26	0.656



	LTE Band 38	0.473
	LTE Band 40	0.371
	LTE Band 41	1.132
	LTE Band 66	1.190
	2.4G WLAN	0.391
	5.2G WLAN	0.200
	5.3G WLAN	0.223
	5.8G WLAN	0.295
	Bluetooth ^{Note}	0.167
	NFC ^{Note}	0.0000005
1-g Sum SAR		1.581
Battery	Rated Voltage:3.8V Capacity: 8000mAh	
Description test modes	SIM 1 and SIM 2 is a chipset unit and tested as single chipset, SIM 1 is used to tested.	
Operating Mode:	GSM: GSM Voice; GPRS/EGPRS Class 12 WCDMA: RMC, HSDPA, HSUPA Release 6 LTE: QPSK, 16QAM 2.4G WLAN: 802.11b(DSSS): CCK, DQPSK, DBPSK 802.11g(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 5G WLAN: 802.11a(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11ac (OFDM): BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM Bluetooth: GFSK + π /4DQPSK+8DPSK BLE: GFSK NFC: ASK	
Antenna Specification	GSM/WCDMA/LTE: PIFA Antenna Bluetooth: PIFA Antenna WLAN: PIFA Antenna	
Operating Mode	Maximum continuous output	
SIM Card	Support dual-SIM, dual standby, the multiple SIM card with two lines cannot trans mitting at the same time	
Hotspot Mode	Support	
DTM Mode	Not Support	
Note 1: The BT value was Estimated.		



1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	FCC Registration No.: 746540
	CAB ID: CN0136



2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	ANSI/IEEE Std. C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D01 v06	Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 941225 D06 v02r01	Hotspot Mode SAR
10	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets
11	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

(A). Limits for Occupational/Controlled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
-------------------	---------------------	---------------------------------------

0.4	8.0	20.0
-----	-----	------

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
-------------------	---------------------	---------------------------------------

0.08	1.6	4.0
------	-----	-----

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE GENERAL POPULATION/UNCONTROLLED EXPOSURE PARTIAL BODY LIMIT 1.6 W/kg
--



3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue;

ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

MVG SAR System Diagram:



COMOSAR is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The COMOSAR system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 1g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe 2225-EPGO-450 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: <0.10 dB
- Spherical Isotropy: <0.10 dB
- Calibration range: 0.15 GHz to 7.5 GHz for head simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1-MVG COMOSAR Dosimetric E field Probe

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.




Figure-SN 06/22 SAM 148



Figure-SN 06/22 ELLI 51

3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The uncertainty due to the liquid conductivity and permittivity arises from two different sources. The first source of error is the deviation of the liquid conductivity from its target value (max _ 5 %) and the second source of error arises from the measurement procedures used to assess conductivity. The uncertainty shall be assessed using a rectangular probability For 1 g averaging, the maximum weighting coefficient for SAR is 0,5.

IEEE SCC-34/SC-2 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head and body tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table.

Frequency	ϵ_r	σ 10g S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800 to 2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27



LIQUID MEASUREMENT RESULTS

Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
2025-11-02	23.9	41	750	20.6	Permittivity	41.90	42.29	0.93	±5
					Conductivity	0.89	0.88	-1.12	±5
2025-11-01	23.7	57	835	23.4	Permittivity	41.50	42.42	2.22	±5
					Conductivity	0.90	0.95	5.56	±5
2025-11-04	21.5	49	1800	21.2	Permittivity	40.00	40.98	2.45	±5
					Conductivity	1.40	1.37	-2.14	±5
2025-11-03	22.9	53	1900	22.6	Permittivity	40.00	41.24	3.10	±5
					Conductivity	1.40	1.39	-0.71	±5
2025-11-02	23.6	55	2450	23.2	Permittivity	39.20	40.02	2.09	±5
					Conductivity	1.80	1.78	-1.11	±5
2025-10-31	22.7	59	2600	22.4	Permittivity	39.00	40.29	3.31	±5
					Conductivity	1.96	1.95	-0.51	±5
2025-11-04	20.9	56	5200	20.1	Permittivity	36.00	36.73	2.03	±5
					Conductivity	4.66	4.62	-0.86	±5
2025-11-05	21.6	59	5400	21.3	Permittivity	35.80	37.12	3.69	±5
					Conductivity	4.86	4.89	0.62	±5
2025-11-05	21	54	5800	20.7	Permittivity	35.30	36.07	2.18	±5
					Conductivity	5.27	5.26	-0.19	±5




5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.





5.2 Validation Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of $\pm 10\%$.

Date	Freq.	Power	Power drift	Tested Value	Normalized SAR	Target SAR	Tolerance
	(MHz)	(mW)	(%)	(W/Kg)	(W/kg)	1g(W/kg)	(%)
2025-11-02	750	100	0.890	8.90	8.51	4.58	10
2025-11-01	835	100	0.968	9.68	9.63	0.52	10
2025-11-04	1800	100	3.691	36.91	36.60	0.85	10
2025-11-03	1900	100	3.996	39.96	40.20	-0.60	10
2025-11-02	2450	100	5.283	52.83	52.98	-0.28	10
2025-10-31	2600	100	5.628	56.28	56.15	0.23	10
2025-11-04	5200	100	7.778	77.78	77.84	-0.08	10
2025-11-05	5400	100	7.695	76.95	76.82	0.17	10
2025-11-05	5800	100	8.043	80.43	80.51	-0.10	10

Note:

1. The tolerance limit of System validation $\pm 10\%$.
2. The dipole input power (forward power) was 100 mW.
3. The results are normalized to 1 W input power.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

➤ Area Scan & Zoom Scan


First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below.

When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Antenna Location Sketch

It is a Tablet PC, support GSM/WCDMA/LTE/WLAN/BT mode.

Top side



Bottom side
(Front view)

Antenna Separation Distance(mm)						
ANT	Back Side	Front Side	Left Side	Right Side	Top Side	Bottom Side
WLAN/BT	≤0.5	≤0.5	75	140	≤0.5	160
WWAN	≤0.5	≤0.5	130	30	≤0.5	160

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



7.1 SAR test exclusion consider table

The WWAN/WLAN/BT SAR evaluation of Maximum power (dBm) summing tolerance.

Exposure Position	Wireless Interface	GSM850	PCS1900	WCDMA II	WCDMA IV	WCDMA V
	Calculated Frequency (MHz)	836.6	1909.8	1852.4	1712.6	846.6
	Maximum Turn-up power (dBm)	31	30.6	24.2	24.5	24.2
	Maximum rated power(mW)	1258.93	1148.15	263.03	281.84	263.03
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.40	10.85	11.02	11.46	16.30
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	130	130	130	130	130
	exclusion threshold(mW)	610.18	908.54	910.21	914.62	614.54
	Testing required?	YES	YES	NO	NO	NO
Right Edge	Separation distance (mm)	30	30	30	30	30
	exclusion threshold(mW)	98.40	65.13	66.13	68.77	97.81
	Testing required?	YES	YES	YES	YES	YES
Top Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.40	10.85	11.02	11.46	16.30
	Testing required?	YES	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	160	160	160	160	160
	exclusion threshold(mW)	777.50	1208.54	1210.21	1214.62	783.86
	Testing required?	YES	NO	NO	NO	NO



Exposure Position	Wireless Interface	LTE Band 4	LTE Band 5	LTE Band 7	LTE Band 12	LTE Band 25
	Calculated Frequency (MHz)	1732.5	844	2510	704	1860
	Maximum Turn-up power (dBm)	24	24.5	23.6	24.5	24.1
	Maximum rated power(mW)	251.19	281.84	229.09	281.84	257.04
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	11.40	16.33	9.47	17.88	11.00
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	130	130	130	130	130
	exclusion threshold(mW)	913.96	613.41	894.68	554.24	909.99
	Testing required?	NO	NO	NO	NO	NO
Right Edge	Separation distance (mm)	30	30	30	30	30
	exclusion threshold(mW)	68.38	97.97	56.81	107.26	65.99
	Testing required?	YES	YES	YES	YES	YES
Top Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	11.40	16.33	9.47	17.88	11.00
	Testing required?	YES	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	160	160	160	160	160
	exclusion threshold(mW)	1213.96	782.21	1194.68	695.04	1209.99
	Testing required?	NO	NO	NO	NO	NO



Exposure Position	Wireless Interface	LTE Band 26	LTE Band 38	LTE Band 40	LTE Band 41	LTE Band 66
	Calculated Frequency (MHz)	841.5	2580	2350	2506	1745
	Maximum Turn-up power (dBm)	24.5	24.2	23.7	25	24.6
	Maximum rated power(mW)	281.84	263.03	234.42	316.23	288.40
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.35	9.34	9.78	9.48	11.36
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	130	130	130	130	130
	exclusion threshold(mW)	612.32	893.39	897.85	894.75	913.55
	Testing required?	NO	NO	NO	NO	NO
Right Edge	Separation distance (mm)	30	30	30	30	30
	exclusion threshold(mW)	98.11	56.03	58.71	56.85	68.13
	Testing required?	YES	YES	YES	YES	YES
Top Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.35	9.34	9.78	9.48	11.36
	Testing required?	YES	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	160	160	160	160	160
	exclusion threshold(mW)	780.62	1193.39	1197.85	1194.75	1213.55
	Testing required?	NO	NO	NO	NO	NO



Exposure Position	Wireless Interface	BT	2.4G WLAN	5.2G WLAN	5.3G WLAN	5.8G WLAN
	Calculated Frequency (MHz)	2441	2412	5240	5320	5785
	Maximum Turn-up power (dBm)	6	16.5	12.2	13.2	13.5
	Maximum rated power(mW)	3.98	44.67	16.60	20.89	22.39
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	9.60	9.66	6.55	6.50	6.24
	Testing required?	NO	YES	YES	YES	YES
Left Edge	Separation distance (mm)	75	75	75	75	75
	exclusion threshold(mW)	346.01	346.58	315.53	315.03	312.36
	Testing required?	NO	NO	NO	NO	NO
Right Edge	Separation distance (mm)	140	140	140	140	140
	exclusion threshold(mW)	996.01	996.58	965.53	965.03	962.36
	Testing required?	NO	NO	NO	NO	NO
Top Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	9.60	9.66	6.55	6.50	6.24
	Testing required?	NO	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	160	160	160	160	160
	exclusion threshold(mW)	1196.01	1196.58	1165.53	1165.03	1162.36
	Testing required?	NO	NO	NO	NO	NO

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. per KDB 447498 D01, standalone SAR test exclusion threshold is applied; if the distance of the antenna to the user is <25mm, 25mm is user to determine SAR exclusion threshold
4. per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distance $\leq 50\text{mm}$ are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz. Power and distance are rounded to the nearest mW and mm before calculation.}$$

The result is rounded to one decimal place for comparison



For <50mm distance, we just calculate mW of the exclusion threshold value(3.0)to do compare

5. per KDB 447498 D01, at 100 MHz to 6GHz and for test separation distances >50mm, the SAR test exclusion threshold is determined according to the following
 - a)[threshold at 50mm in step 1]+(test separation distance -50mm)*(f (MHz)/150)]mW, at 100 MHz to 1500 MHz
 - b) [threshold at 50mm in step1]+(test separation distance -50mm) *10]mW at > 1500MHz and ≤ 6GHz
6. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8.for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode, thus the SAR can be excluded.
7. Per KDB 616217 D04, SAR evaluation for the front surface of tablet display screens are generally not necessary.




8. EUT Test Position

This EUT was tested in Back Side and Top Side.

8.1 Body-worn Position Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing function, the relevant hand and body exposure condition are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surface and edges with a transmitting antenna located within 25 mm from that surface or edge. When form factor of a handset is smaller than 9cm x 5cm, a test separation distance of 5mm (instead of 10mm) is required for testing hotspot mode. When the separate distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty Component	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+/-%)	10g Ui (+/-%)	vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	2.41	2.41	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	1.81	1.81	∞
RF ambient conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, Interpolation and Integration Algorithms for Max, SAR	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.60	2.60	11
Device holder uncertainty	3	N	1	1	1	3.00	3.00	7
Output Power Variation - SAR Drift Measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and tissue parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity - Measurement Uncertainty)	4	N	1	0.78	0.71	3.12	2.84	5
Liquid Permittivity - Measurement Uncertainty	5	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.47	10.34	
Expanded Uncertainty (95% Confidence interval)		K				20.95	20.69	



9.2 System validation Uncertainty

Uncertainty Component	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	0.71	0.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0	N	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions- reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, Interpolation and Integration Algorithms for Max, SAR	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of Experimental Source from Numerical Source	5	N	1	1	1	5.00	5.00	∞
Input Power and SAR Drift Measurement	0.5	R	$\sqrt{3}$	1	1	0.29	0.29	∞
Dipole Axis to Liquid Distance	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity - Measurement Uncertainty)	4	N	1	0.78	0.71	3.12	2.84	5
Liquid Permittivity - Measurement Uncertainty	5	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.16	10.03	
Expanded Uncertainty (95% Confidence interval)		K				20.32	20.06	



10. Conducted Power Measurement

10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1-Slot)	34.26	34.13	34.06	31.13	31.04	31.3
GPRS (GMSK, 1-Slot)	34.26	34.13	34.05	31.12	31.06	31.32
GPRS (GMSK, 2-Slot)	33.51	33.45	33.28	30.3	30.23	30.54
GPRS (GMSK, 3-Slot)	31.82	31.82	31.58	28.26	28.19	28.54
GPRS (GMSK, 4-Slot)	30.74	30.79	30.49	26.96	26.86	27.21
EGPRS (8PSK, 1-Slot)	28.42	28.22	28.15	27.12	27.24	27.52
EGPRS (8PSK, 2-Slot)	27.66	27.78	27.32	26.12	25.93	26.23
EGPRS (8PSK, 3-Slot)	25.4	25.99	25.29	24.11	23.82	24.55
EGPRS (8PSK, 4-Slot)	24.19	24.48	24.43	23.11	22.37	23.17
Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme. Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link						

Frame- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1-Slot)	25.23	25.10	25.03	22.10	22.01	22.27
GPRS (GMSK, 1-Slot)	25.23	25.10	25.02	22.09	22.03	22.29
GPRS (GMSK, 2-Slot)	27.49	27.43	27.26	24.28	24.21	24.52
GPRS (GMSK, 3-Slot)	27.56	27.56	27.32	24.00	23.93	24.28
GPRS (GMSK, 4-Slot)	27.73	27.78	27.48	23.95	23.85	24.20
EGPRS (8PSK, 1-Slot)	19.39	19.19	19.12	18.09	18.21	18.49
EGPRS (8PSK, 2-Slot)	21.64	21.76	21.30	20.10	19.91	20.21
EGPRS (8PSK, 3-Slot)	21.14	21.73	21.03	19.85	19.56	20.29
EGPRS (8PSK, 4-Slot)	21.18	21.47	21.42	20.10	19.36	20.16
Remark: 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum Burst - averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB						



WCDMA

Band	WCDMA Band 2			WCDMA Band 4			WCDMA Band 5		
Channel	9262	9400	9538	1312	1450	1513	4132	4182	4233
Frequency (MHz)	1852.4	1880	1907.6	1712.6	1740	1752.4	826.4	836.4	846.6
RMC 12.2Kbps	23.36	23.55	23.04	24.44	24.2	24.21	23.71	23.59	24.13
HSDPA Subtest-1	24.17	23.69	23.7	23.97	23.9	23.58	23.35	23.2	23.13
HSDPA Subtest-2	23.68	23.27	23.31	23.74	23.77	23.34	22.99	22.92	23.24
HSDPA Subtest-3	23.47	23.16	23.1	23.34	23.37	23.08	22.78	22.7	22.8
HSDPA Subtest-4	23.08	22.78	22.74	23.26	23.32	22.86	22.75	22.79	22.59
HSUPA Subtest-1	24.02	23.43	23.5	23.77	23.82	23.52	23.44	23.17	23.17
HSUPA Subtest-2	23.99	23.56	23.59	23.94	23.97	23.67	23.29	23.26	23.28
HSUPA Subtest-3	23.75	23.28	23.07	23.76	23.31	23.28	23.28	22.97	22.48
HSUPA Subtest-4	23.97	23.57	23.58	23.91	23.86	23.66	23.18	23.19	23.28
HSUPA Subtest-5	23.63	23.48	23.37	23.75	23.76	23.41	23.11	22.96	23.01

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM (db)	MPR (db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: CM=1 for $\beta_c / \beta_d = 12/15$, $\beta_{hs} / \beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.



2.4G WLAN

2.4GWIFI				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11b	1	2412	16.33	42.95
	6	2437	15.12	32.51
	11	2462	14.45	27.86
802.11g	1	2412	15.16	32.81
	6	2437	14.99	31.55
	11	2462	14.5	28.18
802.11 n-HT20	1	2412	15.42	34.83
	6	2437	15.12	32.51
	11	2462	14.58	28.71
802.11 n-HT40	3	2422	13.21	20.94
	6	2437	13.26	21.18
	9	2452	13.31	21.43

Bluetooth

BT				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	2.53	1.79
	39	2441	3.06	2.02
	78	2480	2.94	1.97
$\pi/4$ -QPSK(2Mbps)	0	2402	4.87	3.07
	39	2441	5.35	3.43
	78	2480	5.08	3.22
8DPSK(3Mbps)	0	2402	5.29	3.38
	39	2441	5.83	3.83
	78	2480	5.56	3.60

BLE

BLE				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	-7.46	0.18
	19	2440	-5.48	0.28
	39	2480	-8.04	0.16
GFSK(2Mbps)	0	2402	-7.5	0.18
	19	2440	-5.54	0.28
	39	2480	-8.07	0.16



WLAN (5.2Gband)

5.2G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	36	5180	11.97	15.74
	40	5200	11.22	13.24
	48	5240	12.18	16.52
802.11 n-HT20	36	5180	10.75	11.89
	40	5200	10.48	11.17
	48	5240	10.66	11.64
802.11 n-HT40	38	5190	10.88	12.25
	46	5230	10.63	11.56
802.11ac-VHT20	36	5180	11.14	13.00
	40	5200	11.47	14.03
	48	5240	10.53	11.30
802.11ac-VHT40	38	5190	10.34	10.81
	46	5230	10.54	11.32
802.11ac-VHT80	42	5210	8.53	7.13

WLAN (5.3G band)

5.3G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	52	5260	12.36	17.22
	60	5300	12.35	17.18
	64	5320	13.16	20.70
802.11 n-HT20	52	5260	10.97	12.50
	60	5300	11.34	13.61
	64	5320	11.65	14.62
802.11 n-HT40	54	5270	11.26	13.37
	62	5310	10.97	12.50
802.11ac-VHT20	52	5260	10.97	12.50
	60	5300	11.47	14.03
	64	5320	11.63	14.55
802.11ac-VHT40	54	5270	11.34	13.61
	62	5310	11.41	13.84
802.11ac-VHT80	58	5290	8.52	7.11



WLAN (5.8G band)

5.8G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	149	5745	12.54	17.95
	157	5785	13.33	21.53
	165	5825	13.14	20.61
802.11 n-HT20	149	5745	11.8	15.14
	157	5785	12.07	16.11
	165	5825	12.28	16.90
802.11 n-HT40	151	5755	12.1	16.22
	159	5795	12.57	18.07
802.11ac-VHT20	149	5745	11.59	14.42
	157	5785	12.25	16.79
	165	5825	12.07	16.11
802.11ac-VHT40	151	5755	11.4	13.80
	159	5795	12.36	17.22
802.11ac-VHT80	155	5775	9.76	9.46

NFC		
Mode	Field strength(dBuV/m)	ERP(dBm)
NFC	56.58	-38.62

Note. The power of this EUT NFC is -38.62dBm (0.00014mw), this power is less than the defined low power exclusion level (Pmax: 39 mW), so NFC is exemption.



LTE Conducted Power

General Note:

1. CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.03	24.36	24.31
1.4	1	2		24.1	24.41	24.37
1.4	1	5		24.05	24.39	24.26
1.4	3	0		23.97	24.31	24.28
1.4	3	1		24.03	24.4	24.29
1.4	3	2		23.95	24.3	24.25
1.4	6	0		22.98	23.35	23.32
1.4	1	0	16-QAM	23.24	23.54	23.22
1.4	1	2		23.32	23.56	23.27
1.4	1	5		23.25	23.59	23.2
1.4	3	0		23.23	23.56	23.46
1.4	3	1		23.29	23.58	23.52
1.4	3	2		23.21	23.66	23.48
1.4	6	0		22.21	22.53	22.52
3	1	0	QPSK	24.04	24.42	24.33
3	1	7		24.02	24.4	24.35
3	1	14		23.95	24.38	24.33
3	8	0		23.05	23.38	23.34
3	8	4		23.06	23.37	23.36
3	8	7		23	23.42	23.34
3	15	0		23.09	23.35	23.31
3	1	0	16-QAM	23.61	23.68	23.33
3	1	7		23.49	23.57	23.32
3	1	14		23.43	23.6	23.26
3	8	0		22.12	22.43	22.33
3	8	4		22.09	22.39	22.35
3	8	7		22.03	22.43	22.33
3	15	0		22.06	22.33	22.4



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.18	24.63	24.51
5	1	12		24	24.33	24.33
5	1	24		24.12	24.38	24.34
5	12	0		23.08	23.42	23.42
5	12	6		23.04	23.35	23.38
5	12	11		23.13	23.41	23.36
5	25	0		23.09	23.4	23.36
5	1	0	16-QAM	23.75	23.95	23.88
5	1	12		23.63	23.67	23.62
5	1	24		23.67	23.73	23.74
5	12	0		22.13	22.41	22.45
5	12	6		22.1	22.36	22.36
5	12	11		22.17	22.36	22.33
5	25	0		22.06	22.45	22.32
10	1	0	QPSK	24.16	24.66	24.42
10	1	24		24.09	24.42	24.41
10	1	49		24.3	24.5	24.5
10	25	0		23.07	23.46	23.32
10	25	12		23.1	23.37	23.36
10	25	24		23.19	23.34	23.3
10	50	0		23.13	23.37	23.36
10	1	0	16-QAM	23.61	23.86	23.43
10	1	24		23.64	23.57	23.29
10	1	49		23.76	23.67	23.4
10	25	0		22.02	22.51	22.25
10	25	12		22.13	22.37	22.34
10	25	24		22.2	22.33	22.29
10	50	0		22.11	22.4	22.34



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.04	24.6	24.37
15	1	37		24.17	24.54	24.35
15	1	74		24.21	24.21	24.17
15	36	0		23.11	23.45	23.4
15	36	18		23.31	23.45	23.3
15	36	39		23.33	23.36	23.28
15	75	0		23.23	23.37	23.29
15	1	0	16-QAM	23.41	23.82	23.65
15	1	38		23.53	23.73	23.62
15	1	75		23.52	23.37	23.43
15	36	0		22.17	22.42	22.41
15	36	18		22.37	22.47	22.34
15	36	39		22.35	22.31	22.34
15	75	0		22.26	22.44	22.35
20	1	0	QPSK	24.21	24.76	24.5
20	1	49		24.23	24.47	24.23
20	1	99		24.44	24.5	24.49
20	50	0		23.14	23.48	23.33
20	50	24		23.2	23.48	23.38
20	50	49		23.24	23.34	23.35
20	100	0		23.16	23.42	23.32
20	1	0	16-QAM	23.69	23.9	23.67
20	1	49		23.51	23.47	23.35
20	1	99		23.93	23.68	23.68
20	50	0		22.19	22.58	22.26
20	50	24		22.2	22.56	22.29
20	50	49		22.2	22.46	22.32
20	100	0		22.21	22.41	22.37



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.82	23.67	23.72
1.4	1	2		23.77	23.72	23.77
1.4	1	5		23.77	23.72	23.74
1.4	3	0		23.73	23.53	23.76
1.4	3	1		23.7	23.53	23.77
1.4	3	2		23.74	23.57	23.75
1.4	6	0		22.71	22.54	22.78
1.4	1	0	16-QAM	22.67	22.83	22.98
1.4	1	2		22.69	22.79	22.95
1.4	1	5		22.68	22.81	23.01
1.4	3	0		22.89	22.74	23
1.4	3	1		22.89	22.71	23.01
1.4	3	2		22.91	22.73	22.99
1.4	6	0		21.89	21.76	21.95
3	1	0	QPSK	23.76	23.53	23.73
3	1	7		23.76	23.57	23.79
3	1	14		23.77	23.57	23.75
3	8	0		22.72	22.58	22.78
3	8	4		22.69	22.53	22.8
3	8	7		22.7	22.58	22.79
3	15	0		22.74	22.57	22.78
3	1	0	16-QAM	22.67	23.01	22.95
3	1	7		22.76	23.11	23.01
3	1	14		22.61	23.06	22.98
3	8	0		21.73	21.6	21.75
3	8	4		21.69	21.57	21.78
3	8	7		21.68	21.59	21.81
3	15	0		21.79	21.58	21.72



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.79	23.57	23.89
5	1	12		23.76	23.69	23.93
5	1	24		23.76	23.66	23.94
5	12	0		22.77	22.61	22.8
5	12	6		22.72	22.59	22.81
5	12	11		22.71	22.62	22.86
5	25	0		22.8	22.64	22.88
5	1	0	16-QAM	23.2	22.95	23.38
5	1	12		23.21	23.02	23.42
5	1	24		23.14	23.06	23.39
5	12	0		21.74	21.65	21.82
5	12	6		21.7	21.63	21.84
5	12	11		21.69	21.64	21.86
5	25	0		21.77	21.6	21.8
10	1	0	QPSK	23.78	23.59	23.8
10	1	24		23.7	23.7	23.77
10	1	49		23.63	23.82	23.81
10	25	0		22.78	22.61	22.82
10	25	12		22.7	22.61	22.8
10	25	24		22.69	22.67	22.87
10	50	0		22.72	22.65	22.83
10	1	0	16-QAM	22.99	22.46	23.27
10	1	24		22.92	22.57	23.25
10	1	49		22.82	22.67	23.26
10	25	0		21.74	21.58	21.83
10	25	12		21.68	21.56	21.82
10	25	24		21.68	21.62	21.87
10	50	0		21.73	21.6	21.82



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.78	23.53	23.83
15	1	37		23.7	23.69	23.94
15	1	74		23.56	23.83	23.94
15	36	0		22.73	22.57	22.8
15	36	18		22.65	22.62	22.83
15	36	39		22.63	22.68	22.86
15	75	0		22.68	22.67	22.87
15	1	0	16-QAM	23.28	22.7	22.91
15	1	38		23.2	22.89	23.08
15	1	75		23.04	23.05	22.99
15	36	0		21.77	21.62	21.76
15	36	18		21.66	21.66	21.78
15	36	39		21.66	21.76	21.81
15	75	0		21.69	21.67	21.9
20	1	0	QPSK	23.79	23.59	23.73
20	1	49		23.61	23.78	23.92
20	1	99		23.69	23.97	23.87
20	50	0		22.72	22.63	22.81
20	50	24		22.67	22.68	22.89
20	50	49		22.63	22.78	22.98
20	100	0		22.66	22.73	22.88
20	1	0	16-QAM	23.2	22.83	23.01
20	1	49		23.08	23.06	23.2
20	1	99		23.1	23.2	23.17
20	50	0		21.76	21.6	21.84
20	50	24		21.69	21.65	21.91
20	50	49		21.65	21.75	21.99
20	100	0		21.65	21.68	21.87



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.01	24.27	24.18
1.4	1	2		24.03	24.29	24.2
1.4	1	5		24.02	24.28	24.17
1.4	3	0		24.02	24.13	24.2
1.4	3	1		24	24.13	24.21
1.4	3	2		24.03	24.17	24.21
1.4	6	0		23	23.14	23.19
1.4	1	0	16-QAM	22.85	23.39	23.44
1.4	1	2		22.85	23.42	23.43
1.4	1	5		22.85	23.42	23.45
1.4	3	0		23.11	23.34	23.44
1.4	3	1		23.11	23.33	23.47
1.4	3	2		23.13	23.34	23.46
1.4	6	0		22.16	22.32	22.42
3	1	0	QPSK	23.99	24.15	24.28
3	1	7		23.98	24.16	24.28
3	1	14		23.98	24.17	24.29
3	8	0		23.03	23.14	23.2
3	8	4		22.97	23.18	23.22
3	8	7		22.97	23.21	23.27
3	15	0		23.04	23.21	23.24
3	1	0	16-QAM	23.34	23.38	23.28
3	1	7		23.53	23.43	23.18
3	1	14		23.5	23.4	23.22
3	8	0		22.06	22.14	22.28
3	8	4		22.01	22.14	22.22
3	8	7		21.96	22.21	22.24
3	15	0		22.04	22.1	22.29



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.09	24.25	24.36
5	1	12		24.08	24.24	24.38
5	1	24		24.25	24.3	24.42
5	12	0		23.17	23.15	23.35
5	12	6		23.13	23.23	23.24
5	12	11		23.24	23.33	23.25
5	25	0		23.2	23.22	23.3
5	1	0	16-QAM	23.54	23.42	23.22
5	1	12		23.5	23.46	23.18
5	1	24		23.73	23.5	23.34
5	12	0		22.15	22.13	22.34
5	12	6		22.15	22.22	22.25
5	12	11		22.26	22.32	22.23
5	25	0		22.2	22.26	22.27
10	1	0	QPSK	24.1	24.21	24.42
10	1	24		24.12	24.23	24.42
10	1	49		24.18	24.22	24.46
10	25	0		23.11	23.15	23.35
10	25	12		23.03	23.18	23.29
10	25	24		23.04	23.23	23.31
10	50	0		23.1	23.25	23.4
10	1	0	16-QAM	23.53	23.57	23.81
10	1	24		23.49	23.65	23.87
10	1	49		23.55	23.58	23.82
10	25	0		22.07	22.25	22.34
10	25	12		22	22.27	22.31
10	25	24		22	22.34	22.32
10	50	0		22.14	22.19	22.32



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.44	22.75	22.86
5	1	12		23.41	22.94	22.87
5	1	24		23.28	23	22.47
5	12	0		22.53	21.82	21.89
5	12	6		22.45	21.93	21.84
5	12	11		22.39	21.98	21.78
5	25	0		22.47	21.9	21.87
5	1	0	16-QAM	22.74	22.15	22.07
5	1	12		22.69	22.32	21.98
5	1	24		22.55	22.44	21.81
5	12	0		21.57	20.86	20.89
5	12	6		21.52	20.96	20.82
5	12	11		21.43	21.03	20.75
5	25	0		21.5	20.9	20.8
10	1	0	QPSK	23.51	22.79	22.66
10	1	24		23.47	22.82	22.39
10	1	49		23.47	22.91	22.39
10	25	0		22.46	21.79	21.73
10	25	12		22.43	21.8	21.73
10	25	24		22.43	21.88	21.68
10	50	0		22.49	21.82	21.74
10	1	0	16-QAM	22.42	22.17	21.85
10	1	24		22.33	22.15	21.76
10	1	49		22.41	22.24	21.74
10	25	0		21.48	20.79	20.75
10	25	12		21.43	20.82	20.73
10	25	24		21.42	20.89	20.73
10	50	0		21.47	20.8	20.75



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.51	22.79	22.84
15	1	37		23.49	22.86	22.7
15	1	74		23.4	22.91	22.58
15	36	0		22.47	21.79	21.76
15	36	18		22.44	21.83	21.71
15	36	39		22.41	21.9	21.75
15	75	0		22.46	21.87	21.77
15	1	0	16-QAM	22.86	21.97	21.92
15	1	38		22.89	22.09	21.83
15	1	75		22.8	22.1	21.8
15	36	0		21.52	20.85	20.76
15	36	18		21.48	20.89	20.71
15	36	39		21.45	20.95	20.74
15	75	0		21.47	20.83	20.79
20	1	0	QPSK	23.45	22.82	22.64
20	1	49		23.53	22.85	22.41
20	1	99		23.51	22.93	22.52
20	50	0		22.43	21.74	21.69
20	50	24		22.41	21.77	21.67
20	50	49		22.4	21.78	21.68
20	100	0		22.48	21.81	21.73
20	1	0	16-QAM	22.94	22.11	21.91
20	1	49		22.91	22.17	21.89
20	1	99		22.89	22.21	21.92
20	50	0		21.46	20.75	20.75
20	50	24		21.46	20.75	20.72
20	50	49		21.41	20.78	20.75
20	100	0		21.43	20.82	20.69



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.26	24.29	24.08
1.4	1	2		24.28	24.28	24.13
1.4	1	5		24.32	24.3	24.11
1.4	3	0		24.23	24.13	24.15
1.4	3	1		24.24	24.14	24.11
1.4	3	2		24.26	24.15	24.15
1.4	6	0		23.26	23.14	23.18
1.4	1	0	16-QAM	23.16	23.42	23.37
1.4	1	2		23.18	23.39	23.36
1.4	1	5		23.25	23.42	23.41
1.4	3	0		23.38	23.35	23.34
1.4	3	1		23.39	23.33	23.37
1.4	3	2		23.4	23.33	23.37
1.4	6	0		22.38	22.37	22.34
3	1	0	QPSK	24.17	24.14	24.16
3	1	7		24.19	24.15	24.2
3	1	14		24.17	24.17	24.23
3	8	0		23.12	23.19	23.19
3	8	4		23.15	23.18	23.11
3	8	7		23.15	23.2	23.07
3	15	0		23.13	23.18	23.17
3	1	0	16-QAM	23.68	23.4	23.13
3	1	7		23.67	23.41	23.05
3	1	14		23.59	23.41	23.15
3	8	0		22.18	22.16	22.26
3	8	4		22.23	22.14	22.17
3	8	7		22.21	22.18	22.11
3	15	0		22.23	22.11	22.21



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.34	24.29	24.25
5	1	12		24.29	24.19	24.18
5	1	24		24.34	24.29	24.23
5	12	0		23.26	23.33	23.16
5	12	6		23.2	23.2	23.19
5	12	11		23.19	23.32	23.12
5	25	0		23.24	23.36	23.15
5	1	0	16-QAM	23.22	23.68	23.44
5	1	12		23.19	23.65	23.41
5	1	24		23.23	23.69	23.49
5	12	0		22.17	22.33	22.11
5	12	6		22.17	22.23	22.17
5	12	11		22.16	22.38	22.03
5	25	0		22.24	22.31	22.11
10	1	0	QPSK	24.25	24.18	24.36
10	1	24		24.17	24.22	24.31
10	1	49		24.39	24.21	24.31
10	25	0		23.14	23.23	23.23
10	25	12		23.19	23.19	23.23
10	25	24		23.15	23.23	23.16
10	50	0		23.2	23.28	23.22
10	1	0	16-QAM	23.74	23.57	23.7
10	1	24		23.59	23.59	23.72
10	1	49		23.68	23.67	23.77
10	25	0		22.15	22.27	22.23
10	25	12		22.16	22.25	22.2
10	25	24		22.13	22.33	22.13
10	50	0		22.17	22.23	22.19



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.86	23.62	23.25
1.4	1	2		23.85	23.63	23.24
1.4	1	5		23.85	23.62	23.23
1.4	3	0		23.81	23.6	23.19
1.4	3	1		23.82	23.6	23.17
1.4	3	2		23.83	23.61	23.2
1.4	6	0		22.83	22.62	22.16
1.4	1	0	16-QAM	23.03	22.86	22.13
1.4	1	2		23.01	22.83	22.12
1.4	1	5		23.01	22.88	22.12
1.4	3	0		23.01	22.83	22.34
1.4	3	1		23	22.85	22.32
1.4	3	2		22.97	22.84	22.36
1.4	6	0		22.04	21.79	21.41
3	1	0	QPSK	23.8	23.66	23.26
3	1	7		23.77	23.7	23.24
3	1	14		23.72	23.71	23.21
3	8	0		22.82	22.6	22.38
3	8	4		22.82	22.61	22.25
3	8	7		22.86	22.68	22.17
3	15	0		22.85	22.64	22.33
3	1	0	16-QAM	23.08	22.61	22.57
3	1	7		23.08	22.66	22.63
3	1	14		22.98	22.62	22.61
3	8	0		21.83	21.61	21.35
3	8	4		21.81	21.59	21.23
3	8	7		21.88	21.65	21.11
3	15	0		21.8	21.71	21.31



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.96	23.6	23.57
5	1	12		23.73	23.74	23.44
5	1	24		23.73	23.73	23.39
5	12	0		22.67	22.65	22.62
5	12	6		22.69	22.76	22.46
5	12	11		22.44	22.96	22.47
5	25	0		22.57	22.83	22.52
5	1	0	16-QAM	23.14	22.91	22.93
5	1	12		22.87	23.07	22.81
5	1	24		22.97	23.06	22.81
5	12	0		21.59	21.65	21.66
5	12	6		21.67	21.8	21.44
5	12	11		21.47	21.97	21.49
5	25	0		21.54	21.83	21.52
10	1	0	QPSK	23.92	23.66	23.38
10	1	24		23.84	23.72	23.26
10	1	49		23.69	23.73	23.34
10	25	0		22.73	22.62	22.23
10	25	12		22.79	22.71	22.34
10	25	24		22.84	22.82	22.13
10	50	0		22.81	22.72	22.18
10	1	0	16-QAM	23.39	22.84	22.28
10	1	24		23.18	22.91	22.23
10	1	49		23.03	22.96	22.24
10	25	0		21.78	21.61	21.18
10	25	12		21.82	21.68	21.3
10	25	24		21.85	21.82	21.14
10	50	0		21.78	21.77	21.12



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.92	23.69	23.43
15	1	37		23.73	23.83	23.42
15	1	74		23.6	23.85	23.35
15	36	0		22.72	22.61	22.34
15	36	18		22.68	22.71	22.28
15	36	39		22.58	22.85	22.3
15	75	0		22.63	22.8	22.34
15	1	0	16-QAM	23.1	22.75	22.89
15	1	38		22.94	22.9	22.79
15	1	75		22.8	22.93	22.73
15	36	0		21.79	21.59	21.37
15	36	18		21.76	21.65	21.36
15	36	39		21.65	21.78	21.33
15	75	0		21.66	21.85	21.34
20	1	0	QPSK	24.01	23.69	23.17
20	1	49		24.06	23.77	23.23
20	1	99		23.98	23.75	23.2
20	50	0		22.86	22.64	22.35
20	50	24		22.86	22.67	22.32
20	50	49		22.91	22.73	22.24
20	100	0		22.93	22.75	22.3
20	1	0	16-QAM	23.43	23.12	22.53
20	1	49		23.41	23.25	22.57
20	1	99		23.31	23.17	22.53
20	50	0		21.88	21.62	21.39
20	50	24		21.87	21.66	21.28
20	50	49		21.9	21.71	21.13
20	100	0		21.83	21.73	21.27



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.15	24.2	24.01
1.4	1	2		24.15	24.18	23.98
1.4	1	5		24.14	24.14	24.05
1.4	3	0		24.14	24.08	24
1.4	3	1		24.15	24.07	24.02
1.4	3	2		24.15	24.06	24.01
1.4	6	0		23.15	23.07	23.05
1.4	1	0	16-QAM	23.08	23.33	23.26
1.4	1	2		23.09	23.28	23.18
1.4	1	5		23.1	23.29	23.35
1.4	3	0		23.28	23.29	23.23
1.4	3	1		23.28	23.22	23.26
1.4	3	2		23.28	23.2	23.22
1.4	6	0		22.33	22.26	22.21
3	1	0	QPSK	24.2	24.07	24.02
3	1	7		24.12	24.07	24.06
3	1	14		24.05	24	24.14
3	8	0		23.1	23.02	23.02
3	8	4		23.1	23.11	22.96
3	8	7		23.15	23.14	22.92
3	15	0		23.12	23.11	23
3	1	0	16-QAM	23.51	23.31	22.92
3	1	7		23.54	23.29	22.96
3	1	14		23.55	23.26	23.01
3	8	0		22.18	21.99	22.07
3	8	4		22.14	22.05	22.02
3	8	7		22.25	22.14	21.97
3	15	0		22.2	22	22.09



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.12	24.16	24.09
5	1	12		24.08	24.14	24.05
5	1	24		24.14	24.12	24.15
5	12	0		22.97	23	23.03
5	12	6		23.08	23.1	23.06
5	12	11		23.05	23.12	23.02
5	25	0		23.05	23.15	23.1
5	1	0	16-QAM	23.34	23.56	23.44
5	1	12		23.29	23.56	23.38
5	1	24		23.38	23.56	23.42
5	12	0		22.03	22.05	22.11
5	12	6		22.1	22.11	22.08
5	12	11		22.03	22.08	22.03
5	25	0		22.08	22.16	22.02
10	1	0	QPSK	/	24.25	/
10	1	24		/	24.22	/
10	1	49		/	24.22	/
10	25	0		/	23.11	/
10	25	12		/	23.11	/
10	25	24		/	23.19	/
10	50	0		/	23.25	/
10	1	0	16-QAM	/	23.66	/
10	1	24		/	23.71	/
10	1	49		/	23.73	/
10	25	0		/	22.16	/
10	25	12		/	22.16	/
10	25	24		/	22.26	/
10	50	0		/	22.13	/



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.11	24.19	24.29
1.4	1	2		24.12	24.2	24.3
1.4	1	5		24.12	24.19	24.3
1.4	3	0		24.04	24.18	24.3
1.4	3	1		24.04	24.18	24.3
1.4	3	2		24.08	24.19	24.29
1.4	6	0		23.09	23.18	23.32
1.4	1	0	16-QAM	23.29	23.45	23.2
1.4	1	2		23.27	23.41	23.22
1.4	1	5		23.3	23.46	23.23
1.4	3	0		23.27	23.4	23.41
1.4	3	1		23.28	23.43	23.43
1.4	3	2		23.27	23.41	23.41
1.4	6	0		22.32	22.38	22.43
3	1	0	QPSK	24.03	24.22	24.22
3	1	7		24.06	24.25	24.27
3	1	14		24.09	24.27	24.26
3	8	0		23.13	23.17	23.27
3	8	4		23.06	23.19	23.22
3	8	7		23.04	23.26	23.3
3	15	0		23.1	23.23	23.25
3	1	0	16-QAM	23.33	23.14	23.68
3	1	7		23.3	23.14	23.67
3	1	14		23.32	23.13	23.67
3	8	0		22.16	22.17	22.29
3	8	4		22.08	22.18	22.28
3	8	7		22.07	22.24	22.37
3	15	0		22.04	22.33	22.31



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.36	24.26	24.35
5	1	12		24.34	24.27	24.25
5	1	24		24.36	24.32	24.31
5	12	0		23.23	23.17	23.38
5	12	6		23.16	23.24	23.32
5	12	11		23.14	23.28	23.31
5	25	0		23.22	23.3	23.38
5	1	0	16-QAM	23.65	23.68	23.7
5	1	12		23.73	23.63	23.71
5	1	24		23.69	23.73	23.67
5	12	0		22.21	22.16	22.4
5	12	6		22.14	22.24	22.34
5	12	11		22.12	22.26	22.38
5	25	0		22.15	22.29	22.35
10	1	0	QPSK	24.21	24.22	24.29
10	1	24		24.2	24.22	24.27
10	1	49		24.31	24.35	24.34
10	25	0		23.17	23.1	23.41
10	25	12		23.13	23.2	23.32
10	25	24		23.22	23.34	23.29
10	50	0		23.22	23.26	23.33
10	1	0	16-QAM	23.12	23.66	23.49
10	1	24		23.06	23.67	23.51
10	1	49		23.21	23.82	23.55
10	25	0		22.18	22.18	22.38
10	25	12		22.12	22.26	22.29
10	25	24		22.21	22.37	22.28
10	50	0		22.18	22.26	22.4



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.15	24.17	24.31
15	1	37		24.18	24.25	24.37
15	1	74		24.3	24.36	24.48
15	36	0		23.14	23.13	23.18
15	36	18		23.15	23.23	23.27
15	36	39		23.29	23.31	23.19
15	75	0		23.24	23.25	23.19
15	1	0	16-QAM	23.53	23.37	23.36
15	1	38		23.64	23.44	23.4
15	1	75		23.75	23.56	23.51
15	36	0		22.21	22.2	22.14
15	36	18		22.19	22.3	22.24
15	36	39		22.33	22.37	22.22
15	75	0		22.28	22.22	22.28



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.69	23.72	23.54
5	1	12		23.73	23.86	23.56
5	1	24		23.79	23.82	23.53
5	12	0		23.46	23.81	23.61
5	12	6		23.46	23.88	23.6
5	12	11		23.46	23.85	23.63
5	25	0		23.52	23.93	23.69
5	1	0	16-QAM	23.98	23.91	23.78
5	1	12		23.96	23.98	23.86
5	1	24		24.02	23.96	23.78
5	12	0		23.51	23.85	23.71
5	12	6		23.49	23.89	23.72
5	12	11		23.49	23.89	23.73
5	25	0		23.52	23.94	23.68
10	1	0	QPSK	23.48	23.9	23.83
10	1	24		23.56	24.05	23.66
10	1	49		23.51	23.79	23.6
10	25	0		23.62	23.9	23.81
10	25	12		23.65	23.96	23.76
10	25	24		23.65	23.91	23.75
10	50	0		23.63	23.86	23.75
10	1	0	16-QAM	23.69	23.87	24.09
10	1	24		23.77	23.99	23.95
10	1	49		23.71	23.68	23.86
10	25	0		23.68	23.89	23.84
10	25	12		23.7	23.88	23.8
10	25	24		23.7	23.84	23.76
10	50	0		23.67	23.84	23.84



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.56	23.82	24.09
15	1	37		23.67	24.01	23.97
15	1	74		23.63	23.81	23.95
15	36	0		23.52	23.78	23.68
15	36	18		23.55	23.9	23.67
15	36	39		23.56	23.82	23.63
15	75	0		23.55	23.81	23.68
15	1	0	16-QAM	24.09	23.89	23.99
15	1	38		24.18	24.02	23.88
15	1	75		24.13	23.85	23.87
15	36	0		23.58	23.88	23.77
15	36	18		23.61	23.93	23.72
15	36	39		23.63	23.9	23.72
15	75	0		23.59	23.85	23.77
20	1	0	QPSK	23.52	23.77	23.69
20	1	49		23.54	23.93	23.57
20	1	99		23.62	23.86	23.6
20	50	0		23.53	23.78	23.73
20	50	24		23.53	23.83	23.7
20	50	49		23.61	23.83	23.69
20	100	0		23.51	23.9	23.69
20	1	0	16-QAM	24.12	23.83	23.68
20	1	49		24.14	23.94	23.58
20	1	99		24.19	23.89	23.58
20	50	0		23.5	23.81	23.72
20	50	24		23.48	23.88	23.69
20	50	49		23.56	23.88	23.73
20	100	0		23.55	23.91	23.71



LTE Band 40 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.2	23.08	23.05
5	1	12		23.14	23.08	23.06
5	1	24		23.15	23.04	23
5	12	0		22.07	22.05	21.99
5	12	6		22.06	22.04	21.98
5	12	11		22.1	22.05	22.01
5	25	0		22.09	22.09	22.07
5	1	0	16-QAM	22.67	22.4	22.33
5	1	12		22.58	22.36	22.33
5	1	24		22.66	22.34	22.3
5	12	0		21.1	21.05	21.06
5	12	6		21.07	21.03	21.06
5	12	11		21.13	21.04	21.09
5	25	0		21.09	21.1	21
10	1	0	QPSK	/	23.31	/
10	1	24		/	23.3	/
10	1	49		/	23.3	/
10	25	0		/	22.11	/
10	25	12		/	22.11	/
10	25	24		/	22.09	/
10	50	0		/	22.16	/
10	1	0	16-QAM	/	22.76	/
10	1	24		/	22.69	/
10	1	49		/	22.71	/
10	25	0		/	21.15	/
10	25	12		/	21.12	/
10	25	24		/	21.13	/
10	50	0		/	21.08	/



LTE Band 40 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.55	23.46	23.57
5	1	12		23.54	23.43	23.53
5	1	24		23.51	23.46	23.52
5	12	0		22.51	22.46	22.52
5	12	6		22.49	22.42	22.49
5	12	11		22.47	22.45	22.52
5	25	0		22.54	22.53	22.51
5	1	0	16-QAM	22.84	22.78	23.1
5	1	12		22.82	22.77	22.94
5	1	24		22.81	22.78	23
5	12	0		21.5	21.53	21.53
5	12	6		21.5	21.51	21.49
5	12	11		21.48	21.51	21.54
5	25	0		21.56	21.48	21.52
10	1	0	QPSK	/	23.6	/
10	1	24		/	23.6	/
10	1	49		/	23.64	/
10	25	0		/	22.46	/
10	25	12		/	22.44	/
10	25	24		/	22.47	/
10	50	0		/	22.52	/
10	1	0	16-QAM	/	23.09	/
10	1	24		/	23.07	/
10	1	49		/	23.08	/
10	25	0		/	21.49	/
10	25	12		/	21.47	/
10	25	24		/	21.47	/
10	50	0		/	21.46	/



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.29	23.75	22.92
5	1	12		24.38	23.79	22.87
5	1	24		24.39	23.82	22.86
5	12	0		24.18	23.83	22.97
5	12	6		24.16	23.8	22.86
5	12	11		24.25	23.86	22.81
5	25	0		24.22	23.86	22.93
5	1	0	16-QAM	24.67	23.95	23.11
5	1	12		24.7	23.99	23.07
5	1	24		24.76	24	23.05
5	12	0		24.2	23.86	22.99
5	12	6		24.2	23.89	22.91
5	12	11		24.23	23.84	22.91
5	25	0		24.18	23.94	22.91
10	1	0	QPSK	24.19	23.88	23.16
10	1	24		24.28	23.79	23.02
10	1	49		24.35	23.9	22.96
10	25	0		24.19	23.81	23.09
10	25	12		24.27	23.84	23
10	25	24		24.31	23.86	22.96
10	50	0		24.24	23.84	23.01
10	1	0	16-QAM	24.71	23.88	23.27
10	1	24		24.79	23.87	23.13
10	1	49		24.85	23.89	23.05
10	25	0		24.23	23.89	23.11
10	25	12		24.24	23.83	23.02
10	25	24		24.32	23.84	22.97
10	50	0		24.24	23.89	23.03



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.15	23.88	23.68
15	1	37		24.28	23.97	23.39
15	1	74		24.21	23.88	23.14
15	36	0		24.3	23.9	23.6
15	36	18		24.37	23.94	23.43
15	36	39		24.37	23.92	23.23
15	75	0		24.33	23.9	23.43
15	1	0	16-QAM	24.34	23.98	23.99
15	1	38		24.49	23.93	23.71
15	1	75		24.38	23.78	23.52
15	36	0		24.33	23.88	23.59
15	36	18		24.41	23.93	23.4
15	36	39		24.43	23.87	23.22
15	75	0		24.36	23.86	23.46
20	1	0	QPSK	24.26	23.8	23.71
20	1	49		24.37	23.86	23.42
20	1	99		24.33	23.77	23.41
20	50	0		24.18	23.83	23.33
20	50	24		24.25	23.83	23.22
20	50	49		24.3	23.8	23.09
20	100	0		24.29	23.83	23.24
20	1	0	16-QAM	24.74	23.88	23.74
20	1	49		24.78	23.91	23.48
20	1	99		24.86	23.86	23.33
20	50	0		24.28	23.9	23.4
20	50	24		24.32	23.93	23.25
20	50	49		24.38	23.9	23.15
20	100	0		24.3	23.84	23.29



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.35	24.28	24.18
1.4	1	2		24.34	24.29	24.19
1.4	1	5		24.32	24.29	24.17
1.4	3	0		24.26	24.3	24.15
1.4	3	1		24.26	24.27	24.17
1.4	3	2		24.27	24.27	24.15
1.4	6	0		23.29	23.3	23.17
1.4	1	0	16-QAM	23.49	23.57	23.1
1.4	1	2		23.46	23.55	23.11
1.4	1	5		23.46	23.58	23.13
1.4	3	0		23.52	23.5	23.3
1.4	3	1		23.43	23.54	23.31
1.4	3	2		23.44	23.5	23.32
1.4	6	0		22.53	22.48	22.32
3	1	0	QPSK	24.31	24.34	24.12
3	1	7		24.34	24.38	24.14
3	1	14		24.33	24.35	24.15
3	8	0		23.3	23.37	23.2
3	8	4		23.25	23.32	23.17
3	8	7		23.27	23.34	23.19
3	15	0		23.3	23.36	23.17
3	1	0	16-QAM	23.26	23.77	23.37
3	1	7		23.27	23.79	23.42
3	1	14		23.2	23.8	23.39
3	8	0		22.32	22.35	22.2
3	8	4		22.27	22.3	22.16
3	8	7		22.27	22.37	22.2
3	15	0		22.33	22.36	22.15



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.43	24.35	24.29
5	1	12		24.38	24.39	24.39
5	1	24		24.32	24.39	24.37
5	12	0		23.35	23.4	23.25
5	12	6		23.32	23.38	23.24
5	12	11		23.3	23.42	23.24
5	25	0		23.4	23.47	23.28
5	1	0	16-QAM	23.87	23.77	23.69
5	1	12		23.84	23.77	23.78
5	1	24		23.82	23.78	23.74
5	12	0		22.31	22.43	22.27
5	12	6		22.31	22.4	22.23
5	12	11		22.27	22.47	22.23
5	25	0		22.38	22.39	22.23
10	1	0	QPSK	24.36	24.48	24.24
10	1	24		24.29	24.51	24.24
10	1	49		24.37	24.51	24.28
10	25	0		23.38	23.41	23.32
10	25	12		23.33	23.4	23.27
10	25	24		23.37	23.42	23.27
10	50	0		23.39	23.44	23.27
10	1	0	16-QAM	23.57	23.37	23.66
10	1	24		23.52	23.36	23.66
10	1	49		23.6	23.39	23.69
10	25	0		22.35	22.39	22.3
10	25	12		22.3	22.36	22.24
10	25	24		22.32	22.4	22.19
10	50	0		22.4	22.39	22.25



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.48	24.45	24.27
15	1	37		24.44	24.51	24.29
15	1	74		24.46	24.49	24.27
15	36	0		23.38	23.4	23.31
15	36	18		23.33	23.44	23.27
15	36	39		23.39	23.42	23.26
15	75	0		23.38	23.46	23.27
15	1	0	16-QAM	23.53	23.9	23.52
15	1	38		23.49	23.94	23.56
15	1	75		23.5	23.92	23.51
15	36	0		22.34	22.42	22.39
15	36	18		22.31	22.44	22.34
15	36	39		22.36	22.46	22.32
15	75	0		22.42	22.46	22.31
20	1	0	QPSK	24.37	24.49	24.4
20	1	49		24.39	24.53	24.35
20	1	99		24.41	24.52	24.38
20	50	0		23.45	23.47	23.38
20	50	24		23.44	23.5	23.39
20	50	49		23.44	23.48	23.26
20	100	0		23.47	23.51	23.31
20	1	0	16-QAM	23.76	23.89	23.57
20	1	49		23.75	23.97	23.55
20	1	99		23.75	23.95	23.59
20	50	0		22.48	22.5	22.34
20	50	24		22.47	22.54	22.35
20	50	49		22.47	22.52	22.25
20	100	0		22.45	22.48	22.3



10.2 Tune up Power

Mode	GSM850	GSM1900
GSM/PCS	33.3±1dBm	30.4±1dBm
GPRS (1 Slot)	33.3±1dBm	30.4±1dBm
GPRS (2 Slot)	32.6±1dBm	29.6±1dBm
GPRS (3 Slot)	31±1dBm	27.6±1dBm
GPRS (4 Slot)	30±1dBm	26.3±1dBm
EDGE (1 Slot)	27.5±1dBm	26.6±1dBm
EDGE (2 Slot)	27±1dBm	25.3±1dBm
EDGE (3 Slot)	25±1dBm	23.6±1dBm
EDGE (4 Slot)	23.5±1dBm	22.2±1dBm

Mode	WCDMA Band II	WCDMA Band IV	WCDMA Band V
RMR	22.6±1dBm	23.5±1dBm	23.2±1dBm
HSDPA Subtest-1	23.2±1dBm	23±1dBm	22.4±1dBm
HSDPA Subtest-2	22.7±1dBm	23±1dBm	22.3±1dBm
HSDPA Subtest-3	22.5±1dBm	22.4±1dBm	22±1dBm
HSDPA Subtest-4	22.1±1dBm	22.4±1dBm	22±1dBm
HSUPA Subtest-1	23.1±1dBm	23±1dBm	22.5±1dBm
HSUPA Subtest-2	23±1dBm	23±1dBm	22.3±1dBm
HSUPA Subtest-3	23±1dBm	23±1dBm	22.3±1dBm
HSUPA Subtest-4	23±1dBm	23±1dBm	22.3±1dBm
HSUPA Subtest-5	23±1dBm	23±1dBm	22.2±1dBm

Mode	NFC
NFC	-38±1dBm

Mode	BT
GFSK	2.1±1dBm
π/4-DQPSK	4.5±1dBm
8DPSK	5±1dBm

Mode	BLE
GFSK(1Mbps)	-5.5±1dBm
GFSK(2Mbps)	-6±1dBm

Mode	2.4G WLAN
802.11b	15.5±1dBm
802.11g	15.2±1dBm
802.11n(HT20)	14.5±1dBm
802.11n(HT40)	12.5±1dBm



Mode	5.2G WLAN
802.11a	11.2±1dBm
802.11 n-HT20	10±1dBm
802.11 n-HT40	10±1dBm
802.11 ac-VHT20	10.5±1dBm
802.11 ac-VHT40	9.6±1dBm
802.11 ac-VHT80	8±1dBm

Mode	5.3G WLAN
802.11a	12.2±1dBm
802.11 n-HT20	11±1dBm
802.11 n-HT40	10.3±1dBm
802.11 ac-VHT20	11±1dBm
802.11 ac-VHT40	10.5±1dBm
802.11 ac-VHT80	8±1dBm

Mode	5.8G WLAN
802.11a	12.5±1dBm
802.11 n-HT20	11.3±1dBm
802.11 n-HT40	11.6±1dBm
802.11 ac-VHT20	11.3±1dBm
802.11 ac-VHT40	11.5±1dBm
802.11 ac-VHT80	9±1dBm



BW [MHz]	RB Size	Mode	Band 2	Band 4	Band 5	Band 7	Band 12	Band 25	Band 26 (814-824)
1.4	1	QPSK	23.5±1dBm	23±1dBm	23.3±1dBm	N/A	23.5±1dBm	23±1dBm	23.3±1dBm
1.4	3		23.5±1dBm	23±1dBm	23.3±1dBm	N/A	23.3±1dBm	23±1dBm	23.2±1dBm
1.4	6		22.5±1dBm	22±1dBm	22.2±1dBm	N/A	22.3±1dBm	22±1dBm	22.2±1dBm
1.4	1	16-QAM	22.6±1dBm	22.1±1dBm	22.5±1dBm	N/A	22.5±1dBm	22.1±1dBm	22.5±1dBm
1.4	3		22.7±1dBm	22.1±1dBm	22.5±1dBm	N/A	22.5±1dBm	22.1±1dBm	22.3±1dBm
1.4	6		21.6±1dBm	21±1dBm	21.5±1dBm	N/A	21.5±1dBm	21.1±1dBm	21.5±1dBm
3	1	QPSK	23.5±1dBm	23±1dBm	23.3±1dBm	N/A	23.3±1dBm	23±1dBm	23.3±1dBm
3	8		22.5±1dBm	22±1dBm	22.3±1dBm	N/A	22.3±1dBm	22±1dBm	22.2±1dBm
3	15		22.5±1dBm	22±1dBm	22.3±1dBm	N/A	22.2±1dBm	22±1dBm	22.2±1dBm
3	1	16-QAM	22.7±1dBm	22.2±1dBm	22.6±1dBm	N/A	22.7±1dBm	22.1±1dBm	22.6±1dBm
3	8		21.5±1dBm	21±1dBm	21.3±1dBm	N/A	21.3±1dBm	21±1dBm	21.3±1dBm
3	15		21.5±1dBm	21±1dBm	21.3±1dBm	N/A	21.3±1dBm	21±1dBm	21.3±1dBm
5	1	QPSK	23.7±1dBm	23±1dBm	23.5±1dBm	22.5±1dBm	23.5±1dBm	23±1dBm	23.2±1dBm
5	12		22.5±1dBm	22±1dBm	22.5±1dBm	21.6±1dBm	22.5±1dBm	22±1dBm	22.2±1dBm
5	25		22.5±1dBm	22±1dBm	22.5±1dBm	21.5±1dBm	22.5±1dBm	22±1dBm	22.2±1dBm
5	1	16-QAM	23±1dBm	22.5±1dBm	23±1dBm	22±1dBm	22.7±1dBm	22.2±1dBm	22.6±1dBm
5	12		21.5±1dBm	21±1dBm	21.5±1dBm	20.6±1dBm	21.5±1dBm	21±1dBm	21.2±1dBm
5	25		21.5±1dBm	21±1dBm	21.3±1dBm	20.6±1dBm	21.5±1dBm	21±1dBm	21.2±1dBm
10	1	QPSK	23.7±1dBm	23±1dBm	23.5±1dBm	22.6±1dBm	23.5±1dBm	23±1dBm	23.3±1dBm
10	25		22.5±1dBm	22±1dBm	22.5±1dBm	21.5±1dBm	22.3±1dBm	22±1dBm	22.2±1dBm
10	50		22.5±1dBm	22±1dBm	22.5±1dBm	21.5±1dBm	22.3±1dBm	22±1dBm	22.3±1dBm
10	1	16-QAM	23±1dBm	22.3±1dBm	23±1dBm	21.5±1dBm	23±1dBm	22.5±1dBm	23±1dBm
10	25		21.6±1dBm	21±1dBm	21.5±1dBm	20.5±1dBm	21.5±1dBm	21±1dBm	21.3±1dBm
10	50		21.5±1dBm	21±1dBm	21.5±1dBm	20.5±1dBm	21.5±1dBm	21±1dBm	21.2±1dBm
15	1	QPSK	23.7±1dBm	23±1dBm	N/A	22.6±1dBm	N/A	23±1dBm	N/A
15	36		22.5±1dBm	22±1dBm	N/A	21.5±1dBm	N/A	22±1dBm	N/A
15	75		22.5±1dBm	22±1dBm	N/A	21.5±1dBm	N/A	22±1dBm	N/A
15	1	16-QAM	23±1dBm	22.3±1dBm	N/A	22±1dBm	N/A	22.2±1dBm	N/A
15	36		21.5±1dBm	21±1dBm	N/A	20.6±1dBm	N/A	21±1dBm	N/A
15	75		21.5±1dBm	21±1dBm	N/A	20.5±1dBm	N/A	21±1dBm	N/A
20	1	QPSK	24±1dBm	23±1dBm	N/A	22.6±1dBm	N/A	23.1±1dBm	N/A
20	50		22.5±1dBm	22±1dBm	N/A	21.5±1dBm	N/A	22±1dBm	N/A
20	100		22.5±1dBm	22±1dBm	N/A	21.5±1dBm	N/A	22±1dBm	N/A
20	1	16-QAM	23±1dBm	22.3±1dBm	N/A	22±1dBm	N/A	22.5±1dBm	N/A
20	50		21.6±1dBm	21±1dBm	N/A	20.5±1dBm	N/A	21±1dBm	N/A
20	100		21.5±1dBm	21±1dBm	N/A	20.5±1dBm	N/A	21±1dBm	N/A




BW [MHz]	RB Size	Mode	Band 26 (824-849)	Band 38	Band 40 (2305-2315)	Band 40 (2350-2360)	Band 41	Band 66
1.4	1	QPSK	23.5±1dBm	N/A	N/A	N/A	N/A	23.5±1dBm
1.4	3		23.5±1dBm	N/A	N/A	N/A	N/A	23.5±1dBm
1.4	6		22.5±1dBm	N/A	N/A	N/A	N/A	22.5±1dBm
1.4	1	16-QAM	22.5±1dBm	N/A	N/A	N/A	N/A	22.6±1dBm
1.4	3		22.5±1dBm	N/A	N/A	N/A	N/A	22.6±1dBm
1.4	6		21.5±1dBm	N/A	N/A	N/A	N/A	21.6±1dBm
3	1	QPSK	23.3±1dBm	N/A	N/A	N/A	N/A	23.5±1dBm
3	8		22.5±1dBm	N/A	N/A	N/A	N/A	22.5±1dBm
3	15		22.3±1dBm	N/A	N/A	N/A	N/A	22.5±1dBm
3	1	16-QAM	23±1dBm	N/A	N/A	N/A	N/A	23±1dBm
3	8		21.5±1dBm	N/A	N/A	N/A	N/A	21.5±1dBm
3	15		21.5±1dBm	N/A	N/A	N/A	N/A	21.5±1dBm
5	1	QPSK	23.5±1dBm	23±1dBm	22.3±1dBm	22.6±1dBm	23.5±1dBm	23.5±1dBm
5	12		22.5±1dBm	23±1dBm	21.2±1dBm	21.6±1dBm	23.3±1dBm	22.5±1dBm
5	25		22.5±1dBm	23±1dBm	21.1±1dBm	21.6±1dBm	23.3±1dBm	22.5±1dBm
5	1	16-QAM	23±1dBm	23.1±1dBm	22±1dBm	22.2±1dBm	24±1dBm	23±1dBm
5	12		21.5±1dBm	23±1dBm	20.2±1dBm	20.6±1dBm	23.3±1dBm	21.5±1dBm
5	25		21.5±1dBm	23±1dBm	20.2±1dBm	20.6±1dBm	23.2±1dBm	21.5±1dBm
10	1	QPSK	23.5±1dBm	23.1±1dBm	22.5±1dBm	22.7±1dBm	23.5±1dBm	23.6±1dBm
10	25		22.5±1dBm	23±1dBm	21.2±1dBm	21.5±1dBm	23.5±1dBm	22.5±1dBm
10	50		22.5±1dBm	23±1dBm	21.2±1dBm	21.6±1dBm	23.3±1dBm	22.5±1dBm
10	1	16-QAM	23±1dBm	23.1±1dBm	22±1dBm	22.1±1dBm	24±1dBm	23±1dBm
10	25		21.5±1dBm	23±1dBm	20.2±1dBm	20.5±1dBm	23.5±1dBm	21.5±1dBm
10	50		21.5±1dBm	23±1dBm	20.1±1dBm	20.5±1dBm	23.3±1dBm	21.5±1dBm
15	1	QPSK	23.5±1dBm	23.1±1dBm	N/A	N/A	23.3±1dBm	23.6±1dBm
15	36		22.5±1dBm	23±1dBm	N/A	N/A	23.5±1dBm	22.5±1dBm
15	75		22.3±1dBm	23±1dBm	N/A	N/A	23.5±1dBm	22.5±1dBm
15	1	16-QAM	N/A	23.2±1dBm	N/A	N/A	23.5±1dBm	23±1dBm
15	36		N/A	23±1dBm	N/A	N/A	23.5±1dBm	21.5±1dBm
15	75		N/A	23±1dBm	N/A	N/A	23.5±1dBm	21.5±1dBm
20	1	QPSK	N/A	23.2±1dBm	N/A	N/A	24±1dBm	23.6±1dBm
20	50		N/A	23±1dBm	N/A	N/A	23.5±1dBm	22.6±1dBm
20	100		N/A	23±1dBm	N/A	N/A	23.5±1dBm	22.6±1dBm
20	1	16-QAM	N/A	23±1dBm	N/A	N/A	23.5±1dBm	23±1dBm
20	50		N/A	23±1dBm	N/A	N/A	23.5±1dBm	21.6±1dBm
20	100		N/A	23±1dBm	N/A	N/A	23.5±1dBm	21.5±1dBm



11. EUT and Test Setup Photo

11.1 EUT Photos

Front side




Back side






Right Edge




Left Edge






Top Edge




Bottom Edge






11.2 Setup Photos


Body Back side (separation distance 0mm)



Body Left side (separation distance is 0mm)



Body Right side (separation distance is 0mm)



Body Top side (separation distance is 0mm)





Body Bottom side (separation distance is 0mm)





12. SAR Result Summary

12.2 Body-worn and Hotspot SAR

Band	Model	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
GSM850	GPRS Data-4 Slot	Back Side	836.6	0.555	0.17	31.00	30.79	1.050	0.582	1
		Left Side	836.6	0.192	1.45	31.00	30.79	1.050	0.202	/
		Right Side	836.6	0.056	-0.93	31.00	30.79	1.050	0.059	/
		Top Side	836.6	0.303	3.31	31.00	30.79	1.050	0.318	/
		Bottom Side	836.6	0.053	2.32	31.00	30.79	1.050	0.056	/
PCS 1900	GPRS (GMSK, 2-Slot)	Back Side	1850.2	1.045	-0.01	30.60	30.30	1.072	1.120	/
		Back Side	1880	1.056	1.00	30.60	30.23	1.089	1.150	/
		Back Side	1909.8	1.145	0.44	30.60	30.54	1.014	1.161	2
		Left Side	1909.8	0.377	2.72	30.60	30.54	1.014	0.382	/
		Right Side	1909.8	0.116	0.61	30.60	30.54	1.014	0.118	/
		Top Side	1909.8	0.639	-2.42	30.60	30.54	1.014	0.648	/
WCDMA Band II	HSDPA Subtest-1	Back Side	1852.4	0.858	-2.78	24.20	24.17	1.007	0.864	3
		Back Side	1880	0.756	2.78	24.20	23.69	1.125	0.850	/
		Back Side	1907.6	0.765	-0.77	24.20	23.70	1.122	0.858	/
		Right Side	1852.4	0.087	-1.96	24.20	24.17	1.007	0.088	/
		Top Side	1852.4	0.503	0.23	24.20	24.17	1.007	0.506	/
WCDMA Band IV	RMC	Back Side	1712.6	0.670	-3.35	24.50	24.44	1.014	0.679	4
		Right Side	1712.6	0.07	-0.26	24.50	24.44	1.014	0.071	/
		Top Side	1712.6	0.395	1.31	24.50	24.44	1.014	0.400	/
WCDMA Band V	RMC	Back Side	846.6	0.772	-2.27	24.20	24.13	1.016	0.785	5
		Right Side	846.6	0.081	-1.14	24.20	24.13	1.016	0.082	/
		Top Side	846.6	0.415	3.00	24.20	24.13	1.016	0.422	/
2.4GHz WLAN	802.11b	Back Side	2412	0.376	3.92	16.50	16.33	1.040	0.391	6
		Top Side	2412	0.238	-0.25	16.50	16.33	1.040	0.248	/
5.2GHz WLAN	802.11a	Back Side	5240	0.199	-0.85	12.20	12.18	1.005	0.200	7
		Top Side	5240	0.07	-0.09	12.20	12.18	1.005	0.070	/
5.3GHz WLAN	802.11a	Back Side	5320	0.221	-1.83	13.20	13.16	1.009	0.223	8
		Top Side	5320	0.108	-0.21	13.20	13.16	1.009	0.109	/
5.8GHz WLAN	802.11a	Back Side	5785	0.284	0.35	13.50	13.33	1.040	0.295	9
		Top Side	5785	0.127	3.58	13.50	13.33	1.040	0.132	/



Band	BW (MHz)	Mod.	RB Size	RB off set	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Back Side	1860	0.789	-3.12	25.00	24.44	1.138	0.898	/
			1	0	Back Side	1880	0.859	0.53	25.00	24.76	1.057	0.908	10
			1	0	Back Side	1900	0.802	-1.00	25.00	24.50	1.122	0.900	/
			50	0	Back Side	1880	0.756	-0.64	23.50	23.48	1.005	0.759	/
			1	0	Right Side	1880	0.089	-1.86	25.00	24.76	1.057	0.094	/
			50	0	Right Side	1880	0.076	3.04	23.50	23.48	1.005	0.076	/
			1	0	Top Side	1880	0.479	-1.55	25.00	24.76	1.057	0.506	/
			50	0	Top Side	1880	0.422	0.48	23.50	23.48	1.005	0.424	/
LTE Band 4	20M	QPSK	1	0	Back Side	1732.5	0.215	-2.11	24.00	23.97	1.007	0.216	11
			50	0	Back Side	1745	0.188	-0.33	23.00	22.98	1.005	0.189	/
			1	0	Right Side	1732.5	0.022	2.19	24.00	23.97	1.007	0.022	/
			50	0	Right Side	1745	0.022	-3.10	23.00	22.98	1.005	0.022	/
			1	0	Top Side	1732.5	0.127	-0.16	24.00	23.97	1.007	0.128	/
			50	0	Top Side	1745	0.11	-0.85	23.00	22.98	1.005	0.111	/
LTE Band 5	10M	QPSK	1	0	Back Side	829	0.776	-3.76	24.50	24.18	1.076	0.835	/
			1	0	Back Side	836.5	0.794	0.17	24.50	24.23	1.064	0.845	/
			1	0	Back Side	844	0.842	3.36	24.50	24.46	1.009	0.850	12
			25	0	Back Side	844	0.744	1.94	23.50	23.35	1.035	0.770	/
			1	0	Right Side	844	0.085	0.00	24.50	24.46	1.009	0.086	/
			25	0	Right Side	844	0.075	3.90	23.50	23.35	1.035	0.078	/
			1	0	Top Side	844	0.503	-1.22	24.50	24.46	1.009	0.508	/
			25	0	Top Side	844	0.446	-1.43	23.50	23.35	1.035	0.462	/
LTE Band 7	20M	QPSK	1	0	Back Side	2510	1.078	3.86	23.60	23.53	1.016	1.095	13
			1	0	Back Side	2535	0.926	1.88	23.60	22.93	1.167	1.081	/
			1	0	Back Side	2560	0.871	-2.49	23.60	22.64	1.247	1.086	/
			50	0	Back Side	2510	0.964	0.06	22.50	22.43	1.016	0.980	/
			50	0	Back Side	2535	0.78	2.96	22.50	21.78	1.180	0.921	/
			50	0	Back Side	2560	0.803	0.41	22.50	21.69	1.205	0.968	/
			100	0	Back Side	2510	0.943	3.03	22.50	22.48	1.005	0.947	/
			100	0	Back Side	2535	0.777	-0.15	22.50	21.81	1.172	0.911	/
			100	0	Back Side	2560	0.787	-2.19	22.50	21.73	1.194	0.940	/
			1	0	Right Side	2510	0.118	-1.17	23.60	23.53	1.016	0.120	/
			50	0	Right Side	2510	0.105	-2.99	22.50	22.43	1.016	0.107	/
			1	0	Top Side	2510	0.685	0.94	23.60	23.53	1.016	0.696	/
			50	0	Top Side	2510	0.601	-1.81	22.50	22.43	1.016	0.611	/
LTE Band 12	10M	QPSK	1	0	Back Side	704	0.465	-1.93	24.50	24.39	1.026	0.477	14
			25	0	Back Side	711	0.408	3.59	23.30	23.23	1.016	0.415	/
			1	0	Right Side	704	0.047	2.65	24.50	24.39	1.026	0.048	/
			25	0	Right Side	711	0.042	0.66	23.30	23.23	1.016	0.043	/
			1	0	Top Side	704	0.253	3.61	24.50	24.39	1.026	0.259	/
			25	0	Top Side	711	0.225	-1.36	23.30	23.23	1.016	0.229	/
LTE Band 25	20M	QPSK	1	0	Back Side	1860	0.812	-3.35	24.10	24.06	1.009	0.820	15
			1	0	Back Side	1882.5	0.649	-0.83	24.10	23.77	1.079	0.700	/
			1	0	Back Side	1905	0.656	-3.59	24.10	23.23	1.222	0.802	/
			50	0	Back Side	1860	0.715	-3.05	23.00	22.91	1.021	0.730	/
			1	0	Right Side	1860	0.085	2.16	24.10	24.06	1.009	0.086	/
			50	0	Right Side	1860	0.079	-3.38	23.00	22.91	1.021	0.081	/
			1	0	Top Side	1860	0.438	-3.51	24.10	24.06	1.009	0.442	/
			50	0	Top Side	1860	0.387	1.37	23.00	22.91	1.021	0.395	/
LTE Band 26	15M	QPSK	1	0	Back Side	841.5	0.653	-3.75	24.50	24.48	1.005	0.656	16
			36	0	Back Side	831.5	0.578	-0.74	23.50	23.31	1.045	0.604	/
			1	0	Right Side	841.5	0.065	-1.04	24.50	24.48	1.005	0.065	/
			36	0	Right Side	831.5	0.059	-1.90	23.50	23.31	1.045	0.062	/



			1	0	Top Side	841.5	0.372	-3.40	24.50	24.48	1.005	0.374	/
			36	0	Top Side	831.5	0.328	-2.27	23.50	23.31	1.045	0.343	/
LTE Band 38	20M	QPSK	1	0	Back Side	2580	0.472	-3.50	24.20	24.19	1.002	0.473	17
			50	0	Back Side	2595	0.418	3.37	24.00	23.88	1.028	0.430	/
			1	0	Right Side	2580	0.049	2.79	24.20	24.19	1.002	0.049	/
			50	0	Right Side	2595	0.044	-3.21	24.00	23.88	1.028	0.045	/
			1	0	Top Side	2580	0.28	-1.66	24.20	24.19	1.002	0.281	/
			50	0	Top Side	2595	0.249	-0.38	24.00	23.88	1.028	0.256	/
LTE Band 40	10M	QPSK	1	0	Back Side	2350	0.366	3.06	23.70	23.64	1.014	0.371	18
			50	0	Back Side	2350	0.326	3.73	22.50	22.47	1.007	0.328	/
			1	0	Right Side	2350	0.041	-0.85	23.70	23.64	1.014	0.042	/
			50	0	Right Side	2350	0.036	-2.40	22.50	22.47	1.007	0.036	/
			1	0	Top Side	2350	0.201	-3.85	23.70	23.64	1.014	0.204	/
			50	0	Top Side	2350	0.175	-2.24	22.50	22.47	1.007	0.176	/
LTE Band 41	20M	QPSK	1	0	Back Side	2506	1.096	0.54	25.00	24.86	1.033	1.132	19
			1	0	Back Side	2593	0.872	-0.04	25.00	23.91	1.285	1.121	/
			1	0	Back Side	2680	0.842	-2.95	25.00	23.74	1.337	1.126	/
			50	0	Back Side	2506	0.982	1.32	24.50	23.93	1.140	1.120	/
			50	0	Back Side	2593	0.838	-1.38	24.50	24.38	1.028	0.861	/
			50	0	Back Side	2680	0.862	3.34	24.50	23.40	1.288	1.110	/
			100	0	Back Side	2506	0.983	-3.39	24.50	24.30	1.047	1.029	/
			100	0	Back Side	2593	0.756	3.15	24.50	23.84	1.164	0.880	/
			100	0	Back Side	2680	0.764	-2.76	24.50	23.29	1.321	1.009	/
			1	0	Right Side	2506	0.12	3.36	25.00	24.86	1.033	0.124	/
			50	0	Right Side	2506	0.105	-1.00	24.50	24.38	1.028	0.108	/
			1	0	Top Side	2506	0.696	3.35	25.00	24.86	1.033	0.719	/
			50	0	Top Side	2506	0.614	2.68	24.50	24.38	1.028	0.631	/
LTE Band 66	20M	QPSK	1	0	Back Side	1720	1.078	2.74	24.60	24.41	1.045	1.127	/
			1	0	Back Side	1745	1.171	-2.60	24.60	24.53	1.016	1.190	20
			1	0	Back Side	1770	1.099	2.81	24.60	24.40	1.047	1.151	/
			50	0	Back Side	1720	0.853	-2.21	23.60	23.45	1.035	0.883	/
			50	0	Back Side	1745	0.958	-1.17	23.60	23.50	1.023	0.980	/
			50	0	Back Side	1770	0.875	2.22	23.60	23.39	1.050	0.918	/
			100	0	Back Side	1720	0.88	1.93	23.60	23.47	1.030	0.907	/
			100	0	Back Side	1745	0.944	3.45	23.60	23.51	1.021	0.964	/
			100	0	Back Side	1770	0.893	2.07	23.60	23.31	1.069	0.955	/
			1	0	Right Side	1745	0.131	-0.31	24.60	24.53	1.016	0.133	/
			50	0	Right Side	1745	0.119	-1.69	23.60	23.50	1.023	0.122	/
			1	0	Top Side	1745	0.74	-0.82	24.60	24.53	1.016	0.752	/
			50	0	Top Side	1745	0.65	2.63	23.60	23.50	1.023	0.665	/

Note:

- The test separation of all above table is 0mm.
- Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - Scaled SAR(W/kg) = Measured SAR(W/kg) *Tune-up Scaling Factor
- When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.



12.3 Repeated SAR

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)
PCS 1900	GPRS (GMSK, 2-Slot)	Back Side	1850.2	1.006	-1.74	30.60	30.30	1.072	1.078
		Back Side	1880	1.018	0.21	30.60	30.23	1.089	1.109
		Back Side	1909.8	1.120	3.24	30.60	30.54	1.014	1.136
WCDMA Band II	HSDPA Subtest-1	Back Side	1852.4	0.856	-2.13	24.20	24.17	1.007	0.862
		Back Side	1880	0.751	-2.41	24.20	23.69	1.125	0.845
		Back Side	1907.6	0.732	-1.62	24.20	23.70	1.122	0.821

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)
LTE Band 2	20M	QPSK	1	0	Back Side	1860	0.763	-2.34	25.00	24.44	1.138	0.868
			1	0	Back Side	1880	0.829	2.47	25.00	24.76	1.057	0.876
			1	0	Back Side	1900	0.764	-1.55	25.00	24.50	1.122	0.857
LTE Band 5	10M	QPSK	1	0	Back Side	829	0.757	-0.77	24.50	24.18	1.076	0.815
			1	0	Back Side	836.5	0.787	3.56	24.50	24.23	1.064	0.837
			1	0	Back Side	844	0.805	0.14	24.50	24.46	1.009	0.812
LTE Band 7	20M	QPSK	1	0	Back Side	2510	1.034	-1.93	23.60	23.53	1.016	1.051
			1	0	Back Side	2535	0.918	0.26	23.60	22.93	1.167	1.071
			1	0	Back Side	2560	0.824	-3.47	23.60	22.64	1.247	1.028
			50	0	Back Side	2510	0.955	2.86	22.50	22.43	1.016	0.971
			50	0	Back Side	2535	0.766	2.44	22.50	21.78	1.180	0.904
			50	0	Back Side	2560	0.778	-0.78	22.50	21.69	1.205	0.938
			100	0	Back Side	2510	0.927	1.18	22.50	22.48	1.005	0.931
			100	0	Back Side	2535	0.773	-0.60	22.50	21.81	1.172	0.906
			100	0	Back Side	2560	0.785	-1.04	22.50	21.73	1.194	0.937
LTE Band 41	20M	QPSK	1	0	Back Side	2506	1.038	0.53	25.00	24.86	1.033	1.072
			1	0	Back Side	2593	0.822	-1.25	25.00	23.91	1.285	1.057
			1	0	Back Side	2680	0.819	0.75	25.00	23.74	1.337	1.095
			50	0	Back Side	2506	0.974	2.47	24.50	23.93	1.140	1.111
			50	0	Back Side	2593	0.804	-0.37	24.50	24.38	1.028	0.827
			50	0	Back Side	2680	0.830	0.00	24.50	23.40	1.288	1.069
			100	0	Back Side	2506	0.983	1.58	24.50	24.30	1.047	1.029
			100	0	Back Side	2593	0.748	-2.65	24.50	23.84	1.164	0.871
			100	0	Back Side	2680	0.734	3.45	24.50	23.29	1.321	0.970



LTE Band 66	20M	QPSK	1	0	Back Side	1720	1.049	3.64	24.60	24.41	1.045	1.096
			1	0	Back Side	1745	1.124	0.60	24.60	24.53	1.016	1.142
			1	0	Back Side	1770	1.051	3.45	24.60	24.40	1.047	1.101
			50	0	Back Side	1720	0.848	-1.99	23.60	23.45	1.035	0.878
			50	0	Back Side	1745	0.946	-3.25	23.60	23.50	1.023	0.968
			50	0	Back Side	1770	0.773	1.56	23.60	23.39	1.050	0.811
			100	0	Back Side	1720	0.858	-1.09	23.60	23.47	1.030	0.884
			100	0	Back Side	1745	0.898	1.24	23.60	23.51	1.021	0.917
			100	0	Back Side	1770	0.857	-3.87	23.60	23.31	1.069	0.916

12.4 Repeated SAR measurement

Band	Mode	Test Position	Ch.	Original Measured SAR 1g (W/kg)	1 st Repeated SAR 1g	Ratio
PCS 1900	GPRS (GMSK, 2-Slot)	Back Side	1850	1.045	1.006	1.038
		Back Side	1880	1.056	1.018	1.038
		Back Side	1910	1.145	1.120	1.022
WCDMA Band II	HSDPA Subtest-1	Back Side	1852	0.858	0.856	1.002
		Back Side	1880	0.756	0.751	1.007
		Back Side	1908	0.765	0.732	1.045

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Original Measured SAR 1g(W/kg)	1 st Repeated SAR 1g	Ratio
LTE Band 4	20M	QPSK	1	0	Back Side	1860	0.789	0.763	1.034
			1	0	Back Side	1880	0.859	0.829	1.036
			1	0	Back Side	1900	0.802	0.764	1.050
LTE Band 4	20M	QPSK	1	0	Back Side	829	0.776	0.757	1.025
			1	0	Back Side	836.5	0.794	0.787	1.009
			1	0	Back Side	844	0.842	0.805	1.046
LTE Band 7	20M	QPSK	1	0	Back Side	2510	1.078	1.034	1.043
			1	0	Back Side	2535	0.926	0.918	1.009
			1	0	Back Side	2560	0.871	0.824	1.057
			50	0	Back Side	2510	0.968	0.955	1.014
			50	0	Back Side	2535	0.778	0.766	1.016
			50	0	Back Side	2560	0.802	0.778	1.031
			100	0	Back Side	2510	0.944	0.927	1.018
			100	0	Back Side	2535	0.779	0.773	1.008
			100	0	Back Side	2560	0.789	0.785	1.005
LTE Band 41	20M	QPSK	1	0	Back Side	2506	1.096	1.038	1.056
			1	0	Back Side	2593	0.872	0.822	1.061
			1	0	Back Side	2680	0.842	0.819	1.028
			50	0	Back Side	2506	0.983	0.974	1.009
			50	0	Back Side	2593	0.837	0.804	1.041
			50	0	Back Side	2680	0.864	0.830	1.041



LTE Band 66	20M	QPSK	100	0	Back Side	2506	0.984	0.983	1.001
			100	0	Back Side	2593	0.753	0.748	1.007
			100	0	Back Side	2680	0.767	0.734	1.045
			1	0	Back Side	1720	1.078	1.049	1.028
			1	0	Back Side	1745	1.171	1.124	1.042
			1	0	Back Side	1770	1.099	1.051	1.046
			50	0	Back Side	1720	0.879	0.848	1.037
			50	0	Back Side	1745	0.962	0.946	1.017
			50	0	Back Side	1770	0.79	0.773	1.022
			100	0	Back Side	1720	0.877	0.858	1.022
			100	0	Back Side	1745	0.942	0.898	1.049
			100	0	Back Side	1770	0.892	0.857	1.041

Note:

1. Per KDB 865664 D01,for each frequency band ,repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/Kg}$.
2. Per KDB 865664 D01,if the ratio of largest to smallest SAR for the original and first repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/Kg}$, only one repeated measurement is required.
3. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45\text{W/Kg}$.
4. The ratio is the difference in percentage between original and repeated measured SAR.



12.5 Simultaneous Multi-band Transmission Evaluation

Application Simultaneous Transmission information:

Position	Simultaneous State
Body	1. GSM + 2.4GHz WLAN/5G WLAN+NFC
	2. GSM + Bluetooth+NFC
	3. WCDMA + 2.4GHz WLAN/5G WLAN+NFC
	4. WCDMA + Bluetooth+NFC
	5. LTE + 2.4GHz WLAN/5G WLAN+NFC
	6. LTE + Bluetooth+NFC

NOTE:

1. Bluetooth and WLAN can't simultaneous transmission at the same time.
2. For simultaneous transmission at head and body exposure position, 2 transmitters simultaneous transmission was the worst state.
3. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
4. KDB 447498 / 4.3.2 (2) when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
 - a) $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f} \text{ (GHz)} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$;
Where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - b) 0.4 W/Kg for 1-g SAR and 1.0 W/Kg for 10-g SAR, when the separation distance is $>50 \text{ mm}$.

Estimated SAR		Maximum Turn-up Power		Antenna to user(mm)	Frequency (GHz)	Stand Alone SAR(1g) [W/kg]
		dBm	mW			
BT	Body	6	3.981	5	2.48	0.167
NFC	Body	-38	0.000158	5	0.01356	0.0000005



Simultaneous Mode	Position	Mode	Max. 1-g SAR	1-g Sum SAR
			(W/kg)	(W/kg)
GSM + 2.4G WLAN + NFC	Body	GSM	1.161	1.552
		NFC	0.0000005	
		2.4G WLAN	0.391	
GSM + Bluetooth+ NFC	Body	GSM	1.161	1.328
		NFC	0.0000005	
		BT	0.167	
GSM + 5G WLAN+ NFC	Body	GSM	1.161	1.456
		NFC	0.0000005	
		5G WLAN	0.295	
WCDMA + 2.4G WLAN + NFC	Body	WCDMA	0.864	1.255
		NFC	0.0000005	
		2.4G WLAN	0.391	
WCDMA + Bluetooth+ NFC	Body	WCDMA	0.864	1.031
		NFC	0.0000005	
		BT	0.167	
WCDMA + 5G WLAN+ NFC	Body	WCDMA	0.864	1.159
		NFC	0.0000005	
		5G WLAN	0.295	
LTE + 2.4G WLAN + NFC	Body	LTE	1.190	1.581
		NFC	0.0000005	
		2.4G WLAN	0.391	
LTE + Bluetooth+ NFC	Body	LTE	1.190	1.357
		NFC	0.0000005	
		BT	0.167	
LTE + 5G WLAN+ NFC	Body	LTE	1.190	1.485
		NFC	0.0000005	
		5G WLAN	0.295	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.



13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
750MHz Dipole	MVG	DIP0G750	SN 06/22 DIP0G750-638	2025.05.20	2028.05.19
835MHz Dipole	MVG	DIP0G835	SN 06/22 DIP0G835-639	2025.05.20	2028.05.19
1800MHz Dipole	MVG	DIP1G800	SN 06/22 DIP1G800-640	2025.05.20	2028.05.19
1900MHz Dipole	MVG	DIP1G900	SN 06/22 DIP1G900-641	2025.05.20	2028.05.19
2450MHz Dipole	MVG	DIP2G450	SN 06/22 DIP2G450-645	2025.05.20	2028.05.19
2600MHz Dipole	MVG	DIP2G600	SN 06/22 DIP2G600-646	2025.05.20	2028.05.19
5000MHz Dipole	MVG	DIP5G000	SN 06/22 DIP5G000-653	2025.05.22	2028.05.21
E-Field Probe	MVG	SSE2	2225-EPGO-450	2025.06.06	2026.06.05
Liquid Calibration Kit	MVG	OCPG 87	SN 06/22 OCPG87	2025.06.02	2026.06.01
Antenna	MVG	ANTA 73	SN 06/22 ANTA 73	N/A	N/A
Ellipsoid Phantom	MVG	ELLI 51	SN 06/22 ELLI 51	N/A	N/A
Phantom	MVG	SAM 148	SN 06/22 SAM148	N/A	N/A
Phone holder	MVG	MSH 117	SN 06/22 MSH 117	N/A	N/A
Laptop positioner	MVG	LSH 36	SN 06/22 LSH 38	N/A	N/A
Directional coupler	SHW	SHWDCP	202203280013	N/A	N/A
Network Analyzer	ZVL	R&S	116184	2025.03.05	2026.03.04
Multi Meter	DMM6500	Keithley	4527252	2025.03.06	2026.03.05
Signal Generator	Keysight	N5182B	MY59100717	2025.03.05	2026.03.04
Wireless Communication Test Set	R&S	CMW500	137737	2025.03.05	2026.03.04
Power Sensor	R&S	Z11	116184	2025.03.05	2026.03.04
Electronic Temperature hygrometer	N/A	ST-W2318	N/A	2025.03.05	2026.03.04
Temperature hygrometer	N/A	TP101	N/A	2025.03.05	2026.03.04



Appendix A. System Validation Plots

System Performance Check Data (750MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-11-02

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels	Middle
Signal	CW
Frequency (MHz)	750.000
Relative permittivity	42.29
Conductivity (S/m)	0.88
Probe	2225-EPGO-450
ConvF	1.08
Crest factor:	1:1




Maximum location: X=-3.00, Y=0.00 ; SAR Peak: 1.22 W/kg

SAR 10g (W/Kg)	0.578
SAR 1g (W/Kg)	0.890



Z Axis Scan





System Performance Check Data (835MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-11-01

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels	Middle
Signal	CW
Frequency (MHz)	835.000
Relative permittivity	42.42
Conductivity (S/m)	0.95
Probe	2225-EPGO-450
ConvF	1.02
Crest factor:	1:1




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.24 W/kg

SAR 10g (W/Kg)	0.608
SAR 1g (W/Kg)	0.968



Z Axis Scan





System Performance Check Data (1800MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2025-11-04

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Channels	Middle
Signal	CW
Frequency (MHz)	1800.000
Relative permittivity	40.98
Conductivity (S/m)	1.37
Probe	2225-EPGO-450
ConvF	1.21
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 5.88 W/kg

SAR 10g (W/Kg)	1.886
SAR 1g (W/Kg)	3.691



Z Axis Scan





System Performance Check Data (1900MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2025-11-03

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW
Frequency (MHz)	1900.000
Relative permittivity	41.24
Conductivity (S/m)	1.39
Probe	2225-EPGO-450
ConvF	1.34
Crest factor:	1:1




Maximum location: X=5.00, Y=1.00 ; SAR Peak: 6.89 W/kg

SAR 10g (W/Kg)	2.093
SAR 1g (W/Kg)	3.996



Z Axis Scan





System Performance Check Data (2450MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2025-11-02

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels	Middle
Signal	CW
Frequency (MHz)	2450.000
Relative permittivity	40.02
Conductivity (S/m)	1.78
Probe	2225-EPGO-450
ConvF	1.51
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 8.26 W/kg

SAR 10g (W/Kg)	2.457
SAR 1g (W/Kg)	5.283



Z Axis Scan





System Performance Check Data (2600MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2025-10-31

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Channels	Middle
Signal	CW
Frequency (MHz)	2600.000
Relative permittivity	40.29
Conductivity (S/m)	1.95
Probe	2225-EPGO-450
ConvF	1.44
Crest factor:	1:1




Maximum location: X=-5.00, Y=0.00 ; SAR Peak: 10.31 W/kg

SAR 10g (W/Kg)	2.489
SAR 1g (W/Kg)	5.628



Z Axis Scan





System Performance Check Data (5200MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement:2025-11-04

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels	Middle
Signal	CW
Frequency (MHz)	5200.000
Relative permittivity	36.73
Conductivity (S/m)	4.62
Probe	2225-EPGO-450
ConvF	1.58
Crest factor:	1:1




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 19.02 W/kg

SAR 10g (W/Kg)	2.280
SAR 1g (W/Kg)	7.778



Z Axis Scan





System Performance Check Data (5400MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement:2025-11-05

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5400
Channels	Middle
Signal	CW
Frequency (MHz)	5400.000
Relative permittivity	37.12
Conductivity (S/m)	4.89
Probe	2225-EPGO-450
ConvF	1.60
Crest factor:	1:1




Maximum location: X=6.00, Y=5.00 ; SAR Peak: 25.07 W/kg

SAR 10g (W/Kg)	2.253
SAR 1g (W/Kg)	7.695



Z Axis Scan





System Performance Check Data (5800MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement:2025-11-05

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels	Middle
Signal	CW
Frequency (MHz)	5800.000
Relative permittivity	36.07
Conductivity (S/m)	5.26
Probe	2225-EPGO-450
ConvF	1.62
Crest factor:	1:1




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 20.84 W/kg

SAR 10g (W/Kg)	2.334
SAR 1g (W/Kg)	8.043



Z Axis Scan






Appendix B. SAR Test Plots

Plot 1:

Test Date	2025-11-01
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS850
Signal	TDMA (GPRS)
Frequency	836.6
SAR 10g (W/Kg)	0.555
SAR 1g (W/Kg)	1.296
ConvF	1.72
Relative permittivity	42.42
Conductivity (S/m)	0.95

Maximum location: X=-32.00, Y=-23.00 ; SAR Peak: 2.52 W/kg






Plot 2:

Test Date	2025-11-03
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS1900
Signal	TDMA (GPRS)
Frequency	1909.8
SAR 10g (W/Kg)	0.791
SAR 1g (W/Kg)	1.145
ConvF	2.20
Relative permittivity	41.24
Conductivity (S/m)	1.39

Maximum location: X=16.00, Y=-15.00 ; SAR Peak: 2.23 W/kg






Plot 3:

Test Date	2025-11-03
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 2 (1900)
Signal	HSDPA
Frequency	1852.4
SAR 10g (W/Kg)	0.386
SAR 1g (W/Kg)	0.858
ConvF	1.92
Relative permittivity	41.24
Conductivity (S/m)	1.39

Maximum location: X=-37.00, Y=-49.00 ; SAR Peak: 1.66 W/kg






Plot 4:

Test Date	2025-11-04
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 4 (1700)
Signal	HSDPA
Frequency	1712.6
SAR 10g (W/Kg)	0.326
SAR 1g (W/Kg)	0.670
ConvF	1.92
Relative permittivity	40.98
Conductivity (S/m)	1.37

Maximum location: X=-37.00, Y=-38.00 ; SAR Peak: 1.43 W/kg






Plot 5:

Test Date	2025-11-01
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 5 (850)
Signal	WCDMA
Frequency	846.6
SAR 10g (W/Kg)	0.326
SAR 1g (W/Kg)	0.670
ConvF	1.72
Relative permittivity	42.42
Conductivity (S/m)	0.95

Maximum location: X=-37.00, Y=-38.00 ; SAR Peak: 1.43 W/kg






Plot 6:

Test Date	2025-11-02
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	ISM
Signal	IEEE 802.11b
Frequency	2412
SAR 10g (W/Kg)	0.197
SAR 1g (W/Kg)	0.376
ConvF	2.33
Relative permittivity	40.02
Conductivity (S/m)	1.78

Maximum location: X=50.00, Y=78.00 ; SAR Peak: 0.77 W/kg






Plot 7:

Test Date	2025-11-04
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-1
Signal	802.11ac-VHT80
Frequency	5240
SAR 10g (W/Kg)	0.095
SAR 1g (W/Kg)	0.199
ConvF	1.99
Relative permittivity	36.73
Conductivity (S/m)	4.62

Maximum location: X=-55.00, Y=64.00 ; SAR Peak: 0.96 W/kg






Plot 8:

Test Date	2025-11-05
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-2
Signal	IEEE 802.11a
Frequency	5320
SAR 10g (W/Kg)	0.121
SAR 1g (W/Kg)	0.221
ConvF	1.87
Relative permittivity	37.12
Conductivity (S/m)	4.89

Maximum location: X=32.00, Y=51.00 ; SAR Peak: 1.22 W/kg






Plot 9:

Test Date	2025-11-05
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-3
Signal	IEEE 802.11a
Frequency	5785
SAR 10g (W/Kg)	0.167
SAR 1g (W/Kg)	0.284
ConvF	1.70
Relative permittivity	36.07
Conductivity (S/m)	5.26

Maximum location: X=26.00, Y=-9.00 ; SAR Peak: 1.55 W/kg






Plot 10:

Test Date	2025-11-03
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back side
Band	LTE band 2
Signal	LTE FDD
Frequency	1880
SAR 10g (W/Kg)	0.396
SAR 1g (W/Kg)	0.859
ConvF	2.20
Relative permittivity	41.24
Conductivity (S/m)	1.39

Maximum location: X=-37.00, Y=-65.00 ; SAR Peak: 1.62 W/kg






Plot 11:

Test Date	2025-11-04
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back side
Band	LTE band 4
Signal	LTE FDD
Frequency	1732.5
SAR 10g (W/Kg)	0.104
SAR 1g (W/Kg)	0.215
ConvF	1.92
Relative permittivity	40.98
Conductivity (S/m)	1.37


Maximum location: X=-30.00, Y=-31.00 ; SAR Peak: 0.68 W/kg



Plot 12:

Test Date	2025-11-01
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 5
Signal	LTE FDD
Frequency	844
SAR 10g (W/Kg)	0.390
SAR 1g (W/Kg)	0.842
ConvF	1.72
Relative permittivity	42.42
Conductivity (S/m)	0.95


Maximum location: X=-21.00, Y=-29.00 ; SAR Peak: 1.51 W/kg



Plot 13:

Test Date	2025-10-31
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 7
Signal	LTE FDD
Frequency	2510
SAR 10g (W/Kg)	0.556
SAR 1g (W/Kg)	1.078
ConvF	2.37
Relative permittivity	40.29
Conductivity (S/m)	1.95

Maximum location: X=-29.00, Y=-2.00 ; SAR Peak: 2.14 W/kg






Plot 14:

Test Date	2025-11-02
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 12
Signal	LTE FDD
Frequency	704
SAR 10g (W/Kg)	0.261
SAR 1g (W/Kg)	0.465
ConvF	1.67
Relative permittivity	42.29
Conductivity (S/m)	0.88

Maximum location: X=-29.00, Y=-25.00 ; SAR Peak: 0.79 W/kg






Plot 15:

Test Date	2025-11-03
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 25
Signal	LTE FDD
Frequency	1860
SAR 10g (W/Kg)	0.365
SAR 1g (W/Kg)	0.812
ConvF	2.20
Relative permittivity	41.24
Conductivity (S/m)	1.39

Maximum location: X=-30.00, Y=-46.00 ; SAR Peak: 1.49 W/kg






Plot 16:

Test Date	2025-11-01
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 26
Signal	LTE FDD
Frequency	841.5
SAR 10g (W/Kg)	0.368
SAR 1g (W/Kg)	0.653
ConvF	1.72
Relative permittivity	42.42
Conductivity (S/m)	0.95

Maximum location: X=-29.00, Y=-56.00 ; SAR Peak: 1.10 W/kg






Plot 17:

Test Date	2025-10-31
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 38
Signal	LTE TDD
Frequency	2580
SAR 10g (W/Kg)	0.253
SAR 1g (W/Kg)	0.472
ConvF	2.37
Relative permittivity	40.29
Conductivity (S/m)	1.95

Maximum location: X=-36.00, Y=-43.00 ; SAR Peak: 0.94 W/kg






Plot 18:

Test Date	2025-11-02
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 40
Signal	LTE TDD
Frequency	2350
SAR 10g (W/Kg)	0.168
SAR 1g (W/Kg)	0.366
ConvF	2.33
Relative permittivity	40.02
Conductivity (S/m)	1.78

Maximum location: X=-22.00, Y=-47.00 ; SAR Peak: 0.74 W/kg






Plot 19:

Test Date	2025-10-31
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 41
Signal	LTE TDD
Frequency	2506
SAR 10g (W/Kg)	0.555
SAR 1g (W/Kg)	1.096
ConvF	2.37
Relative permittivity	40.29
Conductivity (S/m)	1.95

Maximum location: X=-32.00, Y=-23.00 ; SAR Peak: 2.52 W/kg






Plot 20:

Test Date	2025-11-04
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 66
Signal	LTE FDD
Frequency	1745
SAR 10g (W/Kg)	0.776
SAR 1g (W/Kg)	1.171
ConvF	1.92
Relative permittivity	40.98
Conductivity (S/m)	1.37

Maximum location: X=-29.00, Y=-49.00 ; SAR Peak: 2.24 W/kg





Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※※END OF THE REPORT※※※※※