

TEST REPORT

Applicant: FJ Dynamics Co.,Ltd

Address: Floor 21, Das Tower, No.28, 1st South Keji Road, High-tech Zone, Yuehai Subdistrict, Nanshan District, Shenzhen, China

Product Name: GNSS Receiver

FCC ID: 2A2LL-V10L

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2020
KDB 558074 D01 15.247 Meas Guidance v05r02

Report Number: 2602P06299E-RF-00C

Report Date: 2026/6/17

The above device has been tested and found compliant with the requirement of the relevant standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Alice Tan

Pedro Yun

Reviewed By: Alice Tan

Approved By: Pedro Yun

Title: RF Engineer

Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL [▲]	5
1.4 EQUIPMENT MODIFICATIONS	5
2. SUMMARY OF TEST RESULTS	6
3. DESCRIPTION OF TEST CONFIGURATION	7
3.1 OPERATION FREQUENCY DETAIL	7
3.2 EUT OPERATION CONDITION	7
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	7
3.4 SUPPORT CABLE LIST AND DETAILS	8
3.5 BLOCK DIAGRAM OF TEST SETUP	8
3.6 TEST FACILITY	10
3.7 MEASUREMENT UNCERTAINTY	10
4. REQUIREMENTS AND TEST PROCEDURES	11
4.1 AC LINE CONDUCTED EMISSIONS	11
4.1.1 Applicable Standard	11
4.1.2 EUT Setup	12
4.1.3 EMI Test Receiver Setup	12
4.1.4 Test Procedure	13
4.1.5 Corrected Amplitude & Margin Calculation	13
4.1.6 Test Result	13
4.2 RADIATION SPURIOUS EMISSIONS	14
4.2.1 Applicable Standard	14
4.2.2 EUT Setup	14
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
4.2.4 Test Procedure	17
4.2.5 Corrected Result & Margin Calculation	17
4.2.6 Test Result	17
4.3 MAXIMUM CONDUCTED OUTPUT POWER	18
4.3.1 Applicable Standard	18
4.3.2 EUT Setup	18
4.3.3 Test Procedure	18
4.3.4 Test Result	18
4.4 DUTY CYCLE	19
4.4.1 EUT Setup	19
4.4.2 Test Procedure	19
4.4.3 Judgment	19
4.5 ANTENNA REQUIREMENT	20
4.5.1 Applicable Standard	20
4.5.2 Judgment	20
5. TEST DATA AND RESULTS	21
5.1 AC LINE CONDUCTED EMISSIONS	21

5.2 RADIATION SPURIOUS EMISSIONS	24
5.3 SPOT CHECK WITH MAXIMUM CONDUCTED OUTPUT POWER.....	47
5.4 DUTY CYCLE	48
EXHIBIT A - EUT PHOTOGRAPHS.....	50
EXHIBIT B - TEST SETUP PHOTOGRAPHS	51

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2602P06299E-RF-00C	Original Report	2026/6/17

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	GNSS Receiver
EUT Model:	V10L
Operation Frequency:	2412-2462MHz (802.11b/g/n ht20) 2422-2452MHz(802.11n ht40)
Maximum Peak Output Power (Conducted) ▲:	21.59dBm
Modulation Type:	802.11b:DSSS-DBPSK, DQPSK, CCK 802.11g/n: OFDM-BPSK, QPSK, 16QAM, 64QAM
Rated Input Voltage:	DC 9~32V, Typical: DC 12V from AC/DC Adapter; or DC 7.27V from Built-in Battery
Serial Number:	CE&RE Test:3GPB-3 RF Conducted Test:3GPB-2
EUT Received Date:	2026/2/2
EUT Received Status:	Good

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
Adapter	HUIZHOU FUJIA APPLIANCE TECH CO., LTD.	FJ-GN236CN	Input: 100-240Vac 50/60Hz ,1.2A Max Output: DC5V/3.0A,9V/3.0A,12V/3.0A,15V/2.4A, 20V/1.8A 36.0W MAX

1.3 Antenna Information Detail▲

Antenna Type	input impedance (Ohm)	Frequency Range (MHz)	Antenna Gain (dBi)
PIFA	50	2402-2480	-0.62
The design of compliance with §15.203:			
☒	Unit uses a permanently attached antenna.		
☐	Unit uses a unique coupling to the intentional radiator.		
☐	Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.		

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result	Note
§15.207(a)	AC Line Conducted Emissions	Compliant	/
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliant	/
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Note*	The test result please refer to report SEWA2307000102RG04▲ page31-34
§15.247(b)(3)	Maximum Conducted Output Power	Reporting	The test result please refer to report SEWA2307000102RG04▲ page39
§15.247(d)	Conducted Spurious Emission	Note*	The test result please refer to report SEWA2307000102RG04▲ page44-52
§15.247(e)	Power Spectral Density	Note*	The test result please refer to report SEWA2307000102RG04▲ page40-43
§15.203	Antenna Requirement	Compliant	/

Note*: The device built in a certified module, model: SC206E-GL, FCC ID: XMR2023SC206EGL, the certified module base on an original module, FCC ID: XMR2023SC200EGL, per spot check, the RF parameters are identical with the original module report, therefore, the RF conducted test items please refer to the module report: SEWA2307000102RG04▲, which was issued by SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. on 2023/10/26. (according to KDB 996369 D02 Module Q&A v02r02, Answer 1 b))

The Bay Area Compliance Laboratories Corp.(Dongguan) is responsible for all the information provided in this report, except when information is provided by the customer as identified in this report.

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11n ht40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	/	/

Note 1: The above frequencies in bold were performed the test.

Note 2: For AC line conducted emissions, the maximum peak output power mode and channel was tested.

Note 3: For Radiated Spurious Emissions 9kHz~1GHz and 18~25GHz, the maximum peak output power mode and channel was tested.

3.2 EUT Operation Condition

The EUT was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration as below:

EUT Exercise Software: QRCT				
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:				
Test Modes	Data Rate	Power Level Setting		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	default	default	default
802.11g	6Mbps	default	default	default
802.11n ht20	MCS0	default	default	default
802.11n ht40	MCS0	default	default	default
The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.				

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

3.4 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	no	no	1.5	Adapter	EUT

3.5 Block Diagram of Test Setup


AC line conducted emissions:



Spurious Emissions:
Below 1GHz:



Spurious Emissions:
Above 1GHz:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.55 dB
Power Spectral Density, conducted	±0.55 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.06dB, 30MHz~1GHz: 6.13 dB, 1GHz~6GHz: 4.79 dB, 6GHz~18GHz: 4.63 dB, 18GHz~26.5GHz: 4.79 dB, 26.5GHz~40GHz: 4.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.83 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

- (1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.
- (2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.
- (3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground[protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor=attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions


4.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.2.2 EUT Setup


9kHz~30MHz:




30MHz~1GHz:



1-18GHz:



18-25GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, and FCC 15.247 limits.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	QP/AV	200 Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz	QP/AV
30MHz – 1000 MHz	PK	120 kHz	500 kHz	/	PK
	QP	/	/	120kHz	QP

1GHz- 25GHz:

Pre-scan:

Frequency Range	Measurement	RBW	Video B/W	Detector
Above 1 GHz	Peak	1MHz	3 MHz	PK
	AV	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	≥1/T

Note: T is minimum transmission duration

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz -1 GHz, except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

For Radiated 18-25GHz test, which was performed at 1.0 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.0m
Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1.0m]})$ dB = 9.54 dB

4.2.5 Corrected Result& Margin Calculation

$$E_{Log} = 20 \times \log_{10}(E_{Linear})$$

E_{Linear} is the field strength of the emission, in μ V/m

E_{Log} is the field strength of the emission, in dB μ V/m

For 9kHz-30MHz test, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{\text{limit-measure}} = E_{\text{limit-Standard}} + 40 \times \log_{10} (d_{\text{standard}}/d_{\text{measure}})$$

The basic equation except 18-25GHz test is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

For Radiated 18-25GHz test:

Factor = Antenna Factor + Cable Loss- Distance extrapolation Factor- Amplifier Gain

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.2.6 Test Result

Please refer to section 5.2.


4.3 Maximum Conducted Output Power

4.3.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable/attenuator was offset into the setting of test equipment:

Offset=Insert loss of RF cable+ Insert loss of attenuator

4.3.3 Test Procedure

According to ANSI C63.10-2020 Section 11.9.1.2

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

- Set the EUT in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
- Add a correction factor to the display.
- Set the power meter to test peak output power, record the result.

According to ANSI C63.10-2020 Section 11.9.2.3.2

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

4.3.4 Test Result

Please refer to section 5.3.

4.4 Duty Cycle

4.4.1 EUT Setup



4.4.2 Test Procedure

According to ANSI C63.10-2020 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.4.3 Judgment

Report Only. Please refer to section 5.4.

4.5 Antenna Requirement

4.5.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.5.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. TEST DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	3GPB-3	Test Date:	2026/02/25
Test Site:	CE	Test Mode:	Transmitting
Tester:	Yolo Fan	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.1	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100.8
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2025/6/25	2026/6/24
Unknown	Coaxial Cable	RG 142	C-0200-05	2025/5/6	2026/5/5
Audix	Test Software	E3	191218 V9	N/A	N/A
R&S	EMI Test Receiver	ESCI	100224	2025/6/25	2026/6/24

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


Please refer to the below plots.

Note:802.11n40 Middle channel was tested.

Project No.: 2602P06299E-RF
Port: Line
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 3GPB-3
Tester: Yolo Fan
Note: Part 15.247_2.4G WIFI

Date: 2026-02-25




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.182	31.85	10.95	42.80	64.41	21.61	QP
2	0.182	25.28	10.95	36.23	54.41	18.18	Average
3	0.221	20.13	10.79	30.92	62.77	31.85	QP
4	0.221	4.09	10.79	14.88	52.77	37.89	Average
5	0.469	30.40	10.63	41.03	56.54	15.51	QP
6	0.469	19.02	10.63	29.65	46.54	16.89	Average
7	0.499	26.99	10.61	37.60	56.02	18.42	QP
8	0.499	16.32	10.61	26.93	46.02	19.09	Average
9	0.530	21.82	10.58	32.40	56.00	23.60	QP
10	0.530	2.03	10.58	12.61	46.00	33.39	Average
11	0.692	18.59	10.42	29.01	56.00	26.99	QP
12	0.692	11.70	10.42	22.12	46.00	23.88	Average

Project No.: 2602P06299E-RF
Port: neutral
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 3GPB-3
Tester: Yolo Fan
Note: Part 15.247_2.4G WIFI

Date: 2026-02-25



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Measurement
1	0.180	28.80	10.82	39.62	64.50	24.88	QP
2	0.180	13.09	10.82	23.91	54.50	30.59	Average
3	0.278	20.27	10.80	31.07	60.88	29.81	QP
4	0.278	10.37	10.80	21.17	50.88	29.71	Average
5	0.367	16.49	10.69	27.18	58.58	31.40	QP
6	0.367	1.37	10.69	12.06	48.58	36.52	Average
7	0.469	30.09	10.55	40.64	56.52	15.88	QP
8	0.469	21.93	10.55	32.48	46.52	14.04	Average
9	0.503	29.03	10.51	39.54	56.00	16.46	QP
10	0.503	20.64	10.51	31.15	46.00	14.85	Average
11	0.810	18.15	10.59	28.74	56.00	27.26	QP
12	0.810	6.83	10.59	17.42	46.00	28.58	Average

5.2 Radiation Spurious Emissions

1)9kHz - 1GHz

Serial Number:	3GPB-3	Test Date:	2026/2/14
Test Site:	Chamber10m	Test Mode:	Transmitting
Tester:	Mikey Lin	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	21	Relative Humidity: (%)	47	ATM Pressure: (kPa)	101.1

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
GLOBAL	Active Loop Antenna	1313-1A	4060411	2025/6/26	2028/6/25
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2023/9/6	2026/9/5
Narda	Coaxial Attenuator	779-6dB	04269	2023/9/6	2026/9/5
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2025/7/1	2026/6/30
Sonoma	Amplifier	310N	185914	2025/8/25	2026/8/24
R&S	EMI Test Receiver	ESR3	102453	2025/6/25	2026/6/24
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below plots.


Note:802.11n40 Middle channel was tested.

9kHz~30MHz

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:

Project No.: 2602P06299E-RF
Polarization: Parallel
Test Mode: Transmitting 2.4G WIFI
Note:
RBW:200Hz VBW:1kHz

Serial No.: 3GPB-3
Tester: Mikey Lin




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	0.012	67.88	4.96	72.84	126.15	53.31	Peak
2	0.021	54.21	3.22	57.43	121.05	63.62	Peak
3	0.032	57.01	1.73	58.74	117.47	58.73	Peak
4	0.035	61.39	1.33	62.72	116.81	54.09	Peak
5	0.038	56.43	0.87	57.30	116.10	58.80	Peak
6	0.048	56.23	-0.31	55.92	113.89	57.97	Peak

Project No.: 2602P06299E-RF
Polarization: Parallel
Test Mode: Transmitting 2.4G WIFI
Note:
RBW:9kHz VBW:30kHz

Serial No.: 3GPB-3
Tester: Mikey Lin

Date: 2026-02-14




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Measurement
1	0.174	66.99	-9.36	57.63	102.79	45.16	Peak
2	0.497	72.32	-20.51	51.81	73.68	21.87	Peak
3	10.847	63.64	-30.03	33.61	69.54	35.93	Peak
4	12.124	64.87	-30.17	34.70	69.54	34.84	Peak
5	16.140	70.06	-30.31	39.75	69.54	29.79	Peak
6	19.122	70.66	-30.42	40.24	69.54	29.30	Peak

30MHz-1GHz

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting 2.4G WIFI
Note:
: RBW:120kHz VBW:500kHz


Serial No.: 3GPB-3
Tester: Mikey Lin



No.	Frequency	Reading	Factor	Result	Limit	Margin	Measurement
	(MHz)	(dBμV)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)	
1	30.00	28.04	-1.86	26.18	40.00	13.82	Peak
2	71.71	35.96	-13.89	22.07	40.00	17.93	Peak
3	154.16	36.39	-9.82	26.57	43.52	16.95	Peak
4	163.86	35.07	-10.00	25.07	43.52	18.45	Peak
5	202.66	39.62	-10.80	28.82	43.52	14.70	Peak
6	256.98	44.29	-10.69	33.60	46.02	12.42	Peak

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting 2.4G WIFI
Note:
: RBW:120kHz VBW:500kHz

Serial No.: 3GPB-3
Tester: Mikey Lin



2) 1-25GHz:

Serial Number:	3GPB-3	Test Date:	2026/2/26
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Willem Qiu	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	24.6	Relative Humidity: (%)	55	ATM Pressure: (kPa)	100.7

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2026/2/21	2029/2/20
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2025/11/14	2026/11/13
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2025/11/14	2026/11/13
AH	Preamplifier	PAM-0118P	469	2025/4/11	2026/4/10
AH	Preamplifier	PAM-1840VH	191	2025/7/31	2026/7/30
R&S	Spectrum Analyzer	FSV40	101944	2025/8/8	2026/8/7
Audix	Test Software	E3	191218 V9	N/A	N/A
Decentest	Multiplex Switch Test Control Set & Filter Switch Unit	DT7220SCU & DT7220FSU	DS79902 & DS79905	2025/8/25	2026/8/24

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Please refer to the below plots.

1-18GHz:

802.11b Low Channel Horizontal

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBI:3MHz

Serial No.: 3GPB-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	3991.60	49.69	-3.45	46.24	74.00	27.76	Peak

802.11b Low Channel Vertical

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBI:3MHz


Serial No.: 3GPB-3
Tester: Willem Qiu



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1000.60	53.14	-8.04	45.10	74.00	28.90	Peak

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBI:3MHz Ave: RBW:1MHz, VBI:5kHz


Serial No.: 3GPB-3
Tester: Willem Qiu



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4824.00	48.99	-7.53	41.46	74.00	32.54	Peak
2	7236.00	48.15	-3.30	44.85	74.00	29.15	Peak
3	17958.00	48.62	10.93	59.55	74.00	14.45	Peak
4	17958.00	37.04	10.93	47.97	54.00	6.03	Average

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBI:3MHz Ave: RBW:1MHz, VBI:5kHz

Serial No.: 3GPB-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4824.00	48.78	-7.53	41.25	74.00	32.75	Peak
2	7236.00	48.38	-3.30	45.08	74.00	28.92	Peak
3	17997.00	48.96	11.15	60.11	74.00	13.89	Peak
4	17997.00	36.83	11.15	47.98	54.00	6.02	Average

802.11b Middle Channel Horizontal

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b middle channel 2437MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3GPB-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1199.80	52.97	-7.65	45.32	74.00	28.68	Peak

802.11b Middle Channel Vertical

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b middle channel 2437MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 3GPB-3
Tester: Willem Qiu



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1006.60	53.18	-8.03	45.15	74.00	28.85	Peak

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b middle channel 2437MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 3GPB-3
Tester: Willem Qiu



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4874.00	48.65	-7.56	41.09	74.00	32.91	Peak
2	7311.00	48.32	-2.97	45.35	74.00	28.65	Peak
3	17955.20	49.71	10.91	60.62	74.00	13.38	Peak
4	17955.20	37.05	10.91	47.96	54.00	6.04	Average

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b middle channel 2437MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3GPB-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4874.00	47.78	-7.56	40.22	74.00	33.78	Peak
2	7311.00	49.44	-2.97	46.47	74.00	27.53	Peak
3	17986.00	49.65	11.10	60.75	74.00	13.25	Peak
4	17986.00	36.84	11.10	47.94	54.00	6.06	Average

802.11b High Channel Horizontal

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3GPB-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1000.00	55.11	-8.04	47.07	74.00	26.93	Peak

802.11b High Channel Vertical

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 3GPB-3
Tester: Willem Qiu



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1000.00	54.94	-8.04	46.90	74.00	27.10	Peak

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 3GPB-3
Tester: Willem Qiu



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4924.00	46.86	-7.49	39.37	74.00	34.63	Peak
2	7386.00	48.96	-2.45	46.51	74.00	27.49	Peak
3	17997.20	49.20	11.15	60.35	74.00	13.65	Peak
4	17997.20	36.77	11.15	47.92	54.00	6.08	Average

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3GPB-3
Tester: Willem Qiu



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4924.00	47.94	-7.49	40.45	74.00	33.55	Peak
2	7386.00	48.75	-2.45	46.30	74.00	27.70	Peak
3	17969.20	48.75	11.00	59.75	74.00	14.25	Peak
4	17969.20	36.89	11.00	47.89	54.00	6.11	Average

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	3904.00	49.56	-3.61	45.95	74.00	28.05	Peak

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26

Level (dBuV/m)

Fundamental test with Filter Switch Unit

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1006.00	52.37	-8.03	44.34	74.00	29.66	Peak

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26

Level (dBuV/m)

Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4824.00	49.11	-7.53	41.58	74.00	32.42	Peak
2	7236.00	48.50	-3.30	45.20	74.00	28.80	Peak
3	17927.20	50.58	10.72	61.30	74.00	12.70	Peak
4	17927.20	37.24	10.72	47.96	54.00	6.04	Average

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3GPB-3
Tester: Willem Qiu


Date: 2026-02-26

Level (dBuV/m)




Frequency (MHz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4824.00	48.86	-7.53	41.33	74.00	32.67	Peak
2	7236.00	49.27	-3.30	45.97	74.00	28.03	Peak
3	17977.60	49.41	11.06	60.47	74.00	13.53	Peak
4	17977.60	36.93	11.06	47.99	54.00	6.01	Average


802.11g Middle Channel Horizontal






802.11g Middle Channel Vertical




802.11g High Channel Horizontal






802.11g High Channel Vertical



802.11n20 Low Channel Horizontal



802.11n20 Low Channel Vertical




802.11n20 Middle Channel Horizontal

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20 middle channel 2437MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	3702.40	50.09	-4.15	45.94	74.00	28.06	Peak

802.11n20 Middle Channel Vertical

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20 middle channel 2437MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1000.60	54.01	-8.04	45.97	74.00	28.03	Peak

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20 middle channel 2437MHz
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4874.00	47.69	-7.56	40.13	74.00	33.87	Peak
2	7311.00	48.51	-2.97	45.54	74.00	28.46	Peak
3	17980.40	48.61	11.07	59.68	74.00	14.32	Peak
4	17980.40	36.84	11.07	47.91	54.00	6.09	Average

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20 middle channel 2437MHz
Peak: RBW:1MHz, VBW:3MHz Ave:RBW:1MHz, VBW:5kHz

Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4874.00	48.11	-7.56	40.55	74.00	33.45	Peak
2	7311.00	48.74	-2.97	45.77	74.00	28.23	Peak
3	17949.60	49.37	10.88	60.25	74.00	13.75	Peak
4	17949.60	37.06	10.88	47.94	54.00	6.06	Average

802.11n20 High Channel Horizontal

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20 high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	3991.60	49.26	-3.45	45.81	74.00	28.19	Peak

802.11n20 High Channel Vertical

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20 high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	1004.80	55.29	-8.04	47.25	74.00	26.75	Peak

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20 high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4924.00	47.66	-7.49	40.17	74.00	33.83	Peak
2	7386.00	48.54	-2.45	46.09	74.00	27.91	Peak
3	17988.00	49.08	11.11	60.19	74.00	13.81	Peak
4	17988.00	36.85	11.11	47.96	54.00	6.04	Average

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20 high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 3GPB-3
Tester: Willem Qiu

Date: 2026-02-26






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	4924.00	47.82	-7.49	40.33	74.00	33.67	Peak
2	7386.00	48.30	-2.45	45.85	74.00	28.15	Peak
3	17958.00	49.01	10.93	59.94	74.00	14.06	Peak
4	17958.00	36.99	10.93	47.92	54.00	6.08	Average


802.11n40 Low Channel Horizontal






802.11n40 Low Channel Vertical




802.11n40 Middle Channel Horizontal






802.11n40 Middle Channel Vertical



802.11n40 High Channel Horizontal



802.11n40 High Channel Vertical



18-25GHz:
No Emission was detected in the range 18-25GHz, test was performed on the mode and channel which with the maximum power.

Project No.: 2602P06299E-RF

Serial No.: 36PB-3

Polarization: Horizontal

Tester: Willem Qiu

Test Mode: Transmitting

Note: 2.4G WIFI

Peak: RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)

2026-02-26

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	20189.60	48.44	-3.29	45.15	74.00	28.85	Peak

Project No.: 2602P06299E-RF

Serial No.: 36PB-3

Polarization: Vertical

Tester: Willem Qiu

Test Mode: Transmitting

Note: 2.4G WIFI

Peak: RBW:1MHz,VBW:3MHz

Level (dBuV/m)

Frequency (MHz)


2026-02-26

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	20487.80	47.64	-3.22	44.42	74.00	29.58	Peak

Bandedge:**802.11b Low Channel Bandedge Horizontal**

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 36PB-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2353.00	49.59	-0.51	49.08	74.00	24.92	Peak
2	2390.00	47.64	-0.47	47.17	74.00	26.83	Peak

802.11b Low Channel Bandedge Vertical

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 36PB-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2362.45	48.94	-0.50	48.44	74.00	25.56	Peak
2	2390.00	46.41	-0.47	45.94	74.00	28.06	Peak

802.11b High Channel Bandedge Horizontal

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 36PB-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	47.12	-0.30	46.82	74.00	27.18	Peak
2	2486.22	52.00	-0.30	51.70	74.00	22.30	Peak

802.11b High Channel Bandedge Vertical

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 36PB-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	46.49	-0.30	46.19	74.00	27.81	Peak
2	2543.00	50.19	-0.05	50.14	74.00	23.86	Peak

802.11g Low Channel Bandedge Horizontal

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3GPH-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2360.76	49.78	-0.49	49.29	74.00	24.71	Peak
2	2390.00	49.35	-0.47	48.88	74.00	25.12	Peak

802.11g Low Channel Bandedge Vertical

Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 3GPH-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2371.27	50.19	-0.49	49.70	74.00	24.30	Peak
2	2390.00	50.61	-0.47	50.14	74.00	23.86	Peak

802.11g High Channel Bandedge Horizontal

Project No.: 2602P06299E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3GPH-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	49.92	-0.30	49.62	74.00	24.38	Peak
2	2485.42	59.33	-0.30	59.03	74.00	14.97	Peak
3	2485.42	37.08	-0.30	36.78	54.00	17.22	Average

802.11g High Channel Bandedge Vertical


Project No.: 2602P06299E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 3GPH-3
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement
1	2483.50	50.13	-0.30	49.83	74.00	24.17	Peak
2	2487.24	55.36	-0.30	55.06	74.00	18.94	Peak
3	2487.24	36.58	-0.30	36.28	54.00	17.72	Average


802.11n20 Low Channel Bandedge Horizontal




802.11n20 Low Channel Bandedge Vertical




802.11n20 High Channel Bandedge Horizontal




802.11n20 High Channel Bandedge Vertical




802.11n40 Low Channel Bandedge Horizontal




802.11n40 Low Channel Bandedge Vertical



802.11n40 High Channel Bandedge Horizontal



802.11n40 High Channel Bandedge Vertical



5.3 Spot Check With Maximum Conducted Output Power

Test Information:

Sample No.:	3GPB-2	Test Date:	2026/05/08
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rini Yan	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23.5	Relative Humidity: (%)	54	ATM Pressure: (kPa)	100.8
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Anritsu	Microwave Peak Power Sensor	MA24418A	12618	2025/6/11	2026/6/10
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM504	2026/3/30	2027/3/29

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Mode	Test Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Verdict
802.11n40	2422	20.55	30	Pass
	2437	20.73	30	Pass
	2452	20.64	30	Pass

Note:
The Spot Check data were similar to the original data.

5.4 Duty Cycle

Test Information:

Sample No.:	3GPB-2	Test Date:	2026/06/16
Test Site:	RF	Test Mode:	Transmitting
Tester:	Rini Yan	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	24.2	Relative Humidity: (%)	51	ATM Pressure: (kPa)	100.3
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200160/026	2025/7/28	2026/7/27

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Mode	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	1/Ton (Hz)	VBW Setting (kHz)
802.11b	2412	12.243	12.379	98.90	/	0.010
802.11g	2412	2.033	2.072	98.12	/	0.010
802.11n20	2412	1.887	1.926	97.98	530	1
802.11n40	2422	0.928	0.980	94.69	1078	2

Duty Cycle = Ton/(Ton+Toff)*100%



ProjectNo.:2602P06299E-RF Tester:Rini Yan
Date: 16.JUN.2026 21:53:20



ProjectNo.:2602P06299E-RF Tester:Rini Yan
Date: 16.JUN.2026 21:55:43

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2602P06299E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2602P06299E-RF-INP EUT INTERNAL PHOTOGRAPHS.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2602P06299E-RF-00A-TSP TEST SETUP PHOTOGRAPHS.

******* END OF REPORT *******