



Product Name:	NEO	ROXX®	
Product Key:	14202201		
Operating Voltage:	100V-240V AC, 50/60Hz		
Power Consumption:	1050W		
Max. Power Thru:	6A @ 100V / 11A @ 230V		
Power Linking:	1 unit @ 100V / 3 units @ 230V		
Weight:	15,4kg/ 33,95lbs		
Protection Class:	IP65		
To:	45°C / 113°F		

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: 1- This device may NOT cause harmful interference, and 2- This device must accept any interference received, including interference that may cause undesired operation. FCC-ID: 2A2LS-NEO
Conforms to UL Std. 1573. Certified to CSA Std. C22.2NO.166



CONFORMS TO UL STD. 1573
CERTIFIED TO CSA STD. C22.2 NO.166

SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENT MOUILLÉS
NOT FOR RESIDENTIAL USE
NON DESTINÉ A UN USAGE DOMESTIQUE
NOT FOR HOUSEHOLD USE
NON DESTINÉ A UN USAGE DOMESTIQUE

SN

ROXX GmbH | Hansestr.91 | 51149 Köln | Germany
Designed & Engineered in Germany. Assembled in PRC

For safety and operating instructions see user guide.
Minimum distance to combustible surface:
