Product Name:	NEO mini
Product Key:	14201001
Operating Voltage:	100V-240V AC, 50/60Hz
Power Consumption:	706W @ 100V / 668W @ 230V
Max. Power Thru:	5A @ 100V / 9A @ 230V
Power Linking:	1 unit @ 120V / 3 units @ 230V
Weight:	7,7kg / 16,98lbs
Protection Class:	IP65
Ta:v	45°C / 113° F

SN

Minimum distance to combustible surface: 0,7m

ROXX®

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: 1- This device may NOT cause harmful interference, and 2- This device must accept any interference received, including interfe - rence that may cause undesired operation. FCC ID: 2A2LS-NEOMINI
CONFORMS TO UL STD.1573 CERTIFIED TO CSA STD.C22.2 NO.166
Highest exterior surface temperature if exceeds 75 °C

SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENT MOUILLÉS
NOT FOR RESIDENTIAL USE
NON DESTINÉ A UN USAGE DOMESTIQUE
NOT FOR HOUSEHOLD USE
NON DESTINÉ A UN USAGE DOMESTIQUE

Intertek
5020960

ROXX GmbH | Hansestr.91 | 51149 Köln | Germany | **Designed & Engineered in Germany. Assembled in PRC**