

FCC RF EXPOSURE REPORT


FCC ID: 2A2NK-ZTM03-001

Project No. : 2512C346
Equipment : Golf charter control system
Brand Name : N/A
Test Model : ZTM03
Model Name : ZTM03, ZTM05
Hardware Version : R05
Software Version : 1# For ZTM03: V1.12.0.4
2# For ZTM05: V1.14.0.1
Applicant : Hangzhou HopeChart IoT Technology Co., Ltd.
Address : 17th Floor, Hongquan Building, 35 Qizhi Street, Xixing Street, Binjiang District, Hangzhou city, Hangzhou, China
Manufacturer : Hangzhou HopeChart IoT Technology Co., Ltd.
Address : 17th Floor, Hongquan Building, 35 Qizhi Street, Xixing Street, Binjiang District, Hangzhou city, Hangzhou, China
Factory : Zhejiang Hongquan Electronic Technology Co., Ltd
Address : 508 Tianzihu Avenue, Tianzihu Town, Anji County, Huzhou City, Zhejiang Province, China
Date of Receipt : Dec. 30, 2025
Date of Test : Dec. 30, 2025 ~ Jan. 20, 2026
Issued Date : Mar. 26, 2026
Test Sample : Engineering Sample No.: DG920251229246
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & KDB447498 D01

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc. (Dongguan)

Prepared by


:



Evan Yang

Approved by

:



Chay Cai

No.3, Jinshagang 1st Road, Dalang, Dongguan, Guangdong People's Republic of China.

Tel: +86-769-8318-3000

Web: www.newbtl.com

Service mail: btl_qa@newbtl.com

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-2-2512C346	R00	Original Report.	Mar. 26, 2026	Valid

1. GENERAL CONCLUSION

According to FCC KDB447498 D01, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}]$$

 ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Appendix A - SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm											
MHz	5	10	15	20	25	30	35	40	45	50	mm
150	39	77	116	155	194	232	271	310	349	387	SAR Test Exclusion Thresholds (mW)
300	27	55	82	110	137	164	192	219	246	274	
450	22	45	67	89	112	134	157	179	201	224	
835	16	33	49	66	82	98	115	131	148	164	
900	16	32	47	63	79	95	111	126	142	158	
1500	12	24	37	49	61	73	86	98	110	122	
1900	11	22	33	44	54	65	76	87	98	109	
2450	10	19	29	38	48	57	67	77	86	96	
3600	8	16	24	32	40	47	55	63	71	79	
5200	7	13	20	26	33	39	46	53	59	66	
5400	6	13	19	26	32	39	45	52	58	65	
5800	6	12	19	25	31	37	44	50	56	62	

2. TABLE FOR FILED ANTENNA

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	 ZIDASV 正大信维	ZDXV-RF1.13	FPC	N/A	4.58

Note: The antenna gain is provided by the manufacturer.

3. TEST RESULTS

Function	Frequency (MHz)	Max. Output Power (dBm)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Exclusion Thresholds	Limit	Result
BLE	2402	-0.49	-0.49	0.8933	0.2770	3	Pass

Note: No SAR evaluation required since transmitter power is below FCC threshold.

End of Test Report