



SAR Test exclusion documentation according to FCC KDB 447498, RSS-102

Report identification number: 1-1501/20-01-06 Exclusion (FCC_ISED)

contains the module with the following certification numbers	
FCC ID	2A2OUAUMAPF00001
ISED number	27543-AUMAPF00001
HVIN (Hardware Version Identification Number)	A01
PMN (Product Marketing Name)	PROFOX
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:

cn=Alexander Hnatovskiy, o=CTC advanced
GmbH, ou=HNA-161129,
email=Alexander.Hnatovskiy@ctcadvanced.c
om, c=DE
2021.11.10 15:19:05 +01'00'

Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC

cn=Marco Scigliano, o=CTC advanced
GmbH, ou=SCI-161125,
email=marco.scigliano@ctcadvanced.com,
c=DE
2021.11.10 08:09:40 +01'00'

Marco Scigliano
Testing Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. measured peak EIRP
BT / BT LE 2450 MHz	-4.7 dBm

NOTE: Test results taken from CTC advanced GmbH report 1-1501/20-04-02 (page 20).

SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

(1) Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances $\leq 50\text{mm}$

$$(\text{Threshold}_{1\text{-g};10\text{-g}}) \times d_{\text{separation}} / f^{0.5}$$

where

Threshold_{1-g;10-g} is 3 for 1-g; 7.5 for 10-g

d_{separation} is the min. test separation distance; 5mm is used if the distance is less

f is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	d _{separation} [mm]	Threshold _{1-g}	Powerlimit [mW]	P _{max-declared}		Exclusion
				[dBm]	[mW]	
2450.00	5	3	9.58	-4.70	0.34	yes

SAR test exclusion according to RSS-102 Issue 5 Section 2.5.1/Table 1

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

frequency [MHz]	d _{separation} [mm]	tissue volume	Powerlimit [mW]	P _{max-declared}		Exclusion
				[dBm]	[mW]	
2450.00	5	1 g	4.00	-4.70	0.34	yes

The limits above are defined for body worn application and therefore cover all use cases.