



RADIO FREQUENCY EXPOSURE

Limit

According to section B.4 of 447498 D04 Interim General RF Exposure Guidance v01

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).



**Results****BT**

RF Exposure at Separation distance (cm): 20									
Mode	Antenna	Frequency [MHz]	Conducted Power [dBm]	Manufacturing tolerance		Antenna Gain [dBi]	Max of ERP and Conducted Power including Tune Up		SAR-based exemption threshold Pth [mW]
				Target Power [dBm]	Tolerance ±[dB]		[dBm]	[mW]	
DH5	Ant1	2402	13.4	13	1	4.29	16.14	41.11	3060.00
DH5	Ant1	2441	13.51	13	1	4.29	16.14	41.11	3060.00
DH5	Ant1	2480	13.68	13	1	4.29	16.14	41.11	3060.00
2DH5	Ant1	2402	12.98	12.5	1	4.29	15.64	36.64	3060.00
2DH5	Ant1	2441	13.03	12.5	1	4.29	15.64	36.64	3060.00
2DH5	Ant1	2480	13.19	12.5	1	4.29	15.64	36.64	3060.00
3DH5	Ant1	2402	13.22	12.5	1	4.29	15.64	36.64	3060.00
3DH5	Ant1	2441	13.27	13	1	4.29	16.14	41.11	3060.00
3DH5	Ant1	2480	13.45	13	1	4.29	16.14	41.11	3060.00

BLE

RF Exposure at Separation distance (cm): 20									
Mode	Antenna	Frequency [MHz]	Conducted Power [dBm]	Manufacturing tolerance		Antenna Gain [dBi]	Max of ERP and Conducted Power including Tune Up		SAR-based exemption threshold Pth [mW]
				Target Power [dBm]	Tolerance ±[dB]		[dBm]	[mW]	
BLE_1M	Ant1	2402	10.43	10	1	4.29	13.14	20.61	3060.00
BLE_1M	Ant1	2440	10.62	10	1	4.29	13.14	20.61	3060.00
BLE_1M	Ant1	2480	10.75	10.5	1	4.29	13.64	23.12	3060.00
BLE_2M	Ant1	2402	10.32	10	1	4.29	13.14	20.61	3060.00
BLE_2M	Ant1	2440	10.47	10	1	4.29	13.14	20.61	3060.00
BLE_2M	Ant1	2480	10.58	10	1	4.29	13.14	20.61	3060.00



**WIFI 2.4G PEAK**

RF Exposure at Separation distance (cm): 20									
Mode	Antenna	Frequency [MHz]	Conducted Power [dBm]	Manufacturing tolerance		Antenna Gain [dBi]	Max of ERP and Conducted Power including Tune Up		SAR-based exemption threshold Pth [mW]
				Target Power [dBm]	Tolerance ±[dB]		[dBm]	[mW]	
11B	Ant1	2412	14.3	14	1	4.29	17.14	51.76	3060.00
11B	Ant1	2437	14.38	14	1	4.29	17.14	51.76	3060.00
11B	Ant1	2462	12.91	12.5	1	4.29	15.64	36.64	3060.00
11G	Ant1	2412	19.86	19.5	1	4.29	22.64	183.65	3060.00
11G	Ant1	2437	20.62	20	1	4.29	23.14	206.06	3060.00
11G	Ant1	2462	19.31	19	1	4.29	22.14	163.68	3060.00
11N20SISO	Ant1	2412	18.92	18.5	1	4.29	21.64	145.88	3060.00
11N20SISO	Ant1	2437	19.94	19.5	1	4.29	22.64	183.65	3060.00
11N20SISO	Ant1	2462	18.85	18.5	1	4.29	21.64	145.88	3060.00
11N40SISO	Ant1	2422	19.13	18.5	1	4.29	21.64	145.88	3060.00
11N40SISO	Ant1	2437	19.75	19.5	1	4.29	22.64	183.65	3060.00
11N40SISO	Ant1	2452	19.29	19	1	4.29	22.14	163.68	3060.00



**WIFI 2.4G AV**

RF Exposure at Separation distance (cm): 20									
Mode	Antenna	Frequency [MHz]	Conducted Power [dBm]	Manufacturing tolerance		Antenna Gain [dBi]	Max of ERP and Conducted Power including Tune Up		SAR-based exemption threshold Pth [mW]
				Target Power [dBm]	Tolerance $\pm$ [dB]		[dBm]	[mW]	
11B	Ant1	2412	12.12	11.5	1	4.29	14.64	29.11	3060.00
11B	Ant1	2437	12.01	11.5	1	4.29	14.64	29.11	3060.00
11B	Ant1	2462	10.27	10	1	4.29	13.14	20.61	3060.00
11G	Ant1	2412	13.52	13	1	4.29	16.14	41.11	3060.00
11G	Ant1	2437	14.2	13.5	1	4.29	16.64	46.13	3060.00
11G	Ant1	2462	12.38	12	1	4.29	15.14	32.66	3060.00
11N20SISO	Ant1	2412	11.36	11	1	4.29	14.14	25.94	3060.00
11N20SISO	Ant1	2437	12.55	12	1	4.29	15.14	32.66	3060.00
11N20SISO	Ant1	2462	11.85	11.5	1	4.29	14.64	29.11	3060.00
11N40SISO	Ant1	2422	11.59	11	1	4.29	14.14	25.94	3060.00
11N40SISO	Ant1	2437	12.32	12	1	4.29	15.14	32.66	3060.00
11N40SISO	Ant1	2452	12.21	11.5	1	4.29	14.64	29.11	3060.00





WIFI 5.2G

RF Exposure at Separation distance (cm): 20									
Mode	Antenna	Frequency [MHz]	Conducted Power [dBm]	Manufacturing tolerance		Antenna Gain [dBi]	Max of ERP and Conducted Power including Tune Up		SAR-based exemption threshold Pth [mW]
				Target Power [dBm]	Tolerance $\pm$ [dB]		[dBm]	[mW]	
11A	Ant1	5180	9.75	9.5	1	0.67	10.5	11.22	3060.00
11A	Ant1	5200	10.86	10.5	1	0.67	11.5	14.13	3060.00
11A	Ant1	5240	11	10.5	1	0.67	11.5	14.13	3060.00
11N20SISO	Ant1	5180	11.18	10.5	1	0.67	11.5	14.13	3060.00
11N20SISO	Ant1	5200	10.91	10.5	1	0.67	11.5	14.13	3060.00
11N20SISO	Ant1	5240	10.94	10.5	1	0.67	11.5	14.13	3060.00
11N40SISO	Ant1	5190	9.99	9.5	1	0.67	10.5	11.22	3060.00
11N40SISO	Ant1	5230	10.81	10.5	1	0.67	11.5	14.13	3060.00
11AC20SISO	Ant1	5180	10.69	10	1	0.67	11	12.59	3060.00
11AC20SISO	Ant1	5200	11.14	10.5	1	0.67	11.5	14.13	3060.00
11AC20SISO	Ant1	5240	10.8	10.5	1	0.67	11.5	14.13	3060.00
11AC40SISO	Ant1	5190	10.65	10	1	0.67	11	12.59	3060.00
11AC40SISO	Ant1	5230	10.55	10	1	0.67	11	12.59	3060.00



**WIFI 5.8G**

RF Exposure at Separation distance (cm): 20									
Mode	Antenna	Frequency [MHz]	Conducted Power [dBm]	Manufacturing tolerance		Antenna Gain [dBi]	Max of ERP and Conducted Power including Tune Up		SAR-based exemption threshold Pth [mW]
				Target Power [dBm]	Tolerance ±[dB]		[dBm]	[mW]	
11A	Ant1	5745	13.61	13	1	2.67	14.52	28.31	3060.00
11A	Ant1	5785	13.13	12.5	1	2.67	14.02	25.23	3060.00
11A	Ant1	5825	14.16	13.5	1	2.67	15.02	31.77	3060.00
11N20SISO	Ant1	5745	11	10.5	1	2.67	12.02	15.92	3060.00
11N20SISO	Ant1	5785	11.28	11	1	2.67	12.52	17.86	3060.00
11N20SISO	Ant1	5825	11.99	11.5	1	2.67	13.02	20.04	3060.00
11N40SISO	Ant1	5755	9.57	9	1	2.67	10.52	11.27	3060.00
11N40SISO	Ant1	5795	10.73	10	1	2.67	11.52	14.19	3060.00
11AC20SISO	Ant1	5745	11.07	10.5	1	2.67	12.02	15.92	3060.00
11AC20SISO	Ant1	5785	10.86	10.5	1	2.67	12.02	15.92	3060.00
11AC20SISO	Ant1	5825	11.58	11	1	2.67	12.52	17.86	3060.00
11AC40SISO	Ant1	5755	10.25	10	1	2.67	11.52	14.19	3060.00
11AC40SISO	Ant1	5795	10.05	9.5	1	2.67	11.02	12.65	3060.00

Note: Wi-Fi & Bluetooth cannot transmit simultaneously

Max of ERP and Conducted Power including Tune Up (dBm) = Max Conducted Tune Up Power(dBm) and Max Conducted Tune Up Power(dBm) + Antenna Gain(dBi)-2.15), whichever is greater.

The Maximum Erp is used for Routine Evaluation Exemption according to B.4 of 447498 D04 Interim General RF Exposure Guidance v01.

So, the SAR evaluation is not required.

