TEST REPORT

Report Number	:	TZ0037260605FRF07
Product Name	:	Wireless Car Adapter
Model/Type reference	:	TC02A
FCC ID	:	2A2P5-TC02A
Prepared for	:	Acer Gadget Inc.
		24F., No. 112, Sec. 1, Xintai 5th Rd., Xizhi Dist. New Taipei City 221, Taiwan

Prepared By	:	Shenzhen Tongzhou Testing Co.,Ltd.
		1st Floor, Building 1, Haomai High-tech Park, Huating Road 387, Dalang Street, Longhua, Shenzhen, China
Standards	:	FCC CFR Title 47 Part 15E, ANSI C63.10-2020 + Cor.1-2023
Date of Test	:	2026-06-26 ~ 2026-07-10
Date of Issue	:	2026-07-10

Prepared by	:	Lena Wen	Lena Wen
Reviewed by	:	Allen Lai	Allen Lai
Approved by	:	Max Zhang (Authorized Officer)	Max Zhang

Shenzhen Tongzhou Testing Co., Ltd.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Tongzhou Testing Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Tongzhou Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.
The test report apply only to the specific sample(s) tested under stated test conditions.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

** Report Revise Record **

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	2026-07-10	Valid	Initial release

TABLE OF CONTENTS

1. GENERAL INFORMATION 4
1.1. Client Information 4
1.2. Description of Device (EUT) 4
1.3. Wireless Function Tested in this Report 4
1.4. EUT configuration 5
1.5. Description of Test Facility 5
1.6. Statement of the Measurement Uncertainty 6
1.7. Measurement Uncertainty 6
1.8. Description of Test Modes 6
2. TEST METHODOLOGY 7
2.1. EUT Configuration 7
2.2. EUT Exercise 7
2.3. Test Sample 7
3. SYSTEM TEST CONFIGURATION 8
3.1. Justification 8
3.2. EUT Exercise Software 8
3.3. Special Accessories 8
3.4. Block Diagram/Schematics 8
3.5. Equipment Modifications 8
3.6. Test Setup 8
4. SUMMARY OF TEST RESULTS 9
5. TEST RESULT 10
5.1. On Time and Duty Cycle 10
5.2. Maximum Conducted Output Power Measurement 11
5.3. Power Spectral Density Measurement 13
5.4. 6dB Emission Bandwidth and Occupied Channel Bandwidth Measurement 15
5.5. Radiated Emissions Measurement 16
5.6. Power line conducted emissions 28
5.7. Undesirable Emissions Measurement 31
5.8. Antenna Requirements 33
5.9. Frequency Stability 34
6. LIST OF MEASURING EQUIPMENT 35
7. TEST SETUP PHOTOGRAPHS OF EUT 36
8. EXTERIOR PHOTOGRAPHS OF THE EUT 36
9. INTERIOR PHOTOGRAPHS OF THE EUT 36

1. GENERAL INFORMATION

1.1. Client Information

Applicant	:	Acer Gadget Inc.
Address	:	24F., No. 112, Sec. 1, Xintai 5th Rd., Xizhi Dist. New Taipei City 221, Taiwan
Manufacturer	:	HK Linghan Technology Co., Limited
Address	:	Room 803B, 8/F., West Coast International Building, 290-296 Un Chau Street, Cheung Sha Wan, Kowloon, Hong Kong

1.2. Description of Device (EUT)

Product Name	:	Wireless Car Adapter
Trade Mark	:	acer
Model Number	:	TC02A
Model Declaration	:	N/A
Test Model	:	TC02A
Power Supply	:	Input: 5V⎓1A
Hardware version	:	V1.0
Software version	:	V1.0

1.3. Wireless Function Tested in this Report

WiFi		
WLAN FCC Operation Frequency	:	IEEE 802.11a: 5745-5825MHz IEEE 802.11ac VHT20: 5745-5825MHz IEEE 802.11ac VHT40: 5755-5795MHz
WLAN Channel Number	:	5 Channels for 5745-5825MHz(IEEE 802.11a/ac VHT20/n HT20) 2 Channels for 5755-5795MHz(IEEE 802.11ac VHT40/n HT40)
WLAN Modulation Technology	:	IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Type And Gain	:	PCB antenna, 2.67dBi

Note 1: Antenna position refer to EUT Photos.
Note 2: the above information was supplied by the applicant.

1.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:
●supplied by the manufacturer

○supplied by the lab

○	/	Model:	/
		Input:	/
		Output:	/

1.5. Description of Test Facility

FCC

Designation Number: CN1275
Test Firm Registration Number: 167722
Shenzhen Tongzhou Testing Co.,Ltd has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA

Certificate Number: 5463.01
Shenzhen Tongzhou Testing Co.,Ltd has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

IC

ISED#: 22033
CAB identifier: CN0099
Shenzhen Tongzhou Testing Co.,Ltd has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010

1.6. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the Shenzhen Tongzhou Testing Co.,Ltd quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.7. Measurement Uncertainty

Test Item		Uncertainty	Note
Radiation Uncertainty(9KHz~30MHz)	:	±3.26dB	(1)
Radiation Uncertainty(30MHz~1000MHz)	:	±3.92dB	(1)
Radiation Uncertainty(1GHz~40GHz)	:	±5.62dB	(1)
Conduction Uncertainty	:	±2.71dB	(1)
Occupied Channel Bandwidth	:	±3.0%	(1)
RF power, conducted	:	±0.16dB	(1)
Power Spectral Density, conducted	:	±1.3dB	(1)
Unwanted Emissions, conducted	:	±1.3dB	(1)
Time	:	±1.0%	(1)
Duty Cycle	:	±3.0%	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.8. Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Worst-case mode and channel used for 150 kHz-30 MHz power line conducted emissions was the mode and channel with the highest output power that was determined to be **802.11a high channel**

Worst-case mode and channel used for 9kHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be **802.11a high channel**

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

IEEE 802.11a Mode : 6 Mbps, OFDM
IEEE 802.11ac VHT20 Mode: MCS0
IEEE 802.11n HT20 Mode: MCS0
IEEE 802.11ac VHT40 Mode: MCS0
IEEE 802.11n HT40 Mode: MCS0

Antenna & Bandwidth

Antenna	Antenna 1			Simultaneously
Bandwidth Mode	20MHz	40MHz	80MHz	/
IEEE 802.11a	☑	☐	☐	☐
IEEE 802.11n	☑	☑	☐	☑
IEEE 802.11ac	☑	☑	☐	☑

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2020 + Cor.1-2023, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.
The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen Tongzhou Testing Co.,Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.
According to FCC's request, Test Procedure 789033 D02 General UNII Test Procedures New Rules v02r01 and KDB 6622911 are required to be used for this kind of FCC 15.407 UII device.
According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.407 under the FCC Rules Part 15 Subpart E

2.3. Test Sample

Sample ID	Description
TZ0037260605–1#	Engineer sample – continuous transmit
TZ0037260605–2#	Normal sample – Intermittent transmit

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (Xshell 7(Build 0076) at power level 10) provided by application.

3.3. Special Accessories

No.	Equipment	Manufacturer	Model No.	Serial No.	Length	shielded/ unshielded	Notes
1	PC	ASUS	X454L	15105-0038A100	/	/	/

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen Tongzhou Testing Co.,Ltd has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart E			
FCC Rules	Description of Test	Sample ID	Result
§15.407(a)	Maximum Conducted Output Power	TZ0037260605–1#	Compliant
§15.407(a)	Power Spectral Density	TZ0037260605–1#	Compliant
§15.407(e)	6dB Bandwidth	TZ0037260605–1#	Compliant
/	99% Occupied Bandwidth	TZ0037260605–1#	Note 1
§15.407(b)	Radiated Emissions	TZ0037260605–1#& TZ0037260605–2#	Compliant
§15.407(b)	Band edge Emissions	TZ0037260605–1#	Compliant
§15.407(g)	Frequency Stability	TZ0037260605–1#	Compliant
§15.207(a)	Line Conducted Emissions	TZ0037260605–2#	Compliant
§15.203	Antenna Requirements	N/A	Compliant
Note 1: only for report purpose.			

Remark: The measurement uncertainty is not included in the test result.

5. TEST RESULT

5.1. On Time and Duty Cycle

5.1.1. Standard Applicable

None. for reporting purpose only.

5.1.2. Block Diagram of Test Setup



5.1.3. Test Procedures

1. Set the Centre frequency of the spectrum analyzer to the transmitting frequency.
2. Set the span=0MHz, RBW=8MHz, VBW=8MHz.
3. Detector = peak.
4. Trace mode = Single hold.

5.1.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.5. Test Result

Pass

Remark:
1. Please refer to Appendix F of Appendix Test Data for RLAN(5.8G) for test data.

5.2. Maximum Conducted Output Power Measurement

5.2.1. Standard Applicable

For 5725~5850MHz

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2.2. Block Diagram of Test Setup



5.2.3. Test Procedures

The transmitter output (antenna port) was connected to the power meter.

According to KDB 789033 D02 Section 3 (a) Method PM (Measurement using an RF average power meter):

(i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
- At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
- The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

(ii) If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in section II.B.

(iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

(iv) Adjust the measurement in dBm by adding 10 log (1/x) where x is the duty cycle (e.g., 10 log (1/0.25) if the duty cycle is 25%).

5.2.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.5. Test Result

Pass

Remark:
1. Measured output power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss.
3. For MIMO with CCD technology device:

4. Directional gain = 10 log[($10^{G1/10}$ + $10^{G2/10}$ + … + $10^{GN/10}$)/N_{ANT}] dBi,where antenna gains given by G1, G2, …, GN dBi, N_{ANT} is the antennas total Number
5. Report conducted average power = measured conducted average power + Duty Cycle factor.
6. Please refer to Appendix B of Appendix Test Data for RLAN(5.8G) for test data.

5.3. Power Spectral Density Measurement

5.3.1. Standard Applicable

For 5725~5850MHz

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.3.2. Block Diagram of Test Setup



5.3.3. Test Procedures

1. The transmitter was connected directly to a Spectrum Analyzer through a directional couple.
2. The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
3. Set the RBW = 300 KHz.
4. Set the VBW ≥ 3*RBW
5. Span=Encompass the entire emissions bandwidth (EBW) of the signal
6. Detector = RMS Average.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. If measurement bandwidth of Maximum PSD is specified in 500 kHz, add 10 log (500 kHz/RBW) to the measured result, whereas RBW (<500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
11. If measurement bandwidth of Maximum PSD is specified in 1 MHz, add 10 log (1MHz/RBW) to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
12. Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

5.3.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.3.5. Test Result of Power Spectral Density

Pass

Remark:
1. Measured power spectrum density at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss.
3. For MIMO with CCD technology device
   Directional gain = 10 log[($10^{G1/10}$ + $10^{G2/10}$ + … + $10^{GN/10}$)/N_{ANT}] dBi,where antenna gains given by G1, G2, …, GN dBi, N_{ANT} is the antennas total Number.
4. Report conducted PSD = measured conducted PSD + Duty Cycle factor + RBW factor.
5. Please refer to Appendix C of Appendix Test Data for RLAN(5.8G) for test data.

5.4. 6dB Emission Bandwidth and Occupied Channel Bandwidth Measurement

5.4.1. Standard Applicable

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

5.4.2. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span	> 26dB Bandwidth
Detector	Peak
Trace	Max Hold

5.4.3. Block Diagram of Test Setup



5.4.4. Test Procedures

6dB Spectrum Bandwidth Test Procedure:
1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth and the video bandwidth were set according to C63.10 11.8.1.
3. Measured the spectrum width with power higher than 6dB below carrier.

Occupied Bandwidth Spectrum Bandwidth Test Procedure:
1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth and the video bandwidth were set according to C63.10 6.9.3
3. Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.4.6. Test Result

Pass

Remark:
1. Measured 6dB bandwidth at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss.
3. Please refer to Appendix A of Appendix Test Data for RLAN(5.8G) for test data.

5.5. Radiated Emissions Measurement

5.5.1. Standard Applicable

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.Android 10-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293.	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
\2\ Above 38.6

For transmitters operating in the 5.725-5.85 GHz band:
All emissions shall be limited to a level of −27 dBm/MHz(68.2dBuV/m at 3m) at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz(105.2dBuV/m at 3m) at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6(110.8dBuV/m at 3m) dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz(122.2dBuV/m at 3m) at the band edge.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

5.5.2. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak/Average
RB / VB (Emission in non-restricted band)	1MHz / 3MHz for Peak/Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

5.5.3. Block Diagram of Test Setup



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade form 3m to 1m.
Distance extrapolation factor = 20 log (specific distanc [3m] / test distance [1.5m]) (dB).
Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.5.4. Test Procedures

1) **Sequence of testing 9 kHz to 30 MHz**
Setup:
--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
--- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
--- If the EUT is a floor standing device, it is placed on the ground.
--- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
--- The measurement distance is 3 meter.
--- The EUT was set into operation.
Premeasurement:
--- The turntable rotates from 0° to 315° using 45° steps.
--- The antenna height is 1.0 meter.
--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions
Final measurement:
--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
--- Auxiliary equipment and cables were positioned to simulate normal operation conditions
--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
--- The measurement distance is 3 meter.
--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.
--- The antenna is polarized vertical and horizontal.
--- The antenna height changes from 1 to 3 meter.
--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.
--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter.
--- The final measurement will be done with QP detector with an EMI receiver.
--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
--- Auxiliary equipment and cables were positioned to simulate normal operation conditions
--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
--- The measurement distance is 3 meter.
--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.
--- The antenna is polarized vertical and horizontal.
--- The antenna height scan range is 1 meter to 2.5 meter.
--- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.
--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
--- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
--- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
--- Auxiliary equipment and cables were positioned to simulate normal operation conditions
--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
--- The measurement distance is 1 meter.
--- The EUT was set into operation.

Premeasurement:

--- The antenna is moved spherical over the EUT in different polarizations of the antenna.

Final measurement:

--- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
--- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

5.5.5. Test Results

Pass

Results of Radiated Emissions (9 KHz~30MHz)

Temperature	22.5℃	Humidity	56%
Test Engineer	Tony Luo	Configurations	IEEE 802.11a/n/ac
Test Volgate	DC 5V	/	/

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:
The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
Limit line = specific limits (dBuV) + distance extrapolation factor.

Results of Radiated Emissions (30MHz~1GHz)

Temperature	22.5℃	Humidity	56%
Test Engineer	Tony Luo	Configurations	IEEE 802.11a/n/ac
Test Volgate	DC 5V	/	/

Vertical



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	56.06	5.69	14.58	20.27	40.00	19.73	100	90	Vertical
2	97.77	6.40	12.29	18.69	43.50	24.81	100	10	Vertical
3	175.0	6.42	11.24	17.66	43.50	25.84	100	40	Vertical
4	223.7	4.74	13.97	18.71	46.00	27.29	100	80	Vertical
5	321.7	4.59	16.90	21.49	46.00	24.51	100	240	Vertical
6	444.4	3.89	19.84	23.73	46.00	22.27	100	280	Vertical

***Note:
1. Level [dBμV/m] = Reading [dBμV] + Factor [dB/m]
2. Margin [dB] = Limit [dBμV/m] - Level [dBμV/m]
3.Pre-scan all modes and recorded the worst case results in this report.

Horizontal



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	54.37	7.16	14.72	21.88	40.00	18.12	100	240	Horizontal
2	99.59	4.91	13.10	18.01	43.50	25.49	100	130	Horizontal
3	208.8	5.12	13.31	18.43	43.50	25.07	100	160	Horizontal
4	288.6	6.35	15.87	22.22	46.00	23.78	100	310	Horizontal
5	489.7	3.66	20.48	24.14	46.00	21.86	100	220	Horizontal
6	533.4	4.82	21.08	25.90	46.00	20.10	100	280	Horizontal

***Note:
1. Level [dBμV/m] = Reading [dBμV] + Factor [dB/m]
2. Margin [dB] = Limit [dBμV/m] - Level [dBμV/m]
3.Pre-scan all modes and recorded the worst case results in this report.

Results for Radiated Emissions (1GHz to 40GHz)

Temperature	24℃	Humidity	55.2%
Test Engineer	Tony Luo	Configurations	IEEE 802.11 a/n/ac
Test Volgate	DC 5V	/	/

Remark: Measured all modes and recorded worst case.

IEEE 802.11a

Channel 149 / 5745 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.24	55.60	33.06	35.04	3.94	57.56	68.20	10.64	Peak	Horizontal
17.24	43.77	33.06	35.04	3.94	45.73	54.00	8.27	Average	Horizontal
17.24	56.18	33.06	35.04	3.94	58.14	68.20	10.06	Peak	Vertical
17.24	43.51	33.06	35.04	3.94	45.47	54.00	8.53	Average	Vertical

Channel 157 / 5785 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.36	52.43	33.16	35.15	3.96	54.40	68.20	13.80	Peak	Horizontal
17.36	43.65	33.16	35.15	3.96	45.62	54.00	8.38	Average	Horizontal
17.36	51.63	33.16	35.15	3.96	53.60	68.20	14.60	Peak	Vertical
17.36	41.03	33.16	35.15	3.96	43.00	54.00	11.00	Average	Vertical

Channel 165 / 5825 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.48	54.92	33.26	35.14	3.98	57.02	68.20	11.18	Peak	Horizontal
17.48	41.60	33.26	35.14	3.98	43.70	54.00	10.30	Average	Horizontal
17.48	55.71	33.26	35.14	3.98	57.81	68.20	10.39	Peak	Vertical
17.48	43.26	33.26	35.14	3.98	45.36	54.00	8.64	Average	Vertical

IEEE 802.11n HT20

Channel 149 / 5745 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.24	52.44	33.06	35.04	3.94	54.40	68.20	13.80	Peak	Horizontal
17.24	41.70	33.06	35.04	3.94	43.66	54.00	10.34	Average	Horizontal
17.24	55.64	33.06	35.04	3.94	57.60	68.20	10.60	Peak	Vertical

17.24	42.31	33.06	35.04	3.94	44.27	54.00	9.73	Average	Vertical

Channel 157 / 5785 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.36	56.08	33.16	35.15	3.96	58.05	68.20	10.15	Peak	Horizontal
17.36	44.48	33.16	35.15	3.96	46.45	54.00	7.55	Average	Horizontal
17.36	55.41	33.16	35.15	3.96	57.38	68.20	10.82	Peak	Vertical
17.36	43.93	33.16	35.15	3.96	45.90	54.00	8.10	Average	Vertical

Channel 165 / 5825 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.48	53.16	33.26	35.14	3.98	55.26	68.20	12.94	Peak	Horizontal
17.48	44.24	33.26	35.14	3.98	46.34	54.00	7.66	Average	Horizontal
17.48	53.52	33.26	35.14	3.98	55.62	68.20	12.58	Peak	Vertical
17.48	40.14	33.26	35.14	3.98	42.24	54.00	11.76	Average	Vertical

IEEE 802.11n HT40

Channel 151 / 5755 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.27	56.12	33.06	35.04	3.94	58.08	68.20	10.12	Peak	Horizontal
17.27	42.36	33.06	35.04	3.94	44.32	54.00	9.68	Average	Horizontal
17.27	52.59	33.06	35.04	3.94	54.55	68.20	13.65	Peak	Vertical
17.27	43.15	33.06	35.04	3.94	45.11	54.00	8.89	Average	Vertical

Channel 159 / 5795 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.39	51.81	33.16	35.15	3.96	53.78	68.20	14.42	Peak	Horizontal
17.39	40.50	33.16	35.15	3.96	42.47	54.00	11.53	Average	Horizontal
17.39	51.68	33.16	35.15	3.96	53.65	68.20	14.55	Peak	Vertical
17.39	41.33	33.16	35.15	3.96	43.30	54.00	10.70	Average	Vertical

IEEE 802.11ac VHT20

Channel 149 / 5745 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.

				dB					
17.24	54.97	33.06	35.04	3.94	56.93	68.20	11.27	Peak	Horizontal
17.24	44.55	33.06	35.04	3.94	46.51	54.00	7.49	Average	Horizontal
17.24	55.90	33.06	35.04	3.94	57.86	68.20	10.34	Peak	Vertical
17.24	44.64	33.06	35.04	3.94	46.60	54.00	7.40	Average	Vertical

Channel 157 / 5785 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.36	54.84	33.16	35.15	3.96	56.81	68.20	11.39	Peak	Horizontal
17.36	40.18	33.16	35.15	3.96	42.15	54.00	11.85	Average	Horizontal
17.36	51.59	33.16	35.15	3.96	53.56	68.20	14.64	Peak	Vertical
17.36	43.62	33.16	35.15	3.96	45.59	54.00	8.41	Average	Vertical

Channel 165 / 5825 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.48	53.90	33.26	35.14	3.98	56.00	68.20	12.20	Peak	Horizontal
17.48	42.43	33.26	35.14	3.98	44.53	54.00	9.47	Average	Horizontal
17.48	55.88	33.26	35.14	3.98	57.98	68.20	10.22	Peak	Vertical
17.48	41.71	33.26	35.14	3.98	43.81	54.00	10.19	Average	Vertical

IEEE 802.11ac VHT40

Channel 151 / 5755 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.27	53.85	33.06	35.04	3.94	55.81	68.20	12.39	Peak	Horizontal
17.27	44.24	33.06	35.04	3.94	46.20	54.00	7.80	Average	Horizontal
17.27	51.70	33.06	35.04	3.94	53.66	68.20	14.54	Peak	Vertical
17.27	40.12	33.06	35.04	3.94	42.08	54.00	11.92	Average	Vertical

Channel 159 / 5795 MHz

Freq. GHz	Reading dBμV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Level dBμV/m	Limit dBμV/m	Margin dB	Remark	Pol.
17.39	52.53	33.16	35.15	3.96	54.50	68.20	13.70	Peak	Horizontal
17.39	40.22	33.16	35.15	3.96	42.19	54.00	11.81	Average	Horizontal
17.39	55.17	33.16	35.15	3.96	57.14	68.20	11.06	Peak	Vertical
17.39	40.78	33.16	35.15	3.96	42.75	54.00	11.25	Average	Vertical

Notes:

1. Measuring frequencies from 9 KHz ~40 GHz, No emission found between lowest internal used/generated frequencies to 30MHz.
2. Radiated emissions measured in frequency range from 9 KHz ~40GHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Level = Reading + Ant. Fac - Pre. Fac. + Cab. Loss. Margin = Limit - Level

5.6. Power line conducted emissions

5.6.1. Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreasing linearly with the logarithm of the frequency

5.6.2. Block Diagram of Test Setup



Note: the distance between LISN and Vertical reference plane is 40 cm and the distance between LISN and EUT is 80 cm.

5.6.3. Test Results

Temperature	24℃	Humidity	55.2%
Test Engineer	Tony Luo	Configurations	802.11a/n/ac
Test Volgate	AC 120V 60Hz	/	/

PASS

Neutral Line



Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.159000	28.50	9.6	66	37.0	QP	N	GND
0.564000	26.60	9.6	56	29.4	QP	N	GND
0.955500	20.60	9.7	56	35.4	QP	N	GND
2.094000	17.10	9.7	56	38.9	QP	N	GND
5.352000	11.50	9.7	60	48.5	QP	N	GND
24.022500	7.00	9.8	60	53.0	QP	N	GND

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.339000	14.00	9.7	49	35.2	AV	N	GND
0.564000	17.90	9.6	46	28.1	AV	N	GND
0.951000	14.30	9.7	46	31.7	AV	N	GND
2.121000	10.00	9.7	46	36.0	AV	N	GND
5.140500	7.20	9.7	50	42.8	AV	N	GND
15.985500	3.00	9.8	50	47.0	AV	N	GND

Note:
1. Margin(dB)= Limit(dBµV) - Level(dBµV)
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.
4. Pre-scan all modes and recorded the worst case results in this report.

Live Line



Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.334500	24.90	9.7	59	34.4	QP	L1	GND
0.564000	32.90	9.6	56	23.1	QP	L1	GND
0.942000	25.00	9.7	56	31.0	QP	L1	GND
2.679000	23.10	9.7	56	32.9	QP	L1	GND
5.118000	20.00	9.7	60	40.0	QP	L1	GND
13.114500	12.20	9.7	60	47.8	QP	L1	GND

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.285000	19.00	9.6	51	31.7	AV	L1	GND
0.564000	23.80	9.6	46	22.2	AV	L1	GND
0.964500	18.50	9.7	46	27.5	AV	L1	GND
3.534000	13.60	9.7	46	32.4	AV	L1	GND
5.779500	12.10	9.7	50	37.9	AV	L1	GND
15.967500	9.60	9.8	50	40.4	AV	L1	GND

Note:
1. Margin(dB)= Limit(dBµV) - Level(dBµV)
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.
4. Pre-scan all modes and recorded the worst case results in this report.

5.7. Undesirable Emissions Measurement

5.7.1. Limit

According to §15.407 (b) Undesirable emission limits. Except as shown in paragraph (b) (7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:
(a) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(b) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(c) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.
(d) For transmitters operating in the 5.725-5.85 GHz band:
(i) All emissions shall be limited to a level of −27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
(ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
(e) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
(f) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.
(g) The provisions of §15.205 apply to intentional radiators operating under this section.
(h) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

5.7.2. Block Diagram of Test Setup



5.7.3. Test Procedure

1. The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
2. Set the RBW = 1MHz.
3. Set the VBW = 3MHz
4. Number of points in sweep ≥ 2 × span / RBW. (This ensures that bin-to-bin spacing is ≤ RBW/2, so that

narrowband signals are not lost between frequency bins.)
5. Manually set sweep time ≥ 10 × (number of points in sweep) × (total on/off period of the transmitted signal).
6. Set detector = Peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.

5.7.4. Test Results

Pass

Remark:
1. Measured unwanted emission at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss.
3. For MIMO with CCD technology device:
   Directional gain = 10 log[(10G1 /10 + 10G2 /10 + … + 10GN /10)/NANT] dBi,where antenna gains given by G1, G2, …, GN dBi, NANT is the antennas total Number.
4. E.I.R.P = Conducted power + Directional Gain.
5. Please refer to Appendix D of Appendix Test Data for RLAN(5.8G) for test data.

5.8. **Antenna Requirements**

5.8.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.8.2. Antenna Connector Construction

The directional gains of antenna refer to section 1.3, and the antenna is an internal antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

5.8.3. Results

Compliance

5.9. Frequency Stability

5.9.1. Standard Applicable

According to FCC §15.407(g) “Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user manual.”

According to FCC §2.1055(a) “The frequency stability shall be measured with variation of ambient temperature as follows:”

(1) From −30° to + 50° centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section.

(2) From −20° to + 50° centigrade for equipment to be licensed for use in the Maritime Services under part 80 of this chapter, except for Class A, B, and S Emergency Position Indicating Radio beacons (EPIRBS), and equipment to be licensed for use above 952 MHz at operational fixed stations in all services, stations in the Local Television Transmission Service and Point-to-Point Microwave Radio Service under part 21 of this chapter, equipment licensed for use aboard aircraft in the Aviation Services under part 87 of this chapter, and equipment authorized for use in the Family Radio Service under part 95 of this chapter.

(3) From 0° to + 50° centigrade for equipment to be licensed for use in the Radio Broadcast Services under part 73 of this chapter.

5.9.2. Block Diagram of Test Setup



5.9.3. Test Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum anzlyer via feed through attenators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low engouh to obtain the desired frequency resoluation and measure EUT 20 degree operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30 degree. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure wuth 10 degree increased per stage until the highest temperature of +50 degree reached.

5.9.4. 5.9.4 Test Results

PASS

Remark:
1. Measured all conditions and recorded worst case.
2. Please refer to Appendix E of Appendix Test Data for RLAN(5.8G) for test data.

6. LIST OF MEASURING EQUIPMENT

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
1	MXA Signal Analyzer	Keysight	N9020A	MY52091623	2026-01-11	2027-01-10
2	Power Sensor	Agilent	U2021XA	MY5365004	2026-01-11	2027-01-10
3	Power Meter	Agilent	U2531A	TW53323507	2026-01-11	2027-01-10
4	Loop Antenna	schwarzbeck	FMZB1519B	00023	2025-10-18	2028-10-17
5	Wideband Antenna	schwarzbeck	VULB 9163	958	2025-10-18	2028-10-17
6	Horn Antenna	schwarzbeck	BBHA 9120D	01989	2025-10-18	2028-10-17
7	EMI Test Receiver	R&S	ESCI	100849/003	2026-01-11	2027-01-10
8	Controller	MF	MF7802	N/A	N/A	N/A
9	Amplifier	schwarzbeck	BBV 9743	209	2026-01-11	2027-01-10
10	Amplifier	Tonscend	TSAMP-0518SE	--	2026-01-11	2027-01-10
11	RF Cable(below 1GHz)	HUBER+SUHNER	RG214	N/A	2026-01-11	2027-01-10
12	RF Cable(above 1GHz)	HUBER+SUHNER	RG214	N/A	2026-01-11	2027-01-10
13	Artificial Mains	ROHDE & SCHWARZ	ENV 216	101333-IP	2026-01-11	2027-01-10
14	EMI Test Software	ROHDE & SCHWARZ	ESK1	V1.71	N/A	N/A
15	Amplifier	Chengyi	EMC184045SE	980508	2026-01-11	2027-01-10
16	Horn Antenna	A-INFO	LB-180400-KF	J211020657	2025-10-18	2028-10-17
17	Spectrum Analyzer	R&S	FSV40	101321	2026-01-11	2027-01-10
18	Fixed Attenuator	Mini circuits	BW-S6-2W263A+	N/A	2026-01-11	2027-01-10
19	DC Source	Keysight	E3646A	MY40006693	2026-01-11	2027-01-10
20	Climate Chamber	KRUOMR	KRM-1000	KRM16072901	2026-01-11	2027-01-10

Test software used:

Item	Test Software	Manufacturer	Name	Version
1	EMI Test Software	ROHDE & SCHWARZ	ESK1	V1.71
2	RE test software	Tonscend	JS32-RE	V5.0.0.0
3	Test Software	Tonscend	JS1120-3	V3.2.22

7. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

----------THE END OF REPORT----------