

RF

TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
TWS Coding Earphones

ISSUED TO
Foshan BOZY med Co., Ltd

807, 8/ F, Building 8, Zone A, Hantian Science and Technology City,
No.17, Shenhai Road, Guicheng Street, Nanhai District, Foshan
GuangDong China



Tested by:
Ye Hongji

Date: Aug. 26, 2021

Approved by:
Wei Yanquan
(Chief Engineer)

Date: Aug. 26, 2021

Report No.: BL-SZ2170636-603
EUT Name: TWS Coding Earphones
Model Name: So-coding
Brand Name: SoCoding
Test Standard: 47 CFR Part 15 Subpart C
(refer section 3.1)
FCC ID: 2A2PDSO-CODING2021R

Test conclusion: Pass
Test Date: Aug. 02, 2021 ~ Aug. 05, 2021
Date of Issue: Aug. 26, 2021

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Aug. 26, 2021</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	5
1.1	Identification of the Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Laboratory Condition	5
1.4	Announce	5
2	PRODUCT INFORMATION	6
2.1	Applicant Information	6
2.2	Manufacturer Information	6
2.3	Factory Information	6
2.4	General Description for Equipment under Test (EUT)	6
2.5	Technical Information	7
2.6	Additional Instructions	8
3	SUMMARY OF TEST RESULTS	9
3.1	Test Standards	9
3.2	Verdict	9
4	GENERAL TEST CONFIGURATIONS	10
4.1	Test Environments	10
4.2	Test Equipment List	10
4.3	Measurement Uncertainty	10
4.4	Description of Test Setup	11
4.4.1	For Antenna Port Test	11
4.4.2	For AC Power Supply Port Test	11
4.4.3	For Radiated Test (Below 30 MHz)	12
4.4.4	For Radiated Test (30 MHz-1 GHz)	12
4.4.5	For Radiated Test (Above 1 GHz)	13
4.5	Measurement Results Explanation Example	14
4.5.1	For conducted test items:	14

5	TEST ITEMS.....	15
5.1	Antenna Requirements.....	15
5.1.1	Relevant Standards.....	15
5.1.2	Antenna Anti-Replacement Construction	15
5.1.3	Antenna Gain	15
5.2	Frequency Hopping Systems	16
5.2.1	Relevant Standards.....	16
5.2.2	Description of the systems	16
5.3	Number of Hopping Frequencies	18
5.3.1	Limit.....	18
5.3.2	Test Setup.....	18
5.3.3	Test Procedure.....	18
5.3.4	Test Result	18
5.4	Peak Output Power and E.I.R.P.....	19
5.4.1	Test Limit.....	19
5.4.2	Test Setup	19
5.4.3	Test Procedure.....	19
5.4.4	Test Result	19
5.5	Occupied Bandwidth	20
5.5.1	Limit.....	20
5.5.2	Test Setup	20
5.5.3	Test Procedure.....	20
5.5.4	Test Result	20
5.6	Carrier Frequency Separation	21
5.6.1	Limit.....	21
5.6.2	Test Setup	21
5.6.3	Test Procedure.....	21
5.6.4	Test Result	21
5.7	Time of Occupancy (Dwell time)	22
5.7.1	Limit.....	22
5.7.2	Test Setup	22
5.7.3	Test Procedure.....	22
5.7.4	Test Result	23

5.8	Conducted Spurious Emission & Authorized-band band-edge	24
5.8.1	Limit.....	24
5.8.2	Test Setup	24
5.8.3	Test Procedure	24
5.8.4	Test Result	24
5.9	Conducted Emission	25
5.9.1	Limit.....	25
5.9.2	Test Setup	25
5.9.3	Test Procedure	25
5.9.4	Test Result	25
5.10	Radiated Spurious Emission	26
5.10.1	Limit.....	26
5.10.2	Test Setup	26
5.10.3	Test Procedure	26
5.10.4	Test Result	27
5.11	Band Edge (Restricted-band band-edge).....	28
5.11.1	Limit.....	28
5.11.2	Test Setup	28
5.11.3	Test Procedure	28
5.11.4	Test Result	28
ANNEX A	TEST RESULT	29
A.1	Number of Hopping Frequency	29
A.2	Peak Output Power	30
A.3	20 dB and 99% bandwidth	33
A.4	Hopping Frequency Separation.....	38
A.5	Average Time of Occupancy	39
A.6	Conducted Spurious Emissions & Authorized-band band-edge	42
A.7	Conducted Emissions.....	49
A.8	Radiated Spurious Emission	51
A.9	Band Edge (Restricted-band band-edge).....	69
ANNEX B	TEST SETUP PHOTOS	77
ANNEX C	EUT EXTERNAL PHOTOS	77
ANNEX D	EUT INTERNAL PHOTOS	77

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20°C to 25°C
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v5.7.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Foshan BOZY med co., Ltd
Address	807, 8/ F, Building 8, Zone A, Hantian Science and Technology City, No.17, Shenhai Road, Guicheng Street, Nanhai District, Foshan Guangdong China

2.2 Manufacturer Information

Manufacturer	Foshan BOZY med Co., Ltd
Address	807, 8/ F, Building 8, Zone A, Hantian Science and Technology City, No.17, Shenhai Road, Guicheng Street, Nanhai District, Foshan Guangdong China

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	TWS Coding Earphones
Model Name Under Test	So-coding
Series Model Name	N/A
Description of Model name differentiation	N/A
Serial Number	N/A
Hardware Version	V1.0
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE)
-----------------------------------	------------------------

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	DH5: 1 Mbps 2DH5: 2 Mbps 3DH5: 3 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)
Antenna Type	Ceramic Antenna
Antenna Gain	1 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
Antenna Impedance	50 Ω
Antenna System (MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	2402	21	2423	42	2444	63	2465
1	2403	22	2424	43	2445	64	2466
2	2404	23	2425	44	2446	65	2467
3	2405	24	2426	45	2447	66	2468
4	2406	25	2427	46	2448	67	2469
5	2407	26	2428	47	2449	68	2470
6	2408	27	2429	48	2450	69	2471
7	2409	28	2430	49	2451	70	2472
8	2410	29	2431	50	2452	71	2473
9	2411	30	2432	51	2453	72	2474
10	2412	31	2433	52	2454	73	2475
11	2413	32	2434	53	2455	74	2476
12	2414	33	2435	54	2456	75	2477
13	2415	34	2436	55	2457	76	2478
14	2416	35	2437	56	2458	77	2479
15	2417	36	2438	57	2459	78	2480
16	2418	37	2439	58	2460	-	-
17	2419	38	2440	59	2461	-	-
18	2420	39	2441	60	2462	-	-
19	2421	40	2442	61	2463	-	-
20	2422	41	2443	62	2464	-	-

2.6 Additional Instructions


EUT Software Settings:

Mode	☒ Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software			
Test Software Version	BlueTest3		
Support Units (Software installation media)	Description	Manufacturer	Model
	Notebook	Lenovo	X220
Mode	Channel	Frequency (MHz)	Soft Set
DH5	CH0	2402	Power parameter Settings is 3
	CH39	2441	
	CH78	2480	
2DH5	CH0	2402	
	CH39	2441	
	CH78	2480	
3DH5	CH0	2402	
	CH39	2441	
	CH78	2480	

Run Software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	N/A	--	Pass	Note ¹
2	Number of Hopping Frequencies	15.247(a)	Hopping Mode	ANNEX A.1	Pass	Note ²
3	Peak Output Power and E.I.R.P	15.247(b)	Low/Middle/High	ANNEX A.2	Pass	--
4	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.3	Pass	Note ²
5	Carrier Frequency Separation	15.247(a)	Hopping Mode	ANNEX A.4	Pass	Note ²
6	Time of Occupancy (Dwell time)	15.247(a)	Hopping Mode	ANNEX A.5	Pass	Note ²
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	Low/Middle/High	ANNEX A.6	Pass	Note ²
8	Conducted Emission	15.207	Low/Middle/High	ANNEX A.7	Pass	Note ²
9	Radiated Spurious Emission	15.209 15.247(d)	Hopping Mode, Low/Middle/High	ANNEX A.8	Pass	Note ²
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Hopping Mode, Low/Middle/High	ANNEX A.9	Pass	Note ²
11	Receiver Spurious Emissions	--	--	--	N/A	Note ³

Note ¹: Please refer to section 5.1

Note ²: $\pi/4$ -DQPSK is the EDR 2M rate mode, 8-DPSK is the EDR 3M rate mode. The consistency of test results in $\pi/4$ -DQPSK and 8-DPSK is very high. So we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item.

Note ³: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	5 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-40	101544	2021.04.01	2022.03.31
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2021.06.01	2022.05.31
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2021.06.01	2022.05.31
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2021.06.01	2022.05.31
LISN	SCHWARZBECK	NSLK 8127	8127-687	2021.06.01	2022.05.31
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2019.10.29	2021.10.28
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2019.07.02	2022.07.01
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1917	2019.07.02	2022.07.01
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2021.01.05	2023.01.04
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2022.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2019.08.08	2022.08.07
Shielded Enclosure	ChangNing	CN-130701	130703	--	--

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±2.8%
RF output power, conducted	±1.28 dB
Power Spectral Density, conducted	±1.30 dB
Unwanted Emissions, conducted	±1.84 dB
All emissions, radiated	±5.36 dB
Temperature	±0.82°C
Humidity	±4.1%


4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Frequency Hopping Systems

5.2.1 Relevant Standards

FCC §15.247(a) (1) (i) (ii) (iii) (iv)

Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, to demonstrate that the sequence meets the requirement specified in the definition of an FHSS system. Per the definition in Section 2.1(c), the hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event).

Describe how the associated receiver(s) complies with the requirement that the input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal.

Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.


For short burst systems, describe how the EUT complies with the requirement that it be designed to be capable of operating as a true frequency hopping system. Specifically, the device shall comply with the equal frequency use and pseudorandom hopping sequence requirement when transmitting in short bursts, and shall be designed to comply when presented with continuous data (or information) stream.

Describe how the EUT complies with the requirement that it not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

5.2.2 Description of the systems

1. According to the preset procedure of the whole network, all the stations in the automatic control network synchronously change the frequency multiple times within one second, and temporarily stay on each frequency hopping channel. Periodic synchronization signaling is sent from the primary station, instructing all slaves to simultaneously change the operating frequency, then the hopping sequence is generated.
2. The hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Reference Documents



3. Channels are classified into two categories, used and unused, where used channels are part of the hopping sequence and unused channels are replaced in the hopping sequence by used channels in a pseudo-random way. Make each individual EUT meets the requirement that each of its hopping channels is used equally on average.
4. The input bandwidth and transmitted bandwidth are both 1MHz, the associated receiver(s) complies with the requirement that the input bandwidth matches the bandwidth of the transmitted signal.
5. Connected devices communicate on the same physical channel by synchronizing with a common clock and hopping sequence.
6. EUT isn't short burst systems.
7. EUT can't have the ability to be coordinated with other FHSS systems in an effort.

5.3 Number of Hopping Frequencies

5.3.1 Limit

FCC §15.247(a) (1) (iii)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = The frequency band of operation

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.3.4 Test Result

Please refer to ANNEX A.1.

5.4 Peak Output Power and E.I.R.P

5.4.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.2.

5.5 Occupied Bandwidth

5.5.1 Limit

FCC §15.247(a)

Measurement of the 20dB bandwidth of the modulated signal.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.5.4 Test Result

Please refer to ANNEX A.3.

5.6 Carrier Frequency Separation

5.6.1 Limit

FCC §15.247(a)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 2/3 of the 20 dB bandwidth of the hopping channel, whichever is greater.

5.6.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.6.4 Test Result

Please refer to ANNEX A.4.

5.7 Time of Occupancy (Dwell time)

5.7.1 Limit

FCC §15.247(a)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.7.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

Span: Zero span, centered on a hopping channel

RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel

Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel

Detector function: Peak

Trace: Max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

The average time of occupancy on any channel within the Period can be calculated with formulas:

For GFSK and 8-DPSK:

For DH1 package type

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (1600 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

For DH3 package type

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (1600 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

For DH5 package type

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

For AFH Mode:

For DH1 package type

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (800 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

For DH3 package type

$$\begin{aligned}\{\text{Total of Dwell}\} &= \{\text{Pulse Time}\} * (800 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\} \\ \{\text{Period}\} &= 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}\end{aligned}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

{Period} = 0.4 s * {Number of Hopping Frequency}

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.7.4 Test Result

Please refer to ANNEX A.5.

5.8 Conducted Spurious Emission & Authorized-band band-edge

5.8.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW = 300 kHz

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.8.4 Test Result

Please refer to ANNEX A.6.

5.9 Conducted Emission

5.9.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.9.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Please refer to ANNEX A.7.

5.10 Radiated Spurious Emission

5.10.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \cdot \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: $54\text{dB}\mu\text{V/m}@3\text{m}$ (AV) and $74\text{dB}\mu\text{V/m}@3\text{m}$ (PK).

5.10.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Please refer to ANNEX A.8.

5.11 Band Edge (Restricted-band band-edge)

5.11.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.11.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.11.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.11.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT


A.1 Number of Hopping Frequency

Test Data


Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

Test plots


GFSK 2.4 GHz ~ 2.4415 GHz




GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK		dBm	mW	
	dBm	mW			
Low	-1.34	0.73	21	125	Pass
Middle	-1.26	0.75			Pass
High	-1.43	0.72			Pass

Channel	Measured Output Peak Power				Limit		Verdict
	$\pi/4$ -DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW			
Low	-2.92	0.51	-2.33	0.59	21	125	Pass
Middle	-2.90	0.51	-2.28	0.59			Pass
High	-3.05	0.50	-2.41	0.57			Pass

Test plots

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



$\pi/4$ -DQPSK LOW CHANNEL



$\pi/4$ -DQPSK MIDDLE CHANNEL




$\pi/4$ -DQPSK HIGH CHANNEL




8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL



A.3 20 dB and 99% bandwidth

Test Data

GFSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	0.960000	0.876330
Middle	0.955000	0.876220
High	0.960000	0.873710
$\pi/4$ -DQPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.340000	1.208000
Middle	1.345000	1.209700
High	1.345000	1.212400
8-DPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.305000	1.209900
Middle	1.305000	1.211800
High	1.305000	1.213200

Test plots

20 dB Bandwidth

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



$\pi/4$ -DQPSK LOW CHANNEL



$\pi/4$ -DQPSK MIDDLE CHANNEL



Center Freq 2.480000000 GHz
 #Res BW 30 kHz
 Span 3.000 MHz
 #Sweep 500.0 ms (601 pts)

Ref Offset 7.5 dB
 Ref 15.00 dBm

2.480 GHz
 0.587 MHz
 0.587 dB

INVT	MODE	TYPE	SQL	F	FUNCTION	FUNCTION WIDTH	FUNCTION AVAL
1	4	1	1	2.480 245 GHz	-0.896 dBm		
2	4	1	1	1.345 MHz (Δ)	0.587 dB		
3	4	1	1	2.479 410 GHz	-21.319 dBm		

Copyright Spectrum Analyzer - Screenshot

Center Freq 2.402000000 GHz

Ref Offset 7.61 dB
Ref 15.00 dBm

Span 3.000 MHz

Res BW 30 kHz

VBW 91 kHz

#Sweep 500.0 ms (601 pts)

Auto Tune

Center Freq 2.402000000 GHz

Start Freq 2.400500000 GHz

Stop Freq 2.403500000 GHz

CF Step 300.000 kHz

Freq Offset 0 Hz

ΔMkr2 1.305 MHz
0.844 dB

1
2Δ3

15 dBm

10 dBm

8 dBm

6 dBm

4 dBm

2 dBm

0 dBm

-2 dBm

-4 dBm

-6 dBm

-8 dBm

-10 dBm

-12 dBm

-14 dBm

-16 dBm

-18 dBm

-20 dBm

2.402 240 GHz

2.401 425 GHz

0.558 dBm

0.844 dB

-20.884 dBm

MARK	MODE	TRIG	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	2.402 240 GHz	0.558 dBm			
2	Δ	1	f (A)	1.305 MHz (A)	0.844 dB			
3	F	1	f	2.401 425 GHz	-20.884 dBm			
4								
5								
6								
7								
8								
9								
10								
11								

MODE

STATUS

Daylight Spectrum Analyzer - Sweep 5a

Center Freq 2.441000000 GHz

Ref Offset 7.7 dB
Ref 15.00 dBm

Pho: Wide → Trg: Free Run Attenu: 18 dB

Avg Type: Log-Pwr AvgHold: 2020

DMkr2 1.305 MHz
-0.198 dB

Auto Tune

Center Freq
2.441000000 GHz

Start Freq
2.439600000 GHz

Stop Freq
2.442500000 GHz

CF Step
300.000 kHz

CF Stop
Man

Center 2.441000 GHz
#Res BW 30 kHz

Span 3.000 MHz
#Sweep 500.0 ms (601 pts)

VBW 91 kHz

Auto

Frequency

Ref

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

Keysight Spectrum Analyzer - Single SA

Center Freq 2.480000000 GHz

Span 3.000 MHz

Res BW 30 kHz

VBW 91 kHz

#Sweep 500.0 ms (601 pts)

Ref Offset 7.5 dB

Ref 15.00 dBm


ΔMkr2 1.305 MHz

0.588 dB


MARKER	FREQ (GHz)	AMPL (dBm)
1	2.480245	0.474
2	2.480245	1.305
3	2.479430	-20.235

99% Bandwidth


GFSK LOW CHANNEL




GFSK MIDDLE CHANNEL




GFSK HIGH CHANNEL




$\pi/4$ -DQPSK LOW CHANNEL




$\pi/4$ -DQPSK MIDDLE CHANNEL




$\pi/4$ -DQPSK HIGH CHANNEL




8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL



A.4 Hopping Frequency Separation

Test Data


Mode	Frequency separation (MHz)	2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	0.98	0.640000	Pass
8-DPSK	1.00	0.870000	Pass

Test Plots

GFSK



8-DPSK




A.5 Average Time of Occupancy

Test Data


GFSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38080	121.856	0.4	Pass
DH 3	1.63400	261.440	0.4	Pass
DH 5	2.88800	308.053	0.4	Pass
8-DPSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38240	122.368	0.4	Pass
DH 3	1.63400	261.440	0.4	Pass
DH 5	2.88800	308.053	0.4	Pass
AFH Mode				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.37760	60.416	0.4	Pass
DH 3	1.63400	130.720	0.4	Pass
DH 5	2.88800	154.027	0.4	Pass

Test Plots


GFSK DH1




GFSK DH3




GFSK DH5




8-DPSK DH1




8-DPSK DH3




8-DPSK DH5




AFH Mode DH1



AFH Mode DH3



AFH Mode DH5



A.6 Conducted Spurious Emissions & Authorized-band band-edge

Test Data


GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-36.21	-1.55	-21.547	Pass
Middle	-34.52	-1.51	-21.506	Pass
High	-35.91	-1.65	-21.645	Pass
8-DPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-35.80	-5.54	-25.544	Pass
Middle	-35.84	-5.57	-25.567	Pass
High	-35.99	-5.70	-25.695	Pass
Hopping Mode				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-34.20	-1.52	-21.523	Pass
8-DPSK	-34.86	-5.59	-25.588	Pass

Test Plots


GFSK LOW CHANNEL, CARRIER LEVEL




GFSK LOW CHANNEL, BAND EDGE




GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK MIDDLE CHANNEL, CARRIER LEVEL




GFSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK HIGH CHANNEL, CARRIER LEVEL




GFSK HIGH CHANNEL, BAND EDGE




GFSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




8-DPSK LOW CHANNEL, CARRIER LEVEL




8-DPSK LOW CHANNEL, BAND EDGE




8-DPSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




8-DPSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



8-DPSK MIDDLE CHANNEL, CARRIER LEVEL




8-DPSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




8-DPSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




8-DPSK HIGH CHANNEL, CARRIER LEVEL




8-DPSK HIGH CHANNEL, BAND EDGE




8-DPSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




8-DPSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK HOPPING, CARRIER LEVEL




GFSK HOPPING BAND EDGE (LOW)




GFSK HOPPING BAND EDGE (HIGH)




GFSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz




GFSK Hopping Mode, SPURIOUS 30 GHz ~ 25 GHz



8-DPSK HOPPING, CARRIER LEVEL




8-DPSK Hopping BAND EDGE (LOW)




8-DPSK Hopping BAND EDGE (HIGH)



8-DPSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



8-DPSK Hopping Mode, SPURIOUS 30 GHz ~ 25 GHz



A.7 Conducted Emissions

Note¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.


Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15B_Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.174	44.51	10.39	64.77	-20.26	Peak	L	Pass
1**	0.174	29.16	10.39	54.77	-25.61	AV	L	Pass
2	0.284	40.25	10.34	60.70	-20.45	Peak	L	Pass
2**	0.284	27.83	10.34	50.70	-22.87	AV	L	Pass
3	0.512	38.16	10.30	56.00	-17.84	Peak	L	Pass
3**	0.512	26.02	10.30	46.00	-19.98	AV	L	Pass
4	2.706	36.38	10.28	56.00	-19.62	Peak	L	Pass
4**	2.706	24.26	10.28	46.00	-21.74	AV	L	Pass
5	6.000	36.86	10.33	60.00	-23.14	Peak	L	Pass
5**	6.000	24.97	10.33	50.00	-25.03	AV	L	Pass
6	8.450	36.71	10.35	60.00	-23.29	Peak	L	Pass
6**	8.450	24.77	10.35	50.00	-25.23	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15B_Class B



No.	Frequency (MHz)	Results (dBUV)	Factor (dB)	Limit (dBUV)	Over Limit (dB)	Detector	Line	Verdict
1	0.212	44.25	10.38	63.13	-18.88	Peak	N	Pass
1**	0.212	28.68	10.38	53.13	-24.45	AV	N	Pass
2	0.312	41.56	10.33	59.92	-18.36	Peak	N	Pass
2**	0.312	26.97	10.33	49.92	-22.95	AV	N	Pass
3	0.520	40.02	10.30	56.00	-15.98	Peak	N	Pass
3**	0.520	28.46	10.30	46.00	-17.54	AV	N	Pass
4	1.002	35.98	10.23	56.00	-20.02	Peak	N	Pass
4**	1.002	23.68	10.23	46.00	-22.32	AV	N	Pass
5	4.266	36.67	10.30	56.00	-19.33	Peak	N	Pass
5**	4.266	25.02	10.30	46.00	-20.98	AV	N	Pass
6	6.020	37.52	10.33	60.00	-22.48	Peak	N	Pass
6**	6.020	23.86	10.33	50.00	-26.14	AV	N	Pass

A.8 Radiated Spurious Emission

Test Data and Plots

Note¹: The symbol of "--" in the table which means not application.


Note²: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note³: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and DH5-Hopping mode is the worst.

Note⁴: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)


The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	55.456	13.14	-27.45	30.0	-16.86	Peak	95.00	200	Horizontal	Pass
2	127.946	12.96	-27.34	33.5	-20.54	Peak	199.00	100	Horizontal	Pass
3	172.069	11.47	-26.98	33.5	-22.03	Peak	327.00	200	Horizontal	Pass
4	287.956	16.23	-26.09	36.0	-19.77	Peak	312.00	200	Horizontal	Pass
5	463.482	17.28	-21.21	36.0	-18.72	Peak	256.00	200	Horizontal	Pass
6	870.052	25.30	-13.12	36.0	-10.70	Peak	0.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	69.033	16.24	-29.55	30.0	-13.76	Peak	222.00	100	Vertical	Pass
2	107.823	15.74	-29.33	33.5	-17.76	Peak	111.00	100	Vertical	Pass
3	175.706	19.01	-27.52	33.5	-14.49	Peak	272.00	100	Vertical	Pass
4	209.405	19.41	-29.49	33.5	-14.09	Peak	282.00	100	Vertical	Pass
5	239.953	23.12	-27.87	36.0	-12.88	Peak	252.00	100	Vertical	Pass
6	298.623	22.78	-25.87	36.0	-13.22	Peak	262.00	100	Vertical	Pass

Test Data and Plots (1 GHz ~ 10th Harmonic)


Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

Note 3: All spurious emissions are tested both vertically and horizontally and only the worst orientation are recorded in this test report.

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1327.900	40.28	-16.39	74.0	-33.72	Peak	32.00	150	Horizontal	Pass
1**	1327.900	24.29	-16.39	54.0	-29.71	AV	32.00	150	Horizontal	Pass
2	2402.000	90.69	-11.42	74.0	16.69	Peak	145.00	150	Horizontal	N/A
2**	2402.000	88.73	-11.42	54.0	34.73	AV	145.00	150	Horizontal	N/A
3	3050.250	46.36	-4.53	74.0	-27.64	Peak	303.00	150	Horizontal	Pass
3**	3050.250	36.31	-4.53	54.0	-17.69	AV	303.00	150	Horizontal	Pass
4	7230.500	55.02	3.16	74.0	-18.98	Peak	199.00	150	Horizontal	Pass
4**	7230.500	44.76	3.16	54.0	-9.24	AV	199.00	150	Horizontal	Pass
5	9349.000	52.69	3.34	74.0	-21.31	Peak	43.00	150	Horizontal	Pass
5**	9349.000	43.70	3.34	54.0	-10.30	AV	43.00	150	Horizontal	Pass
6	13617.000	55.39	6.13	74.0	-18.61	Peak	192.00	150	Horizontal	Pass
6**	13617.000	46.19	6.13	54.0	-7.81	AV	192.00	150	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1593.200	39.95	-16.48	74.0	-34.05	Peak	118.00	150	Vertical	Pass
1**	1593.200	25.95	-16.48	54.0	-28.05	AV	118.00	150	Vertical	Pass
2	2402.000	83.97	-11.42	74.0	9.97	Peak	201.00	150	Vertical	N/A
2**	2402.000	80.74	-11.42	54.0	26.74	AV	201.00	150	Vertical	N/A
3	5177.750	52.47	0.62	74.0	-21.53	Peak	283.00	150	Vertical	Pass
3**	5177.750	43.66	0.62	54.0	-10.34	AV	283.00	150	Vertical	Pass
4	7249.750	55.87	3.37	74.0	-18.13	Peak	56.00	150	Vertical	Pass
4**	7249.750	45.09	3.37	54.0	-8.91	AV	56.00	150	Vertical	Pass
5	9357.000	52.38	3.28	74.0	-21.62	Peak	42.00	150	Vertical	Pass
5**	9357.000	43.98	3.28	54.0	-10.02	AV	42.00	150	Vertical	Pass
6	13378.500	55.70	6.32	74.0	-18.30	Peak	156.00	150	Vertical	Pass
6**	13378.500	47.55	6.32	54.0	-6.45	AV	156.00	150	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1598.600	38.94	-16.55	74.0	-35.06	Peak	80.00	150	Horizontal	Pass
1**	1598.600	25.19	-16.55	54.0	-28.81	AV	80.00	150	Horizontal	Pass
2	2440.900	92.63	-11.18	74.0	18.63	Peak	150.00	150	Horizontal	N/A
2**	2440.900	89.39	-11.18	54.0	35.39	AV	150.00	150	Horizontal	N/A
3	4806.000	51.18	1.05	74.0	-22.82	Peak	323.00	150	Horizontal	Pass
3**	4806.000	41.33	1.05	54.0	-12.67	AV	323.00	150	Horizontal	Pass
4	6683.250	54.33	2.31	74.0	-19.67	Peak	251.00	150	Horizontal	Pass
4**	6683.250	44.08	2.31	54.0	-9.92	AV	251.00	150	Horizontal	Pass
5	9833.500	54.21	2.31	74.0	-19.79	Peak	65.00	150	Horizontal	Pass
5**	9833.500	45.43	2.31	54.0	-8.57	AV	65.00	150	Horizontal	Pass
6	13375.000	55.81	6.34	74.0	-18.19	Peak	122.00	150	Horizontal	Pass
6**	13375.000	47.60	6.34	54.0	-6.40	AV	122.00	150	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1331.700	41.21	-16.40	74.0	-32.79	Peak	60.00	150	Vertical	Pass
1**	1331.700	24.73	-16.40	54.0	-29.27	AV	60.00	150	Vertical	Pass
2	2440.900	85.71	-11.18	74.0	11.71	Peak	143.00	150	Vertical	N/A
2**	2440.900	81.14	-11.18	54.0	27.14	AV	143.00	150	Vertical	N/A
3	3240.250	45.68	-5.92	74.0	-28.32	Peak	0.00	150	Vertical	Pass
3**	3240.250	34.60	-5.92	54.0	-19.40	AV	0.00	150	Vertical	Pass
4	7924.250	55.73	4.37	74.0	-18.27	Peak	28.00	150	Vertical	Pass
4**	7924.250	45.92	4.37	54.0	-8.08	AV	28.00	150	Vertical	Pass
5	9322.000	53.43	3.37	74.0	-20.57	Peak	306.00	150	Vertical	Pass
5**	9322.000	44.25	3.37	54.0	-9.75	AV	306.00	150	Vertical	Pass
6	13369.000	56.05	6.38	74.0	-17.95	Peak	67.00	150	Vertical	Pass
6**	13369.000	47.28	6.38	54.0	-6.72	AV	67.00	150	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1329.700	38.89	-16.39	74.0	-35.11	Peak	60.00	150	Horizontal	Pass
1**	1329.700	25.48	-16.39	54.0	-28.52	AV	60.00	150	Horizontal	Pass
2	2479.900	89.66	-10.98	74.0	15.66	Peak	143.00	150	Horizontal	N/A
2**	2479.900	86.84	-10.98	54.0	32.84	AV	143.00	150	Horizontal	N/A
3	3614.500	46.71	-3.76	74.0	-27.29	Peak	173.00	150	Horizontal	Pass
3**	3614.500	37.84	-3.76	54.0	-16.16	AV	173.00	150	Horizontal	Pass
4	7126.750	55.21	2.32	74.0	-18.79	Peak	61.00	150	Horizontal	Pass
4**	7126.750	46.43	2.32	54.0	-7.57	AV	61.00	150	Horizontal	Pass
5	10063.000	53.63	3.46	74.0	-20.37	Peak	307.00	150	Horizontal	Pass
5**	10063.000	45.41	3.46	54.0	-8.59	AV	307.00	150	Horizontal	Pass
6	13369.500	55.27	6.38	74.0	-18.73	Peak	238.00	150	Horizontal	Pass
6**	13369.500	46.57	6.38	54.0	-7.43	AV	238.00	150	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1595.900	38.68	-16.37	74.0	-35.32	Peak	121.00	150	Vertical	Pass
1**	1595.900	26.84	-16.37	54.0	-27.16	AV	121.00	150	Vertical	Pass
2	2479.800	84.21	-10.98	74.0	10.21	Peak	148.00	150	Vertical	N/A
2**	2479.800	80.25	-10.98	54.0	26.25	AV	148.00	150	Vertical	N/A
3	3983.750	48.00	-2.72	74.0	-26.00	Peak	340.00	150	Vertical	Pass
3**	3983.750	38.19	-2.72	54.0	-15.81	AV	340.00	150	Vertical	Pass
4	7217.000	54.82	2.83	74.0	-19.18	Peak	250.00	150	Vertical	Pass
4**	7217.000	44.59	2.83	54.0	-9.41	AV	250.00	150	Vertical	Pass
5	9332.000	52.47	3.36	74.0	-21.53	Peak	31.00	150	Vertical	Pass
5**	9332.000	44.01	3.36	54.0	-9.99	AV	31.00	150	Vertical	Pass
6	13614.000	55.58	6.11	74.0	-18.42	Peak	237.00	150	Vertical	Pass
6**	13614.000	46.50	6.11	54.0	-7.50	AV	237.00	150	Vertical	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1554.400	38.84	-16.34	74.0	-35.16	Peak	106.00	150	Horizontal	Pass
1**	1554.400	24.54	-16.34	54.0	-29.46	AV	106.00	150	Horizontal	Pass
2	2402.000	87.94	-11.42	74.0	13.94	Peak	146.00	150	Horizontal	N/A
2**	2402.000	84.05	-11.42	54.0	30.05	AV	146.00	150	Horizontal	N/A
3	4050.500	49.17	-2.37	74.0	-24.83	Peak	105.00	150	Horizontal	Pass
3**	4050.500	38.42	-2.37	54.0	-15.58	AV	105.00	150	Horizontal	Pass
4	6863.250	54.46	2.53	74.0	-19.54	Peak	250.00	150	Horizontal	Pass
4**	6863.250	45.82	2.53	54.0	-8.18	AV	250.00	150	Horizontal	Pass
5	9336.500	52.57	3.35	74.0	-21.43	Peak	8.00	150	Horizontal	Pass
5**	9336.500	44.75	3.35	54.0	-9.25	AV	8.00	150	Horizontal	Pass
6	12497.000	55.50	4.44	74.0	-18.50	Peak	113.00	150	Horizontal	Pass
6**	12497.000	45.42	4.44	54.0	-8.58	AV	113.00	150	Horizontal	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.100	39.59	-16.40	74.0	-34.41	Peak	57.00	150	Vertical	Pass
1**	1332.100	29.95	-16.40	54.0	-24.05	AV	57.00	150	Vertical	Pass
2	2402.000	81.68	-11.42	74.0	7.68	Peak	199.00	150	Vertical	N/A
2**	2402.000	74.69	-11.42	54.0	20.69	AV	199.00	150	Vertical	N/A
3	3694.000	46.86	-4.02	74.0	-27.14	Peak	245.00	150	Vertical	Pass
3**	3694.000	37.57	-4.02	54.0	-16.43	AV	245.00	150	Vertical	Pass
4	7390.250	55.80	3.80	74.0	-18.20	Peak	278.00	150	Vertical	Pass
4**	7390.250	47.56	3.80	54.0	-6.44	AV	278.00	150	Vertical	Pass
5	9314.000	52.99	3.38	74.0	-21.01	Peak	318.00	150	Vertical	Pass
5**	9314.000	44.00	3.38	54.0	-10.00	AV	318.00	150	Vertical	Pass
6	13379.500	56.47	6.31	74.0	-17.53	Peak	0.00	150	Vertical	Pass
6**	13379.500	46.86	6.31	54.0	-7.14	AV	0.00	150	Vertical	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1597.300	41.12	-16.49	74.0	-32.88	Peak	71.00	150	Horizontal	Pass
1**	1597.300	26.08	-16.49	54.0	-27.92	AV	71.00	150	Horizontal	Pass
2	2440.800	87.13	-11.18	74.0	13.13	Peak	145.00	150	Horizontal	N/A
2**	2440.800	80.09	-11.18	54.0	26.09	AV	145.00	150	Horizontal	N/A
3	3792.000	48.33	-3.89	74.0	-25.67	Peak	97.00	150	Horizontal	Pass
3**	3792.000	37.81	-3.89	54.0	-16.19	AV	97.00	150	Horizontal	Pass
4	5156.250	52.65	0.17	74.0	-21.35	Peak	64.00	150	Horizontal	Pass
4**	5156.250	42.59	0.17	54.0	-11.41	AV	64.00	150	Horizontal	Pass
5	9297.500	52.50	3.36	74.0	-21.50	Peak	180.00	150	Horizontal	Pass
5**	9297.500	44.25	3.36	54.0	-9.75	AV	180.00	150	Horizontal	Pass
6	14078.000	56.39	5.87	74.0	-17.61	Peak	111.00	150	Horizontal	Pass
6**	14078.000	47.02	5.87	54.0	-6.98	AV	111.00	150	Horizontal	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1597.200	40.47	-16.48	74.0	-33.53	Peak	104.00	150	Vertical	Pass
1**	1597.200	25.09	-16.48	54.0	-28.91	AV	104.00	150	Vertical	Pass
2	2440.800	82.11	-11.18	74.0	8.11	Peak	140.00	150	Vertical	N/A
2**	2440.800	73.96	-11.18	54.0	19.96	AV	140.00	150	Vertical	N/A
3	3123.000	45.84	-5.34	74.0	-28.16	Peak	37.00	150	Vertical	Pass
3**	3123.000	35.98	-5.34	54.0	-18.02	AV	37.00	150	Vertical	Pass
4	6678.500	54.77	2.23	74.0	-19.23	Peak	125.00	150	Vertical	Pass
4**	6678.500	45.04	2.23	54.0	-8.96	AV	125.00	150	Vertical	Pass
5	10071.000	53.68	3.18	74.0	-20.32	Peak	168.00	150	Vertical	Pass
5**	10071.000	44.98	3.18	54.0	-9.02	AV	168.00	150	Vertical	Pass
6	14037.000	56.01	6.13	74.0	-17.99	Peak	77.00	150	Vertical	Pass
6**	14037.000	47.84	6.13	54.0	-6.16	AV	77.00	150	Vertical	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1599.400	39.51	-16.53	74.0	-34.49	Peak	83.00	150	Horizontal	Pass
1**	1599.400	25.33	-16.53	54.0	-28.67	AV	83.00	150	Horizontal	Pass
2	2479.900	86.32	-10.98	74.0	12.32	Peak	118.00	150	Horizontal	N/A
2**	2479.900	79.94	-10.98	54.0	25.94	AV	118.00	150	Horizontal	N/A
3	4432.250	50.40	-1.47	74.0	-23.60	Peak	187.00	150	Horizontal	Pass
3**	4432.250	38.78	-1.47	54.0	-15.22	AV	187.00	150	Horizontal	Pass
4	7949.500	55.81	4.78	74.0	-18.19	Peak	98.00	150	Horizontal	Pass
4**	7949.500	46.68	4.78	54.0	-7.32	AV	98.00	150	Horizontal	Pass
5	9319.999	52.57	3.37	74.0	-21.43	Peak	224.00	150	Horizontal	Pass
5**	9319.999	44.37	3.37	54.0	-9.63	AV	224.00	150	Horizontal	Pass
6	13810.000	56.73	6.97	74.0	-17.27	Peak	236.00	150	Horizontal	Pass
6**	13810.000	47.19	6.97	54.0	-6.81	AV	236.00	150	Horizontal	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1594.700	39.97	-16.42	74.0	-34.03	Peak	104.00	150	Vertical	Pass
1**	1594.700	26.60	-16.42	54.0	-27.40	AV	104.00	150	Vertical	Pass
2	2479.800	80.55	-10.98	74.0	6.55	Peak	174.00	150	Vertical	N/A
2**	2479.800	75.08	-10.98	54.0	21.08	AV	174.00	150	Vertical	N/A
3	3503.000	46.14	-5.15	74.0	-27.86	Peak	37.00	150	Vertical	Pass
3**	3503.000	34.96	-5.15	54.0	-19.04	AV	37.00	150	Vertical	Pass
4	6674.250	54.32	2.20	74.0	-19.68	Peak	157.00	150	Vertical	Pass
4**	6674.250	45.67	2.20	54.0	-8.33	AV	157.00	150	Vertical	Pass
5	9830.000	52.92	2.33	74.0	-21.08	Peak	205.00	150	Vertical	Pass
5**	9830.000	44.63	2.33	54.0	-9.37	AV	205.00	150	Vertical	Pass
6	13357.500	55.56	6.46	74.0	-18.44	Peak	262.00	150	Vertical	Pass
6**	13357.500	47.04	6.46	54.0	-6.96	AV	262.00	150	Vertical	Pass

Hopping Mode:

GFSK MODE 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1331.900	39.97	-16.40	74.0	-34.03	Peak	33.00	150	Horizontal	Pass
1**	1331.900	25.07	-16.40	54.0	-28.93	AV	33.00	150	Horizontal	Pass
2	2427.900	91.57	-11.16	74.0	17.57	Peak	149.00	150	Horizontal	N/A
2**	2427.900	83.37	-11.16	54.0	29.37	AV	149.00	150	Horizontal	N/A
3	4775.500	51.49	1.11	74.0	-22.51	Peak	246.00	150	Horizontal	Pass
3**	4775.500	41.30	1.11	54.0	-12.70	AV	246.00	150	Horizontal	Pass
4	7719.250	55.51	3.67	74.0	-18.49	Peak	101.00	150	Horizontal	Pass
4**	7719.250	46.92	3.67	54.0	-7.08	AV	101.00	150	Horizontal	Pass
5	9327.000	53.03	3.36	74.0	-20.97	Peak	271.00	150	Horizontal	Pass
5**	9327.000	44.13	3.36	54.0	-9.87	AV	271.00	150	Horizontal	Pass
6	13809.500	56.45	6.97	74.0	-17.55	Peak	157.00	150	Horizontal	Pass
6**	13809.500	47.67	6.97	54.0	-6.33	AV	157.00	150	Horizontal	Pass

GFSK MODE 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1596.900	39.07	-16.45	74.0	-34.93	Peak	114.00	150	Vertical	Pass
1**	1596.900	26.16	-16.45	54.0	-27.84	AV	114.00	150	Vertical	Pass
2	2453.000	85.03	-11.60	74.0	11.03	Peak	141.00	150	Vertical	N/A
2**	2453.000	78.12	-11.60	54.0	24.12	AV	141.00	150	Vertical	N/A
3	4053.500	49.11	-2.60	74.0	-24.89	Peak	106.00	150	Vertical	Pass
3**	4053.500	38.33	-2.60	54.0	-15.67	AV	106.00	150	Vertical	Pass
4	6685.750	54.34	2.29	74.0	-19.66	Peak	291.00	150	Vertical	Pass
4**	6685.750	45.35	2.29	54.0	-8.65	AV	291.00	150	Vertical	Pass
5	9365.500	52.81	3.22	74.0	-21.19	Peak	270.00	150	Vertical	Pass
5**	9365.500	43.51	3.22	54.0	-10.49	AV	270.00	150	Vertical	Pass
6	13633.500	56.12	6.27	74.0	-17.88	Peak	258.00	150	Vertical	Pass
6**	13633.500	47.27	6.27	54.0	-6.73	AV	258.00	150	Vertical	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1327.000	39.16	-16.37	74.0	-34.84	Peak	74.00	150	Horizontal	Pass
1**	1327.000	25.13	-16.37	54.0	-28.87	AV	74.00	150	Horizontal	Pass
2	2458.200	89.32	-11.46	74.0	15.32	Peak	144.00	150	Horizontal	N/A
2**	2458.200	82.48	-11.46	54.0	28.48	AV	144.00	150	Horizontal	N/A
3	3730.000	46.91	-3.71	74.0	-27.09	Peak	101.00	150	Horizontal	Pass
3**	3730.000	36.86	-3.71	54.0	-17.14	AV	101.00	150	Horizontal	Pass
4	7784.250	55.33	4.60	74.0	-18.67	Peak	77.00	150	Horizontal	Pass
4**	7784.250	46.16	4.60	54.0	-7.84	AV	77.00	150	Horizontal	Pass
5	9322.000	52.90	3.37	74.0	-21.10	Peak	341.00	150	Horizontal	Pass
5**	9322.000	44.67	3.37	54.0	-9.33	AV	341.00	150	Horizontal	Pass
6	13843.000	55.57	6.55	74.0	-18.43	Peak	54.00	150	Horizontal	Pass
6**	13843.000	46.73	6.55	54.0	-7.27	AV	54.00	150	Horizontal	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT V

RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.400	40.74	-16.40	74.0	-33.26	Peak	63.00	150	Vertical	Pass
1**	1332.400	24.72	-16.40	54.0	-29.28	AV	63.00	150	Vertical	Pass
2	2451.300	82.81	-11.60	74.0	8.81	Peak	147.00	150	Vertical	N/A
2**	2451.300	73.68	-11.60	54.0	19.68	AV	147.00	150	Vertical	N/A
3	4211.500	48.46	-0.71	74.0	-25.54	Peak	113.00	150	Vertical	Pass
3**	4211.500	39.42	-0.71	54.0	-14.58	AV	113.00	150	Vertical	Pass
4	7777.000	55.46	4.52	74.0	-18.54	Peak	186.00	150	Vertical	Pass
4**	7777.000	46.35	4.52	54.0	-7.65	AV	186.00	150	Vertical	Pass
5	8826.000	52.35	2.47	74.0	-21.65	Peak	191.00	150	Vertical	Pass
5**	8826.000	43.78	2.47	54.0	-10.22	AV	191.00	150	Vertical	Pass
6	13349.500	55.95	6.49	74.0	-18.05	Peak	42.00	150	Vertical	Pass
6**	13349.500	46.96	6.49	54.0	-7.04	AV	42.00	150	Vertical	Pass

A.9 Band Edge (Restricted-band band-edge)

Note¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note⁴: The Level (dBuV/m) has been corrected by factor.


Test Data

GFSK LOW CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	56.55	32.63	74.0	-17.45	Peak	5.00	150	Horizontal	Pass
1**	2390.000	46.76	32.63	54.0	-7.24	AV	5.00	150	Horizontal	Pass
2	2388.500	58.38	32.69	74.0	-15.62	Peak	9.00	150	Horizontal	Pass
2**	2388.500	46.57	32.69	54.0	-7.43	AV	9.00	150	Horizontal	Pass

GFSK HIGH CHANNEL,




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	57.26	32.80	74.0	-16.74	Peak	15.00	100	Horizontal	Pass
1**	2483.500	46.71	32.80	54.0	-7.29	AV	15.00	100	Horizontal	Pass
2	2492.450	58.25	32.62	74.0	-15.75	Peak	5.00	100	Horizontal	Pass
2**	2492.450	46.20	32.62	54.0	-7.80	AV	5.00	100	Horizontal	Pass

8-DPSK LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	57.62	32.63	74.0	-16.38	Peak	2.00	150	Horizontal	Pass
1**	2390.000	46.73	32.63	54.0	-7.27	AV	2.00	150	Horizontal	Pass
2	2362.167	58.83	32.57	74.0	-15.17	Peak	6.00	150	Horizontal	Pass
2**	2362.167	46.56	32.57	54.0	-7.44	AV	6.00	150	Horizontal	Pass


8-DPSK HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	59.54	32.80	74.0	-14.46	Peak	13.00	150	Horizontal	Pass
1**	2483.500	46.81	32.80	54.0	-7.19	AV	13.00	150	Horizontal	Pass
2	2485.200	58.36	32.77	74.0	-15.64	Peak	11.00	150	Horizontal	Pass
2**	2485.200	46.47	32.77	54.0	-7.53	AV	11.00	150	Horizontal	Pass


Hopping Mode:

GFSK LOW FREQUENCY BAND



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	57.93	32.63	74.0	-16.07	Peak	5.00	150	Horizontal	Pass
1**	2390.000	46.83	32.63	54.0	-7.17	AV	5.00	150	Horizontal	Pass
2	2336.667	59.92	32.82	74.0	-14.08	Peak	5.00	150	Horizontal	Pass
2**	2336.667	46.59	32.82	54.0	-7.41	AV	5.00	150	Horizontal	Pass

GFSK HIGH FREQUENCY BAND,




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	57.42	32.80	74.0	-16.58	Peak	14.00	150	Horizontal	Pass
1**	2483.500	46.49	32.80	54.0	-7.51	AV	14.00	150	Horizontal	Pass
2	2492.450	59.01	32.62	74.0	-14.99	Peak	5.00	150	Horizontal	Pass
2**	2492.450	46.41	32.62	54.0	-7.59	AV	5.00	150	Horizontal	Pass

8-DPSK LOW FREQUENCY BAND



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	57.77	32.63	74.0	-16.23	Peak	7.00	150	Horizontal	Pass
1**	2390.000	46.69	32.63	54.0	-7.31	AV	7.00	150	Horizontal	Pass
2	2368.500	58.64	32.59	74.0	-15.36	Peak	7.00	150	Horizontal	Pass
2**	2368.500	46.53	32.59	54.0	-7.47	AV	7.00	150	Horizontal	Pass

8-DPSK HIGH FREQUENCY BAND



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	57.98	32.80	74.0	-16.02	Peak	6.00	150	Horizontal	Pass
1**	2483.500	46.43	32.80	54.0	-7.57	AV	6.00	150	Horizontal	Pass
2	2484.300	59.31	32.80	74.0	-14.69	Peak	6.00	150	Horizontal	Pass
2**	2484.300	46.36	32.80	54.0	-7.64	AV	6.00	150	Horizontal	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2170636-AR-2.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2170636-AW-2.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2170636-AI-2.PDF”.

--END OF REPORT--