

Yuyao Yuchang Electrical Appliance Co. ,Ltd

RF TEST REPORT

Report Type:

FCC Part 15C RF report

Model:

PJ1060, PJ1063, MWCP2

REPORT NUMBER:

210801369SHA-003

ISSUE DATE:

August 23, 2021

DOCUMENT CONTROL NUMBER:

TTRFFCCPART15C_V1 © 2018 Intertek



Applicant : Yuyao Yuchang Electrical Appliance Co., Ltd
NO.18 North Tongji Road, Simen Town, Yuyao, Zhejiang, China. 315470

Manufacturer : Yuyao Yuchang Electrical Appliance Co., Ltd
NO.18 North Tongji Road, Simen Town, Yuyao, Zhejiang, China. 315470

FCC ID : 2A2U8-PJ1063

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2019): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2014): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

PREPARED BY:

Project Engineer
Sky Yang

REVIEWED BY:

Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY.....	4
MEASUREMENT RESULT SUMMARY	5
1 GENERAL INFORMATION	6
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	6
1.2 TECHNICAL SPECIFICATION	6
1.3 DESCRIPTION OF TEST FACILITY	7
2 TEST SPECIFICATIONS.....	8
2.1 STANDARDS OR SPECIFICATION	8
2.2 MODE OF OPERATION DURING THE TEST.....	8
2.3 TEST SOFTWARE LIST	8
2.4 TEST PERIPHERALS LIST	8
2.5 TEST ENVIRONMENT CONDITION:.....	8
2.6 INSTRUMENT LIST	10
2.7 MEASUREMENT UNCERTAINTY	11
3 RADIATED EMISSIONS	12
3.1 LIMIT	12
3.2 MEASUREMENT PROCEDURE	12
3.3 TEST CONFIGURATION	13
3.4 TEST RESULTS OF RADIATED EMISSIONS	15
4 CONDUCTED EMISSIONS	19
4.1 LIMIT	19
4.2 TEST CONFIGURATION	19
4.3 MEASUREMENT PROCEDURE	20
4.4 TEST RESULTS OF CONDUCTED EMISSIONS.....	21

Revision History

Report No.	Version	Description	Issued Date
210801369SHA-003	Rev. 01	Initial issue of report	August 23, 2021

Measurement result summary

TEST ITEM	FCC REFERENCE	RESULT
Radiated emissions	15.209	Pass
Conducted emissions	15.207	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

TEST REPORT

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Wireless Charging Pad
Type/Model:	PJ1060, PJ1063, MWCP2
Description of EUT:	The product covered by this report is a wireless charging pad. All models are same except model PJ1060 have a different appearance. After evaluation, we choose PJ1063 for all tests.
Rating:	Input: 5V-3A/9V-2A/12V-1.5A Wireless output: Max 9W*2
Category of EUT:	Class B
EUT type:	☒ Table top ☐ Floor standing
Software Version:	/
Hardware Version:	/
Sample number:	0210812-19-004
Sample received date:	August 12, 2021
Date of test:	August 13, 2021~ August 20, 2021

1.2 Technical Specification

Frequency Range:	110kHz – 205kHz
------------------	-----------------

TEST REPORT

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road (North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

TEST REPORT

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2019)
ANSI C63.10 (2014)

2.2 Mode of operation during the test

Within this test report, EUT was tested under all available operation modes and tested under its rating voltage and frequency. Other voltage and frequency are specified if used.

There are three modes when using the product.

Mode 1: Using wireless charging pad 1 only;

Mode 2: Using wireless charging pad 2 only;

Mode 3: Using two wireless charging pad simultaneously;

We perform tests under three modes, and we list the worst result in the report.

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	SKET Auto EMC Test Software	Keleto	V3.0
Radiated emission	SKET Auto EMC Test Software	Keleto	V3.0

2.4 Test peripherals list

Item No.	Name	Band and Model	Description
1	Wireless load	KjB/ZS3012	100%/50%/0% power level
2	Wireless load	EESON	100%/50%/0% power level
3	Power Adapter	A138A-120150U-US3	Input:100-240VAC/50-60Hz Output: 5V-3A/9V-2A/12V-1.5A

2.5 Test environment condition:

Test items	Temperature	Humidity
Radiated emission	25°C	54% RH

TEST REPORT

Power line conducted emission	24°C	54% RH
-------------------------------	------	--------

TEST REPORT

2.6 Instrument list

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESCS 30	EC 2107	2022-07-14
☒	A.M.N.	R&S	ESH2-Z5	EC 3119	2021-12-07
☒	Shielding room	Zhongyu	-	EC 2838	2022-01-06
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESIB 26	EC 3045	2022-09-11
☒	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2022-05-29
☐	Pre-amplifier	R&S	AFS42-00101800-25-S-42	EC5262	2022-06-09
☐	Horn antenna	R&S	HF 906	EC 3049	2021-11-17
☐	Horn antenna	ETS	3117	EC 4792-1	2022-01-08
☒	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2022-03-06
☒	Semi-anechoic chamber	Albatross project	-	EC 3048	2022-09-14
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3783	2022-03-03
☒	Pressure meter	YM3	Shanghai Mengde	EC 4620	2022-09-09

TEST REPORT

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Frequency	Expanded Uncertainty ($k=2$)
Conducted emission at mains ports	9kHz ~ 150kHz	3.52 dB
	150kHz ~ 30MHz	3.19 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	4.90 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.02 dB
	6GHz ~ 18GHz	5.28 dB

TEST REPORT

3 Radiated emissions

Test result: Pass

3.1 Limit

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

3.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

TEST REPORT


- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. All modes of operation were evaluated and the worst-case emissions were reported

3.3 Test Configuration


For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:



For Radiated emission above 1GHz:





TEST REPORT

3.4 Test Results of Radiated Emissions

EUT was tested with empty load, half load and full load, the full load is the worst case and we listed the results in the report.


Below 30MHz:

Test Curve:



TEST REPORT

Z





Test Data:

Antenna Polarization	Frequency (MHz)	Limit (dBuV/m)	Level (dBuV/m)	Delta	Factor (dB/m)	Detector	Remark
X	0.138	104.8	74.8	30.0	20.2	PK	Fundamental
X	0.569	72.5	52.1	20.4	20.0	PK	Spurious
X	0.868	68.8	43.1	25.7	20.2	PK	Spurious
X	1.346	65.0	36.5	28.5	20.4	PK	Spurious
X	1.586	63.6	37.0	26.7	20.4	PK	Spurious
X	8.525	69.5	36.2	33.3	20.3	PK	Spurious
Y	0.138	104.7	58.2	46.4	20.2	PK	Fundamental
Y	0.569	72.5	57.1	15.4	20.0	PK	Spurious
Y	0.808	69.5	44.8	24.6	20.2	PK	Spurious
Y	1.646	63.3	37.9	25.4	20.4	PK	Spurious
Y	7.209	69.5	40.4	29.1	20.3	PK	Spurious
Y	13.430	69.5	31.1	38.4	20.4	PK	Spurious
Z	0.138	104.8	71.9	32.9	20.2	PK	Fundamental
Z	0.329	97.2	59.5	37.8	20.1	PK	Spurious
Z	0.569	72.5	45.8	26.7	20.0	PK	Spurious
Z	1.107	66.7	37.0	29.8	20.3	PK	Spurious
Z	1.646	63.3	34.4	28.9	20.4	PK	Spurious
Z	2.124	69.5	31.3	38.2	20.5	PK	Spurious

TEST REPORT

30MHz to 1000MHz:

Test Curve:



TEST REPORT

Test Data:

Frequency (MHz)	Limit (dBuV/m)	Level (dBuV/m)	Delta	Factor (dB/m)	Detector	Polar
81.196	40.0	28.9	11.1	14.3	QP	Hor
177.658	43.5	31.2	12.3	17.0	QP	Hor
288.747	46.0	39.9	6.1	20.6	QP	Hor
319.078	46.0	36.1	9.9	21.3	QP	Hor
367.485	46.0	33.5	12.5	22.5	QP	Hor
445.186	46.0	37.1	8.9	24.4	QP	Hor
44.009	40.0	34.0	6.0	17.9	QP	Ver
58.983	40.0	27.6	12.4	13.6	QP	Ver
66.548	40.0	29.9	10.1	13.5	QP	Ver
101.768	43.5	25.2	18.3	18.3	QP	Ver
120.194	43.5	24.6	18.9	19.5	QP	Ver
524.207	46.0	31.2	14.8	26.0	QP	Ver

- Remark: 1. Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Level = Original Receiver Reading + Factor
3. Delta = Limit - Level
4. If the PK Level is lower than AV limit, the AV test can be elided.

TEST REPORT

4 Conducted emissions


Test result: Pass

4.1 Limit

Frequency of Emission (MHz)	Conducted Emissions Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

4.2 Test Configuration



TEST REPORT**4.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.


The bandwidth of the test receiver is set at 9 kHz.

TEST REPORT


4.4 Test Results of Conducted Emissions

Test Curve:

L Line



N Line



TEST REPORT

Test Data:

Frequency	Limit (dBuV)	Level (dBuV)	Delta	Reading (dBuV)	Factor (dB)	Detector	Phase
622.500kHz	56.0	40.2	15.8	29.8	10.4	QP	L
874.500kHz	56.0	40.4	15.6	29.8	10.6	QP	L
1.127MHz	56.0	40.7	15.3	30.1	10.6	QP	L
1.379MHz	56.0	38.5	17.5	27.9	10.6	QP	L
1.626MHz	56.0	39.4	16.6	28.9	10.5	QP	L
2.850MHz	56.0	36.3	19.7	25.8	10.5	QP	L
618.000kHz	56.0	40.2	15.8	29.8	10.4	QP	N
870.000kHz	56.0	40.5	15.5	29.9	10.6	QP	N
1.122MHz	56.0	40.8	15.2	30.2	10.6	QP	N
1.374MHz	56.0	40.7	15.3	30.2	10.5	QP	N
1.608MHz	56.0	38.9	17.1	28.4	10.5	QP	N
2.126MHz	56.0	39.7	16.3	29.3	10.4	QP	N
874.500kHz	46.0	35.9	10.1	25.3	10.6	CAV	L
1.127MHz	46.0	35.7	10.3	25.1	10.6	CAV	L
1.374MHz	46.0	35.9	10.1	25.3	10.6	CAV	L
1.626MHz	46.0	35.4	10.6	24.9	10.5	CAV	L
2.373MHz	46.0	35.1	10.9	24.6	10.5	CAV	L
2.625MHz	46.0	35.5	10.5	25.0	10.5	CAV	L
874.500kHz	46.0	36.5	9.5	25.9	10.6	CAV	N
1.127MHz	46.0	36.6	9.4	26.0	10.6	CAV	N
1.626MHz	46.0	36.1	9.9	25.6	10.5	CAV	N
1.874MHz	46.0	35.8	10.2	25.3	10.5	CAV	N
2.625MHz	46.0	35.8	10.2	25.4	10.4	CAV	N
2.877MHz	46.0	35.6	10.4	25.2	10.4	CAV	N

- Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.*
- 2. Level = Reading + Factor*
- 3. Delta = Limit - Level*
- 4. If the PK Level is lower than AV limit, the AV test can be elided.*

***** END *****