

产品规格书

Product specification book



规格编号 Specification number	20220829005
生效日期 effective date	2022/8/29

客户名称 customer name	东莞市佳家通塑胶模具有限公司 Dongguan jiajiaotong plastic mould Co., Ltd
产品类型 product type	A11线圈/A11 coil
客户料号 Customer Material Numbe	

【☒新版发行, ☐版本修订】 【本规范含目录共 3页】 【RoHS Compliant Parts】

编制 authorized strength	审核 audit	批准 ratify

本承认书在客户收到30天内, 请务必签章返回, 逾期视为生产时按此承认书的标准执行。
This acknowledgement must be signed and returned to the customer within 30 days after receipt. If
overdue, it shall be deemed that the production shall be carried out according to the standards of
this acknowledgement.

【客户核准】 【 Customer approval 】

日期/date:

☐承认状态/Recognition state: ☐完全承认/make a clean breast of
☐条件承认/Conditional recognition ☐拒绝承认/disallow

批准 ratify	审核 audit	复检 recheck	检查 examine


说明/explain:

产品规格书
Product specification book

客户名称 customer name	东莞市佳家通塑胶模具有限公司 Dongguan jiajiatong plastic mould Co., Ltd	客户料号 Customer Material Numbe	
		规格编号 Specification number	20220829005
发行/修订记录 Issue/amendment record			
版本 versions	生效日期 effective date	变更内容/原因 Change content/reason	核准 examine and approve
01	2022/8/29	新规格发行 New specification issue	
编制 authorized strength		审核audit	批准 ratify

产品规格书

Product specification book

客户名称 customer name		东莞市佳家通塑胶模具有限公司 Dongguan jiajiatong plastic mould Co., Ltd		客户料号 Customer Material Numbe							
				规格编号 Specification number		20220829005		版本versions		1	
<div>◆、外形尺寸/boundary dimension</div> <div></div>								(单位/unit: mm)			
								A		43.4 ±0.3	
								B		42.0 ±0.5	
								C		20.0 ±0.5	
								D		5.3Ref ±0.5	
								E		10.0 Ref	
								F		3.0 ±1.0	
								G		1.5 ±0.5	
								H		120.0 ±1.0	
								I		±0.2(磁片厚度 /Thickness of 0.8 magnetic	
								(1)线径: 0.08*105P 丝包线 (1)wire diameter:0.08*105Psilk-covered wire			
								(2)绕线圈数:10TS (2)Number of coils wound:10TS			
(3)起尾线是否交叉: 是 (3)Whether the starting and ending lines cross- yes											
(4)线圈包8mm宽高温胶带 (4)Coil pack 8mm wide high temperature tape											
(5)线圈与磁片需粘贴居中 (5)The coil and magnetic disk must be centered											
(6)磁片背43双槽圆双面胶 (6)Magnetic sheet back 43 double slot round double-sided tape											
◆、电气特性/electrical specification:											
参数parameter		规格/specification		测试条件/test condition		测试仪器/test instrument					
L0		6.3 ±10% μH		100KHz/1V		■TH1816B					
Q		>60 min		100KHz/1V		■TH1816B					
DCR		<50 mΩ		@ 25℃		■CH-502BC					
◆、温度等级/temperature grade:											
操作温度 operating temperature		-40℃~ 125℃									
◆、材料清/bill of materials:											
序号 serial number		品名 Trade name		材料规格 material specification		供应商 supplier		备注 remark			
1		磁片 magnetic sheet		43.5*0.8*10T 开双槽 43.5*0.8*10T Double				PC95 猛锌 PC95 zinc			
2		铜线 copper wire		0.08*105				丙铜丝包线 Acrylic copper silk covered wire			
3		高温胶带 high temperature tape		8MM				环保胶带 Environmental adhesive tape			
4		锡/tin		107H				千岛环保锡 Thousand Island environmental protection tin			
5		胶/glue		黄胶/Yellow gum				环保胶水 Eco-friendly glue			
6		胶/glue		43双槽双面胶 43 Double-sided tape with two slots				环保 environmental protection			
编制 authorized strength				审核 audit				批准 ratify			