TEST REPORT

Applicant:	ShenZhen FLYSKY Technology Co.,Ltd
Address of Applicant:	16F, Huafeng Building, No. 6006 Shennan Road, Futian District, Shenzhen, Guangdong, China
Manufacturer:	ShenZhen FLYSKY Technology Co.,Ltd
Address of Manufacturer:	16F, Huafeng Building, No. 6006 Shennan Road, Futian District, Shenzhen, Guangdong, China
Factory:	Dongguan Flysky RC Model technology Co.,Ltd
Address of Factory:	West building 3, HuangjinyuanInd Park, Qiaoli North Gate, Changping Town, Dongguan, China

Equipment Under Test (EUT)

Product Name:	3-CHANNEL RECEVIER
Model No.:	FS-R3ABL-ESC-BS
Trade Mark:	FLYSKY
FCC ID:	2A2UNR3ABL00
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	November 04, 2024
Date of Test:	November 05-19, 2024
Date of report issued:	November 19, 2024
Test Result :	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	*November 19, 2024*	*Original*

Prepared By: ***Date:*** *November 19, 2024*

Project Engineer

Check By: ***Date:*** *November 19, 2024*

Reviewer

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

4.1 MEASUREMENT UNCERTAINTY 4

5 GENERAL INFORMATION 5

5.1 GENERAL DESCRIPTION OF EUT 5
5.2 TEST MODE 7
5.3 TEST FACILITY 7
5.4 TEST LOCATION 7
5.5 DESCRIPTION OF SUPPORT UNITS 7
5.6 DEVIATION FROM STANDARDS 7
5.7 ABNORMALITIES FROM STANDARD CONDITIONS 7
5.8 ADDITIONAL INSTRUCTIONS 7

6 TEST INSTRUMENTS LIST 8

7 TEST RESULTS AND MEASUREMENT DATA 10

7.1 ANTENNA REQUIREMENT 10
7.2 CONDUCTED EMISSIONS 11
7.3 CONDUCTED PEAK OUTPUT POWER 14
7.4 20DB EMISSION BANDWIDTH 15
7.5 CARRIER FREQUENCIES SEPARATION 16
7.6 HOPPING CHANNEL NUMBER 17
7.7 DWELL TIME 18
7.8 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS 19
7.8.1 Conducted Emission Method 19
7.8.2 Radiated Emission Method 20

8 TEST SETUP PHOTO 38

9 EUT CONSTRUCTIONAL DETAILS 38

4 Test Summary

Test Item	Section	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)(iii)	Pass
Dwell Time	15.247 (a)(1)(iii)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.10:2013 .

4.1 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25\times 10^{-8}$
2	Duty cycle	±0.37%
3	Occupied Bandwidth	±3%
4	RF conducted power	±0.75dB
5	RF power density	±3dB
6	Conducted Spurious emissions	±2.58dB
7	AC Power Line Conducted Emission	±3.44dB (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	±3.1dB (9kHz-30MHz)
		±3.8039dB (30MHz-200MHz)
		±3.9679dB (200MHz-1GHz)
		±4.29dB (1GHz-18GHz)
		±3.30dB (18GHz-40GHz)
9	Temperature test	±1°C
10	Humidity test	±3%
11	Time	±3%

5 General Information

5.1 General Description of EUT

Product Name:	3-CHANNEL RECEVIER
Model No.:	FS-R3ABL-ESC-BS
Serial No.:	RD1001656
Test sample(s) ID:	GTS2024110038-1
Sample(s) Status	Engineer sample
Operation Frequency:	2408MHz~2475MHz
Channel numbers:	135
Modulation method:	FHSS
Modulation technology:	GFSK
Antenna Type:	Integral antenna
Antenna gain:	-1.11dBi(declare by applicant)
Power supply:	DC 6-13V(2-3S Lithium battery)

Remark:
1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.
3. The system works in the frequency range of 2408MHz to 2475MHz. This band has been divided to 135 independent channels. Each radio system uses 16 different channels; the minimum channel separation is ≥4MHz. By using various switch-on times, hopping scheme and channel frequencies, the system can guarantee a jamming free radio transmission. Pre-testing all radio systems, this radio system recorded in the report is the worst mode.The channel list is below.

The test frequencies are below:

Channel	Frequency
The lowest channel	2408MHz
The middle channel	2440MHz
The Highest channel	2475MHz

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2408	36	2425.5	71	2443	106	2460.5
2	2408.5	37	2426	72	2443.5	107	2461
3	2409	38	2426.5	73	2444	108	2461.5
4	2409.5	39	2427	74	2444.5	109	2462
5	2410	40	2427.5	75	2445	110	2462.5
6	2410.5	41	2428	76	2445.5	111	2463
7	2411	42	2428.5	77	2446	112	2463.5
8	2411.5	43	2429	78	2446.5	113	2464
9	2412	44	2429.5	79	2447	114	2464.5
10	2412.5	45	2430	80	2447.5	115	2465
11	2413	46	2430.5	81	2448	116	2465.5
12	2413.5	47	2431	82	2448.5	117	2466
13	2414	48	2431.5	83	2449	118	2466.5
14	2414.5	49	2432	84	2449.5	119	2467
15	2415	50	2432.5	85	2450	120	2467.5
16	2415.5	51	2433	86	2450.5	121	2468
17	2416	52	2433.5	87	2451	122	2468.5
18	2416.5	53	2434	88	2451.5	123	2469
19	2417	54	2434.5	89	2452	124	2469.5
20	2417.5	55	2435	90	2452.5	125	2470
21	2418	56	2435.5	91	2453	126	2470.5
22	2418.5	57	2436	92	2453.5	127	2471
23	2419	58	2436.5	93	2454	128	2471.5
24	2419.5	59	2437	94	2454.5	129	2472
25	2420	60	2437.5	95	2455	130	2472.5
26	2420.5	61	2438	96	2455.5	131	2473
27	2421	62	2438.5	97	2456	132	2473.5
28	2421.5	63	2439	98	2456.5	133	2474
29	2422	64	2439.5	99	2457	134	2474.5
30	2422.5	65	2440	100	2457.5	135	2475
31	2423	66	2440.5	101	2458		
32	2423.5	67	2441	102	2458.5		
33	2424	68	2441.5	103	2459		
34	2424.5	69	2442	104	2459.5		
35	2425	70	2442.5	105	2460		

5.2 Test mode

Transmitting mode	Keep the EUT in transmitting mode.

5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

● **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing.

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.4 Test Location

All other tests were performed at:

Global United Technology Services Co., Ltd.
Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number
ShenZhen FLYSKY Technology Co.,Ltd	Remote control	FS-MG6-BS	N/A
GW	DC POWER SUPPLY	GPR-6030D	EF924756

5.6 Deviation from Standards

None.

5.7 Abnormalities from Standard Conditions

None.

5.8 Additional Instructions

Software (Used for test) from client

Built-in by manufacturer, power set default.

6 Test Instruments list

Radiated Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Jun. 22, 2024	Jun. 21, 2027
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 11, 2024	Apr. 10, 2025
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Mar. 19, 2023	Mar. 18, 2025
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 17, 2023	Apr. 16, 2025
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Apr. 11, 2024	Apr. 10, 2025
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.12, 2024	Nov.11, 2025
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2024	Apr. 10, 2025
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2024	Apr. 10, 2025
10	Horn Antenna (15GH-40GHz)	SCHWARZBECK	01296	GTS691	Mar. 07, 2024	Mar. 06, 2025
11	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 12, 2024	Mar. 11, 2025
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2024	Apr. 10, 2025
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 07, 2024	Nov. 06, 2025
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2024	Apr. 10, 2025
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 18, 2024	Apr. 17, 2025
16	RE cable 1	GTS	N/A	GTS675	Jul. 02, 2024	Jul. 01, 2025
17	RE cable 2	GTS	N/A	GTS676	Jul. 02, 2024	Jul. 01, 2025
18	RE cable 3	GTS	N/A	GTS677	Jul. 02, 2024	Jul. 01, 2025
19	RE cable 4	GTS	N/A	GTS678	Jul. 02, 2024	Jul. 01, 2025
20	RE cable 5	GTS	N/A	GTS679	Jul. 02, 2024	Jul. 01, 2025
21	RE cable 6	GTS	N/A	GTS680	Jul. 02, 2024	Jul. 01, 2025
22	RE cable 7	GTS	N/A	GTS681	Jul. 05, 2024	Jul. 04, 2025
23	RE cable 8	GTS	N/A	GTS682	Jul. 05, 2024	Jul. 04, 2025
24	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

Conducted Emission						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	Jul. 12, 2022	Jul. 11, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 11, 2024	Apr. 10, 2025
3	LISN	ROHDE & SCHWARZ	ENV216	GTS226	Apr. 11, 2024	Apr. 10, 2025
4	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
5	Thermo meter	JINCHUANG	GSP-8A	GTS642	Apr. 18, 2024	Apr. 17, 2025
6	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	Apr. 11, 2024	Apr. 10, 2025
7	ISN	SCHWARZBECK	NTFM 8158	GTS565	Apr. 11, 2024	Apr. 10, 2025
8	High voltage probe	SCHWARZBECK	TK9420	GTS537	Apr. 11, 2024	Apr. 10, 2025
9	Antenna end assembly	Weinschel	1870A	GTS560	Apr. 11, 2024	Apr. 10, 2025
10	EMI Test Software	AUDIX	E3-6.100622	GTS726	N/A	N/A

RF Conducted Test:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 13, 2024	Apr. 12, 2025
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 13, 2024	Apr. 12, 2025
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 13, 2024	Apr. 12, 2025
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 13, 2024	Apr. 12, 2025
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 13, 2024	Apr. 12, 2025
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 13, 2024	Apr. 12, 2025
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 13, 2024	Apr. 12, 2025
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 13, 2024	Apr. 12, 2025
9	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 18, 2024	Apr. 17, 2025
10	EXA Signal Analyzer	Keysight	N9010B	MY60241168	Nov. 02, 2024	Nov. 01, 2025

General used equipment:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Barometer	KUMAO	SF132	GTS647	Apr. 18, 2024	Apr. 17, 2025

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(c) (1)(i) requirement:** (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is integral antenna, reference to the appendix II for details.	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test setup:



Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.

Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data:

Pre-scan all test modes, found worst case at 2408MHz, and so only show the test result of it.

Line:



Freq	Reading level	LISN/ISN factor	Cable loss	Level	Limit level	Over limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.16	22.89	9.55	0.01	32.45	65.65	-33.20	QP
0.16	0.62	9.55	0.01	10.18	55.65	-45.47	Average
0.32	19.82	9.49	0.01	29.32	59.71	-30.39	QP
0.32	7.73	9.49	0.01	17.23	49.71	-32.48	Average
0.89	12.70	9.49	0.03	22.22	56.00	-33.78	QP
0.89	-2.70	9.49	0.03	6.82	46.00	-39.18	Average
1.82	-0.60	9.59	0.04	9.03	56.00	-46.97	QP
1.82	-4.83	9.59	0.04	4.80	46.00	-41.20	Average
7.61	1.56	9.31	0.09	10.96	60.00	-49.04	QP
7.61	-4.73	9.31	0.09	4.67	50.00	-45.33	Average
22.06	11.88	10.00	0.19	22.07	60.00	-37.93	QP
22.06	5.56	10.00	0.19	15.75	50.00	-34.25	Average

Neutral:



Freq	Reading level	LISN/ISN factor	Cable loss	Level	Limit level	Over limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.20	27.82	9.56	0.01	37.39	63.45	-26.06	QP
0.20	4.97	9.56	0.01	14.54	53.45	-38.91	Average
0.35	26.69	9.57	0.01	36.27	58.96	-22.69	QP
0.35	3.05	9.57	0.01	12.63	48.96	-36.33	Average
0.50	26.27	9.57	0.01	35.85	56.01	-20.16	QP
0.50	4.03	9.57	0.01	13.61	46.01	-32.40	Average
0.84	15.18	9.55	0.03	24.76	56.00	-31.24	QP
0.84	6.58	9.55	0.03	16.16	46.00	-29.84	Average
2.11	8.24	9.55	0.05	17.84	56.00	-38.16	QP
2.11	-4.72	9.55	0.05	4.88	46.00	-41.12	Average
6.56	1.42	9.54	0.08	11.04	60.00	-48.96	QP
6.56	-5.29	9.54	0.08	4.33	50.00	-45.67	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss

7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247(a)(1)
Test Method:	ANSI C63.10:2013
Limit:	20.97dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.4 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=150KHz, VBW=470KHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=120KHz, VBW=360KHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=470KHz, VBW=470KHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.8 Spurious Emission in Non-restricted & restricted Bands

7.8.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for 2.4G.

7.8.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average
Note: For Duty cycle ≥ 98%, average detector set as above For Duty cycle < 98%, average detector set as below: VBW ≥ 1 / T				

Limit: (Spurious Emissions)

Frequency	Limit (uV/m)	Value	Measurement Distance
0.009MHz-0.490MHz	2400/F(KHz)	QP	300m
0.490MHz-1.705MHz	24000/F(KHz)	QP	30m
1.705MHz-30MHz	30	QP	30m
30MHz-88MHz	100	QP	3m
88MHz-216MHz	150	QP	
216MHz-960MHz	200	QP	
960MHz-1GHz	500	QP	
Above 1GHz	500	Average	
	5000	Peak	

Test setup:

Below 30MHz



Below 1GHz



Above 1GHz



Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8 meters for below 1GHz and 1.5meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.2 for details

Temp. / Hum.	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar

Test results:	Pass

Remark:

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Measurement data:

■ **Below 30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

30MHz ~ 1GHz

Test channel:	Lowest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
157.559	30.42	14.74	2.53	32.44	15.25	43.50	-28.25	QP
273.234	32.50	11.53	3.29	32.33	14.99	46.00	-31.01	QP
408.946	33.30	14.98	3.91	32.25	19.94	46.00	-26.06	QP
588.905	27.46	18.68	4.58	31.87	18.85	46.00	-27.15	QP
782.345	24.05	21.75	5.40	31.16	20.04	46.00	-25.96	QP
972.337	24.13	23.80	5.94	31.10	22.77	54.00	-31.23	QP

Test channel:	Lowest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
57.999	33.85	12.30	1.46	32.33	15.28	40.00	-24.72	QP
90.537	36.50	8.65	1.78	32.46	14.47	43.50	-29.03	QP
167.824	38.36	13.62	2.62	32.43	22.17	43.50	-21.33	QP
317.701	30.35	12.81	3.51	32.29	14.38	46.00	-31.62	QP
645.120	26.09	19.80	4.84	31.67	19.06	46.00	-26.94	QP
968.934	25.39	23.78	5.93	31.10	24.00	54.00	-30.00	QP

Test channel:	Middle	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
157.559	28.22	14.74	2.53	32.44	13.05	43.50	-30.45	QP
276.124	30.92	11.65	3.30	32.32	13.55	46.00	-32.45	QP
410.383	32.76	15.01	3.92	32.24	19.45	46.00	-26.55	QP
541.373	24.71	17.46	4.38	32.05	14.50	46.00	-31.50	QP
691.987	25.48	20.44	5.05	31.50	19.47	46.00	-26.53	QP
972.337	24.10	23.80	5.94	31.10	22.74	54.00	-31.26	QP

Test channel:	Middle	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
43.966	34.30	13.20	1.32	32.30	16.52	40.00	-23.48	QP
69.114	36.63	10.89	1.64	32.38	16.78	40.00	-23.22	QP
167.824	36.96	13.62	2.62	32.43	20.77	43.50	-22.73	QP
407.515	29.39	14.95	3.91	32.25	16.00	46.00	-30.00	QP
670.489	25.77	20.20	4.95	31.57	19.35	46.00	-26.65	QP
962.162	25.14	23.70	5.91	31.10	23.65	54.00	-30.35	QP

Test channel:	Highest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
157.559	27.81	14.74	2.53	32.44	12.64	43.50	-30.86	QP
275.157	32.58	11.61	3.30	32.32	15.17	46.00	-30.83	QP
406.088	33.77	14.92	3.90	32.25	20.34	46.00	-25.66	QP
566.622	25.76	18.13	4.49	31.96	16.42	46.00	-29.58	QP
684.745	27.06	20.30	5.02	31.52	20.86	46.00	-25.14	QP
903.309	24.53	23.10	5.74	31.10	22.27	46.00	-23.73	QP

Test channel:	Highest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
34.396	37.11	12.92	1.18	32.30	18.91	40.00	-21.09	QP
57.392	37.46	12.18	1.46	32.33	18.77	40.00	-21.23	QP
167.824	37.14	13.62	2.62	32.43	20.95	43.50	-22.55	QP
300.367	30.18	12.41	3.42	32.30	13.71	46.00	-32.29	QP
578.670	25.55	18.37	4.54	31.91	16.55	46.00	-29.45	QP
827.493	25.36	22.35	5.54	31.10	22.15	46.00	-23.85	QP

- **Above 1GHz**
- **Unwanted Emissions in Non-restricted Frequency Bands**

Test channel:	Lowest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4816.000	47.86	32.03	6.01	38.54	47.36	54.00	-6.64	Average
4816.000	59.99	32.03	6.01	38.54	59.49	74.00	-14.51	Peak
7224.000	33.22	36.25	7.94	39.16	38.25	54.00	-15.75	Average
7224.000	43.45	36.25	7.94	39.16	48.48	74.00	-25.52	Peak
9632.000	30.98	38.20	14.32	40.23	43.27	54.00	-10.73	Average
9632.000	45.73	38.20	14.32	40.23	58.02	74.00	-15.98	Peak

Test channel:	Lowest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4816.000	42.87	32.03	6.01	38.54	42.37	54.00	-11.63	Average
4816.000	55.01	32.03	6.01	38.54	54.51	74.00	-19.49	Peak
7224.000	34.41	36.25	7.94	39.16	39.44	54.00	-14.56	Average
7224.000	45.22	36.25	7.94	39.16	50.25	74.00	-23.75	Peak
9632.000	30.73	38.20	14.32	40.23	43.02	54.00	-10.98	Average
9632.000	44.91	38.20	14.32	40.23	57.20	74.00	-16.80	Peak

Test channel:	Middle	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	48.42	32.10	6.03	38.52	48.03	54.00	-5.97	Average
4880.000	59.23	32.10	6.03	38.52	58.84	74.00	-15.16	Peak
7320.000	32.05	36.30	8.04	39.22	37.17	54.00	-16.83	Average
7320.000	44.12	36.30	8.04	39.22	49.24	74.00	-24.76	Peak
9760.000	34.69	38.20	11.35	40.25	43.99	54.00	-10.01	Average
9760.000	45.50	38.20	11.35	40.25	54.80	74.00	-19.20	Peak

Test channel:	Middle	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	44.75	32.10	6.03	38.52	44.36	54.00	-9.64	Average
4880.000	54.96	32.10	6.03	38.52	54.57	74.00	-19.43	Peak
7320.000	33.81	36.30	8.04	39.22	38.93	54.00	-15.07	Average
7320.000	43.94	36.30	8.04	39.22	49.06	74.00	-24.94	Peak
9760.000	35.58	38.20	11.35	40.25	44.88	54.00	-9.12	Average
9760.000	45.78	38.20	11.35	40.25	55.08	74.00	-18.92	Peak

Test channel:	Highest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4950.000	48.08	32.20	6.05	38.51	47.82	54.00	-6.18	Average
4950.000	60.70	32.20	6.05	38.51	60.44	74.00	-13.56	Peak
7425.000	33.39	36.30	8.14	39.30	38.53	54.00	-15.47	Average
7425.000	44.59	36.30	8.14	39.30	49.73	74.00	-24.27	Peak
9900.000	35.47	38.20	10.70	40.28	44.09	54.00	-9.91	Average
9900.000	44.39	38.20	10.70	40.28	53.01	74.00	-20.99	Peak

Test channel:	Highest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4950.000	45.42	32.20	6.05	38.51	45.16	54.00	-8.84	Average
4950.000	56.37	32.20	6.05	38.51	56.11	74.00	-17.89	Peak
7425.000	34.44	36.30	8.14	39.30	39.58	54.00	-14.42	Average
7425.000	46.63	36.30	8.14	39.30	51.77	74.00	-22.23	Peak
9900.000	35.85	38.20	10.70	40.28	44.47	54.00	-9.53	Average
9900.000	44.93	38.20	10.70	40.28	53.55	74.00	-20.45	Peak

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
3. *For above 18GHz, no emission found.*

■ **Unwanted Emissions in Restricted Frequency Bands**

Test channel:	Lowest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	33.65	27.00	4.13	39.14	25.64	54.00	-28.36	Average
2310.000	49.75	27.00	4.13	39.14	41.74	74.00	-32.26	Peak
2387.900	44.44	27.08	4.17	39.33	36.36	54.00	-17.64	Average
2387.900	72.54	27.08	4.17	39.33	64.46	74.00	-9.54	Peak
2390.000	37.30	27.08	4.17	39.34	29.21	54.00	-24.79	Average
2390.000	53.16	27.08	4.17	39.34	45.07	74.00	-28.93	Peak

Test channel:	Lowest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	32.59	27.00	4.13	39.14	24.58	54.00	-29.42	Average
2310.000	48.46	27.00	4.13	39.14	40.45	74.00	-33.55	Peak
2387.800	44.28	27.08	4.17	39.33	36.20	54.00	-17.80	Average
2387.800	63.44	27.08	4.17	39.33	55.36	74.00	-18.64	Peak
2390.000	36.28	27.08	4.17	39.34	28.19	54.00	-25.81	Average
2390.000	48.46	27.08	4.17	39.34	40.37	74.00	-33.63	Peak

Test channel:	Highest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	48.24	27.27	4.08	39.56	40.03	54.00	-13.97	Average
2483.500	70.01	27.27	4.08	39.56	61.80	74.00	-12.20	Peak
2486.878	51.46	27.27	4.08	39.57	43.24	54.00	-10.76	Average
2486.878	70.40	27.27	4.08	39.57	62.18	74.00	-11.82	Peak
2500.000	33.19	27.30	4.06	39.60	24.95	54.00	-29.05	Average
2500.000	54.06	27.30	4.06	39.60	45.82	74.00	-28.18	Peak

Test channel:	Highest	Polarziation:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	46.15	27.27	4.08	39.56	37.94	54.00	-16.06	Average
2483.500	63.37	27.27	4.08	39.56	55.16	74.00	-18.84	Peak
2486.932	47.16	27.27	4.08	39.57	38.94	54.00	-15.06	Average
2486.932	64.04	27.27	4.08	39.57	55.82	74.00	-18.18	Peak
2500.000	32.91	27.30	4.06	39.60	24.67	54.00	-29.33	Average
2500.000	48.83	27.30	4.06	39.60	40.59	74.00	-33.41	Peak

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

---End---