



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Shanghai Xiangcheng Communication Technology Co.,Ltd

Address: 6th Floor, Building 10, No.3000 Longdong Avenue, Pudong New District, Shanghai, China

FCC ID: 2A2UU-MF-T1522

Product Name: Intelligent Mobile Data Capture Terminal

Standard(s): 47 CFR Part 2
47 CFR Part 22, Subpart H
47 CFR Part 24, Subpart E
47 CFR Part 27
47 CFR Part 90
ANSI C63.26-2015

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230953899-00G

Date Of Issue: 2023/12/4

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	7
1.2.1 EUT Operation Condition:.....	7
1.2.2 Support Equipment List and Details	9
1.2.3 Support Cable List and Details	9
1.2.4 Block Diagram of Test Setup.....	10
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 Applicable Standard For Part 22 Subpart H:.....	12
3.1.1 RF Output Power	12
3.1.2 Spurious Emissions	12
3.1.3 Frequency stability.....	12
3.2 Applicable Standard For Part 24 Subpart E:	14
3.2.1 RF Output Power	14
3.2.2 Spurious Emissions	14
3.2.3 Frequency stability	14
3.3 Applicable Standard For Part 27:.....	15
3.3.1 RF Output Power	15
3.3.2 Spurious Emissions	15
3.3.3 Frequency stability	17
3.4 Applicable Standard For Part 90:.....	18
3.5 Test Method:	19
3.5.1 RF Output Power	19
Test Setup Block:.....	19
3.5.2 Occupied Bandwidth.....	20
Test Setup Block:.....	20
3.5.3 Spurious emissions at antenna terminals.....	21
Test Setup Block:.....	21
3.5.4 Out of band emission	22
Test Setup Block:.....	22
3.5.5 Frequency stability.....	23
Test Setup Block:.....	23
3.5.6 Field strength of spurious radiation.....	24
4. Test DATA AND RESULTS	26
4.1 ANTENNA PORT TEST DATA AND RESULTS FOR GSM 850 BAND:.....	26
4.2 ANTENNA PORT TEST DATA AND RESULTS FOR GSM 1900 BAND:.....	32
4.3 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 2:	38
4.4 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 4:	45

4.5 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 5:	52
4.6 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 2:	59
4.7 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 4:	80
4.8 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 5:	101
4.9 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 7:	117
4.10 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 12:	133
4.11 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 17:	149
4.12 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 25:	159
4.13 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 26:	180
4.14 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 38:	216
4.15 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 41:	232
4.16 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 66:	250
4.17 RADIATED SPURIOUS EMISSIONS:	271
5. EUT PHOTOGRAPHS	288
6. TEST SETUP PHOTOGRAPHS	289

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230953899-00G	Original Report	2023/12/4

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

General:

EUT Name:	Intelligent Mobile Data Capture Terminal
EUT Model:	T15
Multiple Models:	T1522, Ranger2
Operation Bands and modes:	GSM/GPRS/EDGE: 850/1900 WCDMA: Band 2/4/5 LTE: Band 2/4/5/7/12/17/25/26/38/41/66
Modulation Type:	GMSK, 8PSK, BPSK, QPSK, 16QAM
Rated Input Voltage:	DC 5V from adapter or DC 3.85V from battery
Serial Number:	Radiation Spurious Emissions: 2B7S-1 RF conducted: 2B7S-2
EUT Received Date:	2023/9/14
EUT Received Status:	Good
Note: The Multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer.	

Operation Voltage(V_{DC}) ▲:

Lowest:	3.4	Normal:	3.85	Highest:	4.4
---------	-----	---------	------	----------	-----

Antenna Information ▲:

Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain (G_T) (dBi)	L_c (dB)
PCB	GSM850	824-849	-0.33	0.1
	PCS1900	1850-1910	0.74	0.2
	WCDMA B5	824-849	-0.33	0.1
	LTE B5	824-849	-0.33	0.1
	WCDMA B2	1850-1910	0.74	0.2
	WCDMA B4	1710-1755	0.69	0.2
	LTE B2	1850-1910	0.74	0.2
	LTE B4	1710-1755	0.69	0.2
	LTE B7	2500-2570	0.63	0.4
	LTE B12	699-716	-1.82	0.1
	LTE B17	704-716	-1.82	0.1
	LTE B25	1850-1915	0.74	0.2
	LTE B26	814-849	-0.33	0.1
	LTE B38	2570-2620	0.66	0.4
	LTE B41	2535-2655	0.66	0.4
	LTE B66	1710-1785	0.69	0.2
Note: L_c = Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.				

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in each operation mode.
Equipment Modifications:	No
EUT Exercise Software:	No
The maximum power was configured per 3GPP Standard for each operation modes as below setting: GSM/GPRS/EGPRS Function: Menu select > GSM Mobile Station > GSM 850/1900 Press Connection control to choose the different menus Press RESET > choose all the reset all settings Connection Press Signal Off to turn off the signal and change settings Network Support > GSM + GPRS or GSM + EGSM Main Service > Packet Data Service selection > Test Mode A – Auto Slot Config. off MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting > Slot configuration > Uplink/Gamma > 33 dBm for GPRS 850 > 30 dBm for GPRS 1900 > 27 dBm for EGPRS 850 > 26 dBm for EGPRS 1900 BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel Frequency Offset > + 0 Hz Mode > BCCH and TCH BCCH Level > -85 dBm (May need to adjust if link is not stable) BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel] Channel Type > Off P0 > 4 dB Slot Config > Unchanged (if already set under MS signal) TCH > choose desired test channel Hopping > Off Main Timeslot > 3 Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS) Bit Stream > 2E9-1 PSR Bit Stream AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input Connection Press Signal on to turn on the signal and change settings	

WCDMA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2		4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30 15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.	2.0	3.0	1.0
	MPR(dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs}=\beta_{hs}/\beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	A Index	20	12	1	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate k_p	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18		E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27

LTE (FDD):

The following tests were conducted according to the test requirements in 3GPP TS36.101

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Fangxin	Adapter	FX2U-050200U	AD220930001
Unknown	Antenna	Unknown	Unknown

1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	1.2	EUT	Adapter

1.2.4 Block Diagram of Test Setup

Radiation Test:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
RF Frequency	±0.082×10 ⁻⁶

2. SUMMARY OF TEST RESULTS

Rules	Description of Test	Result
FCC§2.1046; § 22.913;§ 24.232; §27.50; §90.635	RF Output Power	Compliant
FCC§ 2.1047	Modulation Characteristics	Not Applicable
FCC§ 2.1049; § 22.905, §22.917; § 24.238; §27.53; §90.209	Occupied Bandwidth	Compliant
FCC§ 2.1051;§ 22.917; § 24.238; §27.53;§90.691	Spurious Emissions at Antenna Terminal	Compliant
FCC§ 22.917; § 24.238; §27.53; §90.691	Out of band emission, Band Edge	Compliant
FCC§ 2.1055;§ 22.355; § 24.235; §27.54;§90.213	Frequency stability vs. temperature Frequency stability vs. voltage	Compliant
FCC§ 2.1053§ 22.917; § 24.238; §27.53; §90.691	Field Strength of Spurious Radiation	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 Applicable Standard For Part 22 Subpart H:

3.1.1 RF Output Power

FCC §22.913

(a)(5) The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7watts.

(d) *Power measurement.* Measurement of the ERP of Cellular base transmitters and repeaters must be made using an average power measurement technique. The peak-toaverage ratio (PAR) of the transmission must not exceed 13 dB. Power measurements for base transmitters and repeaters must be made in accordance with either of the following:

- (1) A Commission-approved average power technique (*see* FCC Laboratory's Knowledge Database); or
- (2) For purposes of this section, peak transmit power must be measured over an interval of continuous transmission using instrumentation calibrated in terms of an rmsequivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, *etc.*, so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

3.1.2 Spurious Emissions

FCC §22.917

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a reference bandwidth as follows:

- (1) In the spectrum below 1 GHz, instrumentation should employ a reference bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy, provided that the measured power is integrated over the full required reference bandwidth (i.e., 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.
- (2) In the spectrum above 1 GHz, instrumentation should employ a reference bandwidth of 1 MHz

3.1.3 Frequency stability

FCC §22.355

Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section.

Table C-1 - Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency range (MHz)	Base, fixed (ppm)	Mobile >3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20	20	50
50 to 450	5	5	50
450 to 512	2.5	5	5
821 to 896	1.5	2.5	2.5
928 to 929	5	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10	n/a	n/a

3.2 Applicable Standard For Part 24 Subpart E:

3.2.1 RF Output Power

FCC §24.232

(c) Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

(d) Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of § 24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.2.2 Spurious Emissions

FCC §24.238

The rules in this section govern the spectral characteristics of emissions in the Broadband Personal Communications Service.

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(c) Alternative out of band emission limit. Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(d) Interference caused by out of band emissions. If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

3.2.3 Frequency stability

FCC §24.235

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.3 Applicable Standard For Part 27:

3.3.1 RF Output Power

FCC §27.50

(a)(3) *Mobile and portable stations.*

(i) For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

(ii) Mobile and portable stations are not permitted to transmit in the 2315-2320 MHz and 2345-2350 MHz bands.

(iii) *Automatic transmit power control.* Mobile and portable stations transmitting in the 2305-2315 MHz band or in the 2350-2360 MHz band must employ automatic transmit power control when operating so the stations operate with the minimum power necessary for successful communications.

(iv) *Prohibition on external vehicle-mounted antennas.* The use of external vehicle-mounted antennas for mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band is prohibited.

(b)(10) Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

(c)(10) Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

(d)(4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(h) The following power limits shall apply in the BRS and EBS:

(2) Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

3.3.2 Spurious Emissions

FCC §27.53

(a) For operations in the 2305-2320 MHz band and the 2345-2360 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power P (with averaging performed only during periods of transmission) within the licensed band(s) of operation, in watts, by the following amounts:

(4) For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

(i) By a factor of not less than: $43 + 10 \log (P)$ dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log (P)$ dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than $61 + 10 \log (P)$ dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than $67 + 10 \log (P)$ dB on all frequencies between 2328 and 2337 MHz;

(ii) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2300 and 2305 MHz, $55 + 10 \log (P)$ dB on all frequencies between 2296 and 2300 MHz, $61 + 10 \log (P)$ dB on all frequencies between 2292 and 2296 MHz, $67 + 10 \log (P)$ dB on all frequencies between 2288 and 2292 MHz, and $70 + 10 \log (P)$ dB below 2288 MHz;

(iii) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2360 and 2365 MHz, and not less than $70 + 10 \log (P)$ dB above 2365 MHz.

(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;

(3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to – 70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and – 80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

(h) AWS emission limits

(1) **General protection levels.** Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.

(m)(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.3.3 Frequency stability

FCC §27.54

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

3.4 Applicable Standard For Part 90:

3.4.1 RF Output Power

FCC §90.635

(b) The maximum output power of the transmitter for mobile stations is 100 watts (20 dBw).

3.4.2 Spurious Emissions

FCC §90.691

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

3.4.3 Frequency stability

FCC §90.213

809-824 MHz band, 2.5ppm for 2W or less output power.

3.5 Test Method:**3.5.1 RF Output Power**

According to CFR Part 2.1046, ANSI C63.26-2015 Section 5.2.5.5:

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$


where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively
(expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

Test Setup Block:

Note: The Insertion loss of the RF cable and coaxial Attenuator was offset into the Reading of CMW500.

3.5.2 Occupied Bandwidth


According to CFR Part 2.1049, ANSI C63.26-2015 Section 5.4.4

The OBW is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

The following procedure shall be used for measuring (99%) power bandwidth:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (typically a span of $1.5 \times \text{OBW}$ is sufficient).
- b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times \text{RBW}$.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3.
NOTE—Step a), step b), and step c) may require iteration to adjust within the specified tolerances.
- d) Set the detection mode to peak, and the trace mode to max-hold.
- e) If the instrument does not have a 99% OBW function, recover the trace data points and sum directly in linear power terms. Place the recovered amplitude data points, beginning at the lowest frequency, in a running sum until 0.5% of the total is reached. Record that frequency as the lower OBW frequency. Repeat the process until 99.5% of the total is reached and record that frequency as the upper OBW frequency. The 99% power OBW can be determined by computing the difference these two frequencies.
- f) The OBW shall be reported and plot(s) of the measuring instrument display shall be provided with the test report. The frequency and amplitude axis and scale shall be clearly labeled. Tabular data can be reported in addition to the plot(s).

Test Setup Block:




3.5.3 Spurious emissions at antenna terminals

According to ANSI C63.26-2015 Section 5.7.4:

the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz),⁸ effectively depicting the unwanted emission limit in terms of a power spectral density. In those cases where no reference bandwidth is explicitly specified, the values in the preceding sentence should be used.

Test Setup Block:




3.5.4 Out of band emission

According to ANSI C63.26-2015 Section 5.7.3:

Typically, a measurement (resolution) bandwidth smaller than the reference bandwidth is allowed for measurements within a specified frequency range at the edge of the authorized frequency block/band (e.g., within the first Y MHz outside of the authorized frequency band/block, where the value of Y is specified in the relevant rule part). Some FCC out-of-band emission rules permit the use of a narrower RBW (typically limited to a minimum RBW of 1 % of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth. Beyond the specified frequency range in which this relaxation of the uniform reference bandwidth is permitted, it typically is also acceptable to use a narrower RBW (again limited to a minimum of 1 % of OBW) to increase accuracy, but the measurement result must subsequently be integrated over the full reference bandwidth.

Test Setup Block:



3.5.5 Frequency stability

According to ANSI C63.26-2015 Section 5.6:

Frequency stability is a measure of the frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at +20 °C and rated supply voltage.


The operating carrier frequency shall be set up in accordance with the manufacturer's published operation and instruction manual prior to the commencement of these tests. No adjustment of any frequency determining circuit element shall be made subsequent to this initial set-up. Frequency stability is tested:

- a) At 10 °C intervals of temperatures between –30 °C and +50 °C at the manufacturer's rated supply voltage, and
- b) At +20 °C temperature and $\pm 15\%$ supply voltage variations. If a product is specified to operate over a range of input voltage then the –15% variation is applied to the lowermost voltage and the +15% is applied to the uppermost voltage.

During the test all necessary settings, adjustments and control of the EUT have to be performed without disturbing the test environment, i.e., without opening the environmental chamber. The frequency stabilities can be maintained to a lesser temperature range provided that the transmitter is automatically inhibited from operating outside the lesser temperature range. For handheld equipment that is only capable of operating from internal batteries and the supply voltage cannot be varied, the frequency stability tests shall be performed at the nominal battery voltage and the battery end point voltage specified by the manufacturer. An external supply voltage can be used and set at the internal battery nominal voltage, and again at the battery operating end point voltage which shall be specified by the equipment manufacturer.

If an unmodulated carrier is not available, the mean frequency of a modulated carrier can be obtained by using a frequency counter with gating time set to an appropriately large multiple of bit periods (gating time depending on the required accuracy). Full details on the choice of values shall be included in the test report.

Test Setup Block:



3.5.6 Field strength of spurious radiation

According to ANSI C63.26-2015 Section 5.5.3:

Test setup:




Figure 6 —Test site-up for radiated ERP and/or EIRP measurements




Figure 7 —Substitution method set-up for radiated emission

Test Procedure:

- a) Place the EUT in the center of the turntable. The EUT shall be configured to transmit into the standard non-radiating load (for measuring radiated spurious emissions), connected with cables of minimal length unless specified otherwise. If the EUT uses an adjustable antenna, the antenna shall be positioned to the length that produces the worst case emission at the fundamental operating frequency.
- b) Each emission under consideration shall be evaluated:
 - 1) Raise and lower the measurement antenna in accordance 5.5.2, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
 - 2) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - 3) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - 4) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
 - 5) Record the measured emission amplitude level and frequency using the appropriate RBW.
- c) Repeat step b) for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
- d) Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
- e) Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
- f) Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
- g) For each emission that was detected and measured in the initial test [i.e., in step b) and step c)]:
 - 1) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
 - 2) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step b) and step c).
 - 3) Record the output power level of the signal generator when equivalence is achieved in step 2).
- h) Repeat step e) through step g) with the measurement antenna oriented in the opposite polarization.
- i) Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:

$$P_e = P_s(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$
 where

P_e = equivalent emission power in dBm
 P_s = source (signal generator) power in dBm

NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.
- j) Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from: $\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB}$. If necessary, the antenna gain can be calculated from calibrated antenna factor information
- k) Provide the complete measurement results as a part of the test report.

4. Test DATA AND RESULTS

4.1 Antenna Port Test Data and Results for GSM 850 band:

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
GSM	824.2	836.6	848.8
GPRS	824.2	836.6	848.8
EDGE	824.2	836.6	848.8

Test Data:

RF Output Power					
Test Mode	Conducted Peak Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
GSM	31.48	31.59	31.67	29.09	38.45
GPRS 1 Slot	31.12	31.32	31.52	28.94	38.45
GPRS 2 Slots	30.51	30.74	30.93	28.35	38.45
GPRS 3 Slots	29.02	29.13	29.44	26.86	38.45
GPRS 4 Slots	27.88	18.02	28.21	25.63	38.45
EDGE 1 Slot	24.92	24.56	24.75	22.34	38.45
EDGE 2 Slots	23.56	23.26	23.47	20.98	38.45
EDGE 3 Slots	21.34	21.02	21.36	18.78	38.45
EDGE 4 Slots	20.02	19.83	19.98	17.44	38.45
Note: $ERP = \text{Conducted Power(dBm)} - L_c(\text{dB}) + G_T(\text{dBd})$ $G_T(\text{dBd}) = G_T(\text{dBi}) - 2.15$					
				Result:	Pass

Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
GSM	0.24	0.238	0.24	0.262	0.262	0.265
EDGE	0.248	0.25	0.248	0.318	0.314	0.321
Note: The test plots please refer to the Plots of Occupied Bandwidth						


Spurious Emissions at Antenna Terminal	
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.

Out of band emission, Band Edge	
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.

Frequency Stability					
Test Modulation:	GMSK		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	14	0.017	2.5
	-20	3.85	37	0.044	2.5
	-10	3.85	9	0.011	2.5
	0	3.85	5	0.006	2.5
	10	3.85	1	0.001	2.5
	20	3.85	31	0.037	2.5
	30	3.85	20	0.024	2.5
	40	3.85	5	0.006	2.5
	50	3.85	51	0.061	2.5
Frequency Stability vs. Voltage	20	3.4	8	0.010	2.5
	20	4.4	2	0.002	2.5
				Result:	Pass

Test Modulation:	8PSK		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	34	0.041	2.5
	-20	3.85	53	0.063	2.5
	-10	3.85	16	0.019	2.5
	0	3.85	18	0.022	2.5
	10	3.85	7	0.008	2.5
	20	3.85	28	0.033	2.5
	30	3.85	2	0.002	2.5
	40	3.85	44	0.053	2.5
	50	3.85	49	0.059	2.5
Frequency Stability vs. Voltage	20	3.4	24	0.029	2.5
	20	4.4	15	0.018	2.5
				Result:	Pass

Test Plots(Note: The 14.5 dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):




Spurious Emissions at Antenna Terminal


Channel

GSM

Lowest




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 19:02:11




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 19:02:35

Middle




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 19:03:06




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 19:03:22

Highest







ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 19:04:19



ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 19:04:33

Out of band emission, Band Edge

Mode	Lowest	Highest
GSM	Ref 34 dBm *Att 25 dB *RBW 3 kHz *VBW 10 kHz SWT 225 ms Marker 1 [T1] -14.29 dBm 823.997142857 MHz  Center 824 MHz 200 kHz/ Span 2 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 22:07:16	Ref 34 dBm *Att 25 dB *RBW 3 kHz *VBW 10 kHz SWT 225 ms Marker 1 [T1] -14.29 dBm 849.020000000 MHz  Center 849 MHz 200 kHz/ Span 2 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 22:12:23
EGPRS	Ref 34 dBm *Att 25 dB *RBW 3 kHz *VBW 10 kHz SWT 225 ms Marker 1 [T1] -26.50 dBm 823.960000000 MHz  Center 824 MHz 200 kHz/ Span 2 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 22:27:34	Ref 34 dBm *Att 25 dB *RBW 3 kHz *VBW 10 kHz SWT 225 ms Marker 1 [T1] -27.53 dBm 849.034285714 MHz  Center 849 MHz 200 kHz/ Span 2 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 22:36:37

4.2 Antenna Port Test Data and Results for GSM 1900 band:

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
GSM	1850.2	1880	1909.8
GPRS	1850.2	1880	1909.8
EDGE	1850.2	1880	1909.8

Test Data:

RF Output Power					
Test Mode	Conducted Peak Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
GSM	28.45	28.56	28.78	29.32	33
GPRS 1 Slot	28.39	28.38	28.42	28.96	33
GPRS 2 Slots	27.86	27.87	27.92	28.46	33
GPRS 3 Slots	26.37	26.41	26.57	27.11	33
GPRS 4 Slots	25.24	25.32	25.46	26	33
EDGE 1 Slot	25.8	25.44	25.17	26.34	33
EDGE 2 Slots	24.88	24.52	24.2	25.42	33
EDGE 3 Slots	22.89	22.56	22.32	23.43	33
EDGE 4 Slots	21.75	21.44	21.16	22.29	33
Note: EIRP=Conducted Power(dBm) - Lc(dB) + G _T (dBi)					
				Result:	Pass

Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
GSM	0.238	0.238	0.238	0.261	0.263	0.259
EDGE	0.254	0.252	0.252	0.313	0.321	0.317
Note: The test plots please refer to the Plots of Occupied Bandwidth						


Spurious Emissions at Antenna Terminal	
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.

Out of band emission, Band Edge	
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.

Frequency Stability						
Test Mode:	GMSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1850.073	1850.000	1909.921	1910.000
	-20	3.85	1850.061	1850.000	1909.948	1910.000
	-10	3.85	1850.066	1850.000	1909.942	1910.000
	0	3.85	1850.064	1850.000	1909.932	1910.000
	10	3.85	1850.061	1850.000	1909.926	1910.000
	20	3.85	1850.082	1850.000	1909.920	1910.000
	30	3.85	1850.057	1850.000	1909.945	1910.000
	40	3.85	1850.070	1850.000	1909.944	1910.000
	50	3.85	1850.063	1850.000	1909.923	1910.000
Frequency Stability vs. Voltage	20	3.4	1850.072	1850.000	1909.922	1910.000
	20	4.4	1850.054	1850.000	1909.927	1910.000
					Result:	Pass

Test Mode:	8PSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1850.051	1850.000	1909.950	1910.000
	-20	3.85	1850.067	1850.000	1909.944	1910.000
	-10	3.85	1850.070	1850.000	1909.947	1910.000
	0	3.85	1850.065	1850.000	1909.949	1910.000
	10	3.85	1850.047	1850.000	1909.935	1910.000
	20	3.85	1850.074	1850.000	1909.928	1910.000
	30	3.85	1850.071	1850.000	1909.930	1910.000
	40	3.85	1850.060	1850.000	1909.933	1910.000
	50	3.85	1850.050	1850.000	1909.932	1910.000
Frequency Stability vs. Voltage	20	3.4	1850.049	1850.000	1909.947	1910.000
	20	4.4	1850.064	1850.000	1909.956	1910.000
					Result:	Pass

Test Plots(Note: The 14.5dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):




Spurious Emissions at Antenna Terminal


Channel

GSM

Lowest




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 18:56:58




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 18:58:08

Middle




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 18:58:38




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 18:59:20

Highest







ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 19:00:00



ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 19:00:24

Out of band emission, Band Edge

Mode	Lowest	Highest
GSM	 Ref 34 dBm *Att 25 dB *RBW 3 kHz *VBW 10 kHz *SWT 225 ms Marker 1 [T1] -24.55 dBm 1.849997143 GHz Offset 14 dB Center 1.85 GHz 200 kHz/ Span 2 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:58:36	 Ref 34 dBm *Att 25 dB *RBW 3 kHz *VBW 10 kHz *SWT 225 ms Marker 1 [T1] -27.57 dBm 1.910022857 GHz Offset 14 dB Center 1.91 GHz 200 kHz/ Span 2 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 22:03:16
EGPRS	 Ref 34 dBm *Att 25 dB *RBW 3 kHz *VBW 10 kHz *SWT 225 ms Marker 1 [T1] -24.55 dBm 1.849997143 GHz Offset 14 dB Center 1.85 GHz 200 kHz/ Span 2 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 22:15:45	 Ref 34 dBm *Att 25 dB *RBW 3 kHz *VBW 10 kHz *SWT 225 ms Marker 1 [T1] -27.57 dBm 1.910022857 GHz Offset 14 dB Center 1.91 GHz 200 kHz/ Span 2 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 22:22:35

4.3 Antenna Port Test Data and Results for WCDMA Band 2:

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA- JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	1852.4	1880	1907.6

Test Data:**RF Output Power**

Test Mode	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	21.9	21.74	21.65	22.44	33
HSDPA Subtest 1	20.82	20.72	20.63	21.36	33
HSDPA Subtest 2	20.86	20.71	20.62	21.4	33
HSDPA Subtest 3	20.85	20.69	20.61	21.39	33
HSDPA Subtest 4	20.87	20.68	20.62	21.41	33
HSUPA Subtest 1	20.84	20.7	20.64	21.38	33
HSUPA Subtest 2	20.85	20.71	20.64	21.39	33
HSUPA Subtest 3	20.84	20.75	20.59	21.38	33
HSUPA Subtest 4	20.86	20.71	20.58	21.4	33
HSUPA Subtest 5	20.85	20.67	20.59	21.39	33
DC-HSDPA Subtest 1	/	/	/	0.54	33
DC-HSDPA Subtest 2	/	/	/	0.54	33
DC-HSDPA Subtest 3	/	/	/	0.54	33
DC-HSDPA Subtest 4	/	/	/	0.54	33
HSPA+ Subtest 1	/	/	/	0.54	33

Note: EIRP=Conducted Power(dBm) - Lc(dB) + G_T(dBi)**Result:****Pass****Peak-to-average Ratio(PAR)**

Test Mode	Peak-to-average Ratio(dB)			Limit (dB)
	Lowest Channel	Middle Channel	Highest Channel	
WCDMA R99	2.88	2.95	3.01	13
HSDPA	3.94	3.75	3.65	13
HSUPA	3.75	3.62	3.94	13

Result:**Pass****Occupied Bandwidth**

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.18	4.18	4.18	4.76	4.737	4.731
HSDPA	4.18	4.16	4.18	4.737	4.737	4.741
HSUPA	4.18	4.2	4.18	4.737	4.734	4.753

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--

Out of band emission, Band Edge

Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---

Frequency Stability

Test Mode:	WCDMA R99	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1850.319	1850.000	1909.694	1910.000
	-20	3.85	1850.311	1850.000	1909.706	1910.000
	-10	3.85	1850.296	1850.000	1909.705	1910.000
	0	3.85	1850.310	1850.000	1909.692	1910.000
	10	3.85	1850.294	1850.000	1909.694	1910.000
	20	3.85	1850.320	1850.000	1909.680	1910.000
	30	3.85	1850.294	1850.000	1909.706	1910.000
	40	3.85	1850.319	1850.000	1909.690	1910.000
	50	3.85	1850.304	1850.000	1909.693	1910.000
Frequency Stability vs. Voltage	20	3.4	1850.315	1850.000	1909.689	1910.000
	20	4.4	1850.296	1850.000	1909.695	1910.000
Result:					Pass	

Test Plots(Note: The 14.5dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):


Occupied Bandwidth	
Channel	WCDMA R99 HSDPA
Lowest	Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 0.96 dB *VBW 300 kHz SMT 5 ms 4.759743590 MHz Offset 14.5 dB Marker 1 [T1] -10.94 dBm Temp 1 [T1 OAV] 1.850040000 GHz Temp 2 [T1 OAV] 1.854500000 GHz Center 1.8524 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:23:42
Middle	Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 1.17 dB *VBW 300 kHz SMT 5 ms 4.737179487 MHz Offset 14.5 dB Marker 1 [T1] -10.97 dBm Temp 1 [T1 OAV] 1.877631410 GHz Temp 2 [T1 OAV] 1.882100000 GHz Center 1.88 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:26:56
Highest	Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 1.01 dB *VBW 300 kHz SMT 5 ms 4.730897430 MHz Offset 14.5 dB Marker 1 [T1] -10.73 dBm Temp 1 [T1 OAV] 1.905226077 GHz Temp 2 [T1 OAV] 1.909560000 GHz Center 1.9076 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:28:57
	Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] -0.50 dB *VBW 300 kHz SMT 5 ms 4.737179487 MHz Offset 14.5 dB Marker 1 [T1] -10.94 dBm Temp 1 [T1 OAV] 1.850040000 GHz Temp 2 [T1 OAV] 1.854500000 GHz Center 1.8524 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:48:56
	Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 0.88 dB *VBW 300 kHz SMT 5 ms 4.737179487 MHz Offset 14.5 dB Marker 1 [T1] -10.97 dBm Temp 1 [T1 OAV] 1.877631410 GHz Temp 2 [T1 OAV] 1.882100000 GHz Center 1.88 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:01:44
	Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 1.32 dB *VBW 300 kHz SMT 5 ms 4.740512621 MHz Offset 14.5 dB Marker 1 [T1] -10.97 dBm Temp 1 [T1 OAV] 1.905226077 GHz Temp 2 [T1 OAV] 1.909560000 GHz Center 1.9076 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:53:03

Occupied Bandwidth

Channel


HSUPA

Lowest




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 21:27:07

Middle



ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 21:29:01

Highest





ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 21:30:57

Spurious Emissions at Antenna Terminal



Channel

WCDMA R99



Lowest









Middle



Highest



Out of band emission, Band Edge

Mode	Lowest	Highest
R99	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:24:39	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:29:32
HSUPA	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:27:48	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:31:28
HSDPA	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:49:44	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:53:38

4.4 Antenna Port Test Data and Results for WCDMA Band 4:

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA- JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	1712.4	1732.6	1752.6

Test Data:**RF Output Power**

Test Mode	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	22.03	22.05	22.12	22.61	30
HSDPA Subtest 1	20.99	20.99	20.98	21.48	30
HSDPA Subtest 2	20.97	21.01	20.97	21.5	30
HSDPA Subtest 3	21.04	21	20.98	21.53	30
HSDPA Subtest 4	21.01	21	21.02	21.51	30
HSUPA Subtest 1	21.01	20.99	20.97	21.5	30
HSUPA Subtest 2	21	20.98	21.01	21.5	30
HSUPA Subtest 3	21.01	20.97	21.05	21.54	30
HSUPA Subtest 4	20.98	21.02	20.99	21.51	30
HSUPA Subtest 5	20.96	21.03	21.04	21.53	30
DC-HSDPA Subtest 1	/	/	/	0.49	30
DC-HSDPA Subtest 2	/	/	/	0.49	30
DC-HSDPA Subtest 3	/	/	/	0.49	30
DC-HSDPA Subtest 4	/	/	/	0.49	30
HSPA+ Subtest 1	/	/	/	0.49	30
Note: EIRP=Conducted Power(dBm) - Lc(dB) + G _T (dBi)					
				Result:	Pass

Peak-to-average Ratio(PAR)

Test Mode	Peak-to-average Ratio(dB)			Limit (dB)	
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	3.04	3.11	3.14	13	
HSDPA	3.78	3.88	4.33	13	
HSUPA	4.04	4.01	4.01	13	
				Result:	Pass

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.18	4.2	4.18	4.728	4.737	4.728
HSDPA	4.18	4.16	4.18	4.728	4.737	4.737
HSUPA	4.18	4.16	4.2	4.753	4.737	4.737
Note: The test plots please refer to the Plots of Occupied Bandwidth						

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--







Out of band emission, Band Edge

Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---

Frequency Stability

Test Mode:	WCDMA R99	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1710.292	1710.000	1754.697	1755.000
	-20	3.85	1710.299	1710.000	1754.708	1755.000
	-10	3.85	1710.298	1710.000	1754.701	1755.000
	0	3.85	1710.290	1710.000	1754.708	1755.000
	10	3.85	1710.288	1710.000	1754.706	1755.000
	20	3.85	1710.300	1710.000	1754.680	1755.000
	30	3.85	1710.297	1710.000	1754.683	1755.000
	40	3.85	1710.283	1710.000	1754.693	1755.000
	50	3.85	1710.298	1710.000	1754.694	1755.000
Frequency Stability vs. Voltage	20	3.4	1710.291	1710.000	1754.708	1755.000
	20	4.4	1710.276	1710.000	1754.686	1755.000
Result:					Pass	

Test Plots(Note: The 14.5dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):


Occupied Bandwidth		
Channel	WCDMA R99	HSDPA
Lowest	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:31:23	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:55:09
Middle	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:33:55	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:12:39
Highest	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:35:43	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:14:27

Occupied Bandwidth

Channel


HSUPA

Lowest




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 21:35:50

Middle









ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 21:39:35

Highest









ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 21:42:02

Spurious Emissions at Antenna Terminal

Channel	WCDMA R99	
Lowest	 Ref 34 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 100 ms Marker 1 [T1] -41.23 dBm 99.84000000 MHz Start 30 MHz 97 MHz/ Stop 1 GHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:10:40	 Ref 34 dBm * Att 25 dB * RBW 1 MHz * VBW 3 MHz * SWT 110 ms Marker 1 [T1] -35.19 dBm 3.415714286 GHz Start 1 GHz 1.9 GHz/ Stop 20 GHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:11:20
Middle	 Ref 34 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 100 ms Marker 1 [T1] -40.87 dBm 513.00000000 MHz Start 30 MHz 97 MHz/ Stop 1 GHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:12:11	 Ref 34 dBm * Att 25 dB * RBW 1 MHz * VBW 3 MHz * SWT 110 ms Marker 1 [T1] -32.14 dBm 3.470000000 GHz Start 1 GHz 1.9 GHz/ Stop 20 GHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:12:38
Highest	 Ref 34 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 100 ms Marker 1 [T1] -41.78 dBm 887.40000000 MHz Start 30 MHz 97 MHz/ Stop 1 GHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:13:20	 Ref 34 dBm * Att 25 dB * RBW 1 MHz * VBW 3 MHz * SWT 110 ms Marker 1 [T1] -31.57 dBm 3.497142857 GHz Start 1 GHz 1.9 GHz/ Stop 20 GHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:13:38

Out of band emission, Band Edge

Mode	Lowest	Highest
R99	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:32:26	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:36:20
HSUPA	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:36:46	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:42:38
HSDPA	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:55:58	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:14:58

4.5 Antenna Port Test Data and Results for WCDMA Band 5:

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	826.4	836.6	846.6

Test Data:**RF Output Power**

Test Mode	Conducted Average Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	21.95	21.98	21.97	19.4	38.45
HSDPA Subtest 1	20.99	20.89	20.92	18.41	38.45
HSDPA Subtest 2	20.86	20.89	20.95	18.37	38.45
HSDPA Subtest 3	20.9	20.88	20.92	18.34	38.45
HSDPA Subtest 4	20.92	20.9	20.91	18.34	38.45
HSUPA Subtest 1	20.93	20.89	20.92	18.35	38.45
HSUPA Subtest 2	20.91	20.93	20.96	18.38	38.45
HSUPA Subtest 3	20.91	20.93	20.94	18.36	38.45
HSUPA Subtest 4	20.92	20.92	20.95	18.37	38.45
HSUPA Subtest 5	20.91	20.9	20.94	18.36	38.45
DC-HSDPA Subtest 1	/	/	/	-2.58	38.45
DC-HSDPA Subtest 2	/	/	/	-2.58	38.45
DC-HSDPA Subtest 3	/	/	/	-2.58	38.45
DC-HSDPA Subtest 4	/	/	/	-2.58	38.45
HSPA+ Subtest 1	/	/	/	-2.58	38.45
Note: ERP= Conducted Power(dBm) - Lc(dB) + Gr(dBd) Gr(dBd)=Gr(dBi)-2.15					
				Result:	Pass

Peak-to-average Ratio(PAR)

Test Mode	Peak-to-average Ratio(dB)			Limit (dB)
	Lowest Channel	Middle Channel	Highest Channel	
WCDMA R99	2.88	3.08	3.04	13
HSDPA	4.29	3.97	3.81	13
HSUPA	3.78	3.97	4.07	13
				Result: Pass

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.18	4.18	4.2	4.76	4.753	4.856
HSDPA	4.18	4.18	4.2	4.769	4.737	4.753
HSUPA	4.18	4.18	4.2	4.769	4.737	4.753

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal

Result: Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.







Out of band emission, Band Edge

Result: Pass, Please refer to the test plots of Out of band emission, Band Edge.

Frequency Stability

Test Modulation:	WCDMA R99		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{bc})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	8	0.010	2.5
	-20	3.85	49	0.059	2.5
	-10	3.85	23	0.027	2.5
	0	3.85	20	0.024	2.5
	10	3.85	7	0.008	2.5
	20	3.85	21	0.025	2.5
	30	3.85	2	0.002	2.5
	40	3.85	22	0.026	2.5
	50	3.85	34	0.041	2.5
Frequency Stability vs. Voltage	20	3.4	9	0.011	2.5
	20	4.4	23	0.027	2.5
Result:				Pass	

Test Plots(Note: The 14.5dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):


Occupied Bandwidth			
Channel	WCDMA R99		HSDPA
Lowest	 Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 1.72 dB *VBW 300 kHz SMT 5 ms 4.750615395 MHz OBW 4.180000000 MHz Marker 1 [T1] -17.43 dBm 824.025000000 MHz Temp 1 [T1 OBW] 824.320000000 MHz T2 Temp 2 [T2 OBW] 828.500000000 MHz LVL 30dB Center 826.4 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:38:33	 Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 0.78 dB *VBW 300 kHz SMT 5 ms 4.766236769 MHz OBW 4.180000000 MHz Marker 1 [T1] -17.7 dBm 824.015384615 MHz Temp 1 [T1 OBW] 824.320000000 MHz T2 Temp 2 [T2 OBW] 828.500000000 MHz LVL 30dB Center 826.4 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:16:39	
	 Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 1.22 dB *VBW 300 kHz SMT 5 ms 4.753205128 MHz OBW 4.180000000 MHz Marker 1 [T1] -17.43 dBm 834.215384615 MHz Temp 1 [T1 OBW] 834.500000000 MHz T2 Temp 2 [T2 OBW] 838.600000000 MHz LVL 30dB Center 836.6 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:40:26	 Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 1.21 dB *VBW 300 kHz SMT 5 ms 4.737179487 MHz OBW 4.180000000 MHz Marker 1 [T1] -17.85 dBm 834.215384615 MHz Temp 1 [T1 OBW] 834.500000000 MHz T2 Temp 2 [T2 OBW] 838.600000000 MHz LVL 30dB Center 836.6 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:19:06	
Highest	 Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 2.91 dB *VBW 300 kHz SMT 5 ms 4.856769231 MHz OBW 4.200000000 MHz Marker 1 [T1] -17.43 dBm 844.119236769 MHz Temp 1 [T1 OBW] 844.400000000 MHz T2 Temp 2 [T2 OBW] 848.600000000 MHz LVL 30dB Center 846.6 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:43:04	 Ref 40 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] 0.29 dB *VBW 300 kHz SMT 5 ms 4.753205128 MHz OBW 4.200000000 MHz Marker 1 [T1] -17.44 dBm 844.23141256 MHz Temp 1 [T1 OBW] 844.400000000 MHz T2 Temp 2 [T2 OBW] 848.600000000 MHz LVL 30dB Center 846.6 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:21:13	

Occupied Bandwidth

Channel


HSUPA

Lowest




ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 21:47:11

Middle









ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 21:49:04

Highest









ProjectNo.:CR230953899-RF Tester:Arthur Su
Date: 17.OCT.2023 21:51:27

Spurious Emissions at Antenna Terminal

Channel	WCDMA R99	
Lowest	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:14:21	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:14:40
	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:15:24	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:15:48
Highest	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:18:11	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 19:18:32

Out of band emission, Band Edge

Mode	Lowest	Highest
R99	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:39:02	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 20:45:54
HSUPA	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:47:48	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:52:48
HSDPA	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:17:11	 ProjectNo.:CR230953899-RF Tester:Arthur Su Date: 17.OCT.2023 21:23:34

4.6 Antenna Port Test Data and Results for LTE Band 2

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
1.4MHz	1850.7	1880	1909.3
3MHz	1851.5	1880	1908.5
5MHz	1852.5	1880	1907.5
10MHz	1855	1880	1905
15MHz	1857.5	1880	1902.5
20MHz	1860	1880	1900

Test Data:

RF Output Power						
Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
1.4MHz QPSK	RB1#0	21.01	20.76	20.61	21.71	33
	RB1#3	21.17	20.92	20.72		
	RB1#5	20.96	20.74	20.57		
	RB3#0	21.09	20.86	20.66		
	RB3#3	21.09	20.87	20.69		
	RB6#0	20.05	19.82	19.68		
1.4MHz 16QAM	RB1#0	19.98	19.74	19.73	20.7	33
	RB1#3	20.16	19.89	19.91		
	RB1#5	20.04	19.75	19.68		
	RB3#0	20.11	20.01	19.59		
	RB3#3	20.09	20.01	19.64		
	RB6#0	18.97	18.81	18.68		
3MHz QPSK	RB1#0	21.48	20.83	20.66	22.02	33
	RB1#8	21.46	20.8	20.66		
	RB1#14	21.43	20.74	20.63		
	RB6#0	20.25	19.79	19.61		
	RB6#9	20.05	19.76	19.59		
	RB15#0	19.98	19.81	19.64		
3MHz 16QAM	RB1#0	20.05	20.41	19.8	20.95	33
	RB1#8	20	20.35	19.77		
	RB1#14	19.99	20.28	19.79		
	RB6#0	18.91	18.84	18.61		
	RB6#9	18.89	18.86	18.64		
	RB15#0	19.05	18.89	18.58		
5MHz QPSK	RB1#0	21.41	20.77	20.6	21.99	33
	RB1#13	21.45	20.84	20.66		
	RB1#24	21.33	20.72	20.61		
	RB15#0	20.27	19.82	19.65		
	RB15#10	20.03	19.78	19.62		
	RB25#0	19.94	19.76	19.63		
5MHz 16QAM	RB1#0	20.01	19.64	19.9	20.59	33
	RB1#13	20.05	19.71	19.97		
	RB1#24	19.94	19.58	19.89		
	RB15#0	18.95	18.87	18.61		
	RB15#10	19.02	18.84	18.64		
	RB25#0	18.94	18.83	18.57		
10MHz QPSK	RB1#0	21.03	20.91	20.73	21.69	33
	RB1#25	21.15	21.02	20.78		
	RB1#49	20.99	20.83	20.66		

	RB25#0	19.93	19.83	19.74		
	RB25#25	19.94	19.85	19.67		
	RB50#0	19.95	19.79	19.67		
10MHz 16QAM	RB1#0	20.16	19.89	20.3	20.89	33
	RB1#25	20.24	20.01	20.35		
	RB1#49	20.13	19.75	20.19		
	RB25#0	18.98	18.9	18.79		
	RB25#25	18.96	18.9	18.8		
	RB50#0	18.93	18.86	18.7		
15MHz QPSK	RB1#0	20.53	20.84	20.64	21.99	33
	RB1#38	21.45	20.87	20.68		
	RB1#74	21.25	20.73	20.61		
	RB36#0	20.07	19.87	19.76		
	RB36#39	19.95	19.84	19.74		
	RB75#0	20	19.87	19.7		
15MHz 16QAM	RB1#0	20.54	19.96	20.01	21.09	33
	RB1#38	20.54	19.96	20.11		
	RB1#74	20.55	19.72	19.96		
	RB36#0	19	18.87	18.7		
	RB36#39	18.98	18.78	18.65		
	RB75#0	18.98	18.85	18.69		
20MHz QPSK	RB1#0	21.3	20.68	20.48	22.01	33
	RB1#50	21.47	20.98	20.85		
	RB1#99	20.73	20.41	20.45		
	RB50#0	20	19.85	19.81		
	RB50#50	19.94	19.7	19.7		
	RB100#0	20.01	19.79	19.79		
20MHz 16QAM	RB1#0	20.02	20.29	19.82	21.08	33
	RB1#50	20.3	20.54	20.2		
	RB1#99	19.93	19.99	19.74		
	RB50#0	19.01	18.84	18.81		
	RB50#50	18.94	18.73	18.72		
	RB100#0	19.01	18.77	18.83		

Note: EIRP=Conducted Power(dBm) - Lc(dB) + G_T(dBi)**Result:****Pass****Peak-to-average Ratio(PAR)**

Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
20MHz QPSK	RB1#0	6.26	6.48	6.46	13
	RB100#0	6.31	6.44	6.57	13
20MHz 16QAM	RB1#0	7.16	7.61	7.35	13
	RB100#0	7.18	7.18	7.21	13
				Result:	Pass

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
1.4MHz QPSK	1.104	1.104	1.104	1.296	1.296	1.308
1.4MHz 16QAM	1.098	1.11	1.092	1.302	1.326	1.284
3MHz QPSK	2.676	2.687	2.687	2.88	2.868	2.88
3MHz 16QAM	2.676	2.687	2.676	2.856	2.88	2.88
5MHz QPSK	4.5	4.52	4.52	4.88	4.9	4.9
5MHz 16QAM	4.52	4.5	4.48	4.94	4.96	4.86
10MHz QPSK	8.96	8.96	8.96	9.48	9.6	9.6
10MHz 16QAM	8.96	8.96	8.96	9.56	9.56	9.48
15MHz QPSK	13.5	13.5	13.5	14.64	14.7	14.76
15MHz 16QAM	13.5	13.5	13.5	14.64	14.7	14.7
20MHz QPSK	17.92	17.84	18	19.36	19.28	19.36
20MHz 16QAM	17.92	18	18	19.04	19.2	19.36

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--

Out of band emission, Band Edge

Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---

Frequency Stability







Test Mode:	20M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1851.022	1850.000	1909.066	1910.000
	-20	3.85	1851.022	1850.000	1909.055	1910.000
	-10	3.85	1851.040	1850.000	1909.044	1910.000
	0	3.85	1851.035	1850.000	1909.042	1910.000
	10	3.85	1851.017	1850.000	1909.043	1910.000
	20	3.85	1851.040	1850.000	1909.040	1910.000
	30	3.85	1851.017	1850.000	1909.058	1910.000
	40	3.85	1851.026	1850.000	1909.050	1910.000
	50	3.85	1851.034	1850.000	1909.049	1910.000
Frequency Stability vs. Voltage	20	3.4	1851.023	1850.000	1909.062	1910.000
	20	4.4	1851.039	1850.000	1909.047	1910.000
					Result:	Pass

Test Mode:	20M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
------------	-----------	--	--	--	--	--

Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1851.040	1850.000	1909.063	1910.000
	-20	3.85	1851.023	1850.000	1909.044	1910.000
	-10	3.85	1851.011	1850.000	1909.044	1910.000
	0	3.85	1851.018	1850.000	1909.058	1910.000
	10	3.85	1851.023	1850.000	1909.054	1910.000
	20	3.85	1851.040	1850.000	1909.040	1910.000
	30	3.85	1851.013	1850.000	1909.041	1910.000
	40	3.85	1851.014	1850.000	1909.065	1910.000
	50	3.85	1851.037	1850.000	1909.043	1910.000
Frequency Stability vs. Voltage	20	3.4	1851.013	1850.000	1909.065	1910.000
	20	4.4	1851.015	1850.000	1909.040	1910.000
					Result:	Pass

Test Plots(Note: The 14.5dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):

Occupied Bandwidth

Channel	1.4MHz Bandwidth QPSK	1.4MHz Bandwidth 16QAM
Lowest	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:07:45	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:08:06
Middle	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:08:30	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:08:53
Highest	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:09:20	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:09:40


Occupied Bandwidth

Channel


3MHz Bandwidth QPSK

3MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:10:48




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:11:05

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:11:26




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:11:43

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:12:04



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:12:24

Page 66 of 289

Occupied Bandwidth		
Channel	10MHz Bandwidth QPSK	10MHz Bandwidth 16QAM
Lowest	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:17:02	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:17:25
Middle	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:17:46	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:18:06
Highest	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:18:27	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:18:46


Occupied Bandwidth

Channel


15MHz Bandwidth QPSK

15MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:21:29




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:21:53

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:22:14




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:22:34

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:22:54



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:23:15


Occupied Bandwidth		
Channel	20MHz Bandwidth QPSK	20MHz Bandwidth 16QAM
Lowest	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:25:21	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:25:41
Middle	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:26:02	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:26:22
Highest	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:26:46	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:27:06

Spurious Emissions at Antenna Terminal


Channel

1.4MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:00:02




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:00:15

Middle




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:00:33




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:00:46

Highest



ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:01:04




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:01:17

Spurious Emissions at Antenna Terminal


Channel

3MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:02:03




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:02:16

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:02:31




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:02:44

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:02:59




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:03:12

Spurious Emissions at Antenna Terminal


Channel

5MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:03:58




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:04:11

Middle




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:04:30




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:04:43

Highest



ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:04:58




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:05:11

Spurious Emissions at Antenna Terminal


Channel

10MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:05:59




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:06:12

Middle




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:06:30




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:06:41

Highest



ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:06:53





ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:07:04

Spurious Emissions at Antenna Terminal



Channel

15MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

20MHz Bandwidth QPSK



Lowest









Middle








Highest









Out of band emission, Band Edge

Mode	Lowest	Highest
QPSK 1.4MHz	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 100 kHz *SWT 35 ms *Marker 1 [T1] -20.71 dBm 1.850000000 GHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 19:53:54	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 100 kHz *SWT 35 ms *Marker 1 [T1] -23.60 dBm 1.910000000 GHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 19:54:14
QPSK 3MHz	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 100 kHz *SWT 35 ms *Marker 1 [T1] -31.45 dBm 1.850000000 GHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 19:55:22	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 100 kHz *SWT 35 ms *Marker 1 [T1] -33.93 dBm 1.910000000 GHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 19:55:44
QPSK 5MHz	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz *SWT 35 ms *Marker 1 [T1] -28.48 dBm 1.849980000 GHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 19:57:17	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz *SWT 35 ms *Marker 1 [T1] -30.44 dBm 1.910000000 GHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 19:57:39






Out of band emission, Band Edge

Mode	Lowest	Highest
QPSK 10MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -22.50 dBm 1.850000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 19:58:49	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -26.26 dBm 1.910000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 19:59:14
QPSK 15MHz	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -28.13 dBm 1.850000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:01:54	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -30.36 dBm 1.910000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:02:13
QPSK 20MHz	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -33.75 dBm 1.850000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:03:11	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -34.25 dBm 1.910000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:03:38

Out of band emission, Band Edge

Mode	Lowest	Highest
16QAM 1.4MHz	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -27.85 dBm 1.850000000 GHz Center 1.85 GHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 19:54:03	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -31.47 dBm 1.910000000 GHz Center 1.91 GHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 19:54:24
16QAM 3MHz	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -31.73 dBm 1.850000000 GHz Center 1.85 GHz 600 kHz/ Span 6 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 19:55:32	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -36.04 dBm 1.910000000 GHz Center 1.91 GHz 600 kHz/ Span 6 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 19:55:55
16QAM 5MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -32.59 dBm 1.850000000 GHz Center 1.85 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 19:57:27	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -32.07 dBm 1.910020000 GHz Center 1.91 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 19:57:51

Out of band emission, Band Edge

Mode	Lowest	Highest
16QAM 10MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * Marker 1 [T1] * VSW 300 kHz * SWT 35 ms * -34.07 dBm * 1.850000000 GHz Center 1.85 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 19:59:01	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * Marker 1 [T1] * VSW 300 kHz * SWT 35 ms * -37.26 dBm * 1.910000000 GHz Center 1.91 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 19:59:26
16QAM 15MHz	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * Marker 1 [T1] * VSW 1 MHz * SWT 35 ms * -30.85 dBm * 1.850000000 GHz Center 1.85 GHz 3 MHz/ Span 30 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:02:03	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * Marker 1 [T1] * VSW 1 MHz * SWT 35 ms * -31.69 dBm * 1.910000000 GHz Center 1.91 GHz 3 MHz/ Span 30 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:02:22
16QAM 20MHz	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * Marker 1 [T1] * VSW 1 MHz * SWT 35 ms * -34.15 dBm * 1.850000000 GHz Center 1.85 GHz 4 MHz/ Span 40 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:03:20	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * Marker 1 [T1] * VSW 1 MHz * SWT 35 ms * -36.86 dBm * 1.910000000 GHz Center 1.91 GHz 4 MHz/ Span 40 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:03:39

4.7 Antenna Port Test Data and Results for LTE Band 4

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
1.4MHz	1710.7	1732.5	1754.3
3MHz	1711.5	1732.5	1753.5
5MHz	1712.5	1732.5	1752.5
10MHz	1715	1732.5	1750
15MHz	1717.5	1732.5	1747.5
20MHz	1720	1732.5	1745

Test Data:

RF Output Power						
Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
1.4MHz QPSK	RB1#0	21.13	21.07	21.12	21.87	30
	RB1#3	21.29	21.38	21.29		
	RB1#5	21.13	21.08	21.15		
	RB3#0	21.19	21.2	21.26		
	RB3#3	21.18	21.26	21.25		
	RB6#0	20.19	20.14	20.22		
1.4MHz 16QAM	RB1#0	20.23	20.11	20.19	20.94	30
	RB1#3	20.44	20.35	20.36		
	RB1#5	20.2	20.17	20.18		
	RB3#0	20.17	20.3	20.39		
	RB3#3	20.17	20.3	20.45		
	RB6#0	19.17	19.13	19.27		
3MHz QPSK	RB1#0	21.17	21.16	21.18	21.74	30
	RB1#8	21.15	21.15	21.25		
	RB1#14	21.15	21.09	21.24		
	RB6#0	20.11	20.14	20.16		
	RB6#9	20.13	20.11	20.18		
	RB15#0	20.16	20.16	20.2		
3MHz 16QAM	RB1#0	20.19	20.79	20.33	21.28	30
	RB1#8	20.22	20.77	20.38		
	RB1#14	20.17	20.69	20.37		
	RB6#0	19.1	19.21	19.2		
	RB6#9	19.07	19.24	19.23		
	RB15#0	19.25	19.23	19.17		
5MHz QPSK	RB1#0	21.08	21.04	21.11	21.75	30
	RB1#13	21.2	21.26	21.23		
	RB1#24	21.05	21.04	21.13		
	RB15#0	20.21	20.17	20.2		
	RB15#10	20.16	20.18	20.17		
	RB25#0	20.1	20.13	20.19		
5MHz 16QAM	RB1#0	20.13	19.99	20.38	21.04	30
	RB1#13	20.26	20.12	20.55		
	RB1#24	20.12	19.96	20.43		
	RB15#0	19.24	19.22	19.18		
	RB15#10	19.19	19.23	19.16		
	RB25#0	19.18	19.25	19.18		
10MHz QPSK	RB1#0	21.1	21.14	21.11	21.86	30
	RB1#25	21.37	21.34	21.29		
	RB1#49	21.22	21.09	21.18		

	RB25#0	20.18	20.15	20.23		
	RB25#25	20.16	20.18	20.16		
	RB50#0	20.18	20.17	20.18		
10MHz 16QAM	RB1#0	20.14	20.73	20.29	21.4	30
	RB1#25	20.38	20.91	20.5		
	RB1#49	20.18	20.71	20.32		
	RB25#0	19.31	19.27	19.27		
	RB25#25	19.26	19.26	19.16		
	RB50#0	19.2	19.21	19.24		
15MHz QPSK	RB1#0	21.04	21.12	21.09	21.69	30
	RB1#38	21.18	21.2	21.17		
	RB1#74	20.97	21.02	21.1		
	RB36#0	20.21	20.16	20.27		
	RB36#39	20.22	20.16	20.17		
	RB75#0	20.22	20.17	20.21		
15MHz 16QAM	RB1#0	20.64	20.25	20.5	21.26	30
	RB1#38	20.77	20.37	20.57		
	RB1#74	20.59	20.21	20.54		
	RB36#0	19.19	19.17	19.24		
	RB36#39	19.21	19.15	19.09		
	RB75#0	19.23	19.19	19.15		
20MHz QPSK	RB1#0	20.94	20.98	20.92	21.87	30
	RB1#50	21.31	21.38	21.34		
	RB1#99	20.97	20.98	20.96		
	RB50#0	20.25	20.17	20.29		
	RB50#50	20.28	20.13	20.11		
	RB100#0	20.27	20.16	20.21		
20MHz 16QAM	RB1#0	20.26	20.22	20.56	21.4	30
	RB1#50	20.64	20.59	20.91		
	RB1#99	20.3	20.16	20.59		
	RB50#0	19.27	19.17	19.31		
	RB50#50	19.25	19.17	19.15		
	RB100#0	19.33	19.18	19.28		

Note: EIRP=Conducted Power(dBm) - Lc(dB) + G_T(dBi)

Result:

Pass

Peak-to-average Ratio(PAR)

Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
20MHz QPSK	RB1#0	6.87	6.06	6.51	13
	RB100#0	6.51	6.47	6.31	13
20MHz 16QAM	RB1#0	7.74	7.03	7.09	13
	RB100#0	7.24	7.12	7.02	13
				Result:	Pass

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
1.4MHz QPSK	1.104	1.104	1.098	1.308	1.296	1.29
1.4MHz 16QAM	1.092	1.098	1.11	1.284	1.29	1.302
3MHz QPSK	2.7	2.687	2.687	2.868	2.88	2.88
3MHz 16QAM	2.676	2.687	2.687	2.892	2.868	2.856
5MHz QPSK	4.52	4.5	4.52	4.92	4.92	4.96
5MHz 16QAM	4.52	4.5	4.52	4.92	4.98	4.9
10MHz QPSK	8.96	8.96	8.96	9.56	9.6	9.6
10MHz 16QAM	8.96	8.96	8.96	9.52	9.64	9.6
15MHz QPSK	13.56	13.5	13.56	14.82	14.64	14.7
15MHz 16QAM	13.56	13.5	13.56	14.76	14.58	14.64
20MHz QPSK	18	17.92	17.92	19.52	19.04	19.44
20MHz 16QAM	18	18	17.92	19.28	19.36	19.44

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--

Out of band emission, Band Edge

Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---

Frequency Stability

Test Mode:	20M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1711.032	1710.00	1753.971	1755
	-20	3.85	1711.034	1710.00	1753.981	1755
	-10	3.85	1711.023	1710.00	1753.982	1755
	0	3.85	1711.025	1710.00	1753.967	1755
	10	3.85	1711.015	1710.00	1753.978	1755
	20	3.85	1711.040	1710.00	1753.960	1755
	30	3.85	1711.026	1710.00	1753.984	1755
	40	3.85	1711.021	1710.00	1753.988	1755
	50	3.85	1711.024	1710.00	1753.967	1755
Frequency Stability vs. Voltage	20	3.4	1711.022	1710.00	1753.968	1755
	20	4.4	1711.021	1710.00	1753.971	1755
					Result:	Pass

Test Mode:	20M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
------------	-----------	--	--	--	--	--

Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1711.018	1710.00	1753.961	1755
	-20	3.85	1711.027	1710.00	1753.968	1755
	-10	3.85	1711.027	1710.00	1753.964	1755
	0	3.85	1711.014	1710.00	1753.986	1755
	10	3.85	1711.013	1710.00	1753.978	1755
	20	3.85	1711.040	1710.00	1753.960	1755
	30	3.85	1711.011	1710.00	1753.961	1755
	40	3.85	1711.023	1710.00	1753.973	1755
	50	3.85	1711.037	1710.00	1753.972	1755
Frequency Stability vs. Voltage	20	3.4	1711.020	1710.00	1753.972	1755
	20	4.4	1711.038	1710.00	1753.976	1755
					Result:	Pass

Occupied Bandwidth

Page 85 of 289

Page 86 of 289


Occupied Bandwidth

Channel


5MHz Bandwidth QPSK

5MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:32:36




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:33:00

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:33:27




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:33:47

Highest









ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:34:10



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:34:31

Occupied Bandwidth

Channel	10MHz Bandwidth QPSK	10MHz Bandwidth 16QAM
Lowest	 Ref 30 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] -2.62 dB *VBW 300 kHz SWT 10 ms 9.56000000 MHz OSW 9.56000000 MHz Marker 1 [T1] -12.10 dBm Temp 1 [T1] 1.715 GHz Temp 2 [T1] 1.715 GHz LVL 30B Center 1.715 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:35:22	 Ref 30 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] -0.79 dB *VBW 300 kHz SWT 10 ms 9.52000000 MHz OSW 9.52000000 MHz Marker 1 [T1] -11.35 dBm Temp 1 [T1] 1.715 GHz Temp 2 [T1] 1.715 GHz LVL 30B Center 1.715 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:35:43
Middle	 Ref 30 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] -0.18 dB *VBW 300 kHz SWT 10 ms 9.60000000 MHz OSW 9.60000000 MHz Marker 1 [T1] -12.79 dBm Temp 1 [T1] 1.7325 GHz Temp 2 [T1] 1.7325 GHz LVL 30B Center 1.7325 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:36:09	 Ref 30 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] -0.18 dB *VBW 300 kHz SWT 10 ms 9.64000000 MHz OSW 9.64000000 MHz Marker 1 [T1] -11.59 dBm Temp 1 [T1] 1.7325 GHz Temp 2 [T1] 1.7325 GHz LVL 30B Center 1.7325 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:36:32
Highest	 Ref 30 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] -0.18 dB *VBW 300 kHz SWT 10 ms 9.60000000 MHz OSW 9.60000000 MHz Marker 1 [T1] -12.25 dBm Temp 1 [T1] 1.75 GHz Temp 2 [T1] 1.75 GHz LVL 30B Center 1.75 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:36:59	 Ref 30 dBm *Att 25 dB *RBW 100 kHz Delta 1 [T1] -0.88 dB *VBW 300 kHz SWT 10 ms 9.60000000 MHz OSW 9.60000000 MHz Marker 1 [T1] -12.05 dBm Temp 1 [T1] 1.75 GHz Temp 2 [T1] 1.75 GHz LVL 30B Center 1.75 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:37:12


Occupied Bandwidth

Channel


15MHz Bandwidth QPSK

15MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:38:08




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:38:24

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:38:45




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:39:05

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:39:27



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:39:58


Occupied Bandwidth

Channel


20MHz Bandwidth QPSK

20MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 15:48:50




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 15:41:10

Middle




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 15:41:31




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 15:41:51

Highest



ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 15:42:12





ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 15:42:32

Spurious Emissions at Antenna Terminal



Channel

1.4MHz Bandwidth QPSK



Lowest



Middle



Highest




Spurious Emissions at Antenna Terminal


Channel

3MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester:Clair Liu
Date: 25.OCT.2023 21:13:09




ProjectNo.:CR230953899-RF Tester:Clair Liu
Date: 25.OCT.2023 21:13:19

Middle




ProjectNo.:CR230953899-RF Tester:Clair Liu
Date: 25.OCT.2023 21:13:35




ProjectNo.:CR230953899-RF Tester:Clair Liu
Date: 25.OCT.2023 21:13:45

Highest



ProjectNo.:CR230953899-RF Tester:Clair Liu
Date: 25.OCT.2023 21:14:01




ProjectNo.:CR230953899-RF Tester:Clair Liu
Date: 25.OCT.2023 21:14:11

Spurious Emissions at Antenna Terminal


Channel

5MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:15:04




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:15:14

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:15:27




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:15:37

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:15:50





ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:16:00

Spurious Emissions at Antenna Terminal



Channel

10MHz Bandwidth QPSK



Lowest



Middle



Highest




Spurious Emissions at Antenna Terminal

Channel


15MHz Bandwidth QPSK

Lowest



ProjectNo.:CR230953899-RF Tester: Claire Liu


Date: 25.OCT.2023 21:18:38



ProjectNo.:CR230953899-RF Tester: Claire Liu


Date: 25.OCT.2023 21:18:49

Middle



ProjectNo.:CR230953899-RF Tester: Claire Liu


Date: 25.OCT.2023 21:19:01



ProjectNo.:CR230953899-RF Tester: Claire Liu


Date: 25.OCT.2023 21:19:12

Highest



ProjectNo.:CR230953899-RF Tester: Claire Liu

Date: 25.OCT.2023 21:19:24



ProjectNo.:CR230953899-RF Tester: Claire Liu


Date: 25.OCT.2023 21:19:35

Spurious Emissions at Antenna Terminal


Channel

20MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:20:18




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:20:28

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:20:41




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:20:51

Highest








ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:21:04









ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:21:14







Out of band emission, Band Edge

Mode	Lowest	Highest
QPSK 1.4MHz	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 100 kHz *SWT 35 ms Marker 1 [T1] -29.85 dBm 1.710000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:03:54	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 100 kHz *SWT 35 ms Marker 1 [T1] -29.52 dBm 1.755000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:04:14
QPSK 3MHz	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 100 kHz *SWT 35 ms Marker 1 [T1] -34.92 dBm 1.710000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:05:14	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 100 kHz *SWT 35 ms Marker 1 [T1] -35.31 dBm 1.755000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:05:34
QPSK 5MHz	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz *SWT 35 ms Marker 1 [T1] -38.13 dBm 1.710000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:06:35	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz *SWT 35 ms Marker 1 [T1] -38.12 dBm 1.755000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:06:57







Out of band emission, Band Edge

Mode	Lowest	Highest
QPSK 10MHz	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz *SWT 35 ms Marker 1 [T1] -31.85 dBm 1.710000000 GHz Center 1.71 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:07:58	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz *SWT 35 ms Marker 1 [T1] -35.66 dBm 1.755000000 GHz Center 1.755 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:08:22
QPSK 15MHz	 Ref 30 dBm *Att 25 dB *RBW 300 kHz *VBW 1 MHz *SWT 35 ms Marker 1 [T1] -31.10 dBm 1.710000000 GHz Center 1.71 GHz 3 MHz/ Span 30 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:09:22	 Ref 30 dBm *Att 25 dB *RBW 300 kHz *VBW 1 MHz *SWT 35 ms Marker 1 [T1] -30.02 dBm 1.755000000 GHz Center 1.755 GHz 3 MHz/ Span 30 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:09:41
QPSK 20MHz	 Ref 30 dBm *Att 25 dB *RBW 300 kHz *VBW 1 MHz *SWT 35 ms Marker 1 [T1] -34.96 dBm 1.710000000 GHz Center 1.71 GHz 4 MHz/ Span 40 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:10:39	 Ref 30 dBm *Att 25 dB *RBW 300 kHz *VBW 1 MHz *SWT 35 ms Marker 1 [T1] -35.33 dBm 1.755000000 GHz Center 1.755 GHz 4 MHz/ Span 40 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:10:57

Out of band emission, Band Edge

Mode	Lowest	Highest
16QAM 1.4MHz	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -34.42 dBm 1.710000000 GHz Center 1.71 GHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:04:04	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -30.30 dBm 1.755000000 GHz Center 1.755 GHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:04:23
16QAM 3MHz	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -34.57 dBm 1.710000000 GHz Center 1.71 GHz 600 kHz/ Span 6 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:05:25	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -34.65 dBm 1.755000000 GHz Center 1.755 GHz 600 kHz/ Span 6 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:05:43
16QAM 5MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -31.16 dBm 1.710000000 GHz Center 1.71 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:06:45	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -30.86 dBm 1.755000000 GHz Center 1.755 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:07:07

Out of band emission, Band Edge

Mode	Lowest	Highest
16QAM 10MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -30.54 dBm 1.710000000 GHz Center 1.71 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:08:10	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -30.22 dBm 1.755000000 GHz Center 1.755 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:08:33
16QAM 15MHz	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -32.09 dBm 1.710000000 GHz Center 1.71 GHz 3 MHz/ Span 30 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:09:31	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -31.21 dBm 1.755000000 GHz Center 1.755 GHz 3 MHz/ Span 30 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:09:50
16QAM 20MHz	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -34.85 dBm 1.710000000 GHz Center 1.71 GHz 4 MHz/ Span 40 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:10:48	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -34.82 dBm 1.755000000 GHz Center 1.755 GHz 4 MHz/ Span 40 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:11:07

4.8 Antenna Port Test Data and Results for LTE Band 5

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
1.4MHz	824.7	836.5	848.3
3MHz	825.5	836.5	847.5
5MHz	826.5	836.5	846.5
10MHz	829	836.5	844

Test Data:

RF Output Power						
Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
1.4MHz QPSK	RB1#0	21.65	21.53	21.56	19.17	38.45
	RB1#3	21.75	21.71	21.75		
	RB1#5	21.56	21.56	21.56		
	RB3#0	21.68	21.64	21.66		
	RB3#3	21.68	21.67	21.64		
	RB6#0	20.67	20.69	20.71		
1.4MHz 16QAM	RB1#0	20.73	20.58	20.56	18.33	38.45
	RB1#3	20.91	20.8	20.71		
	RB1#5	20.73	20.62	20.6		
	RB3#0	20.66	20.74	20.83		
	RB3#3	20.71	20.75	20.85		
	RB6#0	19.71	19.61	19.68		
3MHz QPSK	RB1#0	21.62	21.64	21.68	19.1	38.45
	RB1#8	21.57	21.61	21.62		
	RB1#14	21.6	21.63	21.64		
	RB6#0	20.64	20.6	20.63		
	RB6#9	20.61	20.64	20.65		
	RB15#0	20.62	20.7	20.64		
3MHz 16QAM	RB1#0	21.18	20.84	20.72	18.6	38.45
	RB1#8	21.14	20.81	20.67		
	RB1#14	21.12	20.8	20.66		
	RB6#0	19.65	19.69	19.59		
	RB6#9	19.6	19.66	19.56		
	RB15#0	19.67	19.64	19.71		
5MHz QPSK	RB1#0	21.52	21.53	21.56	19.12	38.45
	RB1#13	21.7	21.67	21.68		
	RB1#24	21.56	21.55	21.56		
	RB15#0	20.64	20.7	20.69		
	RB15#10	20.62	20.68	20.64		
	RB25#0	20.59	20.67	20.66		
5MHz 16QAM	RB1#0	20.65	20.5	20.87	18.39	38.45
	RB1#13	20.75	20.6	20.97		
	RB1#24	20.69	20.48	20.86		
	RB15#0	19.66	19.71	19.65		
	RB15#10	19.64	19.71	19.64		
	RB25#0	19.62	19.78	19.67		
10MHz QPSK	RB1#0	20.67	21.7	21.62	19.21	38.45
	RB1#25	21.79	21.77	21.78		
	RB1#49	21.64	21.62	21.66		
	RB25#0	20.66	20.77	20.75		

	RB25#25	20.7	20.71	20.7		
	RB50#0	20.67	20.69	20.72		
10MHz 16QAM	RB1#0	21.24	20.79	20.66	18.76	38.45
	RB1#25	21.34	20.96	20.85		
	RB1#49	21.19	20.84	20.65		
	RB25#0	19.72	19.74	19.83		
	RB25#25	19.71	19.74	19.82		
	RB50#0	19.64	19.73	19.76		

Note:

ERP= Conducted Power(dBm) - Lc(dB) + G_T(dBd)G_T(dBd)=G_T(dBi)-2.15**Result:****Pass****Peak-to-average Ratio(PAR)**

Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
10MHz QPSK	RB1#0	5.03	4.29	5.1	13
	RB50#0	5.38	5.71	5.61	13
10MHz 16QAM	RB1#0	6.09	5.03	6.38	13
	RB50#0	6.19	6.57	6.44	13
				Result:	Pass

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
1.4MHz QPSK	1.098	1.098	1.098	1.314	1.296	1.296
1.4MHz 16QAM	1.092	1.098	1.104	1.296	1.296	1.314
3MHz QPSK	2.676	2.676	2.687	2.88	2.868	2.892
3MHz 16QAM	2.687	2.676	2.687	2.88	2.892	2.88
5MHz QPSK	4.52	4.52	4.5	4.94	4.88	4.94
5MHz 16QAM	4.52	4.5	4.5	5.8	4.9	4.94
10MHz QPSK	8.96	8.96	8.96	9.52	9.56	9.6
10MHz 16QAM	8.96	8.96	8.96	9.92	9.68	9.6

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--

Out of band emission, Band Edge







Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---

Frequency Stability					
Test Modulation:	10 MHz QPSK		Test Channel:	836.5	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	24	0.029	2.5
	-20	3.85	37	0.044	2.5
	-10	3.85	24	0.029	2.5
	0	3.85	15	0.018	2.5
	10	3.85	4	0.005	2.5
	20	3.85	4	0.005	2.5
	30	3.85	21	0.025	2.5
	40	3.85	22	0.026	2.5
	50	3.85	17	0.020	2.5
Frequency Stability vs. Voltage	20	3.4	14	0.017	2.5
	20	4.4	15	0.018	2.5
				Result:	Pass

Test Modulation:	10 MHz 16QAM		Test Channel:	836.5	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.85	33	0.039	2.5
	-20	3.85	29	0.035	2.5
	-10	3.85	25	0.030	2.5
	0	3.85	7	0.008	2.5
	10	3.85	10	0.012	2.5
	20	3.85	12	0.014	2.5
	30	3.85	17	0.020	2.5
	40	3.85	33	0.039	2.5
	50	3.85	41	0.049	2.5
Frequency Stability vs. Voltage	20	3.4	19	0.023	2.5
	20	4.4	25	0.030	2.5
				Result:	Pass

Test Plots(Note: The 14.5dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):

Occupied Bandwidth

Channel	1.4MHz Bandwidth QPSK	1.4MHz Bandwidth 16QAM
Lowest	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:42:56	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:43:17
Middle	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:43:34	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:43:53
Highest	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:44:20	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:44:44


Occupied Bandwidth

Channel


3MHz Bandwidth QPSK

3MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:45:43




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:46:03

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:46:27




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:46:47

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:47:11



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:47:35


Occupied Bandwidth

Channel


5MHz Bandwidth QPSK

5MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:49:15




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:49:48

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:50:08




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:50:28

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:50:55



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 15:51:22

Occupied Bandwidth



Channel	10MHz Bandwidth QPSK	10MHz Bandwidth 16QAM
Lowest	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:52:40	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:53:04
Middle	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:53:24	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:53:44
Highest	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:54:04	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:54:24

Spurious Emissions at Antenna Terminal



Channel

1.4MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

3MHz Bandwidth QPSK



Lowest



Middle



Highest




Spurious Emissions at Antenna Terminal


Channel

5MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:25:27




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:25:37

Middle




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:25:53




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:26:03

Highest



ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:26:16




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:26:26

Spurious Emissions at Antenna Terminal


Channel

10MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:27:29




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:27:43

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:27:55




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:28:06

Highest









ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:28:22




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:28:32







Out of band emission, Band Edge

Mode	Lowest	Highest
QPSK 1.4MHz	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:11:19	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:11:39
QPSK 3MHz	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:12:46	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:13:07
QPSK 5MHz	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:14:49	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:15:11



Out of band emission, Band Edge



Out of band emission, Band Edge

Mode	Lowest	Highest
16QAM 1.4MHz	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -21.54 dBm 824.000000000 MHz 30 Offset 14.5 dB 20 10 0 -10 -20 -30 -40 -50 -60 -70 Center 824 MHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:11:28	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -29.91 dBm 849.000000000 MHz 30 Offset 14.5 dB 20 10 0 -10 -20 -30 -40 -50 -60 -70 Center 849 MHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:11:49
16QAM 3MHz	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -34.77 dBm 824.000000000 MHz 30 Offset 14.5 dB 20 10 0 -10 -20 -30 -40 -50 -60 -70 Center 824 MHz 600 kHz/ Span 6 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:12:56	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -36.25 dBm 849.000000000 MHz 30 Offset 14.5 dB 20 10 0 -10 -20 -30 -40 -50 -60 -70 Center 849 MHz 600 kHz/ Span 6 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:13:18
16QAM 5MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -38.08 dBm 824.000000000 MHz 30 Offset 14.5 dB 20 10 0 -10 -20 -30 -40 -50 -60 -70 Center 824 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:15:00	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -39.61 dBm 849.000000000 MHz 30 Offset 14.5 dB 20 10 0 -10 -20 -30 -40 -50 -60 -70 Center 849 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:15:22

Out of band emission, Band Edge

Mode	Lowest	Highest
16QAM 10MHz	 Ref: 30 dBm, Offset: 14.5 dB, Att: 25 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 35 ms, Marker 1 [T1]: 823.95000000 MHz, -24.79 dBm Center: 824 MHz, Span: 20 MHz ProjectNo.: CR230953899-RF, Tester: Claire Liu, Date: 25.OCT.2023 20:16:32	 Ref: 30 dBm, Offset: 14.5 dB, Att: 25 dB, RBW: 100 kHz, VBW: 300 kHz, SWT: 35 ms, Marker 1 [T1]: 849.00000000 MHz, -27.97 dBm Center: 849 MHz, Span: 20 MHz ProjectNo.: CR230953899-RF, Tester: Claire Liu, Date: 25.OCT.2023 20:16:57

4.9 Antenna Port Test Data and Results for LTE Band 7

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
5MHz	2502.5	2535	2567.5
10MHz	2505	2535	2565
15MHz	2507.5	2535	2562.5
20MHz	2510	2535	2560

Test Data:

RF Output Power						
Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
5MHz QPSK	RB1#0	21.06	20.52	20.16	21.36	33
	RB1#13	21.13	20.53	20.28		
	RB1#24	20.99	20.44	20.16		
	RB15#0	20.12	19.58	19.33		
	RB15#10	20.1	19.58	19.31		
	RB25#0	20.09	19.55	19.26		
5MHz 16QAM	RB1#0	20.35	19.56	19.05	20.64	33
	RB1#13	20.41	19.63	19.18		
	RB1#24	20.27	19.5	19.07		
	RB15#0	19.16	18.62	18.36		
	RB15#10	19.1	18.62	18.33		
	RB25#0	19.11	18.56	18.31		
10MHz QPSK	RB1#0	21.11	20.63	20.31	21.42	33
	RB1#25	21.19	20.64	20.41		
	RB1#49	20.97	20.48	20.25		
	RB25#0	20.09	19.67	19.39		
	RB25#25	20.09	19.59	19.29		
	RB50#0	20.09	19.6	19.31		
10MHz 16QAM	RB1#0	20.14	20.23	19.45	20.46	33
	RB1#25	20.19	20.18	19.55		
	RB1#49	19.96	20.07	19.43		
	RB25#0	19.26	18.73	18.41		
	RB25#25	19.18	18.67	18.33		
	RB50#0	19.09	18.62	18.35		
15MHz QPSK	RB1#0	21.02	20.57	20.24	21.25	33
	RB1#38	21	20.53	20.35		
	RB1#74	20.81	20.34	20.19		
	RB36#0	20.09	19.66	19.4		
	RB36#39	20	19.62	19.38		
	RB75#0	20.06	19.64	19.37		
15MHz 16QAM	RB1#0	20.44	20.19	19.39	20.68	33
	RB1#38	20.45	20.17	19.47		
	RB1#74	20.24	19.98	19.31		
	RB36#0	19.13	18.69	18.4		
	RB36#39	19.02	18.59	18.34		
	RB75#0	19.08	18.63	18.37		
20MHz QPSK	RB1#0	20.89	20.55	20.16	21.3	33
	RB1#50	21.07	20.75	20.45		
	RB1#99	20.58	20.21	20.07		
	RB50#0	20.01	19.65	19.33		

	RB50#50	20.02	19.55	19.2		
	RB100#0	20.06	19.62	19.31		
20MHz 16QAM	RB1#0	20.49	19.85	19.33	20.9	33
	RB1#50	20.67	20.06	19.68		
	RB1#99	20.19	19.52	19.26		
	RB50#0	19.05	18.69	18.37		
	RB50#50	19.05	18.55	18.22		
	RB100#0	19.08	18.65	18.36		
Note: EIRP=Conducted Power(dBm) - Lc(dB) + G _T (dBi)						
					Result:	Pass

Peak-to-average Ratio(PAR)					
Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
20MHz QPSK	RB1#0	6.1	6.49	6.13	13
	RB100#0	6.44	6.41	6.38	13
20MHz 16QAM	RB1#0	7.26	7.63	7.52	13
	RB100#0	7.12	7.12	7.21	13
				Result:	Pass

Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
5MHz QPSK	4.52	4.52	4.52	5.3	4.94	5.28
5MHz 16QAM	4.52	4.5	4.52	4.92	4.96	4.98
10MHz QPSK	8.96	8.96	8.96	9.64	9.68	9.68
10MHz 16QAM	8.96	8.96	8.96	9.68	9.64	9.56
15MHz QPSK	13.5	13.56	13.56	14.64	14.76	14.76
15MHz 16QAM	13.5	13.56	13.56	14.64	14.7	14.64
20MHz QPSK	18	18	17.92	19.44	19.36	19.28
20MHz 16QAM	18	18	17.92	19.36	19.2	19.28
Note: The test plots please refer to the Plots of Occupied Bandwidth						

Spurious Emissions at Antenna Terminal	
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.

Out of band emission, Band Edge	
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.

Frequency Stability						
Test Mode:	20M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	2501.021	2500.00	2568.962	2570
	-20	3.85	2501.036	2500.00	2568.975	2570
	-10	3.85	2501.015	2500.00	2568.986	2570
	0	3.85	2501.024	2500.00	2568.969	2570
	10	3.85	2501.024	2500.00	2568.975	2570
	20	3.85	2501.040	2500.00	2568.960	2570
	30	3.85	2501.037	2500.00	2568.967	2570
	40	3.85	2501.032	2500.00	2568.977	2570
	50	3.85	2501.019	2500.00	2568.977	2570
Frequency Stability vs. Voltage	20	3.4	2501.030	2500.00	2568.978	2570
	20	4.4	2501.023	2500.00	2568.976	2570
					Result:	Pass

Test Mode:	20M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	2501.039	2500.00	2568.978	2570
	-20	3.85	2501.027	2500.00	2568.978	2570
	-10	3.85	2501.037	2500.00	2568.986	2570
	0	3.85	2501.032	2500.00	2568.975	2570
	10	3.85	2501.038	2500.00	2568.961	2570
	20	3.85	2501.040	2500.00	2568.960	2570
	30	3.85	2501.029	2500.00	2568.968	2570
	40	3.85	2501.034	2500.00	2568.978	2570
	50	3.85	2501.024	2500.00	2568.965	2570
Frequency Stability vs. Voltage	20	3.4	2501.031	2500.00	2568.964	2570
	20	4.4	2501.013	2500.00	2568.964	2570
					Result:	Pass

Test Plots(Note: The 14.5dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):

		Occupied Bandwidth	
Channel		5MHz Bandwidth QPSK	5MHz Bandwidth 16QAM
Lowest		ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:54:51	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:55:11
Middle		ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:55:31	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:55:51
Highest		ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:56:22	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 15:56:51


Occupied Bandwidth

Channel


15MHz Bandwidth QPSK

15MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:02:12




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:02:33

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:02:54




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:03:17

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:03:38



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:03:58


Occupied Bandwidth

Channel


20MHz Bandwidth QPSK

20MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:05:10




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:05:30

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:05:51




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:06:11

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:06:35





ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:06:59

Spurious Emissions at Antenna Terminal



Channel

5MHz Bandwidth QPSK



Lowest

ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:28:47ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:28:58

Middle

ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:29:11ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:29:21

Highest


ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:29:34ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:29:44

Spurious Emissions at Antenna Terminal


Channel

10MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:30:39




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:30:52

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:31:08




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:31:18

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:31:34




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:31:44

Spurious Emissions at Antenna Terminal


Channel

15MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:32:39




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:32:50

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:33:03




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:33:13

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:33:29




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:33:39

Spurious Emissions at Antenna Terminal


Channel

20MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:34:39




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:34:50

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:35:06




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:35:16

Highest








ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:35:32



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 21:35:43






Out of band emission, Band Edge

Mode	Lowest	Highest
QPSK 5MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -37.13 dBm 2.500000000 GHz Center 2.5 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:17:11	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -31.79 dBm 2.570000000 GHz Center 2.57 GHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:17:32
QPSK 10MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -37.13 dBm 2.499920000 GHz Center 2.5 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:18:32	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -30.33 dBm 2.570000000 GHz Center 2.57 GHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:18:56
QPSK 15MHz	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -31.76 dBm 2.500000000 GHz Center 2.5 GHz 3 MHz/ Span 30 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:19:56	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -33.19 dBm 2.570000000 GHz Center 2.57 GHz 3 MHz/ Span 30 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:20:16



Out of band emission, Band Edge

Mode	Lowest	Highest
QPSK 20MHz	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:21:14	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:21:33

Out of band emission, Band Edge

Mode	Lowest	Highest
16QAM 5MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -21.83 dBm 2.500000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:17:21	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -22.40 dBm 2.570000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:17:43
16QAM 10MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -30.20 dBm 2.500000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:18:43	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -40.98 dBm 2.570000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:19:08
16QAM 15MHz	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -33.21 dBm 2.500000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:20:06	 Ref 30 dBm * Att 25 dB * RBW 300 kHz * VBW 1 MHz * SWT 35 ms * Marker 1 [T1] -34.64 dBm 2.570000000 GHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:20:25

Out of band emission, Band Edge

Mode	Lowest	Highest
16QAM 20MHz	 Ref: 30 dBm Att: 25 dB RBW: 300 kHz VBW: 1 MHz SWT: 35 ms Marker 1 [T1] -29.57 dBm 2.500000000 GHz 30 Offset 14.5 dB -10 -20 -30 -40 -50 -60 -70 01 -13 dBm SWP 50 dB 50 SEL LVL 300 Center: 2.5 GHz 4 MHz/ Span: 40 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:21:23	 Ref: 30 dBm Att: 25 dB RBW: 300 kHz VBW: 1 MHz SWT: 35 ms Marker 1 [T1] -41.50 dBm 2.570000000 GHz 30 Offset 14.5 dB -10 -20 -30 -40 -50 -60 -70 01 -13 dBm SWP 50 dB 50 SEL LVL 300 Center: 2.57 GHz 4 MHz/ Span: 40 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:21:42

4.10 Antenna Port Test Data and Results for LTE Band 12

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
1.4MHz	699.7	707.5	715.3
3MHz	700.5	707.5	714.5
5MHz	701.5	707.5	713.5
10MHz	704	707.5	711

Test Data:

RF Output Power						
Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
1.4MHz QPSK	RB1#0	21.12	21.12	21.13	17.23	34.77
	RB1#3	21.3	21.24	21.27		
	RB1#5	21.1	21.09	21.1		
	RB3#0	21.25	21.18	21.24		
	RB3#3	21.23	21.18	21.23		
	RB6#0	20.19	20.14	20.17		
1.4MHz 16QAM	RB1#0	20.17	20.21	20.1	16.35	34.77
	RB1#3	20.34	20.4	20.33		
	RB1#5	20.2	20.22	20.11		
	RB3#0	20.42	20.16	20.27		
	RB3#3	20.42	20.22	20.26		
	RB6#0	19.32	19.27	19.21		
3MHz QPSK	RB1#0	21.23	21.12	21.24	17.17	34.77
	RB1#8	21.19	21.11	21.19		
	RB1#14	21.18	21.07	21.16		
	RB6#0	20.13	20.1	20.18		
	RB6#9	20.14	20.06	20.08		
	RB15#0	20.23	20.18	20.21		
3MHz 16QAM	RB1#0	20.31	20.77	20.33	16.7	34.77
	RB1#8	20.24	20.71	20.31		
	RB1#14	20.18	20.66	20.33		
	RB6#0	19.18	19.26	19.25		
	RB6#9	19.21	19.25	19.26		
	RB15#0	19.35	19.32	19.25		
5MHz QPSK	RB1#0	21.15	21.12	21.15	17.15	34.77
	RB1#13	21.22	21.14	21.19		
	RB1#24	21.08	21.07	21.05		
	RB15#0	20.29	20.13	20.27		
	RB15#10	20.17	20.17	20.17		
	RB25#0	20.18	20.13	20.23		
5MHz 16QAM	RB1#0	20.21	20	20.43	16.42	34.77
	RB1#13	20.33	20.11	20.49		
	RB1#24	20.19	20	20.39		
	RB15#0	19.43	19.26	19.35		
	RB15#10	19.28	19.3	19.26		
	RB25#0	19.31	19.29	19.32		
10MHz QPSK	RB1#0	21.2	21.18	21.16	17.27	34.77
	RB1#25	21.25	21.31	21.34		
	RB1#49	21.1	21.14	21.17		

	RB25#0	20.35	20.21	20.24		
	RB25#25	20.33	20.17	20.05		
	RB50#0	20.32	20.18	20.2		
10MHz 16QAM	RB1#0	20.83	20.33	20.19	16.86	34.77
	RB1#25	20.93	20.45	20.31		
	RB1#49	20.74	20.28	20.21		
	RB25#0	19.52	19.29	19.42		
	RB25#25	19.4	19.28	19.28		
	RB50#0	19.43	19.28	19.31		

Note:

ERP= Conducted Power(dBm) - Lc(dB) + G_T(dBd)G_T(dBd)=G_T(dBi)-2.15**Result:****Pass****Peak-to-average Ratio(PAR)**

Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
10MHz QPSK	RB1#0	5.26	5.1	6.03	13
	RB50#0	5.74	5.83	5.67	13
10MHz 16QAM	RB1#0	6.15	5.93	7.12	13
	RB50#0	6.54	6.67	6.57	13
				Result:	Pass

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
1.4MHz QPSK	1.098	1.11	1.098	1.32	1.296	1.302
1.4MHz 16QAM	1.092	1.098	1.104	1.284	1.296	1.326
3MHz QPSK	2.676	2.687	2.687	2.892	2.88	2.88
3MHz 16QAM	2.687	2.687	2.687	2.904	2.904	2.88
5MHz QPSK	4.52	4.54	4.52	5.14	5.08	5.14
5MHz 16QAM	4.54	4.52	4.54	5.18	5.12	5.14
10MHz QPSK	8.96	9	8.96	9.76	9.88	9.72
10MHz 16QAM	8.96	8.96	8.96	9.8	9.88	9.68

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--

Out of band emission, Band Edge

Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---

Frequency Stability						
Test Mode:	10M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	699.507	699.00	715.498	716.00
	-20	3.85	699.494	699.00	715.507	716.00
	-10	3.85	699.517	699.00	715.499	716.00
	0	3.85	699.494	699.00	715.506	716.00
	10	3.85	699.502	699.00	715.508	716.00
	20	3.85	699.520	699.00	715.480	716.00
	30	3.85	699.511	699.00	715.507	716.00
	40	3.85	699.512	699.00	715.485	716.00
	50	3.85	699.518	699.00	715.502	716.00
Frequency Stability vs. Voltage	20	3.4	699.502	699.00	715.496	716.00
	20	4.4	699.514	699.00	715.492	716.00
					Result:	Pass

Test Mode:	10M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	699.505	699.00	715.498	716.00
	-20	3.85	699.497	699.00	715.499	716.00
	-10	3.85	699.506	699.00	715.485	716.00
	0	3.85	699.520	699.00	715.498	716.00
	10	3.85	699.494	699.00	715.482	716.00
	20	3.85	699.520	699.00	715.480	716.00
	30	3.85	699.493	699.00	715.497	716.00
	40	3.85	699.513	699.00	715.503	716.00
	50	3.85	699.503	699.00	715.487	716.00
Frequency Stability vs. Voltage	20	3.4	699.493	699.00	715.498	716.00
	20	4.4	699.495	699.00	715.494	716.00
					Result:	Pass

Test Plots(Note: The 14.5dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):

Occupied Bandwidth

Channel	1.4MHz Bandwidth QPSK	1.4MHz Bandwidth 16QAM
Lowest	Ref 30 dBm *Att 25 dB *RBW 30 kHz Delta 1 [T1] -0.49 dB *VBW 100 kHz 1.320000000 MHz SWT 15 ms 30 Offset 14.5 dB Q1 14.06 dBm Q2 -11.04 dBm Center 699.7 MHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:08:02	Ref 30 dBm *Att 25 dB *RBW 30 kHz Delta 1 [T1] 0.90 dB *VBW 100 kHz 1.294000000 MHz SWT 15 ms 30 Offset 14.5 dB Q1 13.77 dBm Q2 -12.23 dBm Center 699.7 MHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:08:25
Middle	Ref 30 dBm *Att 25 dB *RBW 30 kHz Delta 1 [T1] 1.25 dB *VBW 100 kHz 1.296000000 MHz SWT 15 ms 30 Offset 14.5 dB Q1 14.61 dBm Q2 -11.39 dBm Center 707.5 MHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:08:46	Ref 30 dBm *Att 25 dB *RBW 30 kHz Delta 1 [T1] 0.10 dB *VBW 100 kHz 1.296000000 MHz SWT 15 ms 30 Offset 14.5 dB Q1 14.62 dBm Q2 -11.38 dBm Center 707.5 MHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:09:06
Highest	Ref 30 dBm *Att 25 dB *RBW 30 kHz Delta 1 [T1] -0.86 dB *VBW 100 kHz 1.302000000 MHz SWT 15 ms 30 Offset 14.5 dB Q1 14.81 dBm Q2 -11.19 dBm Center 715.3 MHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:09:33	Ref 30 dBm *Att 25 dB *RBW 30 kHz Delta 1 [T1] -0.70 dB *VBW 100 kHz 1.326000000 MHz SWT 15 ms 30 Offset 14.5 dB Q1 14.44 dBm Q2 -11.56 dBm Center 715.3 MHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:09:53


Occupied Bandwidth

Channel


3MHz Bandwidth QPSK

3MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:10:52




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:11:25

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:11:46




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:12:06

Highest



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:12:27



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:12:47


Occupied Bandwidth

Channel


5MHz Bandwidth QPSK

5MHz Bandwidth 16QAM

Lowest




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:13:50




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:14:09

Middle




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:14:30




ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:14:53

Highest









ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:15:13



ProjectNo.:CR230953899-RF Tester:Claire Liu
Date: 25.OCT.2023 16:15:37

Occupied Bandwidth



Channel	10MHz Bandwidth QPSK	10MHz Bandwidth 16QAM
Lowest	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz SWT 10 ms Delta 1 [T1] 1.49 dB 9.760000000 MHz OSW 9.960000000 MHz Marker 1 [T1] -14.5 dBm 659.120000000 MHz Temp 1 [T1 OSW] 659.520000000 MHz Temp 2 [T1 OSW] 709.480000000 MHz Center 704 MHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:16:39	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz SWT 10 ms Delta 1 [T1] 0.11 dB 9.800000000 MHz OSW 9.960000000 MHz Marker 1 [T1] -14.5 dBm 659.160000000 MHz Temp 1 [T1 OSW] 659.520000000 MHz Temp 2 [T1 OSW] 709.480000000 MHz Center 704 MHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:16:59
Middle	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz SWT 10 ms Delta 1 [T1] -0.93 dB 9.800000000 MHz OSW 9.960000000 MHz Marker 1 [T1] -14.5 dBm 702.540000000 MHz Temp 1 [T1 OSW] 702.980000000 MHz Temp 2 [T1 OSW] 711.980000000 MHz Center 707.5 MHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:17:19	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz SWT 10 ms Delta 1 [T1] 2.44 dB 9.800000000 MHz OSW 9.960000000 MHz Marker 1 [T1] -14.5 dBm 702.540000000 MHz Temp 1 [T1 OSW] 702.980000000 MHz Temp 2 [T1 OSW] 711.980000000 MHz Center 707.5 MHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:17:39
Highest	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz SWT 10 ms Delta 1 [T1] -0.28 dB 9.720000000 MHz OSW 9.960000000 MHz Marker 1 [T1] -14.5 dBm 706.120000000 MHz Temp 1 [T1 OSW] 706.520000000 MHz Temp 2 [T1 OSW] 715.480000000 MHz Center 711 MHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:17:59	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz SWT 10 ms Delta 1 [T1] 0.62 dB 9.680000000 MHz OSW 9.960000000 MHz Marker 1 [T1] -14.5 dBm 706.120000000 MHz Temp 1 [T1 OSW] 706.520000000 MHz Temp 2 [T1 OSW] 715.480000000 MHz Center 711 MHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:18:19

Spurious Emissions at Antenna Terminal



Channel

1.4MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

3MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

5MHz Bandwidth QPSK



Lowest



Middle



Highest




Spurious Emissions at Antenna Terminal


Channel

10MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:42:11




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:42:21

Middle




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:42:34




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:42:44

Highest









ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:42:57



ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:43:07







Out of band emission, Band Edge

Mode	Lowest	Highest
QPSK 1.4MHz	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 100 kHz *SWT 35 ms Marker 1 [T1] -31.53 dBm 699.000000000 MHz 30 Offset 14.5 dB 50 dB 50 dB 50 dB Center 699 MHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:22:33	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 100 kHz *SWT 35 ms Marker 1 [T1] -32.43 dBm 716.000000000 MHz 30 Offset 14.5 dB 50 dB 50 dB 50 dB Center 716 MHz 300 kHz/ Span 3 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:22:53
QPSK 3MHz	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 300 kHz *SWT 35 ms Marker 1 [T1] -37.35 dBm 699.000000000 MHz 30 Offset 14.5 dB 50 dB 50 dB 50 dB Center 699 MHz 600 kHz/ Span 6 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:23:54	 Ref 30 dBm *Att 25 dB *RBW 30 kHz *VBW 300 kHz *SWT 35 ms Marker 1 [T1] -38.16 dBm 716.000000000 MHz 30 Offset 14.5 dB 50 dB 50 dB 50 dB Center 716 MHz 600 kHz/ Span 6 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:24:15
QPSK 5MHz	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz *SWT 35 ms Marker 1 [T1] -26.37 dBm 699.000000000 MHz 30 Offset 14.5 dB 50 dB 50 dB 50 dB Center 699 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:25:16	 Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz *SWT 35 ms Marker 1 [T1] -26.50 dBm 716.000000000 MHz 30 Offset 14.5 dB 50 dB 50 dB 50 dB Center 716 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:25:39

Out of band emission, Band Edge

Mode	Lowest	Highest
QPSK 10MHz	Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz *SMT 35 ms Marker 1 [F2] -33.95 dBm 699.000000000 MHz 30 dBm 30dB Center 699 MHz 2 MHz/ Span 20 MHz	Ref 30 dBm *Att 25 dB *RBW 100 kHz *VBW 300 kHz *SMT 35 ms Marker 1 [F2] -35.06 dBm 716.000000000 MHz 30 dBm 30dB Center 716 MHz 2 MHz/ Span 20 MHz
	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:26:40	ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:27:04

Out of band emission, Band Edge

Mode	Lowest	Highest
16QAM 1.4MHz	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -27.52 dBm 699.000000000 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:22:43	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -23.95 dBm 716.000000000 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:23:02
16QAM 3MHz	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -27.16 dBm 699.000000000 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:24:05	 Ref 30 dBm * Att 25 dB * RBW 30 kHz * VBW 100 kHz * SWT 35 ms * Marker 1 [T1] -28.42 dBm 716.000000000 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:24:25
16QAM 5MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -27.62 dBm 699.000000000 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:25:29	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -27.34 dBm 716.000000000 MHz ProjectNo.:CR230953899-RF Tester: Claire Liu Date: 25.OCT.2023 20:25:48

Page 148 of 289

4.11 Antenna Port Test Data and Results for LTE Band 17

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
5MHz	706.5	710	713.5
10MHz	709	710	711

Test Data:**RF Output Power**

Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
5MHz QPSK	RB1#0	21.17	21.1	21.14	17.2	34.77
	RB1#13	21.24	21.19	21.27		
	RB1#24	21.13	21.05	21.05		
	RB15#0	20.19	20.21	20.3		
	RB15#10	20.26	20.16	20.15		
	RB25#0	20.21	20.15	20.17		
5MHz 16QAM	RB1#0	20.42	20.14	20	16.48	34.77
	RB1#13	20.55	20.22	20.12		
	RB1#24	20.46	20.16	20.01		
	RB15#0	19.26	19.31	19.44		
	RB15#10	19.32	19.27	19.29		
	RB25#0	19.31	19.26	19.34		
10MHz QPSK	RB1#0	21.18	21.27	21.23	17.32	34.77
	RB1#25	21.36	21.39	21.36		
	RB1#49	21.18	21.23	21.18		
	RB25#0	20.26	20.22	20.24		
	RB25#25	20.15	20.12	20.12		
	RB50#0	20.19	20.21	20.23		
10MHz 16QAM	RB1#0	20.84	20.38	20.28	16.87	34.77
	RB1#25	20.94	20.56	20.38		
	RB1#49	20.8	20.36	20.23		
	RB25#0	19.36	19.35	19.49		
	RB25#25	19.34	19.25	19.36		
	RB50#0	19.33	19.33	19.34		

Note:

ERP= Conducted Power(dBm) - Lc(dB) + G_T(dBd)G_T(dBd)=G_T(dBi)-2.15**Result:****Pass****Peak-to-average Ratio(PAR)**

Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
10MHz QPSK	RB1#0	5.54	5.61	6.03	13
	RB50#0	5.8	5.74	5.67	13
10MHz 16QAM	RB1#0	6.86	6.28	6.63	13
	RB50#0	6.51	6.6	6.51	13
				Result:	Pass

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
5MHz QPSK	4.52	4.54	4.54	5.14	5.16	5.14
5MHz 16QAM	4.52	4.54	4.52	5.18	5.16	5.12
10MHz QPSK	8.96	8.96	8.96	9.92	9.88	9.76
10MHz 16QAM	8.96	8.96	8.96	9.84	9.68	9.76
Note: The test plots please refer to the Plots of Occupied Bandwidth						

Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--

Out of band emission, Band Edge

Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---

Frequency Stability







Test Mode:	10M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	704.512	704.00	715.488	716.00
	-20	3.85	704.512	704.00	715.502	716.00
	-10	3.85	704.510	704.00	715.502	716.00
	0	3.85	704.502	704.00	715.495	716.00
	10	3.85	704.507	704.00	715.495	716.00
	20	3.85	704.520	704.00	715.480	716.00
	30	3.85	704.516	704.00	715.489	716.00
	40	3.85	704.495	704.00	715.508	716.00
	50	3.85	704.519	704.00	715.501	716.00
Frequency Stability vs. Voltage	20	3.4	704.519	704.00	715.504	716.00
	20	4.4	704.497	704.00	715.492	716.00
Result:					Pass	

Test Mode:	10M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	704.509	704.00	715.487	716.00
	-20	3.85	704.511	704.00	715.507	716.00
	-10	3.85	704.501	704.00	715.494	716.00
	0	3.85	704.494	704.00	715.488	716.00
	10	3.85	704.516	704.00	715.490	716.00
	20	3.85	704.520	704.00	715.480	716.00

Frequency Stability vs. Voltage	30	3.85	704.499	704.00	715.496	716.00
	40	3.85	704.501	704.00	715.495	716.00
	50	3.85	704.504	704.00	715.487	716.00
	20	3.4	704.519	704.00	715.490	716.00
	20	4.4	704.494	704.00	715.507	716.00
					Result:	Pass

Test Plots(Note: The 14.5dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):

Occupied Bandwidth



Channel	5MHz Bandwidth QPSK	5MHz Bandwidth 16QAM
Lowest	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:18:42	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:19:02
Middle	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:19:25	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:19:45
Highest	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:20:06	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:20:29

Spurious Emissions at Antenna Terminal



Channel

5MHz Bandwidth QPSK



Lowest

ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:43:23ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:43:33

Middle

ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:43:46ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:43:56

Highest


ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:44:09ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:44:19

Spurious Emissions at Antenna Terminal


Channel

10MHz Bandwidth QPSK

Lowest




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:45:13




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:45:24

Middle




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:45:16




ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:45:47

Highest







ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:45:19







ProjectNo.:CR230953899-RF Tester: Claire Liu
Date: 25.OCT.2023 21:46:10

Out of band emission, Band Edge

Mode	Lowest	Highest
QPSK 5MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -24.71 dBm 704.00000000 MHz Center 704 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:27:30	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -26.84 dBm 716.00000000 MHz Center 716 MHz 1 MHz/ Span 10 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:27:52
QPSK 10MHz	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -32.83 dBm 704.00000000 MHz Center 704 MHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:28:53	 Ref 30 dBm * Att 25 dB * RBW 100 kHz * VBW 300 kHz * SWT 35 ms * Marker 1 [T1] -35.44 dBm 716.00000000 MHz Center 716 MHz 2 MHz/ Span 20 MHz ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:29:17

Out of band emission, Band Edge

Mode	Lowest	Highest
16QAM 5MHz	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:27:42	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:28:01
16QAM 10MHz	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:29:05	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 20:29:07

4.12 Antenna Port Test Data and Results for LTE Band 25

Serial Number:	2B7S-2	Test Date:	2023/10/17~2023/10/26
Test Site:	RF	Test Mode:	Transmitting
Tester:	Arthur Su/Claire Liu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.2~26.3	Relative Humidity: (%)	52~60	ATM Pressure: (kPa)	100.9~101.5
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100001	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
Weinschel	Power Splitter	1515	RA914	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2023/9/28	2024/9/27
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
1.4MHz	1850.7	1882.5	1914.3
3MHz	1851.5	1882.5	1913.5
5MHz	1852.5	1882.5	1912.5
10MHz	1855	1882.5	1910
15MHz	1857.5	1882.5	1907.5
20MHz	1860	1882.5	1905

Test Data:

RF Output Power						
Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
1.4MHz QPSK	RB1#0	21.04	20.82	20.64	21.73	33
	RB1#3	21.19	20.98	20.77		
	RB1#5	21.04	20.74	20.56		
	RB3#0	21.12	20.83	20.68		
	RB3#3	21.18	20.87	20.66		
	RB6#0	20.11	19.82	19.67		
1.4MHz 16QAM	RB1#0	20.13	19.75	19.64	20.89	33
	RB1#3	20.35	19.94	19.76		
	RB1#5	20.16	19.78	19.6		
	RB3#0	20.06	19.86	19.86		
	RB3#3	20.09	19.88	19.83		
	RB6#0	19.09	18.79	18.72		
3MHz QPSK	RB1#0	21.01	20.83	20.65	21.57	33
	RB1#8	21.03	20.81	20.62		
	RB1#14	21.02	20.76	20.61		
	RB6#0	20.04	19.7	19.7		
	RB6#9	20.02	19.73	19.63		
	RB15#0	20.02	19.78	19.67		
3MHz 16QAM	RB1#0	20.19	19.83	20.19	20.73	33
	RB1#8	20.19	19.76	20.14		
	RB1#14	20.16	19.74	20.1		
	RB6#0	19.03	18.71	18.73		
	RB6#9	19.05	18.68	18.72		
	RB15#0	19.01	18.83	18.75		
5MHz QPSK	RB1#0	20.97	20.7	20.58	21.57	33
	RB1#13	21.03	20.78	20.7		
	RB1#24	20.95	20.71	20.49		
	RB15#0	19.98	19.79	19.8		
	RB15#10	20.04	19.78	19.61		
	RB25#0	19.97	19.78	19.67		
5MHz 16QAM	RB1#0	20.27	19.8	19.48	20.89	33
	RB1#13	20.35	19.84	19.54		
	RB1#24	20.19	19.79	19.46		
	RB15#0	18.94	18.84	18.82		
	RB15#10	19.03	18.82	18.64		
	RB25#0	18.95	18.79	18.73		
10MHz QPSK	RB1#0	21.02	20.78	20.66	21.68	33
	RB1#25	21.14	20.93	20.81		
	RB1#49	20.95	20.72	20.58		
	RB25#0	19.96	19.82	19.75		

	RB25#25	19.92	19.76	19.55		
	RB50#0	19.95	19.81	19.66		
10MHz 16QAM	RB1#0	20.02	20.39	19.78	20.94	33
	RB1#25	20.08	20.4	19.93		
	RB1#49	20	20.3	19.77		
	RB25#0	19.02	18.84	18.77		
	RB25#25	19	18.82	18.58		
	RB50#0	18.96	18.82	18.66		
	RB1#0	20.95	20.83	20.62		
15MHz QPSK	RB1#38	20.98	20.79	20.67	21.52	33
	RB1#74	20.86	20.81	20.56		
	RB36#0	20.06	19.91	19.75		
	RB36#39	19.99	19.82	19.67		
	RB75#0	19.97	19.82	19.7		
	RB1#0	20.52	19.98	20.05	21.08	33
15MHz 16QAM	RB1#38	20.54	19.93	20.02		
	RB1#74	20.43	19.76	19.93		
	RB36#0	19.02	18.87	18.71		
	RB36#39	18.94	18.79	18.57		
	RB75#0	18.96	18.86	18.67		
	RB1#0	20.86	20.69	20.5	21.72	33
20MHz QPSK	RB1#50	21.18	20.9	20.83		
	RB1#99	20.78	20.46	20.43		
	RB50#0	20.06	19.85	19.74		
	RB50#50	19.94	19.68	19.48		
	RB100#0	20.03	19.8	19.61		
	RB1#0	20.05	20.29	19.85	20.98	33
20MHz 16QAM	RB1#50	20.38	20.44	20.14		
	RB1#99	19.96	20.05	19.74		
	RB50#0	19.03	18.83	18.75		
	RB50#50	18.94	18.67	18.46		
	RB100#0	19.02	18.8	18.65		

Note: EIRP=Conducted Power(dBm) - L_C(dB) + G_T(dBi)

Result: Pass

Peak-to-average Ratio(PAR)

Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
20MHz QPSK	RB1#0	6.64	6.26	6.48	13
	RB100#0	6.31	6.44	6.54	13
20MHz 16QAM	RB1#0	7.1	7.22	7.84	13
	RB100#0	7.02	7.24	7.15	13
				Result:	Pass

Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
1.4MHz QPSK	1.104	1.104	1.098	1.308	1.308	1.296
1.4MHz 16QAM	1.092	1.098	1.11	1.296	1.308	1.308
3MHz QPSK	2.687	2.687	2.7	2.892	2.868	2.88
3MHz 16QAM	2.687	2.676	2.676	2.88	2.892	2.88
5MHz QPSK	4.54	4.54	4.54	5.2	5.14	5.18
5MHz 16QAM	4.54	4.54	4.54	5.16	5.16	5.1
10MHz QPSK	8.96	8.96	8.96	9.76	9.88	9.72
10MHz 16QAM	8.96	8.96	8.92	9.84	9.72	9.8
15MHz QPSK	13.44	13.5	13.44	15.06	15.18	15
15MHz 16QAM	13.5	13.5	13.44	14.94	15.12	14.88
20MHz QPSK	17.92	17.92	17.84	19.6	19.52	19.28
20MHz 16QAM	17.92	18	17.92	19.52	19.44	19.6

Note: The test plots please refer to the Plots of Occupied Bandwidth

Spurious Emissions at Antenna Terminal

Result: Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.

Out of band emission, Band Edge

Result: Pass, Please refer to the test plots of Out of band emission, Band Edge.

Frequency Stability







Test Mode:	20M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1851.027	1850.000	1913.890	1915.000
	-20	3.85	1851.036	1850.000	1913.891	1915.000
	-10	3.85	1851.038	1850.000	1913.902	1915.000
	0	3.85	1851.037	1850.000	1913.887	1915.000
	10	3.85	1851.039	1850.000	1913.891	1915.000
	20	3.85	1851.040	1850.000	1913.880	1915.000
	30	3.85	1851.017	1850.000	1913.887	1915.000
	40	3.85	1851.025	1850.000	1913.882	1915.000
	50	3.85	1851.026	1850.000	1913.892	1915.000
Frequency Stability vs. Voltage	20	3.4	1851.021	1850.000	1913.886	1915.000
	20	4.4	1851.021	1850.000	1913.893	1915.000
					Result:	Pass

Test Mode:	20M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
------------	-----------	--	--	--	--	--

Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1851.019	1850.000	1913.975	1915.000
	-20	3.85	1851.027	1850.000	1913.978	1915.000
	-10	3.85	1851.036	1850.000	1913.970	1915.000
	0	3.85	1851.028	1850.000	1913.977	1915.000
	10	3.85	1851.037	1850.000	1913.986	1915.000
	20	3.85	1851.040	1850.000	1913.960	1915.000
	30	3.85	1851.013	1850.000	1913.982	1915.000
	40	3.85	1851.020	1850.000	1913.977	1915.000
	50	3.85	1851.024	1850.000	1913.983	1915.000
Frequency Stability vs. Voltage	20	3.4	1851.026	1850.000	1913.973	1915.000
	20	4.4	1851.031	1850.000	1913.971	1915.000
					Result:	Pass

Test Plots(Note: The 14.5dB is the Insertion loss of the RF cable, Power Splitter and DC Block, which was offset into the Spectrum Analyzer):

Occupied Bandwidth

Channel	1.4MHz Bandwidth QPSK	1.4MHz Bandwidth 16QAM
Lowest	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:23:36	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:23:56
Middle	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:24:16	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:24:48
Highest	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:25:03	 ProjectNo.:CR230953899-RF Tester:Claire Liu Date: 25.OCT.2023 16:25:26