

# TEST REPORT

**Applicant:** Shanghai Xiangcheng Communication Technology Co., Ltd.  
**Address:** 5F-6F, Building 10, No.3000 Longdong Avenue, Pudong New District, Shanghai City, China  
**Equipment Type:** Intelligent Mobile Data Capture Terminal  
**Model Name:** Ranger 2(N) (refer to section 2.3)  
**Brand Name:** N/A  
**FCC ID:** 2A2UU-MF-T2351  
**Test Standard:** 47 CFR Part 15 Subpart C (refer to section 3.1)  
**Sample Arrival Date:** Aug. 08, 2025  
**Test Date:** Aug. 11, 2025 - Aug. 18, 2025  
**Date of Issue:** Sep. 19, 2025

**ISSUED BY:**

Shanghai Tejet Communications Technology Co., Ltd. Testing Center

**Prepared by:** Zhang Rujie

**Reviewed by:** Hai Su

**Approved by:** Zhang Yanqing

(Laboratory Manager)

Zhang Rujie

Hai Su

Zhang Yanqing

### Revision History

| Version        | Issue Date           | Revisions            |
|----------------|----------------------|----------------------|
| <u>Rev. 01</u> | <u>Sep. 19, 2025</u> | <u>Initial Issue</u> |

## TABLE OF CONTENTS

|     |                                                          |    |
|-----|----------------------------------------------------------|----|
| 1   | GENERAL INFORMATION .....                                | 4  |
| 1.1 | Test Laboratory .....                                    | 4  |
| 1.2 | Test Location .....                                      | 4  |
| 2   | PRODUCT INFORMATION .....                                | 5  |
| 2.1 | Applicant Information .....                              | 5  |
| 2.2 | Manufacturer Information .....                           | 5  |
| 2.3 | General Description for Equipment under Test (EUT) ..... | 5  |
| 2.4 | Technical Information .....                              | 6  |
| 3   | SUMMARY OF TEST RESULTS .....                            | 8  |
| 3.1 | Test Standards .....                                     | 8  |
| 3.2 | Test Verdict .....                                       | 9  |
| 4   | GENERAL TEST CONFIGURATIONS .....                        | 10 |
| 4.1 | Test Environments .....                                  | 10 |
| 4.2 | Test Equipment List .....                                | 10 |
| 4.3 | Test Software List .....                                 | 10 |
| 4.4 | Decision Rule .....                                      | 11 |
| 4.5 | Measurement Uncertainty .....                            | 11 |
| 4.6 | Description of Test Setup .....                          | 12 |
| 4.7 | Measurement Results Explanation Example .....            | 15 |
| 5   | TEST ITEMS .....                                         | 16 |
| 5.1 | Antenna Requirements .....                               | 16 |
| 5.2 | Frequency Hopping Systems .....                          | 17 |
| 5.3 | Number of Hopping Frequencies .....                      | 19 |
| 5.4 | Peak Output Power .....                                  | 20 |
| 5.5 | Occupied Bandwidth .....                                 | 21 |

|         |                                                                |    |
|---------|----------------------------------------------------------------|----|
| 5.6     | Carrier Frequency Separation.....                              | 22 |
| 5.7     | Time of Occupancy (Dwell time) .....                           | 23 |
| 5.8     | Conducted Spurious Emission & Authorized-band band-edge.....   | 25 |
| 5.9     | Conducted Emission.....                                        | 26 |
| 5.10    | Radiated Spurious Emission .....                               | 27 |
| 5.11    | Band Edge (Restricted-band band-edge).....                     | 29 |
| ANNEX A | TEST RESULT .....                                              | 30 |
| A.1     | Number of Hopping Frequencies .....                            | 30 |
| A.2     | Peak Output Power .....                                        | 31 |
| A.3     | Occupied Bandwidth.....                                        | 34 |
| A.4     | Carrier Frequency Separation.....                              | 39 |
| A.5     | Time of Occupancy (Dwell time) .....                           | 40 |
| A.6     | Conducted Spurious Emissions & Authorized-band band-edge ..... | 43 |
| A.7     | Conducted Emission.....                                        | 52 |
| A.8     | Radiated Spurious Emission .....                               | 54 |
| A.9     | Band Edge (Restricted-band band-edge).....                     | 60 |
| ANNEX B | TEST SETUP PHOTOS .....                                        | 64 |
| ANNEX C | EUT EXTERNAL PHOTOS.....                                       | 64 |
| ANNEX D | EUT INTERNAL PHOTOS.....                                       | 64 |

# 1 GENERAL INFORMATION

## 1.1 Test Laboratory

|         |                                                                                          |
|---------|------------------------------------------------------------------------------------------|
| Name    | Shanghai Tejet Communications Technology Co., Ltd. Testing Center                        |
| Address | 1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China |

## 1.2 Test Location

|                           |                                                                                                                                  |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Name                      | Shanghai Tejet Communications Technology Co., Ltd. Testing Center                                                                |
| Location                  | 1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China                                         |
| Accreditation Certificate | The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352. |

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

|           |                                                                                        |
|-----------|----------------------------------------------------------------------------------------|
| Applicant | Shanghai Xiangcheng Communication Technology Co., Ltd.                                 |
| Address   | 5F-6F, Building 10, No.3000 Longdong Avenue, Pudong New District, Shanghai City, China |

### 2.2 Manufacturer Information

|              |                                                                                        |
|--------------|----------------------------------------------------------------------------------------|
| Manufacturer | Shanghai Xiangcheng Communication Technology Co., Ltd.                                 |
| Address      | 5F-6F, Building 10, No.3000 Longdong Avenue, Pudong New District, Shanghai City, China |

### 2.3 General Description for Equipment under Test (EUT)

|                                           |                                                                                                                                                                              |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EUT Name                                  | Intelligent Mobile Data Capture Terminal                                                                                                                                     |
| Model Name Under Test                     | Ranger 2(N)                                                                                                                                                                  |
| Series Model Name                         | Ranger 2/N, Ranger2(N), Ranger2/N, RANGER 2(N), RANGER 2/N, Ranger2 Nova, Ranger2 Ultra, M5 Pro, EM5 Pro, M5 PRO, MF50C, MF50N, MF50P, MF50 Pro, MF50 Nova, T23, T2351, T23X |
| Description of Model name differentiation | All the same except for the model name. (this information provided by the applicant)                                                                                         |
| Sample Number                             | SC-SH2580034-S04(conducted)<br>SC-SH2580034-S01(radiated)<br>SC-SH2580034-S03(radiated)                                                                                      |
| Hardware Version                          | V1.0                                                                                                                                                                         |
| Software Version                          | 1.0.0                                                                                                                                                                        |
| Dimensions (Approx.)                      | N/A                                                                                                                                                                          |
| Weight (Approx.)                          | N/A                                                                                                                                                                          |

## 2.4 Technical Information

|                                   |                                                                                                                                                                                                                                      |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network and Wireless connectivity | 2G Network GSM/GPRS/EDGE 850/1900<br>3G Network WCDMA/HSDPA/HSUPA/HSPA+ Band 2/4/5<br>4G Network FDD LTE Band 2/4/5/7/12/13/17/25/26/66/71<br>TDD LTE Band 38/41<br>Bluetooth, 2.4G WIFI, 5G WIFI<br>GPS, GLONASS, BDS, Galileo, NFC |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

The requirement for the following technical information of the EUT was tested in this report:

|                                     |                                                     |
|-------------------------------------|-----------------------------------------------------|
| Modulation Technology               | FHSS                                                |
| Modulation Type                     | GFSK, $\pi/4$ -DQPSK, 8-DPSK                        |
| Transfer Rate                       | DH5: 1 Mbps<br>2DH5: 2 Mbps<br>3DH5: 3 Mbps         |
| Frequency Range                     | The frequency range used is 2400 MHz to 2483.5 MHz. |
| Number of Channel                   | 79 (at intervals of 1 MHz)                          |
| Tested Channel                      | 0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)          |
| Antenna Type                        | PIFA Antenna                                        |
| Antenna Gain                        | 1.90 dBi                                            |
| Antenna Impedance                   | 50 $\Omega$                                         |
| Antenna System (MIMO Smart Antenna) | N/A                                                 |

All channel was listed on the following table:

| Channel number | Freq. (MHz) | Channel number | Freq. (MHz) | Channel number | Freq. (MHz) | Channel number | Freq. (MHz) |
|----------------|-------------|----------------|-------------|----------------|-------------|----------------|-------------|
| <b>0</b>       | <b>2402</b> | 21             | 2423        | 42             | 2444        | 63             | 2465        |
| 1              | 2403        | 22             | 2424        | 43             | 2445        | 64             | 2466        |
| 2              | 2404        | 23             | 2425        | 44             | 2446        | 65             | 2467        |
| 3              | 2405        | 24             | 2426        | 45             | 2447        | 66             | 2468        |
| 4              | 2406        | 25             | 2427        | 46             | 2448        | 67             | 2469        |
| 5              | 2407        | 26             | 2428        | 47             | 2449        | 68             | 2470        |
| 6              | 2408        | 27             | 2429        | 48             | 2450        | 69             | 2471        |
| 7              | 2409        | 28             | 2430        | 49             | 2451        | 70             | 2472        |
| 8              | 2410        | 29             | 2431        | 50             | 2452        | 71             | 2473        |
| 9              | 2411        | 30             | 2432        | 51             | 2453        | 72             | 2474        |
| 10             | 2412        | 31             | 2433        | 52             | 2454        | 73             | 2475        |
| 11             | 2413        | 32             | 2434        | 53             | 2455        | 74             | 2476        |
| 12             | 2414        | 33             | 2435        | 54             | 2456        | 75             | 2477        |
| 13             | 2415        | 34             | 2436        | 55             | 2457        | 76             | 2478        |
| 14             | 2416        | 35             | 2437        | 56             | 2458        | 77             | 2479        |
| 15             | 2417        | 36             | 2438        | 57             | 2459        | <b>78</b>      | <b>2480</b> |
| 16             | 2418        | 37             | 2439        | 58             | 2460        | -              | -           |
| 17             | 2419        | 38             | 2440        | 59             | 2461        | -              | -           |
| 18             | 2420        | <b>39</b>      | <b>2441</b> | 60             | 2462        | -              | -           |
| 19             | 2421        | 40             | 2442        | 61             | 2463        | -              | -           |
| 20             | 2422        | 41             | 2443        | 62             | 2464        | -              | -           |

### 3 SUMMARY OF TEST RESULTS

#### 3.1 Test Standards

| No. | Identity                                      | Document Title                                                                                                                                                                           |
|-----|-----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | 47 CFR Part 15 Subpart C                      | Intentional radiators of radio frequency equipment                                                                                                                                       |
| 2   | ANSI C63.10-2020                              | American National Standard for Testing Unlicensed Wireless Devices                                                                                                                       |
| 3   | KDB 558074 D01 15.247<br>Meas Guidance v05r02 | Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules |

### 3.2 Test Verdict

| No. | Description                                             | FCC Part No.        | ISED Part No. | Channel                       | Test Result | Verdict | Remark            |
|-----|---------------------------------------------------------|---------------------|---------------|-------------------------------|-------------|---------|-------------------|
| 1   | Antenna Requirement                                     | 15.203              | N/A           | N/A                           | --          | Pass    | Note <sup>1</sup> |
| 2   | Number of Hopping Frequencies                           | 15.247(a)           | N/A           | Hopping Mode                  | ANNEX A.1   | Pass    | Note <sup>2</sup> |
| 3   | Peak Output Power                                       | 15.247(b)           | N/A           | Low/Middle/High               | ANNEX A.2   | Pass    | --                |
| 4   | Occupied Bandwidth                                      | 15.247(a)           | N/A           | Low/Middle/High               | ANNEX A.3   | Pass    | Note <sup>2</sup> |
| 5   | Carrier Frequency Separation                            | 15.247(a)           | N/A           | Hopping Mode                  | ANNEX A.4   | Pass    | Note <sup>2</sup> |
| 6   | Time of Occupancy (Dwell time)                          | 15.247(a)           | N/A           | Hopping Mode                  | ANNEX A.5   | Pass    | Note <sup>2</sup> |
| 7   | Conducted Spurious Emission & Authorized-band band-edge | 15.247(d)           | N/A           | Hopping Mode, Low/Middle/High | ANNEX A.6   | Pass    | Note <sup>2</sup> |
| 8   | Conducted Emission                                      | 15.207              | N/A           | Low/Middle/High               | ANNEX A.7   | Pass    | Note <sup>2</sup> |
| 9   | Radiated Spurious Emission                              | 15.209<br>15.247(d) | N/A           | Hopping Mode, Low/Middle/High | ANNEX A.8   | Pass    | Note <sup>2</sup> |
| 10  | Band Edge(Restricted-band band-edge)                    | 15.209<br>15.247(d) | N/A           | Hopping Mode, Low/Middle/High | ANNEX A.9   | Pass    | Note <sup>2</sup> |

Note <sup>1</sup>: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note <sup>2</sup>:  $\pi/4$ -DQPSK is the EDR 2M rate mode, 8-DPSK is the EDR 3M rate mode. The consistency of test results in  $\pi/4$ -DQPSK and 8-DPSK is very high. So we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item.

## 4 GENERAL TEST CONFIGURATIONS

### 4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

|                            |                         |                    |
|----------------------------|-------------------------|--------------------|
| Relative Humidity          | 49% to 58%              |                    |
| Atmospheric Pressure       | 100 kPa to 102 kPa      |                    |
| Temperature                | NT (Normal Temperature) | +21.0°C to +23.9°C |
| Working Voltage of the EUT | NV (Normal Voltage)     | 3.85 V             |

### 4.2 Test Equipment List

| Description                         | Manufacturer | Model        | Equipment No. | Cal. Date  | Cal. Due   |
|-------------------------------------|--------------|--------------|---------------|------------|------------|
| Spectrum Analyzer                   | KEYSIGHT     | N9020A       | BH-EMC-L066   | 2025.02.12 | 2026.02.11 |
| Spectrum Analyzer                   | KEYSIGHT     | N9010B       | BH-EMC-L099   | 2025.02.12 | 2026.02.11 |
| Signal Generator                    | Anritsu      | MG3710E      | BH-EMC-L131   | 2025.02.12 | 2026.02.11 |
| Wideband Radio Communication Tester | R&S          | CMW500       | BH-EMC-L094   | 2025.02.11 | 2026.02.10 |
| EMI Receiver                        | KEYSIGHT     | N9038A       | BH-EMC-L015   | 2025.07.04 | 2026.07.03 |
| Test Antenna-Loop(9 kHz-30 MHz)     | SCHWARZBECK  | FMZB 1519 B  | BH-EMC-L067   | 2024.03.11 | 2027.03.10 |
| Test Antenna-Bi-Log(30 MHz-3 GHz)   | SCHWARZBECK  | VULB 9163    | BH-EMC-L008   | 2024.03.11 | 2027.03.10 |
| Test Antenna-Horn(1-18 GHz)         | SCHWARZBECK  | BBHA 9120D   | BH-EMC-L044   | 2024.03.11 | 2027.03.10 |
| Test Antenna-Horn (18-40 GHz)       | A-INFO       | LB-180400-KF | BH-EMC-L061   | 2024.03.11 | 2027.03.10 |
| Anechoic Chamber                    | YiHeng       | 9m*6m*6m     | BH-EMC-L001   | 2024.04.18 | 2027.04.17 |
| EMI Receiver                        | KEYSIGHT     | N9038A       | BH-EMC-L127   | 2025.02.12 | 2026.02.11 |
| LISN                                | SCHWARZBECK  | NSLK 8127    | BH-EMC-L011   | 2025.02.11 | 2026.02.10 |
| 10dB Limiter                        | SCHWARZBECK  | VTSD 9561-F  | BH-EMC-L014   | 2025.02.11 | 2026.02.10 |
| Shielded Room                       | YiHeng       | 5m*4m*3.2m   | BH-EMC-L006   | 2024.02.22 | 2027.02.21 |

### 4.3 Test Software List

| Description | Manufacturer | Software Version | Serial No. | Applicable Test Setup               |
|-------------|--------------|------------------|------------|-------------------------------------|
| BL410R      | BALUN        | V2.1.1.496       | N/A        | The section 4.6.1                   |
| BL410E      | BALUN        | V21.919          | N/A        | The section 4.6.2&4.6.3&4.6.4&4.6.5 |

## 4.4 Decision Rule

- ☐ No Need
- ☒ Use General conformity decision rule (Consider uncertainty or not ☒No ☐Yes)
- ☐ Use Special Conformity Decision Rule (Consider uncertainty or not ☐No ☐Yes)

## 4.5 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

| Parameters                        | Uncertainty |
|-----------------------------------|-------------|
| Occupied Channel Bandwidth        | 2.4 %       |
| RF output power, conducted        | 0.41 dB     |
| Power Spectral Density, conducted | 1.73 dB     |
| Unwanted Emissions, conducted     | 1.73 dB     |
| All emissions, radiated           | 3.70 dB     |
| Temperature                       | 0.82 °C     |
| Humidity                          | 4.1 %       |


## 4.6 Description of Test Setup

### 4.6.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5 dB used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

### 4.6.2 For AC Power Supply Port Test




(Diagram 2)

## 4.6.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

## 4.6.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

## 4.6.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

## 4.7 Measurement Results Explanation Example

### 4.7.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

## 5 TEST ITEMS

### 5.1 Antenna Requirements

#### 5.1.1 Relevant Standards

FCC §15.203 & 15.247(b)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

#### 5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

| Protected Method                        | Description                            |
|-----------------------------------------|----------------------------------------|
| The antenna is embedded in the product. | An embedded-in antenna design is used. |

| Reference Documents | Item                                     |
|---------------------|------------------------------------------|
| Photo               | Please refer to the EUT Photo documents. |

#### 5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 5.2 Frequency Hopping Systems

### 5.2.1 Relevant Standards

FCC §15.247(a) (1) (i) (ii) (iii) (iv); FCC §15.247(g); FCC §15.247(h)

Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, to demonstrate that the sequence meets the requirement specified in the definition of an FHSS system. Per the definition in Section 2.1(c), the hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event).

Describe how the associated receiver(s) complies with the requirement that the input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal.

Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.


For short burst systems, describe how the EUT complies with the requirement that it be designed to be capable of operating as a true frequency hopping system. Specifically, the device shall comply with the equal frequency use and pseudorandom hopping sequence requirement when transmitting in short bursts, and shall be designed to comply when presented with continuous data (or information) stream.

Describe how the EUT complies with the requirement that it not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

### 5.2.2 Description of the systems

1. According to the preset procedure of the whole network, all the stations in the automatic control network synchronously change the frequency multiple times within one second, and temporarily stay on each frequency hopping channel. Periodic synchronization signaling is sent from the primary station, instructing all slaves to simultaneously change the operating frequency, then the hopping sequence is generated.
2. The hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

#### Reference Documents



3. Channels are classified into two categories, used and unused, where used channels are part of the hopping sequence and unused channels are replaced in the hopping sequence by used channels in a pseudo-random way. Make each individual EUT meets the requirement that each of its hopping channels is used equally on average.
4. The input bandwidth and transmitted bandwidth are both 1MHz, the associated receiver(s) complies with the requirement that the input bandwidth matches the bandwidth of the transmitted signal.
5. Connected devices communicate on the same physical channel by synchronizing with a common clock and hopping sequence.
6. EUT isn't short burst systems.
7. EUT can't have the ability to be coordinated with other FHSS systems in an effort.

## 5.3 Number of Hopping Frequencies

### 5.3.1 Limit

FCC §15.247(a) (1) (iii)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

### 5.3.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.3.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = The frequency band of operation

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

### 5.3.4 Test Result

Please refer to ANNEX A.1.

## 5.4 Peak Output Power

### 5.4.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 5.4.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.4.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

### 5.4.4 Test Result

Please refer to ANNEX A.2.

## **5.5 Occupied Bandwidth**

### **5.5.1 Limit**

FCC §15.247(a)

Measurement of the 20dB bandwidth of the modulated signal.

### **5.5.2 Test Setup**

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### **5.5.3 Test Procedure**

Use the following spectrum analyzer settings:

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

### **5.5.4 Test Result**

Please refer to ANNEX A.3.

## 5.6 Carrier Frequency Separation

### 5.6.1 Limit

FCC §15.247(a)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 2/3 of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 5.6.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.6.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW)  $\geq 1\%$  of the span

Video (or Average) Bandwidth (VBW)  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

### 5.6.4 Test Result

Please refer to ANNEX A.4.

## 5.7 Time of Occupancy (Dwell time)

### 5.7.1 Limit

#### FCC §15.247(a)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 5.7.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.7.3 Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

Span: Zero span, centered on a hopping channel

RBW shall be  $\leq$  channel spacing and where possible RBW should be set  $\gg 1/T$ , where T is the expected dwell time per channel

Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel

Detector function: Peak

Trace: Max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

The average time of occupancy on any channel within the Period can be calculated with formulas:

For GFSK and 8-DPSK:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH3 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For AFH Mode:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH3 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$
$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$
$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

#### 5.7.4 Test Result

Please refer to ANNEX A.5.

## 5.8 Conducted Spurious Emission & Authorized-band band-edge

### 5.8.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 5.8.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.8.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW = 300 kHz

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

### 5.8.4 Test Result

Please refer to ANNEX A.6.

## 5.9 Conducted Emission

### 5.9.1 Limit

#### FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

| Frequency range<br>(MHz) | Conducted Limit (dB $\mu$ V) |          |
|--------------------------|------------------------------|----------|
|                          | Quai-peak                    | Average  |
| 0.15 - 0.50              | 66 to 56                     | 56 to 46 |
| 0.50 - 5                 | 56                           | 46       |
| 5 - 30                   | 60                           | 50       |

### 5.9.2 Test Setup

See section 4.6.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

### 5.9.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

### 5.9.4 Test Result

Please refer to ANNEX A.7.

## 5.10 Radiated Spurious Emission

### 5.10.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength ( $\mu\text{V/m}$ ) | Measurement Distance (m) |
|-----------------|------------------------------------|--------------------------|
| 0.009 - 0.490   | 2400/F(kHz)                        | 300                      |
| 0.490 - 1.705   | 24000/F(kHz)                       | 30                       |
| 1.705 - 30.0    | 30                                 | 30                       |
| 30 - 88         | 100                                | 3                        |
| 88 - 216        | 150                                | 3                        |
| 216 - 960       | 200                                | 3                        |
| Above 960       | 500                                | 3                        |

Note:

1. Field Strength (dB $\mu\text{V/m}$ ) =  $20 \times \log[\text{Field Strength } (\mu\text{V/m})]$ .
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dB $\mu\text{V/m}$ @3m (AV) and 74dB $\mu\text{V/m}$ @3m (PK).

### 5.10.2 Test Setup

See section 4.6.3 to 4.6.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

#### 5.10.4 Test Result

Please refer to ANNEX A.8.

## 5.11 Band Edge (Restricted-band band-edge)

### 5.11.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

### 5.11.2 Test Setup

See section 4.6.3 to 4.6.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.11.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

### 5.11.4 Test Result

Please refer to ANNEX A.9.

## ANNEX A TEST RESULT


### A.1 Number of Hopping Frequencies

#### Test Data


| Test Mode | Frequency Block (MHz) | Measured Channel Numbers | Min. Limit | Verdict |
|-----------|-----------------------|--------------------------|------------|---------|
| GFSK      | 2400 - 2483.5         | 79                       | 15         | Pass    |
| 8-DPSK    | 2400 - 2483.5         | 79                       | 15         | Pass    |

#### Test Plots


GFSK 2.4 GHz ~ 2.4415 GHz




GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



## A.2 Peak Output Power

### Peak Power Test Data

| Channel | Measured Output Peak Power |      |                |      |        |      | Limit |     | Verdict |
|---------|----------------------------|------|----------------|------|--------|------|-------|-----|---------|
|         | GFSK                       |      | $\pi/4$ -DQPSK |      | 8-DPSK |      | dBm   | mW  |         |
|         | dBm                        | mW   | dBm            | mW   | dBm    | mW   |       |     |         |
| Low     | 5.77                       | 3.78 | 4.70           | 2.95 | 4.74   | 2.98 | 21    | 125 | Pass    |
| Middle  | 5.52                       | 3.56 | 4.82           | 3.03 | 4.86   | 3.06 |       |     | Pass    |
| High    | 5.29                       | 3.38 | 4.59           | 2.88 | 5.04   | 3.19 |       |     | Pass    |

## Test Plots

### GFSK LOW CHANNEL



### GFSK MIDDLE CHANNEL



### GFSK HIGH CHANNEL



### $\pi/4$ -DQPSK LOW CHANNEL



### $\pi/4$ -DQPSK MIDDLE CHANNEL



### $\pi/4$ -DQPSK HIGH CHANNEL



### 8-DPSK LOW CHANNEL



### 8-DPSK MIDDLE CHANNEL



### 8-DPSK HIGH CHANNEL



## A.3 Occupied Bandwidth


### Test Data

| GFSK           |                       |                     |
|----------------|-----------------------|---------------------|
| Channel        | 20 dB Bandwidth (MHz) | 99% Bandwidth (MHz) |
| Low            | 0.877                 | 0.775               |
| Middle         | 0.877                 | 0.755               |
| High           | 0.870                 | 0.755               |
| $\pi/4$ -DQPSK |                       |                     |
| Channel        | 20 dB Bandwidth (MHz) | 99% Bandwidth (MHz) |
| Low            | 1.260                 | 1.146               |
| Middle         | 1.267                 | 1.147               |
| High           | 1.267                 | 1.146               |
| 8-DPSK         |                       |                     |
| Channel        | 20 dB Bandwidth (MHz) | 99% Bandwidth (MHz) |
| Low            | 1.260                 | 1.148               |
| Middle         | 1.260                 | 1.153               |
| High           | 1.268                 | 1.148               |


## Test Plots

## 20 dB Bandwidth



## GFSK LOW CHANNEL



## GFSK MIDDLE CHANNEL




## GFSK HIGH CHANNEL

 $\pi/4$ -DQPSK LOW CHANNEL $\pi/4$ -DQPSK MIDDLE CHANNEL


### $\pi/4$ -DQPSK HIGH CHANNEL




### 8-DPSK LOW CHANNEL



### 8-DPSK MIDDLE CHANNEL




### 8-DPSK HIGH CHANNEL




## 99% Bandwidth




## GFSK LOW CHANNEL




## GFSK MIDDLE CHANNEL




## GFSK HIGH CHANNEL

 $\pi/4$ -DQPSK LOW CHANNEL $\pi/4$ -DQPSK MIDDLE CHANNEL


### $\pi/4$ -DQPSK HIGH CHANNEL




### 8-DPSK LOW CHANNEL



### 8-DPSK MIDDLE CHANNEL



### 8-DPSK HIGH CHANNEL




## A.4 Carrier Frequency Separation

### Test Data


| Mode   | Frequency separation (MHz) | 2/3 of the 20 dB Bandwidth (MHz) | Verdict |
|--------|----------------------------|----------------------------------|---------|
| GFSK   | 1.000                      | 0.585                            | Pass    |
| 8-DPSK | 1.000                      | 0.845                            | Pass    |

### Test Plots

#### GFSK



#### 8-DPSK



## A.5 Time of Occupancy (Dwell time)

### Test Data

| GFSK      |                  |                     |             |         |
|-----------|------------------|---------------------|-------------|---------|
| DH Packet | Pulse Width (ms) | Total of Dwell (ms) | Limit (sec) | Verdict |
| DH 1      | 0.375            | 120.000             | 0.4         | Pass    |
| DH 3      | 1.627            | 260.320             | 0.4         | Pass    |
| DH 5      | 2.882            | 307.413             | 0.4         | Pass    |
| 8-DPSK    |                  |                     |             |         |
| DH Packet | Pulse Width (ms) | Total of Dwell (ms) | Limit (sec) | Verdict |
| DH 1      | 0.383            | 122.656             | 0.4         | Pass    |
| DH 3      | 1.640            | 262.400             | 0.4         | Pass    |
| DH 5      | 2.882            | 307.413             | 0.4         | Pass    |
| AFH Mode  |                  |                     |             |         |
| DH Packet | Pulse Width (ms) | Total of Dwell (ms) | Limit (sec) | Verdict |
| DH 1      | 0.375            | 60.000              | 0.4         | Pass    |
| DH 3      | 1.633            | 130.640             | 0.4         | Pass    |
| DH 5      | 2.858            | 152.427             | 0.4         | Pass    |