

Eyenovia, Inc.

RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Optejet® Dispenser Model: Microdose Dispenser 1.0

REPORT NUMBER

104729499MPK-008

ISSUE DATE

September 08, 2021

REVISED DATE

N/A

PAGES

8

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK
© 2017 INTERTEK



**RF Exposure Exhibit
(Portable devices)**

Report Number: 104729499MPK-008

Project Number: G104729499

Report Issue Date: September 08, 2021

Product Designation: Optejet® Dispenser

Model Tested: Microdose Dispenser 1.0

FCC ID: 2A2VJ-EYENOVIAGEN1

to

**47CFR 2.1093
RSS-102 Issue 5**

for

Eyenovia, Inc.

Tested by:

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

Eyenovia, Inc.
8748 Technology Way
Reno, NV 89521 USA

Report prepared by:



Aaron Chang / Senior Project Engineer

Report reviewed by:



Krishna Vemuri / EMC Manager

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No. 104729499MPK-008	
Equipment Under Test:	Optejet® Dispenser
Trade Name:	Eyenovia, Inc.
Model(s) Tested:	Microdose Dispenser 1.0
Applicant:	Eyenovia, Inc.
Contact:	Kris Rodgers
Address:	Eyenovia, Inc. 8748 Technology Way Reno, NV 89521
Country:	USA
Email:	krodgers@eyenovia.com
Applicable Regulation:	47CFR 2.1093 RSS-102 Issue 5

TABLE OF CONTENTS

1.0	<i>RF Exposure Summary.....</i>	5
2.0	<i>RF Exposure Limits</i>	5
3.0	<i>Test Results (Portable Configuration)</i>	6
4.0	<i>Document History</i>	8

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1093	RSS-102 Issue 5	Complies

2.0 RF Exposure Limits

2.1 FCC Limits

According to FCC KDB 447498 D01 v06 Appendix A, at frequency 2450 MHz and separation distance of ≤ 5 mm SAR Exemption limit is ≤ 10 mW.

Note: 10-g Extremity SAR Test Exclusion Power Thresholds are 2.5 times higher than the 1-g SAR Test Exclusion Thresholds indicated above.

2.2 Industry Canada Limits

According to RSS-102 sec. 2.5.1 table 1, at frequency 2450 MHz and separation distance of ≤ 5 mm SAR Exemption limit is ≤ 4 mW.

Note: For limb-worn devices where the 10-gram value applies, the exemption limits for routine evaluation in Table 1 of RSS-102 are multiplied by a factor of 2.5.

3.0 Test Results (Portable Configuration)

3.1 Classification

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Per the applicant, Optejet® Dispenser is not intended to be worn on the body.

3.2 EIRP calculations

The Optejet® Dispenser consists of Bluetooth Low Energy radio.

3.3 Maximum RF Power

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain ¹ (dBi)	Note
2402-2480	-1.03	0.5	Conducted power measurements were taken from Report # 104729499MPK-007.

¹As declared by the manufacturer.

3.4 RF Exposure Calculation for Optejet® Dispenser

3.4.1 RF Exposure calculation for FCC KDB 447498 D01 v06

According to FCC KDB 447498 D01 v06 Appendix A, at frequency 2450 MHz and separation distance of ≤ 5 mm SAR Exemption limit is ≤ 10 mW.

Max Peak Conducted Power measured = -1.03 dBm or 0.789 mW

No duty cycle was considered.

Therefore, the Maximum EIRP calculated is -1.03 dBm (RF Conducted Power) + 0.5 dBi (Antenna Gain) = -0.53 dBm or 0.885 mW.

Results: SAR evaluation is not required since the higher of the maximum conducted or equivalent isotopically radiated power (EIRP) source-based, time averaged output power is below the exemption limit.

Note: Antenna gains below 0 are considered as 0dBi.

3.4.2 RF Exposure calculation for RSS-102 Issue 5

According to RSS-102 sec. 2.5.1, at frequency 2450 MHz and separation distance of ≤ 5 mm SAR Exemption limit is ≤ 4 mW.

Max Peak Conducted Power measured = -1.03 dBm or 0.789 mW

No duty cycle was considered.

Therefore, the Maximum EIRP calculated is -1.03 dBm (RF Conducted Power) + 0.5 dBi (Antenna Gain) = -0.53 dBm or 0.885 mW.

Results: SAR evaluation is not required since the higher of the maximum conducted or equivalent isotopically radiated power (EIRP) source-based, time averaged output power is below the exemption limit.

Note: Antenna gains below 0 are considered as 0dBi.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
1.0/ G104729499	AC	KV	September 08, 2021	Original document