

TEST REPORT

Maximum Permissive Exposure

for

Products Name: Royyt Smart Body Weight Scale

Model No.: VWS530S

FCC ID: 2A2VU2VWS530S

Report No.: SST2605E249

Issued Date: Jun. 02, 2026

Issued for

Shenzhen Subject Technology Co., Ltd.

705, Building 11, Phase II, Tianan Yungu Industrial Park, Gangtou Community, Bantian Sub-District,
Longgang District, Shenzhen, China

Issued by

Dongguan Qiyang Testing Technology Co., Ltd.

Room 101-1, Building 1, No.19, Tianxin Butterfly 1st Road, Huangjiang, Dongguan, Guangdong, China



General disclaimer:

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing Dongguan Qiyang Testing Technology Co., Ltd. The authenticity of this test report and its contents can be verified by contacting the Dongguan Qiyang Testing Technology Co., Ltd., responsible for this test report.

Table of Contents

1.	Basic Introduction	3
2.	RF EXPOSURE EVALUATION MAXIMUM PERMISSIBLE EXPOSURE (MPE)	4
2.1	Introduction.....	4
2.2	MPE Calculation	5
3	Conclusion.....	5

1. Basic Introduction

Applicant's name..... :	Shenzhen Subject Technology Co., Ltd.	
Address	705, Building 11, Phase II, Tianan Yungu Industrial Park, Gangtou Community, Bantian Sub-District, Longgang District, Shenzhen, China	
Manufacturer's name	Shenzhen Subject Technology Co., Ltd.	
Address	705, Building 11, Phase II, Tianan Yungu Industrial Park, Gangtou Community, Bantian Sub-District, Longgang District, Shenzhen, China	
Products Name..... :	Royyt Smart Body Weight Scale	
Model No..... :	VWS530S	
Trade Mark	Ovutēk[®]	
Rating(s)..... :	DC 6V(4*AAA Batteries)	
Operation frequency	2402MHz ~ 2480MHz	
Channel numbers	40	
Channel separation	2MHz	
Modulation technology	GFSK	
Antenna type..... :	PCB antenna	
Antenna gain..... :	2.81dBi	
Date of sample receipt..... :	May 26, 2026	
Date of Test..... :	May 26, 2026 ~ Jun. 02, 2026	
Standard(s)	FCC 47 CFR PART 1.1310 FCC 47 CFR PART 1.1307 KDB 447498 D04	
Tested by (+signature)..... :	Connor Ma	
Check by (+signature)..... :	Davis Zhou	
Approved by (+signature).... :	Tiger Chen	



2. RF EXPOSURE EVALUATION MAXIMUM PERMISSIBLE EXPOSURE (MPE)

2.1 Introduction

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules.

The limit for maximum permissible exposure(MPE), specific in §1.1307of the FCC Rules and KDB 447498 D04 were list in below

The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula.

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

For multiple RF sources

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

2.2 MPE Calculation

Type	Frequency (MHz)	Antenna Gain (dBi)	Output power (dBm)	Output power (mW)	ERP (dBm)	ERP (mW)	Limit (mW, d=0.5cm)	Ratio (%)	Result
BLE	2480	2.81	0.95	1.24	1.61	1.45	2.72	53.31	PASS

Note: The available RF source will be Maximum time-averaged power or ERP, whichever is greater.
 $P_{th} = 3060 * (d/20)^x$, where x is $-\log_{10}(60/3060 * \sqrt{F, \text{ in GHz}})$;
eg: $3060 * (0.5/20)^{-(-\log_{10}(60/3060 * \sqrt{2.48}))} = 2.72$

3 Conclusion

The device meets the portable RF exposure limit at a minimum separation distance as specified in §2.1093 of the FCC Rules and Regulations. An appropriate RF exposure compliance statement will be placed in the user's manual.

*****End of report*****