

RF EXPOSURE EVALUATION

EUT Specification

EUT	Floodlight Cam Pro
Model Number	L5P2CA11, DL5P2CA11, DL5P2CA12, DL5P3CA14, L5P3CA14, DL5P2CA14, L5P2CA14, DL5P3CA13, L5P3CA13, DL5P2CA13, L5P2CA13, DL5P3CA15, L5P3CA15, DL5P2CA15, L5P2CA15, DL5P3CA17, L5P3CA17, DL5P2CA17, L5P2CA17 (Note: All models are the same, except the model name and Trade Mark are different, We choose model L5P2CA11 to do all tests)
FCC ID	2A2VW-L5P
Antenna gain (Max)	2.55dBi
Operation Frequency	WIFI: 2412 MHz to 2462 MHz BLE: 2402 MHz to 2480 MHz
Input Rating	100-240V~ 50/60Hz
Max. output power	BLE: 3.43dBm IEEE 802.11b: 16.94 dBm IEEE 802.11g: 15 dBm IEEE 802.11n-HT20: 14.9 dBm IEEE 802.11n-HT40: 15.33 dBm

Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF)

Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula: $P_d = \frac{P_{out} \cdot G}{4 \cdot \pi \cdot R^2}$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm=20cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

Antenna gain: 2.55dBi

BLE:

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
GFSK	2402	3.42	3±1	4	1.799	0.000902	1
GFSK	2440	3.43	3±1	4	1.799	0.000902	1
GFSK	2480	3.18	3±1	4	1.799	0.000902	1

WIFI:

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	2412	16.85	17±1	18	1.799	0.022582	1
	2437	16.94	17±1	18	1.799	0.022582	1
	2462	16.94	17±1	18	1.799	0.022582	1
802.11g	2412	14.83	15±1	16	1.799	0.014248	1
	2437	14.95	15±1	16	1.799	0.014248	1
	2462	15	15±1	16	1.799	0.014248	1
802.11n HT20	2412	14.69	15±1	16	1.799	0.014248	1
	2437	14.9	15±1	16	1.799	0.014248	1
	2462	14.87	15±1	16	1.799	0.014248	1
802.11n HT40	2422	15.24	15±1	16	1.799	0.014248	1
	2437	15.29	15±1	16	1.799	0.014248	1
	2452	15.33	15±1	16	1.799	0.014248	1

Signature:

Tiger Xu

Tiger Xu

Date: 2023-08-22

