



## FCC RF Exposure Evaluation

### 1. Product Information

|                      |   |                                                                                                                                                          |
|----------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product name         | : | LAVA Guitar                                                                                                                                              |
| Test Model           | : | LAVA ME PLAY                                                                                                                                             |
| Additional Model No. | : | LAVA ME 4, LAVA ME 5, LAVA ME PRO, LAVA ME PRO 2, LAVA ME AIR                                                                                            |
| Model Declaration    | : | PCB board, structure and internal of these model(s) are the same, So no additional models were tested                                                    |
| Power Supply         | : | Input: DC 5V<br>DC 3.7V by Rechargeable Li-ion Battery, 5000mAh                                                                                          |
| Hardware Version     | : | /                                                                                                                                                        |
| Software Version     | : | /                                                                                                                                                        |
| Bluetooth            |   |                                                                                                                                                          |
| Frequency Range      | : | 2402MHz~2480MHz                                                                                                                                          |
| Channel Number       | : | 79 channels for Bluetooth V5.0(DSS)<br>40 channels for Bluetooth V5.0(DTS)                                                                               |
| Channel Spacing      | : | 1MHz for Bluetooth V5.0(DSS)<br>2MHz for Bluetooth V5.0(DTS)                                                                                             |
| Modulation Type      | : | GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0(DSS)<br>GFSK for Bluetooth V5.0(DTS)                                                                     |
| Bluetooth Version    | : | V5.0                                                                                                                                                     |
| Antenna Description  | : | FPC Antenna, 3.9dBi(Max.)                                                                                                                                |
| WIFI(2.4G Band)      |   |                                                                                                                                                          |
| Frequency Range      | : | 2412MHz~2462MHz                                                                                                                                          |
| Channel Spacing      | : | 5MHz                                                                                                                                                     |
| Channel Number       | : | 11 Channels for 20MHz bandwidth (2412~2462MHz)<br>7 Channels for 40MHz bandwidth (2422~2452MHz)                                                          |
| Modulation Type      | : | IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK)<br>IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)                 |
| Antenna Description  | : | ANT0: FPC Antenna, 3.9dBi(Max.)<br>ANT1: FPC Antenna, 3.9dBi(Max.)                                                                                       |
| WIFI(5.2G Band)      |   |                                                                                                                                                          |
| Frequency Range      | : | 5180MHz~5240MHz                                                                                                                                          |
| Channel Number       | : | 4 channels for 20MHz bandwidth(5180MHz~5240MHz)<br>2 channels for 40MHz bandwidth(5190MHz~5230MHz)<br>1 channels for 80MHz bandwidth(5210MHz)            |
| Modulation Type      | : | IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description  | : | Ant0: FPC Antenna, 1.8dBi(Max.)                                                                                                                          |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



|                     |   |                                                                                                                                                          |
|---------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------|
|                     |   | Ant1: FPC Antenna, 1.8dBi(Max.)                                                                                                                          |
| WIFI(5.3G Band)     |   |                                                                                                                                                          |
| Frequency Range     | : | 5260MHz~5320MHz                                                                                                                                          |
| Channel Number      | : | 4 Channels for 20MHz bandwidth(5260MHz~5320MHz)<br>2 channels for 40MHz bandwidth(5270MHz~5310MHz)<br>1 channels for 80MHz bandwidth(5290MHz)            |
| Modulation Type     | : | IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description | : | Ant0: FPC Antenna, 2.1dBi(Max.)<br>Ant1: FPC Antenna, 2.1dBi(Max.)                                                                                       |
| WIFI(5.5G Band)     |   |                                                                                                                                                          |
| Frequency Range     | : | 5500MHz~5700MHz                                                                                                                                          |
| Channel Number      | : | 11 Channels for 20MHz bandwidth(5500MHz~5700MHz)<br>5 Channels for 40MHz bandwidth(5510MHz~5670MHz)<br>2 Channels for 80MHz bandwidth(5530MHz, 5610MHz)  |
| Modulation Type     | : | IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description | : | Ant0: FPC Antenna, 3.2dBi(Max.)<br>Ant1: FPC Antenna, 3.2dBi(Max.)                                                                                       |
| WIFI(5.8G Band)     |   |                                                                                                                                                          |
| Frequency Range     | : | 5745MHz~5825MHz                                                                                                                                          |
| Channel Number      | : | 5 channels for 20MHz bandwidth(5745MHz~5825MHz)<br>2 channels for 40MHz bandwidth(5755MHz~5795MHz)<br>1 channels for 80MHz bandwidth(5775MHz)            |
| Modulation Type     | : | IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) |
| Antenna Description | : | Ant0: FPC Antenna, 3.3dBi(Max.)<br>Ant1: FPC Antenna, 3.3dBi(Max.)                                                                                       |
| Exposure category   | : | General population/uncontrolled environment                                                                                                              |
| EUT Type            | : | Production Unit                                                                                                                                          |
| Device Type         | : | Portable Device                                                                                                                                          |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 2. Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.<sup>22</sup> The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc."

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} \text{ (GHz)}]}{\leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}}$$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions. The grantee is responsible for documenting this according to Class I permissive change requirements. Antennas that qualify for standalone SAR test exclusion must apply the estimated standalone SAR to determine simultaneous transmission test exclusion.

- a) The  $[\sum \text{ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg}] + [\sum \text{ of MPE ratios}] \leq 1.0$ .
- b) The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all  $\leq 0.04$ , and the  $[\sum \text{ of MPE ratios}] \leq 1.0$ .

## 3. Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



#### 4. Conducted Power Results

[BT]

| Mode           | Channel | Frequency (MHz) | Max Conducted Power(dBm) |
|----------------|---------|-----------------|--------------------------|
| GFSK           | 00      | 2402            | 3.04                     |
|                | 39      | 2441            | 4.08                     |
|                | 79      | 2480            | 5.19                     |
| $\pi/4$ -DQPSK | 00      | 2402            | 2.4                      |
|                | 39      | 2441            | 4.22                     |
|                | 79      | 2480            | 5.27                     |
| 8-DPSK         | 00      | 2402            | 2.37                     |
|                | 39      | 2441            | 4.11                     |
|                | 79      | 2480            | 5.2                      |

[BLE 1M]

| Mode | Channel | Frequency (MHz) | Max Conducted Power(dBm) |
|------|---------|-----------------|--------------------------|
| GFSK | 0       | 2402            | 4.45                     |
|      | 19      | 2440            | 5.41                     |
|      | 39      | 2480            | 5.71                     |

[BLE 2M]

| Mode | Channel | Frequency (MHz) | Max Conducted Power(dBm) |
|------|---------|-----------------|--------------------------|
| GFSK | 0       | 2402            | 4.37                     |
|      | 19      | 2440            | 5.37                     |
|      | 39      | 2480            | 5.66                     |

[2.4G WIFI]

| Mode              | Channel | Frequency (MHz) | Ant 0<br>Max Conducted<br>Power(dBm) | Ant 1<br>Max Conducted<br>Power(dBm) |
|-------------------|---------|-----------------|--------------------------------------|--------------------------------------|
| IEEE 802.11b      | 1       | 2412            | 6.31                                 | 6.2                                  |
|                   | 6       | 2437            | 6.9                                  | 6.61                                 |
|                   | 11      | 2462            | 6.84                                 | 6.97                                 |
| IEEE 802.11g      | 1       | 2412            | 6.93                                 | 7.87                                 |
|                   | 6       | 2437            | 7.2                                  | 7.39                                 |
|                   | 11      | 2462            | 7.56                                 | 7.45                                 |
| IEEE 802.11n HT20 | 1       | 2412            | 6.85                                 | 6.85                                 |
|                   | 6       | 2437            | 7.29                                 | 7.33                                 |
|                   | 11      | 2462            | 7.1                                  | 7.18                                 |
| IEEE 802.11n HT40 | 3       | 2422            | 7.01                                 | 7.46                                 |
|                   | 6       | 2437            | 7.35                                 | 7.74                                 |
|                   | 9       | 2452            | 7.47                                 | 7.43                                 |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## [5.2G WIFI]

| Mode                | Channel | Frequency (MHz) | Ant 0<br>Max Conducted<br>Power(dBm) | Ant 1<br>Max Conducted<br>Power(dBm) |
|---------------------|---------|-----------------|--------------------------------------|--------------------------------------|
| IEEE 802.11a        | 36      | 5180            | 6.22                                 | 6.1                                  |
|                     | 40      | 5200            | 5.94                                 | 6.11                                 |
|                     | 48      | 5240            | 6.22                                 | 5.27                                 |
| IEEE 802.11n HT20   | 36      | 5180            | 6.81                                 | 6                                    |
|                     | 40      | 5200            | 6.76                                 | 5.94                                 |
|                     | 48      | 5240            | 6.31                                 | 5.22                                 |
| IEEE 802.11n HT40   | 38      | 5190            | 6.99                                 | 7.17                                 |
|                     | 46      | 5230            | 7.17                                 | 5.53                                 |
| IEEE 802.11ac VHT20 | 36      | 5180            | 6.88                                 | 7.04                                 |
|                     | 40      | 5200            | 6.88                                 | 6.99                                 |
|                     | 48      | 5240            | 6.15                                 | 5.3                                  |
| IEEE 802.11ac VHT40 | 38      | 5190            | 6.99                                 | 7.10                                 |
|                     | 46      | 5230            | 7.2                                  | 5.55                                 |
| IEEE 802.11ac VHT80 | 42      | 5210            | 7.16                                 | 6.17                                 |

## [5.3G WIFI]

| Mode                | Channel | Frequency (MHz) | Ant 0<br>Max Conducted<br>Power(dBm) | Ant 1<br>Max Conducted<br>Power(dBm) |
|---------------------|---------|-----------------|--------------------------------------|--------------------------------------|
| IEEE 802.11a        | 52      | 5260            | 5.05                                 | 4.93                                 |
|                     | 60      | 5300            | 6.00                                 | 5.92                                 |
|                     | 64      | 5320            | 6.49                                 | 6.28                                 |
| IEEE 802.11n HT20   | 52      | 5260            | 4.92                                 | 4.74                                 |
|                     | 60      | 5300            | 6.02                                 | 5.89                                 |
|                     | 64      | 5320            | 6.29                                 | 6.07                                 |
| IEEE 802.11n HT40   | 54      | 5270            | 6.34                                 | 6.13                                 |
|                     | 62      | 5310            | 6.72                                 | 6.55                                 |
| IEEE 802.11ac VHT20 | 52      | 5260            | 5.02                                 | 4.87                                 |
|                     | 60      | 5300            | 6.39                                 | 6.22                                 |
|                     | 64      | 5320            | 6.36                                 | 6.29                                 |
| IEEE 802.11ac VHT40 | 54      | 5270            | 5.32                                 | 5.10                                 |
|                     | 62      | 5310            | 5.43                                 | 5.34                                 |
| IEEE 802.11ac VHT80 | 58      | 5290            | 6.46                                 | 6.43                                 |

## [5.5G WIFI]

| Mode                | Channel | Frequency (MHz) | Ant 0<br>Max Conducted<br>Power(dBm) | Ant 1<br>Max Conducted<br>Power(dBm) |
|---------------------|---------|-----------------|--------------------------------------|--------------------------------------|
| IEEE 802.11a        | 100     | 5500            | 6.87                                 | 6.93                                 |
|                     | 116     | 5580            | 6.43                                 | 6.44                                 |
|                     | 140     | 5700            | 4.67                                 | 4.72                                 |
| IEEE 802.11n HT20   | 100     | 5500            | 6.8                                  | 6.81                                 |
|                     | 116     | 5580            | 6.34                                 | 6.27                                 |
|                     | 140     | 5700            | 4.63                                 | 4.62                                 |
| IEEE 802.11n HT40   | 102     | 5510            | 6.65                                 | 6.92                                 |
|                     | 110     | 5550            | 6.25                                 | 6.44                                 |
|                     | 134     | 5670            | 4.43                                 | 4.58                                 |
| IEEE 802.11ac VHT20 | 100     | 5500            | 6.79                                 | 6.77                                 |
|                     | 116     | 5580            | 6.29                                 | 6.26                                 |
|                     | 140     | 5700            | 4.59                                 | 4.55                                 |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



|                     |     |      |      |      |
|---------------------|-----|------|------|------|
| IEEE 802.11ac VHT40 | 102 | 5510 | 6.54 | 6.67 |
|                     | 110 | 5550 | 6.41 | 6.21 |
|                     | 134 | 5670 | 4.42 | 4.5  |
| IEEE 802.11ac VHT80 | 106 | 5530 | 6.52 | 6.38 |
|                     | 122 | 5610 | 5.98 | 6.04 |

## [5.8G WIFI]

| Mode                | Channel | Frequency (MHz) | Ant 0<br>Max Conducted<br>Power(dBm) | Ant 1<br>Max Conducted<br>Power(dBm) |
|---------------------|---------|-----------------|--------------------------------------|--------------------------------------|
| IEEE 802.11a        | 149     | 5745            | 6.15                                 | 6.28                                 |
|                     | 157     | 5785            | 4.14                                 | 5.79                                 |
|                     | 165     | 5825            | 3.68                                 | 5.41                                 |
| IEEE 802.11n HT20   | 149     | 5745            | 5.97                                 | 6.07                                 |
|                     | 157     | 5785            | 3.87                                 | 5.84                                 |
|                     | 165     | 5825            | 3.51                                 | 5.29                                 |
| IEEE 802.11n HT40   | 151     | 5755            | 6.33                                 | 6.35                                 |
|                     | 159     | 5795            | 4.2                                  | 5.22                                 |
| IEEE 802.11ac VHT20 | 149     | 5745            | 5.87                                 | 6.06                                 |
|                     | 157     | 5785            | 4                                    | 6.19                                 |
|                     | 165     | 5825            | 3.38                                 | 5.24                                 |
| IEEE 802.11ac VHT40 | 151     | 5755            | 6.34                                 | 6.03                                 |
|                     | 159     | 5795            | 4.34                                 | 5.22                                 |
| IEEE 802.11ac VHT80 | 155     | 5775            | 5.13                                 | 6.52                                 |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 5. Manufacturing Tolerance

[BT]

| GFSK(Peak)           |            |            |            |
|----------------------|------------|------------|------------|
| Channel              | Channel 00 | Channel 39 | Channel 78 |
| Target (dBm)         | 3.0        | 4.0        | 5.0        |
| Tolerance $\pm$ (dB) | 1.0        | 1.0        | 1.0        |
| $\pi/4$ -DQPSK(Peak) |            |            |            |
| Channel              | Channel 00 | Channel 39 | Channel 78 |
| Target (dBm)         | 2.0        | 4.0        | 5.0        |
| Tolerance $\pm$ (dB) | 1.0        | 1.0        | 1.0        |
| 8-DPSK(Peak)         |            |            |            |
| Channel              | Channel 00 | Channel 39 | Channel 78 |
| Target (dBm)         | 2.0        | 4.0        | 5.0        |
| Tolerance $\pm$ (dB) | 1.0        | 1.0        | 1.0        |

[BLE 1M]

| BT LE (Peak)         |           |            |            |
|----------------------|-----------|------------|------------|
| Channel              | Channel 0 | Channel 19 | Channel 39 |
| Target (dBm)         | 4.0       | 5.0        | 5.0        |
| Tolerance $\pm$ (dB) | 1.0       | 1.0        | 1.0        |

[BLE 2M]

| BT LE (Peak)         |           |            |            |
|----------------------|-----------|------------|------------|
| Channel              | Channel 0 | Channel 19 | Channel 39 |
| Target (dBm)         | 4.0       | 5.0        | 5.0        |
| Tolerance $\pm$ (dB) | 1.0       | 1.0        | 1.0        |

[2.4G WIFI Ant0]

| IEEE 802.11b (Peak)      |           |           |            |
|--------------------------|-----------|-----------|------------|
| Channel                  | Channel 1 | Channel 6 | Channel 11 |
| Target (dBm)             | 6.0       | 6.0       | 6.0        |
| Tolerance $\pm$ (dB)     | 1.0       | 1.0       | 1.0        |
| IEEE 802.11g (Peak)      |           |           |            |
| Channel                  | Channel 1 | Channel 6 | Channel 11 |
| Target (dBm)             | 6.0       | 7.0       | 7.0        |
| Tolerance $\pm$ (dB)     | 1.0       | 1.0       | 1.0        |
| IEEE 802.11n HT20 (Peak) |           |           |            |
| Channel                  | Channel 1 | Channel 6 | Channel 11 |
| Target (dBm)             | 4.0       | 5.0       | 5.0        |
| Tolerance $\pm$ (dB)     | 1.0       | 1.0       | 1.0        |
| IEEE 802.11n HT40 (Peak) |           |           |            |
| Channel                  | Channel 3 | Channel 6 | Channel 9  |
| Target (dBm)             | 5.0       | 5.0       | 5.0        |
| Tolerance $\pm$ (dB)     | 1.0       | 1.0       | 1.0        |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## [2.4G WIFI Ant1]

| IEEE 802.11b (Peak)      |           |           |            |
|--------------------------|-----------|-----------|------------|
| Channel                  | Channel 1 | Channel 6 | Channel 11 |
| Target (dBm)             | 6.0       | 6.0       | 6.0        |
| Tolerance $\pm$ (dB)     | 1.0       | 1.0       | 1.0        |
| IEEE 802.11g (Peak)      |           |           |            |
| Channel                  | Channel 1 | Channel 6 | Channel 11 |
| Target (dBm)             | 7.0       | 7.0       | 7.0        |
| Tolerance $\pm$ (dB)     | 1.0       | 1.0       | 1.0        |
| IEEE 802.11n HT20 (Peak) |           |           |            |
| Channel                  | Channel 1 | Channel 6 | Channel 11 |
| Target (dBm)             | 4.0       | 5.0       | 5.0        |
| Tolerance $\pm$ (dB)     | 1.0       | 1.0       | 1.0        |
| IEEE 802.11n HT40 (Peak) |           |           |            |
| Channel                  | Channel 3 | Channel 6 | Channel 9  |
| Target (dBm)             | 5.0       | 5.0       | 5.0        |
| Tolerance $\pm$ (dB)     | 1.0       | 1.0       | 1.0        |

## [5.2G WIFI Ant0]

| IEEE 802.11a (Average)        |            |            |            |
|-------------------------------|------------|------------|------------|
| Channel                       | Channel 36 | Channel 40 | Channel 48 |
| Target (dBm)                  | 6.0        | 5.0        | 6.0        |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        | 1.0        |
| IEEE 802.11n HT20 (Average)   |            |            |            |
| Channel                       | Channel 36 | Channel 40 | Channel 48 |
| Target (dBm)                  | 6.0        | 6.0        | 6.0        |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        | 1.0        |
| IEEE 802.11n HT40 (Average)   |            |            |            |
| Channel                       | Channel 38 | Channel 46 |            |
| Target (dBm)                  | 6.0        | 7.0        |            |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        |            |
| IEEE 802.11ac VHT20 (Average) |            |            |            |
| Channel                       | Channel 36 | Channel 40 | Channel 48 |
| Target (dBm)                  | 6.0        | 6.0        | 6.0        |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        | 1.0        |
| IEEE 802.11ac VHT40 (Average) |            |            |            |
| Channel                       | Channel 38 | Channel 46 |            |
| Target (dBm)                  | 6.0        | 7.0        |            |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        |            |
| IEEE 802.11ac VHT80 (Average) |            |            |            |
| Channel                       | Channel 42 |            |            |
| Target (dBm)                  | 7.0        |            |            |
| Tolerance $\pm$ (dB)          | 1.0        |            |            |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## [5.2G WIFI Ant1]

| IEEE 802.11a (Average)        |            |            |            |
|-------------------------------|------------|------------|------------|
| Channel                       | Channel 36 | Channel 40 | Channel 48 |
| Target (dBm)                  | 6.0        | 6.0        | 5.0        |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        | 1.0        |
| IEEE 802.11n HT20 (Average)   |            |            |            |
| Channel                       | Channel 36 | Channel 40 | Channel 48 |
| Target (dBm)                  | 6.0        | 5.0        | 5.0        |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        | 1.0        |
| IEEE 802.11n HT40 (Average)   |            |            |            |
| Channel                       | Channel 38 | Channel 46 |            |
| Target (dBm)                  | 7.0        | 5.0        |            |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        |            |
| IEEE 802.11ac VHT20 (Average) |            |            |            |
| Channel                       | Channel 36 | Channel 40 | Channel 48 |
| Target (dBm)                  | 7.0        | 6.0        | 5.0        |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        | 1.0        |
| IEEE 802.11ac VHT40 (Average) |            |            |            |
| Channel                       | Channel 38 | Channel 46 |            |
| Target (dBm)                  | 7.0        | 5.0        |            |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        |            |
| IEEE 802.11ac VHT80 (Average) |            |            |            |
| Channel                       | Channel 42 |            |            |
| Target (dBm)                  | 6.0        |            |            |
| Tolerance $\pm$ (dB)          | 1.0        |            |            |

## [5.3G WIFI Ant0]

| IEEE 802.11a (Average)        |            |            |            |
|-------------------------------|------------|------------|------------|
| Channel                       | Channel 52 | Channel 60 | Channel 64 |
| Target (dBm)                  | 5.0        | 6.0        | 6.0        |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        | 1.0        |
| IEEE 802.11n HT20 (Average)   |            |            |            |
| Channel                       | Channel 52 | Channel 60 | Channel 64 |
| Target (dBm)                  | 4.0        | 6.0        | 6.0        |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        | 1.0        |
| IEEE 802.11n HT40 (Average)   |            |            |            |
| Channel                       | Channel 54 | Channel 62 |            |
| Target (dBm)                  | 6.0        | 6.0        |            |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        |            |
| IEEE 802.11ac VHT20 (Average) |            |            |            |
| Channel                       | Channel 52 | Channel 60 | Channel 64 |
| Target (dBm)                  | 5.0        | 6.0        | 6.0        |
| Tolerance $\pm$ (dB)          | 1.0        | 1.0        | 1.0        |
| IEEE 802.11ac VHT40 (Average) |            |            |            |
| Channel                       | Channel 54 | Channel 62 |            |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



|                              |            |     |
|------------------------------|------------|-----|
| Target (dBm)                 | 5.0        | 5.0 |
| Tolerance $\pm$ (dB)         | 1.0        | 1.0 |
| IEEE 802.11ac VHT80(Average) |            |     |
| Channel                      | Channel 58 |     |
| Target (dBm)                 | 6.0        |     |
| Tolerance $\pm$ (dB)         | 1.0        |     |

## [5.3G WIFI Ant1]

| IEEE 802.11a (Average)        |            |            |            |
|-------------------------------|------------|------------|------------|
| Channel                       | Channel 52 | Channel 60 | Channel 64 |
| Target (dBm)                  | 4.0        | 5.0        | 6.0        |
| Tolerance ± (dB)              | 1.0        | 1.0        | 1.0        |
| IEEE 802.11n HT20 (Average)   |            |            |            |
| Channel                       | Channel 52 | Channel 60 | Channel 64 |
| Target (dBm)                  | 4.0        | 5.0        | 6.0        |
| Tolerance ± (dB)              | 1.0        | 1.0        | 1.0        |
| IEEE 802.11n HT40 (Average)   |            |            |            |
| Channel                       | Channel 54 | Channel 62 |            |
| Target (dBm)                  | 6.0        | 6.0        |            |
| Tolerance ± (dB)              | 1.0        | 1.0        |            |
| IEEE 802.11ac VHT20 (Average) |            |            |            |
| Channel                       | Channel 52 | Channel 60 | Channel 64 |
| Target (dBm)                  | 4.0        | 6.0        | 6.0        |
| Tolerance ± (dB)              | 1.0        | 1.0        | 1.0        |
| IEEE 802.11ac VHT40 (Average) |            |            |            |
| Channel                       | Channel 54 | Channel 62 |            |
| Target (dBm)                  | 5.0        | 5.0        |            |
| Tolerance ± (dB)              | 1.0        | 1.0        |            |
| IEEE 802.11ac VHT80(Average)  |            |            |            |
| Channel                       | Channel 58 |            |            |
| Target (dBm)                  | 6.0        |            |            |
| Tolerance ± (dB)              | 1.0        |            |            |

## [5.5G WIFI Ant0]

|                               |             |             |             |
|-------------------------------|-------------|-------------|-------------|
| IEEE 802.11a (Peak)           |             |             |             |
| Channel                       | Channel 100 | Channel 116 | Channel 140 |
| Target (dBm)                  | 6.0         | 6.0         | 4.0         |
| Tolerance $\pm$ (dB)          | 1.0         | 1.0         | 1.0         |
| IEEE 802.11n HT20 (Peak)      |             |             |             |
| Channel                       | Channel 100 | Channel 116 | Channel 140 |
| Target (dBm)                  | 6.0         | 6.0         | 4.0         |
| Tolerance $\pm$ (dB)          | 1.0         | 1.0         | 1.0         |
| IEEE 802.11n HT40 (Peak)      |             |             |             |
| Channel                       | Channel 102 | Channel 110 | Channel 134 |
| Target (dBm)                  | 6.0         | 6.0         | 4.0         |
| Tolerance $\pm$ (dB)          | 1.0         | 1.0         | 1.0         |
| IEEE 802.11ac VHT20 (Average) |             |             |             |
| Channel                       | Channel 100 | Channel 116 | Channel 140 |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



|                              |             |             |             |
|------------------------------|-------------|-------------|-------------|
| Target (dBm)                 | 6.0         | 6.0         | 4.0         |
| Tolerance $\pm$ (dB)         | 1.0         | 1.0         | 1.0         |
| IEEE 802.11ac HT40 (Average) |             |             |             |
| Channel                      | Channel 102 | Channel 110 | Channel 134 |
| Target (dBm)                 | 6.0         | 6.0         | 4.0         |
| Tolerance $\pm$ (dB)         | 1.0         | 1.0         | 1.0         |
| IEEE 802.11ac VHT80(Average) |             |             |             |
| Channel                      | Channel 106 | Channel 122 |             |
| Target (dBm)                 | 6.0         | 5.0         |             |
| Tolerance $\pm$ (dB)         | 1.0         | 1.0         |             |

## [5.5G WIFI Ant1]

|                               |             |             |             |
|-------------------------------|-------------|-------------|-------------|
| IEEE 802.11a (Peak)           |             |             |             |
| Channel                       | Channel 100 | Channel 116 | Channel 140 |
| Target (dBm)                  | 6.0         | 6.0         | 4.0         |
| Tolerance $\pm$ (dB)          | 1.0         | 1.0         | 1.0         |
| IEEE 802.11n HT20 (Peak)      |             |             |             |
| Channel                       | Channel 100 | Channel 116 | Channel 140 |
| Target (dBm)                  | 6.0         | 6.0         | 4.0         |
| Tolerance $\pm$ (dB)          | 1.0         | 1.0         | 1.0         |
| IEEE 802.11n HT40 (Peak)      |             |             |             |
| Channel                       | Channel 102 | Channel 110 | Channel 134 |
| Target (dBm)                  | 6.0         | 6.0         | 4.0         |
| Tolerance $\pm$ (dB)          | 1.0         | 1.0         | 1.0         |
| IEEE 802.11ac VHT20 (Average) |             |             |             |
| Channel                       | Channel 100 | Channel 116 | Channel 140 |
| Target (dBm)                  | 6.0         | 6.0         | 4.0         |
| Tolerance $\pm$ (dB)          | 1.0         | 1.0         | 1.0         |
| IEEE 802.11ac HT40 (Average)  |             |             |             |
| Channel                       | Channel 102 | Channel 110 | Channel 134 |
| Target (dBm)                  | 6.0         | 6.0         | 4.0         |
| Tolerance $\pm$ (dB)          | 1.0         | 1.0         | 1.0         |
| IEEE 802.11ac VHT80(Average)  |             |             |             |
| Channel                       | Channel 106 | Channel 122 |             |
| Target (dBm)                  | 6.0         | 6.0         |             |
| Tolerance $\pm$ (dB)          | 1.0         | 1.0         |             |

## [5.8G WIFI Ant0]

|                             |             |             |             |
|-----------------------------|-------------|-------------|-------------|
| IEEE 802.11a (Average)      |             |             |             |
| Channel                     | Channel 149 | Channel 157 | Channel 165 |
| Target (dBm)                | 6.0         | 4.0         | 3.0         |
| Tolerance $\pm$ (dB)        | 1.0         | 1.0         | 1.0         |
| IEEE 802.11n HT20 (Average) |             |             |             |
| Channel                     | Channel 149 | Channel 157 | Channel 165 |
| Target (dBm)                | 5.0         | 3.0         | 3.0         |
| Tolerance $\pm$ (dB)        | 1.0         | 1.0         | 1.0         |
| IEEE 802.11n HT40 (Average) |             |             |             |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



|                               |             |             |             |             |
|-------------------------------|-------------|-------------|-------------|-------------|
| Channel                       | Channel 151 |             | Channel 159 |             |
| Target (dBm)                  | 6.0         |             | 4.0         |             |
| Tolerance ±(dB)               | 1.0         |             | 1.0         |             |
| IEEE 802.11ac VHT20 (Average) |             |             |             |             |
| Channel                       | Channel 149 | Channel 157 |             | Channel 165 |
| Target (dBm)                  | 5.0         | 4.0         |             | 3.0         |
| Tolerance ±(dB)               | 1.0         | 1.0         |             | 1.0         |
| IEEE 802.11ac VHT40 (Average) |             |             |             |             |
| Channel                       | Channe151   |             | Channel 159 |             |
| Target (dBm)                  | 6.0         |             | 4.0         |             |
| Tolerance ±(dB)               | 1.0         |             | 1.0         |             |
| IEEE 802.11ac VHT80 (Average) |             |             |             |             |
| Channel                       | Channel 155 |             |             |             |
| Target (dBm)                  | 5.0         |             |             |             |
| Tolerance ±(dB)               | 1.0         |             |             |             |

## [5.8G WIFI Ant1]

| IEEE 802.11a (Average)        |             |             |             |
|-------------------------------|-------------|-------------|-------------|
| Channel                       | Channel 149 | Channel 157 | Channel 165 |
| Target (dBm)                  | 6.0         | 5.0         | 5.0         |
| Tolerance ±(dB)               | 1.0         | 1.0         | 1.0         |
| IEEE 802.11n HT20 (Average)   |             |             |             |
| Channel                       | Channel 149 | Channel 157 | Channel 165 |
| Target (dBm)                  | 6.0         | 5.0         | 5.0         |
| Tolerance ±(dB)               | 1.0         | 1.0         | 1.0         |
| IEEE 802.11n HT40 (Average)   |             |             |             |
| Channel                       | Channel 151 | Channel 159 |             |
| Target (dBm)                  | 6.0         | 5.0         |             |
| Tolerance ±(dB)               | 1.0         | 1.0         |             |
| IEEE 802.11ac VHT20 (Average) |             |             |             |
| Channel                       | Channel 149 | Channel 157 | Channel 165 |
| Target (dBm)                  | 6.0         | 6.0         | 5.0         |
| Tolerance ±(dB)               | 1.0         | 1.0         | 1.0         |
| IEEE 802.11ac VHT40 (Average) |             |             |             |
| Channel                       | Channel 151 | Channel 159 |             |
| Target (dBm)                  | 6.0         | 5.0         |             |
| Tolerance ±(dB)               | 1.0         | 1.0         |             |
| IEEE 802.11ac VHT80 (Average) |             |             |             |
| Channel                       | Channel 155 |             |             |
| Target (dBm)                  | 6.0         |             |             |
| Tolerance ±(dB)               | 1.0         |             |             |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 6. Evaluation Results

### 6.1 Standalone Evaluation

[BT]

| Band/Mode |               | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|-----------|---------------|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|           |               |                 |                       | dBm             | mW     |                              |                    |
| BT        | GFSK          | 2.480           | 5                     | 6.0             | 3.9811 | 1.2539< 3.0                  | Yes                |
|           | $\pi/4$ DQPSK | 2.480           | 5                     | 6.0             | 3.9811 | 1.2539< 3.0                  | Yes                |
|           | 8DPSK         | 2.480           | 5                     | 6.0             | 3.9811 | 1.2539< 3.0                  | Yes                |

[BLE]

| Band/Mode |      | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|-----------|------|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|           |      |                 |                       | dBm             | mW     |                              |                    |
| BLE 1M    | GFSK | 2.480           | 5                     | 6.0             | 3.9811 | 1.2539< 3.0                  | Yes                |
| BLE 2M    | GFSK | 2.480           | 5                     | 6.0             | 3.9811 | 1.2539< 3.0                  | Yes                |

[2.4G WIFI Ant0]

| Band/Mode         |  | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|-------------------|--|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|                   |  |                 |                       | dBm             | mW     |                              |                    |
| IEEE 802.11b      |  | 2.437           | 5                     | 7.0             | 5.0119 | 1.5648< 3.0                  | Yes                |
| IEEE 802.11g      |  | 2.462           | 5                     | 8.0             | 6.3096 | 1.9800< 3.0                  | Yes                |
| IEEE 802.11n HT20 |  | 2.437           | 5                     | 6.0             | 3.9811 | 1.2430< 3.0                  | Yes                |
| IEEE 802.11n HT40 |  | 2.437           | 5                     | 6.0             | 3.9811 | 1.2430< 3.0                  | Yes                |

[2.4G WIFI Ant1]

| Band/Mode         |  | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|-------------------|--|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|                   |  |                 |                       | dBm             | mW     |                              |                    |
| IEEE 802.11b      |  | 2.462           | 5                     | 7.0             | 5.0119 | 1.5728< 3.0                  | Yes                |
| IEEE 802.11g      |  | 2.412           | 5                     | 8.0             | 6.3096 | 1.9598< 3.0                  | Yes                |
| IEEE 802.11n HT20 |  | 2.437           | 5                     | 6.0             | 3.9811 | 1.2430< 3.0                  | Yes                |
| IEEE 802.11n HT40 |  | 2.437           | 5                     | 6.0             | 3.9811 | 1.2430< 3.0                  | Yes                |

[5.2G WIFI Ant0]

| Band/Mode           |  | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|---------------------|--|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|                     |  |                 |                       | dBm             | mW     |                              |                    |
| IEEE 802.11a        |  | 5.240           | 5                     | 7.0             | 5.0119 | 2.2945< 3.0                  | Yes                |
| IEEE 802.11n HT20   |  | 5.180           | 5                     | 7.0             | 5.0119 | 2.2814< 3.0                  | Yes                |
| IEEE 802.11n HT40   |  | 5.230           | 5                     | 8.0             | 6.3096 | 2.8859< 3.0                  | Yes                |
| IEEE 802.11ac VHT20 |  | 5.200           | 5                     | 7.0             | 5.0119 | 2.2858< 3.0                  | Yes                |
| IEEE 802.11ac VHT40 |  | 5.230           | 5                     | 8.0             | 6.3096 | 2.8859< 3.0                  | Yes                |
| IEEE 802.11ac VHT80 |  | 5.210           | 5                     | 8.0             | 6.3096 | 2.2804< 3.0                  | Yes                |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.2G WIFI Ant1]

| Band/Mode           | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|---------------------|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|                     |                 |                       | dBm             | mW     |                              |                    |
| IEEE 802.11a        | 5.200           | 5                     | 7.0             | 5.0119 | 2.2858< 3.0                  | Yes                |
| IEEE 802.11n HT20   | 5.180           | 5                     | 7.0             | 5.0119 | 2.2814< 3.0                  | Yes                |
| IEEE 802.11n HT40   | 5.190           | 5                     | 8.0             | 6.3096 | 2.8748< 3.0                  | Yes                |
| IEEE 802.11ac VHT20 | 5.180           | 5                     | 8.0             | 6.3096 | 2.8748< 3.0                  | Yes                |
| IEEE 802.11ac VHT40 | 5.190           | 5                     | 8.0             | 6.3096 | 2.8748< 3.0                  | Yes                |
| IEEE 802.11ac VHT80 | 5.210           | 5                     | 7.0             | 5.0119 | 2.2880< 3.0                  | Yes                |

[5.3G WIFI Ant0]

| Band/Mode           | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|---------------------|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|                     |                 |                       | dBm             | mW     |                              |                    |
| IEEE 802.11a        | 5.320           | 5                     | 7.0             | 5.0119 | 2.3120< 3.0                  | Yes                |
| IEEE 802.11n HT20   | 5.320           | 5                     | 7.0             | 5.0119 | 2.3120< 3.0                  | Yes                |
| IEEE 802.11n HT40   | 5.310           | 5                     | 7.0             | 5.0119 | 2.3098< 3.0                  | Yes                |
| IEEE 802.11ac VHT20 | 5.300           | 5                     | 7.0             | 5.0119 | 2.3076< 3.0                  | Yes                |
| IEEE 802.11ac VHT40 | 5.310           | 5                     | 6.0             | 3.9811 | 1.8348< 3.0                  | Yes                |
| IEEE 802.11ac VHT80 | 5.290           | 5                     | 7.0             | 5.0119 | 2.3055< 3.0                  | Yes                |

[5.3G WIFI Ant1]

| Band/Mode           | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|---------------------|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|                     |                 |                       | dBm             | mW     |                              |                    |
| IEEE 802.11a        | 5.320           | 5                     | 7.0             | 5.0119 | 2.3120< 3.0                  | Yes                |
| IEEE 802.11n HT20   | 5.320           | 5                     | 7.0             | 5.0119 | 2.3120< 3.0                  | Yes                |
| IEEE 802.11n HT40   | 5.310           | 5                     | 7.0             | 5.0119 | 2.3098< 3.0                  | Yes                |
| IEEE 802.11ac VHT20 | 5.320           | 5                     | 7.0             | 5.0119 | 2.3120< 3.0                  | Yes                |
| IEEE 802.11ac VHT40 | 5.310           | 5                     | 6.0             | 3.9811 | 1.8348< 3.0                  | Yes                |
| IEEE 802.11ac VHT80 | 5.290           | 5                     | 7.0             | 5.0119 | 2.3055< 3.0                  | Yes                |

[5.5G WIFI Ant0]

| Band/Mode           | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|---------------------|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|                     |                 |                       | dBm             | mW     |                              |                    |
| IEEE 802.11a        | 5.500           | 5                     | 7.0             | 5.0119 | 2.3931< 3.0                  | Yes                |
| IEEE 802.11n HT20   | 5.500           | 5                     | 7.0             | 5.0119 | 2.3931< 3.0                  | Yes                |
| IEEE 802.11n HT40   | 5.510           | 5                     | 7.0             | 5.0119 | 2.3868< 3.0                  | Yes                |
| IEEE 802.11ac VHT20 | 5.500           | 5                     | 7.0             | 5.0119 | 2.3931< 3.0                  | Yes                |
| IEEE 802.11ac VHT40 | 5.510           | 5                     | 7.0             | 5.0119 | 2.3868< 3.0                  | Yes                |
| IEEE 802.11ac VHT80 | 5.530           | 5                     | 7.0             | 5.0119 | 2.3742< 3.0                  | Yes                |



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A &amp; 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



[5.5G WIFI Ant1]

| Band/Mode           | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|---------------------|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|                     |                 |                       | dBm             | mW     |                              |                    |
| IEEE 802.11a        | 5.500           | 5                     | 7.0             | 5.0119 | 2.3508< 3.0                  | Yes                |
| IEEE 802.11n HT20   | 5.500           | 5                     | 7.0             | 5.0119 | 2.3508< 3.0                  | Yes                |
| IEEE 802.11n HT40   | 5.510           | 5                     | 7.0             | 5.0119 | 2.3529< 3.0                  | Yes                |
| IEEE 802.11ac VHT20 | 5.500           | 5                     | 7.0             | 5.0119 | 2.3508< 3.0                  | Yes                |
| IEEE 802.11ac VHT40 | 5.510           | 5                     | 7.0             | 5.0119 | 2.3529< 3.0                  | Yes                |
| IEEE 802.11ac VHT80 | 5.530           | 5                     | 7.0             | 5.0119 | 2.3572< 3.0                  | Yes                |

[5.8G WIFI Ant0]

| Band/Mode           | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|---------------------|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|                     |                 |                       | dBm             | mW     |                              |                    |
| IEEE 802.11a        | 5.745           | 5                     | 7.0             | 5.0119 | 2.4026< 3.0                  | Yes                |
| IEEE 802.11n HT20   | 5.745           | 5                     | 6.0             | 3.9811 | 1.9084< 3.0                  | Yes                |
| IEEE 802.11n HT40   | 5.755           | 5                     | 7.0             | 5.0119 | 2.4047< 3.0                  | Yes                |
| IEEE 802.11ac VHT20 | 5.745           | 5                     | 6.0             | 3.9811 | 1.9084< 3.0                  | Yes                |
| IEEE 802.11ac VHT40 | 5.755           | 5                     | 7.0             | 5.0119 | 2.4047< 3.0                  | Yes                |
| IEEE 802.11ac VHT80 | 5.775           | 5                     | 6.0             | 3.9811 | 1.9134< 3.0                  | Yes                |

[5.8G WIFI Ant1]

| Band/Mode           | Frequency (GHz) | Antenna Distance (mm) | RF output power |        | SAR Test Exclusion Threshold | SAR Test Exclusion |
|---------------------|-----------------|-----------------------|-----------------|--------|------------------------------|--------------------|
|                     |                 |                       | dBm             | mW     |                              |                    |
| IEEE 802.11a        | 5.745           | 5                     | 7.0             | 5.0119 | 2.4026< 3.0                  | Yes                |
| IEEE 802.11n HT20   | 5.745           | 5                     | 7.0             | 5.0119 | 2.4026< 3.0                  | Yes                |
| IEEE 802.11n HT40   | 5.755           | 5                     | 7.0             | 5.0119 | 2.4047< 3.0                  | Yes                |
| IEEE 802.11ac VHT20 | 5.785           | 5                     | 7.0             | 5.0119 | 2.4109< 3.0                  | Yes                |
| IEEE 802.11ac VHT40 | 5.755           | 5                     | 7.0             | 5.0119 | 2.4047< 3.0                  | Yes                |
| IEEE 802.11ac VHT80 | 5.775           | 5                     | 7.0             | 5.0119 | 2.4088< 3.0                  | Yes                |

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 6.2 Simultaneous Transmission

The sample support one BT antenna and two WLAN antenna, they supports difference antenna, need consider simultaneous transmission;

$\sum$  of (the highest measured or estimated SAR BTantenna + SAR WLAN ant0+SAR WLAN ant1)/1.6 = (0.2613+0.3833+0.3833)/1.6 = 0.64 < 1.0;

## 7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

.....THE END OF REPORT.....



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity