

RF TEST REPORT

For

SHENZHEN ANYTEC TECHNOLOGY CO., LTD

Product Name: AI Companion Robot

Test Model(s): AT01

Report Reference No. : DACE260820005RF003

FCC ID : 2A2WF-AT01

Applicant's Name : SHENZHEN ANYTEC TECHNOLOGY CO., LTD

Address : 1st Floor, Building F, ICC Industrial City, Kaicheng 2nd Road, Hangcheng
Sub-district, Bao 'an District, Shenzhen City, China

Testing Laboratory : Shenzhen DACE Testing Technology Co., Ltd.

Address : 102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park,
Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen,
Guangdong, China

Test Specification Standard : 47 CFR Part 15.225


Date of Receipt : August 20, 2026

Date of Test : August 20, 2026 to September 9, 2026

Date of Issue : September 9, 2026

Result : Pass

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample



Apply for company information

Applicant's Name	:	SHENZHEN ANYTEC TECHNOLOGY CO., LTD
Address	:	1st Floor, Building F, ICC Industrial City, Kaicheng 2nd Road, Hangcheng Sub-district, Bao 'an District, Shenzhen City, China
Product Name	:	AI Companion Robot
Test Model(s)	:	AT01
Test Specification Standard(s)	:	47 CFR Part 15.225

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

Lucy Mo

Lucy Mo / Test Engineer

September 9, 2026

Supervised by:

Arron Liu

Arron Liu / Project Engineer

September 9, 2026

Approved by:

Tom Chen

Tom Chen / Manager

September 9, 2026

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	DACE260820005RF003	September 9, 2026

CONTENTS

1	TEST SUMMARY	5
1.1	TEST STANDARDS	5
1.2	SUMMARY OF TEST RESULT	5
2	GENERAL INFORMATION	6
2.1	CLIENT INFORMATION	6
2.2	DESCRIPTION OF DEVICE (EUT)	6
2.3	DESCRIPTION OF TEST MODES	6
2.4	DESCRIPTION OF SUPPORT UNITS	6
2.5	OPERATION FREQUENCY EACH OF CHANNEL	7
2.6	EQUIPMENTS USED DURING THE TEST	8
2.7	STATEMENT OF THE MEASUREMENT UNCERTAINTY	10
3	EVALUATION RESULTS (EVALUATION)	11
3.1	ANTENNA REQUIREMENT	11
3.1.1	Conclusion:	11
4	RADIO SPECTRUM MATTER TEST RESULTS (RF)	12
4.1	20DB BANDWIDTH	12
4.1.1	E.U.T. Operation:	13
4.1.2	Test Setup Diagram:	13
4.1.3	Test Data:	14
4.2	FREQUENCY TOLERANCE	15
4.2.1	E.U.T. Operation:	15
4.2.2	Test Setup Diagram:	15
4.2.3	Test Data:	16
4.3	EMISSIONS IN FREQUENCY BANDS (BELOW 30MHz)	17
4.3.1	E.U.T. Operation:	17
4.3.2	Test Data:	18
4.4	EMISSIONS IN FREQUENCY BANDS (30M-1GHz)	19
4.4.1	E.U.T. Operation:	20
4.4.2	Test Setup Diagram:	20
4.4.3	Test Data:	21
5	TEST SETUP PHOTOS	23
6	PHOTOS OF THE EUT	24

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.225: Operation within the band 13.110–14.010 MHz

1.2 Summary of Test Result

Item	Standard	Method	Requirement	Result
Antenna requirement	47 CFR Part 15.225		47 CFR 15.203	Pass
20dB Bandwidth	47 CFR Part 15.225	ANSI C63.10-2020+C63.10a-2024, section 6.9.2	47 CFR 15.215(c)	Pass
Frequency Tolerance	47 CFR Part 15.225	ANSI C63.10-2020+C63.10a-2024, Section 6.8	47 CFR 15.231(e)	Pass
Field Strength of The Fundamental Signal	47 CFR Part 15.225	ANSI C63.10-2020+C63.10a-2024, Section 6.4	47 CFR 15.225(a)	Pass
Emission Mask	47 CFR Part 15.225	ANSI C63.10-2020+C63.10a-2024, Section 6.4	47 CFR 15.225(b), 15.225(c)	Pass
Emissions in frequency bands (below 30MHz)	47 CFR Part 15.225	ANSI C63.10-2020+C63.10a-2024, Section 6.4	47 CFR 15.225(d)	Pass
Emissions in frequency bands (30M-1GHz)	47 CFR Part 15.225	ANSI C63.10-2020+C63.10a-2024, Section 6.5	47 CFR 15.225(d)	Pass

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : SHENZHEN ANYTEC TECHNOLOGY CO., LTD
Address : 1st Floor, Building F, ICC Industrial City, Kaicheng 2nd Road, Hangcheng Sub-district, Bao 'an District, Shenzhen City, China

Manufacturer : SHENZHEN ANYTEC TECHNOLOGY CO., LTD
Address : 1st Floor, Building F, ICC Industrial City, Kaicheng 2nd Road, Hangcheng Sub-district, Bao 'an District, Shenzhen City, China

2.2 Description of Device (EUT)

Product Name:	AI Companion Robot
Model/Type reference:	AT01
Trade Mark:	N/A
Power Supply:	DC 5V charging from adapter DC 3.85V by battery
Operation Frequency:	13.56MHz
Modulation Type:	ASK
Antenna Type:	Intennal Antenna
Antenna Gain:	1dBi
Hardware Version:	V1.0
Software Version:	V1.0

2.3 Description of Test Modes

No	Title	Description
TM1	TX mode	Keep the EUT in TX mode
Test Environment		Normal Voltage(DC): 3.85V

2.4 Description of Support Units

Title	Manufacturer	Model No.	Serial No.
Adapter	PHOTON	ATXC-069AC65B	/

2.5 Operation Frequency each of channel

CH	Frequency (MHz)
1	13.56

Note: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	
Center Frequency(MHz)	13.56

2.6 Equipments Used During The Test

20dB Bandwidth Frequency Tolerance					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	Tachoy Information Technology(she nzhcn) Co.,Ltd.	RTS-01	V1.0.0	/	/
RF Power Sensor Unit	Tachoy Information Technology(she nzhcn) Co.,Ltd.	TR1029-2	20220428P00 5	/	/
Wideband radio communication tester	R&S	CMW500	113410	2026-04-14	2027-04-13
Signal Generator	Keysight	N5181A	MY50143455	2025-12-02	2026-12-01
Vector Signal Generator	Keysight	N5182A	MY48180415	2025-12-02	2026-12-01
Spectrum Analyzer	Keysight	N9020A	MY53420323	2025-12-02	2026-12-01
RF Control Unit	Tachoy Information Technology(she nzhcn) Co.,Ltd.	TR1029-1	20220428C00 5	/	/

Emissions in frequency bands (below 30MHz)
Emissions in frequency bands (30M-1GHz)
Field Strength of The Fundamental Signal
Emission Mask

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	FA-03A2 RE+	/	/
Positioning Controller	MF	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2024-04-26	2027-04-25
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2024-04-26	2027-04-25
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2026-04-14	2027-04-13
Cable(LF)#2	Schwarzbeck	/	/	2026-04-13	2027-04-12
Cable(LF)#1	Schwarzbeck	/	/	2026-04-14	2027-04-13
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2026-04-14	2027-04-13
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2026-04-14	2027-04-13
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2026-04-14	2027-04-13
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2026-04-14	2027-04-13
Wideband radio communication tester	R&S	CMW500	113410	2026-04-14	2027-04-13
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2026-04-14	2027-04-13
Test Receiver	R&S	ESCI 3	1166.5950K03-101431-Jq	2026-04-14	2027-04-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2026-04-14	2027-04-13
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2026-04-29	2028-04-28

2.7 Statement Of The Measurement Uncertainty


Test Item	Measurement Uncertainty
Occupied Bandwidth	$\pm 3.63\%$
Duty cycle	$\pm 3.1\%$
Radiated Emission (Below 1GHz)	$\pm 5.79\text{dB}$
Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.	

3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

3.1.1 Conclusion:



4 Radio Spectrum Matter Test Results (RF)

4.1 20dB Bandwidth


Test Requirement:	47 CFR 15.215(c)
Test Limit:	Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Test Method:	ANSI C63.10-2020+C63.10a-2024, section 6.9.2
Procedure:	a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. d) Steps a) through c) might require iteration to adjust within the specified tolerances. e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value. f) Set detection mode to peak and trace mode to max hold. g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value). h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - xx]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument. i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j). j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “ixx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value,

	then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “fix dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth. k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).
--	--

4.1.1 E.U.T. Operation:


Operating Environment:					
Temperature:	23.4 °C	Humidity:	52 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.1.2 Test Setup Diagram:



4.1.3 Test Data:

Test Channel (MHz)	20dB Occupy Bandwidth (kHz)	Limit (kHz)	Conclusion
13.56	4.977	N/A	PASS




4.2 Frequency Tolerance

Test Requirement:	47 CFR 15.231(e)
Test Limit:	The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+ 50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.
Test Method:	ANSI C63.10-2020+C63.10a-2024, Section 6.8
Procedure:	Refer to ANSI C63.10-2020+C63.10a-2024, Section 6.8

4.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.5 °C	Humidity:	50 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.2.2 Test Setup Diagram:



4.2.3 Test Data:

Test Conditions			Frequency Deviation		Limit
Frequency (MHz)	Power (V dc)	Temperature (°C)	Measured Freq. (MHz)	Deviation (%)	
13.56	Normal	-20	13.5607	0.0007	±0.01%
	Normal	-10	13.5606	0.0006	
	Normal	0	13.5605	0.0005	
	Normal	10	13.5608	0.0008	
	Normal	20	13.5605	0.0005	
	Normal	30	13.5608	0.0008	
	Normal	40	13.5604	0.0004	
	Normal	50	13.5608	0.0008	
	Normal*85%	20	13.5604	0.0004	
	Normal *115%	20	13.5606	0.0006	

4.3 Emissions in frequency bands (below 30MHz)

Test Requirement:	47 CFR 15.225(d)		
Test Limit:	Refer to 47 CFR Part 15.225(d), The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.		
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.			
Test Method:	ANSI C63.10-2020+C63.10a-2024, Section 6.4		
Procedure:	Refer to ANSI C63.10-2020+C63.10a-2024 section 6.4		

4.3.1 E.U.T. Operation:

Operating Environment:						
Temperature:	22.7 °C		Humidity:	51 %	Atmospheric Pressure:	101.2 kPa
Pretest mode:		TM1				
Final test mode:		TM1				

4.3.2 Test Data:

9kHz-30MHz Test Results:

Azimuth: 0 deg

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
0.35	61.77	14.21	75.98	88.92	-12.94	QP
13.56	90.04	12.33	102.37	124	-21.63	peak
13.56	88.24	12.3	100.54	124	-23.46	AVG
27.12	56.08	12.41	68.49	79.03	-10.54	peak
27.12	56.05	12.41	68.46	79.03	-10.57	AVG
28.88	48.41	12.41	60.82	79.03	-18.21	QP
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits						

Azimuth: 90 deg

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
0.35	61.73	14.21	75.94	88.92	-12.98	QP
13.56	89.54	12.33	101.87	124	-22.13	peak
13.56	86.39	12.3	98.69	124	-25.31	AVG
27.12	55.55	12.41	67.96	79.03	-11.07	peak
27.12	55.08	12.41	67.49	79.03	-11.54	AVG
28.88	50.40	12.41	62.81	79.03	-16.22	QP
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits						

4.4 Emissions in frequency bands (30M-1GHz)


Test Requirement:	47 CFR 15.225(d)																								
Test Limit:	Refer to 47 CFR Part 15.225(d), The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in § 15.209. <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> ** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																							
0.009-0.490	2400/F(kHz)	300																							
0.490-1.705	24000/F(kHz)	30																							
1.705-30.0	30	30																							
30-88	100 **	3																							
88-216	150 **	3																							
216-960	200 **	3																							
Above 960	500	3																							
Test Method:	ANSI C63.10-2020+C63.10a-2024, Section 6.5																								
Procedure:	a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for																								

	Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
--	---

4.4.1 E.U.T. Operation:


Operating Environment:					
Temperature:	23.8 °C	Humidity:	47 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.4.2 Test Setup Diagram:



4.4.3 Test Data:

TM1 / Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	30.7454	28.65	3.00	31.65	40.00	-8.35	QP			P	
2	59.8588	27.84	-8.63	19.21	40.00	-20.79	QP			P	
3	104.1701	32.08	-6.94	25.14	43.50	-18.36	QP			P	
4	186.4408	28.17	-3.99	24.18	43.50	-19.32	QP			P	
5	338.4000	25.07	-1.59	23.48	46.00	-22.52	QP			P	
6	670.4892	24.93	4.68	29.61	46.00	-16.39	QP			P	


TM1 / Polarization: Vertical




Remark: Margin=Level - Limit, Level=Test receiver reading + correction factor

5 TEST SETUP PHOTOS

Emissions in frequency bands (below 30MHz)



Emissions in frequency bands (30M-1GHz)



6 PHOTOS OF THE EUT

Refer to Appendix - EUT Photos for EUT External Photo and Internal Photo.

***** End of Report *****