

RF Exposure Report

Project Number: 4804611**Proposal:** SUW-202106001163**Report Number:** 4804611EMC03**Revision Level:** 0**Client:** Fan Innovations, LLC**Equipment Under Test:** Bite Force Amplitude Controller (Transmitter)**Model Name:** BFAC**Type/HVIN:** 20030**FCC ID:** 2A2WP-20030**Applicable Standards:** 47 CFR §§ 2.1093;**FCC KDB 447498 D01 General RF Exposure Guidance v06****Report issued on:** 08 September 2021**Result:** Exempt

FOR THE SCOPE OF ACCREDITATION UNDER CERTIFICATE NUMBER: 3212.01

This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the Federal Government.

Prepared by:
Jeremy Pickens, RF Lab Manager**Reviewed by:**
Martin Taylor, Project Engineer

Remarks: This report details the results of the testing carried out on one sample; the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This document is issued by the Company under its General Conditions of Service accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful, and offenders may be prosecuted to the fullest extent of the law.

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	CLIENT INFORMATION.....	3
1.2	TEST LABORATORY	3
1.3	GENERAL INFORMATION OF EUT	3
1.4	OPERATING MODES AND CONDITIONS	3
2	SAR EXCLUSION CALCULATIONS	4
3	REVISION HISTORY	5

1 General Information

1.1 Client Information

Name: Fan Innovations, LLC
Address: 6405 Lake Shadows
City, State, Zip, Country: Hixson, TN 37343, USA

1.2 Test Laboratory

Name: SGS North America, Inc.
Address: 620 Old Peachtree Road NW, Suite 100
City, State, Zip, Country: Suwanee, GA 30024, USA

Accrediting Body: A2LA
Type of lab: Testing Laboratory
Certificate Number: 3212.01
Designation Number: US1126
ISED Registration: 9984A
CAB Identifier: US0186

1.3 General Information of EUT

Product Description: Bite Force Amplitude Controller (Transmitter)
Type/HVIN: 20030
Serial Number: 165990011 (Low), 165990001 (Middle), 165990002 (High)

Frequency Range: 912 – 919 MHz
Data Modes: GFSK
Antenna: External Dipole (1.2dBi Peak Gain) Linx, P/N: ANT -916-CW-HWR-CC

Rated Voltage: 9Vdc
Test Voltage: 9Vdc

Sample Received Date: 02 August 2021
Dates of testing: 02– 11 August 2021

1.4 Operating Modes and Conditions

Maximum Conducted Power levels were utilized for all calculations.

2 SAR Exclusion Calculations

	Input	Select Units
Max Power:	13.15	mW
Duty Cycle:	2.9%	
Min separation distance:	5	mm
Frequency, f:	912	MHz

<== Source based time average duty cycle

Value reference Number	Values used for Calculation	Reference number definition
v1	0.00 mW	[max. power of channel, including tune-up tolerance, mW] 'Rounded to nearest mW
v2	5 mm	[min. test separation distance, mm] 'Rounded to nearest mm
v3	0.955	[√f(GHz)]

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR,}$$

Exclusion Calculation(1g):	0.0	number	<== [v2 / v3] must be less than 3
Exclusion Calculation(10g):	0.0	number	<== [v2 / v3] must be less than 7.5

Conclusions (Body):	The EUT max power is BELOW the threshold. SAR Testing is NOT required for Body applications
Conclusions (Extremity):	The EUT max power is BELOW the threshold. SAR Testing is NOT required for Extremity applications

3 Revision History

Revision Level	Description of changes	Revision Date
0	Initial release	08 September 2021