



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF1-22T0010

Page (34) of (56)


Distance of measurement: 3 meter

Mode: 802.11ah_2 MHz


Channel: 06

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 126.89	49.13	Peak	V	-10.49	-	38.64	74.00	35.36
1 144.49	45.55	Peak	H	-10.39	-	35.16	74.00	38.84
1 145.69	52.78	Peak	V	-10.39	-	42.39	74.00	31.61
1 145.69	33.37	Average	V	-10.39	0.86	23.84	54.00	30.16
1 830.02	61.89	Peak	H	-5.84	-	56.05	74.00	17.95
1 830.02	53.75	Average	H	-5.84	0.86	48.77	54.00	5.23
1 829.62	37.98	Average	V	-5.84	0.86	33.00	54.00	21.00



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected at horizontal above 3 GHz.




Distance of measurement: 3 meter

Mode: 802.11ah_2 MHz


Channel: 11

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 132.69	44.86	Peak	H	-10.46	-	34.40	74.00	39.60
1 306.67	51.13	Peak	V	-9.53	-	41.60	74.00	32.40
1 306.67	30.82	Average	V	-9.53	0.86	22.15	54.00	31.85
1 746.83	51.86	Peak	V	-6.50	-	45.36	74.00	28.64
1 746.83	30.23	Average	V	-6.50	0.86	24.59	54.00	29.41
1 851.01	59.13	Peak	H	-5.66	-	53.47	74.00	20.53
1 851.01	50.18	Average	H	-5.66	0.86	45.38	54.00	8.62



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected at horizontal above 3 GHz.



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF1-22T0010
Page (38) of (56)


Distance of measurement: 3 meter

Mode: 802.11ah_4 MHz


Channel: 01

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 226.88	48.34	Peak	H	-9.95	-	38.39	74.00	35.61
1 639.24	44.28	Peak	V	-7.34	-	36.94	74.00	37.06
1 809.82	54.57	Peak	V	-6.00	-	48.57	74.00	25.43
1 809.82	45.08	Average	V	-6.00	2.11	41.19	54.00	12.81
1 810.82	60.46	Peak	H	-6.00	-	54.46	74.00	19.54
1 810.82	42.28	Average	H	-6.00	2.11	38.39	54.00	15.61



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected at horizontal above 3 GHz.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF1-22T0010
Page (40) of (56)


Distance of measurement: 3 meter

Mode: 802.11ah_4 MHz


Channel: 03

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 384.46	45.10	Peak	V	-9.11	-	35.99	74.00	38.01
1 736.83	48.41	Peak	H	-6.58	-	41.83	74.00	32.17
1 825.82	53.29	Peak	V	-5.87	-	47.42	74.00	26.58
1 825.82	42.90	Average	V	-5.87	2.11	39.14	54.00	14.86
1 827.02	58.91	Peak	H	-5.86	-	53.05	74.00	20.95
1 827.02	48.45	Average	H	-5.86	2.11	44.70	54.00	9.30



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected at horizontal above 3 GHz.



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-RF1-22T0010
Page (42) of (56)


Distance of measurement: 3 meter

Mode: 802.11ah_4 MHz

Channel: 05

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 601.44	45.23	Peak	V	-7.64	-	37.59	74.00	36.41
1 842.02	58.07	Peak	H	-5.74	-	52.33	74.00	21.67
1 842.02	48.59	Average	H	-5.74	2.11	44.96	54.00	9.04
1 842.82	50.74	Peak	V	-5.73	-	45.01	74.00	28.99
1 842.82	40.95	Average	V	-5.73	2.11	37.33	54.00	16.67
2 436.76	50.80	Peak	H	-2.58	-	48.22	74.00	25.78



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr