

SPECIFICATION



深圳市大显科技有限公司

Shenzhen Daxian Technology Co., Ltd.

国光 PGReactor-100W WIFI 天线组件

GGEC PGReactor-100W WIFI Antenna assembly

产 品 规 格 书

Product Specification

客 户 connection	国光 GGEC	频 段 frequency range	2400 ~ 2500MHz
项目名称 entry name	PGReactor--100W	版 本 edition	V07
物料编号 Material No	1P-G100W-058	颜 色 Color	黑色 Black
客户料号 Customer Item Number	EAN0051901		
R F 设计 R F Design	靳 群 Qun.Jin	结构设计 Structural Design	周锐斌 Ruibin.Zhou
品质经理 Quality Manager	潘永杰 YongJie.Pan	技术总监 Technical Director	张 磊 Lei.Zhang
日 期 Date	2025-07-25		

客户确认:

Customer confirmation:

装配是否符合贵司要求: ☐OK ☐NGWhether the assembly meets your company's requirements: ☐OK ☐NG

深圳市大显科技有限公司

Shenzhen DaXian Technology Co., Ltd.

深圳市龙岗区布吉镇吉华路 513 号上水径村(国防培训基地
对面) 达成工业园综合楼 7 楼

TEL:0755-28576002

FAX:0755-84276383

上海分部: 上海市张江高科技园区集成电路产业区龙东大道
3000 号 8 号楼 201 室

TEL:021-61630552

FAX:755-84276383

Buji Town, Longgang District, Shenzhen, China Jihua Road 513,
Shangshuijing Village (opposite the national defense
training base) Dacheng Industrial Park, Building 7.

TEL:0755-28576002

FAX:0755-84276383

Room201, Building8, LongDongRoad3000#, Semiconductor Industry
Park, ZhangJiang Hitech Zone, ShangHai

TEL:021-61630552

FAX:755-84276383

变更履历

[illegible]

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

索引 Indexes

一、项目说明 Project Description.....	4
二、WIFI 天线 antenna.....	4
1、规格 specifications.....	4
1.1 电气规格标准 Electrical specifications and standards.....	5
1.1.1 电性能指标 Electrical performance index.....	5
1.1.2 天线位置布局 Antenna Location Layout.....	5
1.2 结构规格标准 Structural specifications and standards.....	5
1.2.1 天线组成 Antenna composition..	5
2、测试环境 testing environment.....	6
3、测试 test.	7
3.1 驻波(VSWR)的测试 Test of standing wave (VSWR).....	7
3.1.1 测试连接 Test connection.....	7
3.2 效率、功率 (TRP)、灵敏度 (TIS) 的测试 Testing of efficiency, power (TRP), sensitivity (TIS).....	7
3.2.1 测试的场地 Test site.....	7
3.2.2 测试的仪表 Tested Instruments.....	7
3.2.3 测试数据 test data.....	7-8
4、VSWR 参数图 Parameter diagram.....	8
5、天线隔离度 Antenna isolation.....	9
6、无源场型图 Passive field pattern diagram.....	9
7、室外拉距测试 Outdoor draw distance test.....	10
7、天线粘贴位置说明 Antenna Paste Position Descriptio.....	11
8、结论 conclusion.....	11
三、工程图 schedule drawing.....	12

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

一 项目说明 Project Description


客户名: Customer Name:	国光 GGEC
整机类型: Type of complete machine:	音箱 loudspeaker box
天线频段: Antenna band:	2400 ~ 2500MHz
天线形式: Antenna form:	FPC+同轴线+线材海绵+EVA 泡棉+磁环 FPC + coaxial cable + wire sponge + EVA foam + magnetic ring
馈电形式: Feed form:	焊接 weld
硬件版本: Hardware version:	/

二 WIFI 天线组件 Antenna assembly

1 规格 specifications

本报告主要提供 PG Reactor 100 项目天线的各项电气和结构性能参数的测试状况。下图为大显设计的天线图片。

This report mainly provides the testing status of various electrical and structural performance parameters of the antenna for the PG Reactor 100 project. The following image shows an antenna with a large display design.



天线外观图

antenna appearing diagram

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

1.1 电气规格标准 Electrical specifications and standards


1.1.1 电性能指标 Electrical performance index

天线工作频段在 **2400 ~ 2500MHz** 。下表是大显设计和量产天线的电性能指标。

The operating frequency band of the antenna is between **2400 and 2500 MHz**. The following table shows the electrical performance indicators of large display design and mass production antennas.

Frequency Range	Frequency (MHz)	VSWR
WIFI	2400 ~ 2500	≤ 2

1.1.2 天线位置布局 Antenna Location Layout



1.2 结构规格标准 Structural specifications and standards

1.2.1 天线组成 Antenna composition

天线主要是由 FPC+同轴线+线材海绵+EVA 泡棉+磁环 组成。

The antenna is mainly composed of FPC + coaxial cable + wire sponge + EVA foam + magnetic ring.

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

2、测试设备 The Equipment of Active Test

Satimo 3D Chamber $4 \times 4 \times 4$ (m)

CMW500 E5071C

Network analyzer-R&S ZVL




图 2

Figure 2

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

3 测试 test

3.1 驻波(VSWR)的测试 Test of standing wave (VSWR)

3.1.1 测试连接: VSWR 测试装置依次的连接为: R&S ZVL 网络分析仪 → 测试线 → 测试治

Test connection: The VSWR test device is sequentially connected as follows: R&S ZVL network analyzer → test line → test fixture

实测(附图)Actual measurement (attached drawing)

3.2 增益及效率、功率 (TRP)、灵敏度 (TIS) 的测试

Gain and efficiency, power (TRP), sensitivity (TIS) testing

3.2.1 测试的场地 Test site:

大显微波暗室。测试频率范围为 400MHz—6GHz, 静区范围为 50cm 圆周, 反射率小于 -50 dB。

Large display microwave anechoic chamber. The test frequency range is 400MHz - 6GHz, the static zone range is 50cm circumferential, and the reflectivity is less than -50dB.

3.2.2 测试的仪表 Tested Instruments:

R&S ZVL 网络分析仪、CMW500 E5071C、标准喇叭天线、法国 SATIMO-SG24SYSTEM 系统、打印机等。

R&S ZVL network analyzer, Agilent 8960 E5515C, standard horn antenna, French SATIMO-SG24SYSTEM system, printer, etc.

3.2.3 测试数据: 在微波暗室中, 测试的功率和灵敏度相关的数值如下表

Test data: In a microwave anechoic chamber, the values related to the power and sensitivity tested are shown in the table below

OTA 有源测试 OTA active testing

		TPR	TIS
802.11-B	1	16.49	-83.31
	6	17.01	-83.77
	11	16.81	-83.18
802.11-G	1	15.31	-71.11
	6	15.88	-71.58
	11	15.65	-71.61
802.11-N	1	15.38	-69.31
	6	15.84	-69.59
	11	15.7	-69.18

主板传导 Motherboard conductio

		TPR	TIS
802.11-B	1	20.72	-87
	7	20.88	-87
	13	21.17	-87
802.11-G	1	19.84	-76
	7	19.85	-76
	13	20.04	-75.5
802.11-N	1	17.97	-75.5
	7	18.33	-75
	13	18.26	-75

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

无源效率&增益 Passive efficiency&gain:

Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)
2400	41.09	-3.86	3.58
2410	41.85	-3.78	3.64
2420	42.45	-3.72	3.79
2430	43.26	-3.64	3.86
2440	44.5	-3.52	3.93
2450	45.17	-3.45	3.81
2460	44.37	-3.53	3.92
2470	43.96	-3.57	3.73
2480	42.55	-3.71	3.65
2490	41.15	-3.86	3.47
2500	40.67	-3.91	3.38

4、VSWR 参数图 VSWR parameter diagram




www.Topant.com.cn


Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

5、天线隔离度 Antenna isolation



6、无源效率场型图 Passive efficiency field pattern diagram



www.1opant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

7、室外拉距测试 Outdoor draw distance test

拉距测试 pull test:WIFI 天线扣在蓝牙模块上 WIFI antenna attached to Bluetooth module

测试时间 Testing time:2025/07/23

测试场地 Test site:深圳烟草公司附近 Near Shenzhen Tobacco Company

测试手机 Testing mobile phones:Iphone 16 Pore



测试手机Tested phone: Iphone 16Pore				
	前 ahead	后 Gempres	左 left	右 right
BT	105M	90M	90M	85M
WiFi	105M	90M	90M	85M

www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

8、天线粘贴位置说明 Antenna Paste Position Descriptio



红色方框位置为磁环位置。如图
The red box indicates the position of the magnetic ring. As shown in the figure.



WiFi同轴线摆放。如图
WiFi coaxial cable placement.
As shown in the figure.



天线贴在木板外面，距边缘约 10MM.如图
The antenna is attached to the outside of the board, about 10mm from the edge, as shown in the figure



天线贴在木板外面，如图
The antenna is attached to the outside of the wooden board.
As shown in the figure.

9、结论 conclusion

此天线是在客户提供样机基础上设计，电参数和结构性能已达到技术要求，请确认！

This antenna is designed based on the prototype provided by the customer. The electrical parameters and structural performance have met the technical requirements, please confirm!



www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

1		2		3		4		5		6	
						0~10		10~30		30~50	
						0.05		0.10		0.15	
								50~		角度	
								0.20		1°	
								0.02		0.02	
										⊥	
										0.03	
										0.05	

端子口朝下

(Terminal port facing downwards)



F	线材海绵 (Cable sponge)	PIF (55*41*1.5)	黑色 (black)	
E	磁环 (magnet ring)	B5H H79128399, 07.9*12.8	黑色 (black)	
D	泡绵 (magnet ring)	EVA	黑色 (black)	
C	线材海绵 (Cable sponge)	PIF	黑色 (black)	
B	端子引线 (RF connector)	Cable	黑色 (black)	
A	FPC	Electrolytic copper PI	黑色 (black)	
序号 (serial number) 零件名称 (Part Name)			材质 (material)	颜色 (colour) 备注 (Note)

技术要求:

(technical requirement:)

1. "※"为重点尺寸；

(1. "※" is the key dimension;)

2. 未标注尺寸请依图纸；

(2. Please refer to the drawing for unspecified dimensions;)

3. 不可有虚焊、漏焊、短焊、断线等操作不良；

(3. There should be no poor operation such as faulty soldering, missing soldering, short wires, broken wires, etc.;)

4. 符合 RoHS 要求；

(4. Meet RoHS requirements.)



深圳大显科技有限公司

Shenzhen Topant Technology Co., Ltd.

机型 (Machine model)	PG Reactor 100W	产品颜色 (Product Color)	黑色 (black)	日期 (date)	2025/07/26
项目编码 (Project Code)	CP-G100W-058	表面处理 (Mold surface treatment)	NA	结构 (MD)	周锐斌
零件名称 (Part Name)	WiFi天线 (WiFi antenna)	单位 (unit)	mm	比例 (scale)	1:1
零件编码 (Part Number)	1P-G100W-058	第三视角 (Third perspective)	⊕ -- ⊖	射频 (RF)	靳群
材质 (material)	FPC+sponge+RF connector	审核 (check)		射频 (RF)	周康
保存路径 (Save Path)		批准 (ratify)		射频 (RF)	张磊
			当前版本 (current version)		

1

2

3

4

5

6

A