



SAR Test Report

Report No.: STS2603088H01

Issued for

Shenzhen city Doowis Industrial Co., Ltd

Room 202, Building B, Yongwei Industrial Park, No. 118
Yongfu Road, Qiaotou Community, Fuhai Subdistrict, Bao'an District, Shenzhen

Product Name: W6C Tablet

Brand Name: Headwolf

Model Name: W6C

Series Model(s): W7B, F9

FCC ID: 2A369-W6C

Test Standard: ANSI/IEEE Std. C95.1
FCC 47 CFR Part 2 (2.1093)
IEEE Std. 1528-2013

Max. Report SAR (10&1g) Body: 1.128 W/kg(1g)

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.



TEST REPORT CERTIFICATION

Applicant's name : Shenzhen city Doowis Industrial Co., Ltd
Room 202, Building B, Yongwei Industrial Park, No. 118 Yongfu
Address : Road, Qiaotou Community, Fuhai Subdistrict, Bao' an District,
Shenzhen

Manufacturer's Name : Shenzhen city Doowis Industrial Co., Ltd
Room 202, Building B, Yongwei Industrial Park, No. 118 Yongfu
Address : Road, Qiaotou Community, Fuhai Subdistrict, Bao' an District,
Shenzhen

Product description

Product name : W6C Tablet

Brand name : Headwolf

Model name : W6C

Series Model(s) :..... W7B, F9

Standards : ANSI/IEEE Std. C95.1
FCC 47 CFR Part 2 (2.1093)
IEEE Std. 1528-2013

The device was tested by Shenzhen STS Test Services Co., Ltd. in accordance with the measurement methods and procedures specified in KDB 865664 The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of Test

Date (s) of performance of tests : 17 Mar. 2026

Date of Issue : 25 Mar. 2026

Test Result..... : **Pass**

Testing Engineer :

Xin Liu

(Xin.Liu)

Technical Manager :

Shi fan. long

(Shifan. Long)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents

1. General Information	5
1.1 EUT Description.....	5
1.2 Test Environment.....	7
1.3 Test Factory	7
2. Test Standards and Limits	8
3. SAR Measurement System.....	9
3.1 Definition of Specific Absorption Rate (SAR).....	9
3.2 SAR System	9
4. Tissue Simulating Liquids	12
4.1 Simulating Liquids Parameter Check.....	12
5. SAR System Validation.....	16
5.1 Validation System	16
5.2 Validation Result	17
6. SAR Evaluation Procedures.....	18
7. EUT Antenna Location Sketch.....	19
7.1 SAR test exclusion consider table	20
8. EUT Test Position.....	23
8.1 Body-worn Position Conditions.....	23
9. Uncertainty	24
9.1 Measurement Uncertainty.....	24
10. Conducted Power Measurement	27
10.1 Test Result.....	27
2.4G WLAN	27
11. EUT and Test Setup Photo	30
11.1 EUT Photo	30
11.2 Setup Photo	33
12. SAR Result Summary	35
12.1 Body SAR	35
12.2 Repeated SAR.....	36
12.3 Repeated SAR measurement.....	37
13. Equipment List	38
Appendix A. System Validation Plots.....	39
Appendix B. SAR Test Plots.....	47
Appendix C. Probe Calibration and Dipole Calibration Report	59



Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	25 Mar. 2026	STS2603088H01	ALL	Initial Issue



1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	W6C Tablet		
Brand Name	Head wolf		
Model Name	W6C		
Series Model	W7B, F9		
Model Difference	The PCB board, circuit, structure and internal of these models are the same, Only model number and colour is different for these model.		
Sample number	260310022-1		
Battery	N/A		
Device Category	Portable		
Product stage	Production unit		
RF Exposure Environment	General Population / Uncontrolled		
Hardware Version	W30-T616ES-V2.0		
Software Version	W6C_V1.0		
Frequency Range	WLAN802.11b/g/n20: 2412 MHz ~ 2462 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5150 ~ 5250 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5250 ~ 5350 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5470 ~ 5725 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5725 ~ 5850 MHz BLE: 2402 MHz to 2480 MHz		
Max. Reported SAR(1g): (Limit:1.6W/kg) Test distance: Body:0mm	Band	Mode	Body Worn (W/kg)
	DTS	2.4G WLAN	1.128
	DSS	BT	0.513
	NII	5.2G WLAN	0.788
	NII	5.3G WLAN	0.969
	NII	5.6G WLAN	0.996
	NII	5.8G WLAN	0.482
Limit			1.6W/kg
FCC Equipment Class	Part 15 Spread Spectrum Transmitter (DSS) Digital Transmission System (DTS) Unlicensed National Information Infrastructure TX(NII)		
Operating Mode:	2.4G WLAN : 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11ax(OFDM):BPSK,QPSK,16-QAM,64-QAM		
Antenna Specification:	WLAN/BT: PIFA Antenna		
Hotspot Mode	Not Support		
DTM Mode			Not Support



Note:

1. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power



1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

ShenZhen STS Test Services Co.,Ltd.

101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration No.: 625569

IC Registration No.: 12108A

A2LA Certificate No.: 4338.01



2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	IEEE Std C95.1, 2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz. It specifies the maximum exposure limit of 1.6 W/kg as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
10	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE

GENERAL POPULATION/UNCONTROLLED EXPOSURE

PARTIAL BODY LIMIT

1.6 W/kg

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,
ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

MVG SAR System Diagram:



COMOSAR is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The COMOSAR system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The Open SAR software computes the results to give a SAR value in a 1g or 10g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 08/21 EPGO352 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 150 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1-MVG COMOSAR Dosimetric E field Dipole

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

SN 32/14 SAM115



Figure-SN 21/21 ELLI48



3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

4. Tissue Simulating Liquids



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The uncertainty due to the liquid conductivity and permittivity arises from two different sources. The first source of error is the deviation of the liquid conductivity from its target value (max _ 5 %) and the second source of error arises from the measurement procedures used to assess conductivity. The uncertainty shall be assessed using a rectangular probability For 1 g averaging, the maximum weighting coefficient for SAR is 0,5.

IEEE SCC-34/SC-2 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head and body tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table.

Frequency	ϵ_r	σ 10g S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800 to 2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20



**LIQUID MEASUREMENT RESULTS**


Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
2026-03-17	23.6	44	2412	23.3	Permittivity	39.27	38.89	-0.96	±5
					Conductivity	1.77	1.78	0.78	±5
2026-03-17	23.6	44	2437	23.3	Permittivity	39.22	39.13	-0.24	±5
					Conductivity	1.79	1.78	-0.47	±5
2026-03-17	23.6	44	2441	23.3	Permittivity	39.22	39.43	0.55	±5
					Conductivity	1.79	1.80	0.45	±5
2026-03-17	23.6	44	2450	23.3	Permittivity	39.20	38.97	-0.59	±5
					Conductivity	1.80	1.79	-0.56	±5
2026-03-17	23.6	44	2462	23.3	Permittivity	39.18	39.34	0.41	±5
					Conductivity	1.81	1.82	0.52	±5
2026-03-17	23.6	44	5200	23.3	Permittivity	36.00	36.86	2.39	±5
					Conductivity	4.66	4.66	0.00	±5
2026-03-17	23.6	44	5210	23.3	Permittivity	35.99	35.59	-1.11	±5
					Conductivity	4.67	4.67	-0.01	±5
2026-03-17	23.6	44	5290	23.3	Permittivity	35.91	36.66	2.09	±5
					Conductivity	4.75	4.75	-0.09	±5
2026-03-17	23.6	44	5510	23.3	Permittivity	35.66	35.30	-1.02	±5
					Conductivity	4.97	4.95	-0.46	±5
2026-03-17	23.6	44	5550	23.3	Permittivity	35.61	35.84	0.64	±5
					Conductivity	5.01	5.01	-0.07	±5
2026-03-17	23.6	44	5600	23.3	Permittivity	35.55	35.66	0.31	±5
					Conductivity	5.07	5.05	-0.30	±5
2026-03-17	23.6	44	5670	23.3	Permittivity	35.46	35.27	-0.54	±5
					Conductivity	5.14	5.13	-0.13	±5
2026-03-17	23.6	44	5785	23.3	Permittivity	35.32	35.64	0.92	±5
					Conductivity	5.25	5.25	-0.08	±5
2026-03-17	23.6	44	5800	23.3	Permittivity	35.30	34.88	-1.19	±5
					Conductivity	5.27	5.27	0.00	±5

5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.





5.2 Validation Result

Justification for Extended SAR Dipole Calibrations

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %.

Date	Frequency (MHz)	Power	SAR _{1g} (W/Kg)	SAR _{10g} (W/Kg)	Drift (%)	1W Target		Difference percentage		Limited %
						SAR _{1g} (W/Kg)	SAR _{10g} (W/Kg)	1g	10g	
2026-03-17	2450	100 mW	5.463	2.394	3.83	54.70	24.11	-0.13%	-0.71%	10
		Normalize to 1 Watt	54.63	23.94						
2026-03-17	5200	10 mW	1.544	0.530	-0.60	163.88	57.29	-5.78%	-7.49%	10
		Normalize to 1 Watt	154.40	53.00						
2026-03-17	5600	10 mW	1.740	0.618	-1.96	181.28	61.57	-4.02%	0.37%	10
		Normalize to 1 Watt	174.00	61.80						
2026-03-17	5800	10 mW	1.892	0.609	-1.42	188.95	63.45	0.13%	-4.02%	10
		Normalize to 1 Watt	189.20	60.90						

Note:

- (1) We use a CW signal of 20dBm(2450MHz) and 10dBm(5000-6000MHz) for system check, and then all SAR values are normalized to 1W forward power. The result must be within $\pm 10\%$ of target value.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.


➤ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below. When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.



7. EUT Antenna Location Sketch

It is a W6C Tablet, support WLAN mode.



Antenna Separation Distance(cm)					
ANT	Back Side	Left Side	Right Side	Top Side	Bottom Side
WLAN/BT	≤0.5	13.6	7.2	≤0.5	16

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



7.1 SAR test exclusion consider table

The WLAN SAR evaluation of Maximum power (dBm) summing tolerance.

Exposure Position	Wireless Interface	BT	2.4G WLAN	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
	Calculated Frequency(GHz)	2.441	2.462	5.21	5.29	5.55	5.785
	Maximum Turn-up power (dBm)	9.5	20	17	17.5	20	19
	Maximum rated power(mW)	8.91	100.00	50.12	56.23	100.00	79.43
Back Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	2.75	2.73	1.50	1.48	1.43	1.38
	Testing required?	YES	YES	YES	YES	YES	YES
Left Side	Separation distance (cm)	13.6	13.6	13.6	13.6	13.6	13.6
	exclusion threshold(mW)	1469.81	1468.76	1379.39	1377.63	1372.11	1367.35
	Testing required?	NO	NO	NO	NO	NO	NO
Right Side	Separation distance (cm)	7.2	7.2	7.2	7.2	7.2	7.2
	exclusion threshold(mW)	438.63	437.79	370.72	369.47	365.56	362.21
	Testing required?	NO	NO	NO	NO	NO	NO
Top Side	Separation distance (cm)	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5
	exclusion threshold(mW)	2.75	2.73	1.50	1.48	1.43	1.38
	Testing required?	YES	YES	YES	YES	YES	YES
Bottom Side	Separation distance (cm)	16	16	16	16	16	16
	exclusion threshold(mW)	2001.99	2001.16	1929.77	1928.35	1923.87	1920.01
	Testing required?	NO	NO	NO	NO	NO	NO

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. Per KDB 447498 D04, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. Per KDB 447498 D04, if the maximum time-averaged power available does not exceed 1 mW. This stand-alone SAR exemption test.



4. Per KDB 447498 D04, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

5. Per KDB 447498 D04, An alternative to the SAR-based exemption is using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in below table to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.



6. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8. for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode, thus the SAR can be excluded.
7. Per KDB 616217 D04, SAR evaluation for the front surface of tablet display screens are generally not necessary.
8. Per KDB 248227, as maximum rated power for U-NII-1 > U-NII-2A, U-NII-1 was chosen for SAR evaluation. Based on the measurements obtained, SAR measurements on U-NII-2A are not required as highest reported SAR from U-NII-1 band is $\leq 1.2\text{W/Kg}$.


8. EUT Test Position

This EUT was tested in Back Side and Top Side.

8.1 Body-worn Position Conditions

Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D04 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

SATIMO Uncertainty- SN 08/21 EPG0352									
Measurement uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+ %)	10g Ui (+ %)	vi
Measurement System									
Probe calibration	E.2.1	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	0.71	0.71	0.07	0.07	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.71	0.71	0.42	0.42	∞
Boundary effect	E.2.3	0.80	R	1.73	1.00	1.00	0.46	0.46	∞
Linearity	E.2.4	1.25	R	1.73	1.00	1.00	0.72	0.72	∞
System detection limits	E.2.4	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Modulation response	E.2.5	3.42	R	1.73	1.00	1.00	1.97	1.97	∞
Readout Electronics	E.2.6	0.26	N	1.00	1.00	1.00	0.26	0.26	∞
Response Time	E.2.7	0.17	R	1.73	1.00	1.00	0.10	0.10	∞
Integration Time	E.2.8	1.43	R	1.73	1.00	1.00	0.83	0.83	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	1.00	1.00	2.03	2.03	∞
RF ambient conditions- reflections	E.6.1	3.15	R	1.73	1.00	1.00	1.82	1.82	∞
Probe positioner mechanical tolerance	E.6.2	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.40	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.10	R	1.73	1.00	1.00	1.21	1.21	∞
Test sample Related									
Test sample positioning	E.4.2	3.10	N	1.00	1.00	1.00	3.10	3.10	∞
Device holder uncertainty	E.4.1	3.80	N	1.00	1.00	1.00	3.80	3.80	∞
Output power variation— SAR drift measurement	E.2.9	4.50	R	1.73	1.00	1.00	2.60	2.60	∞
SAR scaling	E.6.5	1.80	R	1.73	1.00	1.00	1.04	1.04	∞
Phantom and tissue parameters									
Phantom shell uncertainty— shape, thickness, and permittivity	E.3.1	3.70	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	2.40	R	1.73	0.78	0.71	1.08	0.98	M
Liquid permittivity measurement	E.3.3	4.10	N	1.00	0.78	0.71	3.20	2.91	M
Liquid conductivity— temperature uncertainty	E.3.4	2.70	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity— temperature uncertainty	E.3.4	4.80	N	1.00	0.23	0.26	1.10	1.25	∞
Combined Standard Uncertainty			RSS				10.08	9.59	
Expanded Uncertainty (95% Confidence interval)			K=2				19.58	19.18	



SATIMO Uncertainty- SN 08/21 EPGO352									
System Validation uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System									
Probe calibration	E.2.1	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	1.00	1.00	0.10	0.10	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.00	0.00	0.00	0.00	∞
Boundary effect	E.2.3	0.80	R	1.73	1.00	1.00	0.46	0.46	∞
Linearity	E.2.4	1.25	R	1.73	1.00	1.00	0.72	0.72	∞
System detection limits	E.2.4	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Modulation response	E.2.5	3.42	R	1.73	0.00	0.00	0.00	0.00	∞
Readout Electronics	E.2.6	0.26	N	1.00	1.00	1.00	0.26	0.26	∞
Response Time	E.2.7	0.17	R	1.73	0.00	0.00	0.00	0.00	∞
Integration Time	E.2.8	1.43	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	1.00	1.00	2.03	2.03	∞
RF ambient conditions-reflections	E.6.1	3.15	R	1.73	1.00	1.00	1.82	1.82	∞
Probe positioner mechanical tolerance	E.6.2	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.40	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.10	R	1.73	1.00	1.00	1.21	1.21	∞
System validation source									
Deviation of experimental dipole from numerical dipole	E.6.4	4.80	N	1.00	1.00	1.00	4.80	4.80	∞
Input power and SAR drift measurement	8,6.6.4	5.10	R	1.73	1.00	1.00	2.94	2.94	∞
Dipole axis to liquid distance	8,E.6.6	2.40	R	1.73	1.00	1.00	1.39	1.39	∞
Phantom and set-up									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	3.70	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity (temperature uncertainty)	E.3.3	2.40	R	1.73	0.78	0.71	1.08	0.98	∞
Liquid conductivity (measured)	E.3.3	4.10	N	1.00	0.78	0.71	3.20	2.91	M
Liquid permittivity (temperature uncertainty)	E.3.4	2.70	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity (measured)	E.3.4	4.80	N	1.00	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty			RSS				9.72	9.52	
Expanded Uncertainty (95% Confidence interval)			K=2				19.44	19.03	



SATIMO Uncertainty- SN 08/21 EPGO352									
◦ System Check uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+- %)	10g Ui (+-%)	vi
Measurement System									
Probe calibration drift	E.2.1.3	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	0.00	0.00	0.00	0.00	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.00	0.00	0.00	0.00	∞
Boundary effect	E.2.3	0.8	R	1.73	0.00	0.00	0.00	0.00	∞
Linearity	E.2.4	1.25	R	1.73	0.00	0.00	0.00	0.00	∞
System detection limits	E.2.4	1.20	R	1.73	0.00	0.00	0.00	0.00	∞
Modulation response	E.2.5	3.42	R	1.73	0.00	0.00	0.00	0.00	∞
Readout Electronics	E.2.6	0.26	N	1.00	0.00	0.00	0.00	0.00	∞
Response Time	E.2.7	0.17	R	1.73	0.00	0.00	0.00	0.00	∞
Integration Time	E.2.8	1.43	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions- Noise	E.6.1	3.51	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions- reflections	E.6.1	3.15	R	1.73	0.00	0.00	0.00	0.00	∞
Probe positioner mechanical tolerance	E.6.2	1.2	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.4	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	3.9	R	1.73	0.00	0.00	0.00	0.00	∞
System check source (dipole)									
Deviation of experimental dipoles	E.6.4	4.8	N	1.00	1.00	1.00	4.80	4.80	∞
Input power and SAR drift measurement	8,6.6.4	5.1	R	1.73	1.00	1.00	2.94	2.94	∞
Dipole axis to liquid distance	8,E.6.6	2.4	R	1.73	1.00	1.00	1.39	1.39	∞
Phantom and tissue parameters									
Phantom shell uncertainty— shape, thickness, and permittivity	E.3.1	3.7	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	2.4	R	1.73	0.78	0.71	1.08	0.98	∞
Liquid permittivity measurement	E.3.3	4.1	N	1.00	0.78	0.71	3.20	2.91	M
Liquid conductivity— temperature uncertainty	E.3.4	2.7	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity— temperature uncertainty	E.3.4	4.8	N	1.00	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty			RSS				5.56	5.20	
Expanded Uncertainty (95% Confidence interval)			K=2				11.12	10.41	



10. Conducted Power Measurement

10.1 Test Result

2.4G WLAN

2.4GWIFI				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
802.11b	1	2412	17.83	60.67
	7	2437	18.65	73.28
	11	2462	17.98	62.81
802.11g	1	2412	17.56	57.02
	7	2437	18.70	74.13
	11	2462	18.49	70.63
802.11 n-HT20	1	2412	17.88	61.38
	7	2437	18.65	73.28
	11	2462	19.66	92.47

5.2G WLAN

5.2G WLAN				
Mode	Channel Number	Frequency (MHz)	Result [dBm]	Output Power (mW)
802.11a	36	5180	15.77	37.76
	40	5200	15.91	38.99
	48	5240	15.59	36.22
802.11 n-HT20	36	5180	15.86	38.55
	40	5200	15.83	38.28
	48	5240	15.49	35.40
802.11 n-HT40	38	5190	16.31	42.76
	46	5230	16.04	40.18
802.11ac-VHT20	36	5180	15.73	37.41
	40	5200	15.64	36.64
	48	5240	15.36	34.36
802.11ac-VHT40	38	5190	16.07	40.46
	46	5230	15.88	38.73
802.11ac-VHT80	42	5210	16.69	46.67

**5.3G WLAN**

5.3G WLAN				
Mode	Channel Number	Frequency (MHz)	Result [dBm]	Output Power (mW)
802.11a	52	5260	16.03	40.09
	60	5300	16.48	44.46
	64	5320	16.79	47.75
802.11 n-HT20	52	5260	16.03	40.09
	60	5300	16.42	43.85
	64	5320	16.88	48.75
802.11 n-HT40	54	5270	16.59	45.60
	62	5310	17.18	52.24
802.11ac-VHT20	52	5260	16.11	40.83
	60	5300	16.50	44.67
	64	5320	16.79	47.75
802.11ac-VHT40	54	5270	16.73	47.10
	62	5310	17.22	52.72
802.11ac-VHT80	58	5290	17.36	54.45

5.6G WLAN

5.6G WLAN				
Mode	Channel Number	Frequency (MHz)	Result [dBm]	Output Power (mW)
802.11a	100	5500	19.13	81.85
	116	5580	19.52	89.54
	140	5700	18.74	74.82
802.11 n-HT20	100	5500	19.12	81.66
	116	5580	19.58	90.78
	140	5700	18.75	74.99
802.11 n-HT40	102	5510	19.12	81.66
	110	5550	19.81	95.72
	134	5670	18.89	77.45
802.11ac-VHT20	100	5500	18.93	78.16
	116	5580	19.50	89.13
	140	5700	18.63	72.95
802.11ac-VHT40	102	5510	18.99	79.25
	110	5550	19.57	90.57
	134	5670	18.83	76.38
802.11ac-VHT80	106	5530	19.77	94.84
	122	5610	19.60	91.20

**5.8G WLAN**

5.8G WLAN				
Mode	Channel Number	Frequency (MHz)	Result [dBm]	Output Power (mW)
802.11a	149	5745	17.83	60.67
	157	5785	17.41	55.08
	165	5825	17.49	56.10
802.11 n-HT20	149	5745	18.63	72.95
	157	5785	18.93	78.16
	165	5825	17.08	51.05
802.11 n-HT40	151	5755	18.03	63.53
	159	5795	17.03	50.47
802.11ac-VHT20	149	5745	17.64	58.08
	157	5785	17.30	53.70
	165	5825	16.32	42.85
802.11ac-VHT40	151	5755	17.92	61.94
	159	5795	17.54	56.75
802.11ac-VHT80	155	5775	17.23	52.84


11. EUT and Test Setup Photo

11.1 EUT Photo

Front side




Back side







Top side




Bottom side



Left side




Right side





11.2 Setup Photo

Back Side (separation distance is 0mm)




Top side(separation distance is 0mm)





Liquid depth (15 cm)





12. SAR Result Summary

12.1 Body SAR

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
2.4GHz WLAN	N/A	802.11b	N/A	N/A	Back Side	2412	0.892	-2.12	18.00	17.83	1.040	0.928	/
					Back Side	2437	1.041	3.98	19.00	18.65	1.084	1.128	1
					Back Side	2462	0.901	0.04	18.00	17.98	1.005	0.905	/
					Top Side	2412	0.83	-3.93	18.00	17.83	1.040	0.863	/
					Top Side	2437	0.851	-3.58	19.00	18.65	1.084	0.922	/
					Top Side	2462	0.819	1.72	18.00	17.98	1.005	0.823	/
BT	N/A	8DPSK (3Mbps)	N/A	N/A	Back Side	2441	0.477	-0.48	9.50	9.18	1.076	0.513	2
					Top Side	2441	0.425	3.78	9.50	9.18	1.076	0.457	/
5.2GHz WLAN	N/A	802.11ac-VHT80	N/A	N/A	Back Side	5210	0.734	-0.17	17.00	16.69	1.074	0.788	3
					Top Side	5210	0.667	-2.10	17.00	16.69	1.074	0.716	/
5.3GHz WLAN	N/A	802.11ac-VHT80	N/A	N/A	Back Side	5290	0.938	-2.04	17.50	17.36	1.033	0.969	4
					Top Side	5290	0.868	-1.60	17.50	17.36	1.033	0.896	/
5.6GHz WLAN	N/A	802.11 n-HT40	N/A	N/A	Back Side	5510	0.908	-0.77	19.50	19.12	1.091	0.991	/
					Back Side	5550	0.953	-1.88	20.00	19.81	1.045	0.996	5
					Back Side	5670	0.925	-2.22	19.00	18.89	1.026	0.949	/
					Top Side	5510	0.824	1.41	19.50	19.12	1.091	0.899	/
					Top Side	5550	0.887	-1.44	20.00	19.81	1.045	0.927	/
					Top Side	5670	0.831	0.38	19.00	18.89	1.026	0.852	/
5.8GHz WLAN	N/A	802.11 n-HT20	N/A	N/A	Back Side	5785	0.474	-1.40	19.00	18.93	1.016	0.482	6
					Top Side	5785	0.452	0.73	19.00	18.93	1.016	0.459	/

Note:

- The test separation of all above table is 0mm.
- Per KDB 447498 D04, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
- When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.

**12.2 Repeated SAR**

Band	Mode	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaled SAR(W/Kg)	Meas. No.
2.4GHz WLAN	802.11b	Back Side	2412	0.878	0.30	18	17.83	0.913	-
		Back Side	2437	1.025	-1.03	19	18.65	1.111	-
		Back Side	2462	0.868	-3.56	18	17.98	0.872	-
		Top Side	2412	0.825	0.38	18	17.83	0.858	-
		Top Side	2437	0.843	0.34	19	18.65	0.913	-
		Top Side	2462	0.808	3.18	18	17.98	0.811	-
5.3GHz WLAN	802.11ac-VHT80	Back Side	5290	0.908	1.82	17.5	17.36	0.938	-
		Top Side	5290	0.867	-2.54	17.5	17.36	0.896	-
5.6GHz WLAN	802.11 n-HT40	Back Side	5510	0.887	-2.63	19.5	19.12	0.968	-
		Back Side	5550	0.926	-0.60	20	19.81	0.968	-
		Back Side	5670	0.908	2.53	19	18.89	0.931	-
		Top Side	5510	0.807	-2.81	19.5	19.12	0.880	-
		Top Side	5550	0.876	-3.95	20	19.81	0.915	-
		Top Side	5670	0.817	-3.46	19	18.89	0.838	-

**12.3 Repeated SAR measurement**

Band	Mode	Test Position	Freq.	Original Measured SAR 1g(W/kg)	1 st Repeated SAR 1g	Ratio	Original Measured SAR 1g(W/kg)	2nd Repeated SAR 1g	Ratio
2.4GHz WLAN	802.11b	Back Side	2412	0.892	0.878	1.016	-	-	-
		Back Side	2437	1.041	1.025	1.016	-	-	-
		Back Side	2462	0.901	0.868	1.038	-	-	-
		Top Side	2412	0.83	0.825	1.006	-	-	-
		Top Side	2437	0.851	0.843	1.010	-	-	-
		Top Side	2462	0.819	0.808	1.014	-	-	-
5.3GHz WLAN	802.11ac-VHT80	Back Side	5290	0.938	0.908	1.033	-	-	-
		Top Side	5290	0.868	0.867	1.001	-	-	-
5.6GHz WLAN	802.11 n-HT40	Back Side	5510	0.908	0.887	1.024	-	-	-
		Back Side	5550	0.953	0.926	1.029	-	-	-
		Back Side	5670	0.925	0.908	1.019	-	-	-
		Top Side	5510	0.824	0.807	1.022	-	-	-
		Top Side	5550	0.887	0.876	1.012	-	-	-
		Top Side	5670	0.831	0.817	1.017	-	-	-

Note:

1. Per KDB 865664 D01,for each frequency band ,repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/Kg}$.
2. Per KDB 865664 D01,if the ratio of largest to smallest SAR for the original and first repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/Kg}$, only one repeated measurement is required.
3. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45\text{W/Kg}$.
4. The ratio is the difference in percentage between original and repeated measured SAR.



13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
2450MHzDipole	MVG	SID2450	SN 30/14 DIP2G450-335	2023.07.04	2026.07.03
Waveguide	MVG	SWG5500	SN 13/14 WGA32	2023.07.04	2026.07.03
E-Field Probe	MVG	SSE2	SN 08/21 EPGO352	2024.09.18	2025.09.17
Dielectric Probe Kit	MVG	SCLMP	SN 32/14 OCPG67	2024.09.18	2025.09.17
Antenna	MVG	ANTA3	SN 07/13 ZNTA52	N/A	N/A
Phantom1	MVG	SAM	SN 32/14 SAM115	N/A	N/A
Phantom3	MVG	SAM	SN 21/21 ELLI48	N/A	N/A
Phone holder	MVG	N/A	SN 32/14 MSH97	N/A	N/A
Laptop holder	MVG	N/A	SN 32/14 LSH29	N/A	N/A
Attenuator	Agilent	HXT-10-8-SMA	240327017	2025-02-22	2026-02-21
Directional coupler	Xi'an Xingbo	XBOH-OA08- 20dB	211123-4-3	2025-02-22	2026-02-21
Network Analyzer	Agilent	E5071C	MY46520378	2024-09-25	2025-09-26
Multi Meter	Keithley	Multi Meter 2000	4050073	2024-09-25	2025-09-26
Signal Generator	Agilent	N5182A	MY50140530	2024-09-25	2025-09-26
Wireless Communication Test Set	Agilent	8960-E5515C	MY48360751	2025-02-22	2026-02-21
Wireless Communication Test Set	R&S	CMW500	156324	2024-09-25	2025-09-26
Power Amplifier	DESAY	ZHL-42W	9638	2024-09-25	2025-09-26
Power Meter	R&S	NRP	100510	2024-09-25	2025-09-26
Power Sensor	R&S	NRP-Z11	101919	2024-09-25	2025-09-26
Power Sensor	Keysight	U2021XA	MY56280002	2024-09-25	2025-09-26
Temperature hygrometer	SuWei	SW-108	N/A	2024.10.15	2025.10.14
Thermograph	Elitech	RC-4	S/N EF7176501537	2024.10.15	2025.10.14



Appendix A. System Validation Plots

System Performance Check Data (2450MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2026-03-17

Experimental conditions.

Device Position	Validation plane
Band	2450 MHz
Channels	-
Signal	CW
Frequency (MHz)	2450
Relative permittivity	38.97
Conductivity (S/m)	1.79
Probe	SN 08/21 EPGO352
ConvF	1.82
Crest factor:	1:1





Maximum location: X=3.00, Y=2.00 ; SAR Peak: 8.35 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	2.394
SAR 1g (W/Kg)	5.463
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	55.852595

**E. Z Axis Scan**

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	8.359	5.361	2.994	1.676	0.950	0.534	0.300

**F. 3D Image**

**System Performance Check Data (5200MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2026-03-17

Experimental conditions.

Device Position	Validation plane
Band	5200 MHz
Channels	-
Signal	CW
Frequency (MHz)	5200
Relative permittivity	36.86
Conductivity (S/m)	4.66
Probe	SN 08/21 EPGO352
ConvF	1.37
Crest factor:	1:1





Maximum location: X=-3.00, Y=-8.00 ; SAR Peak: 4.15 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.530
SAR 1g (W/Kg)	1.544
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	59.388783

**E. Z Axis Scan**

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	3.871	2.478	1.472	0.865	0.588	0.368	0.230	0.144	0.090	0.057	0.035	0.022

**F. 3D Image**

**System Performance Check Data (5600MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2026-03-17

Experimental conditions.

Device Position	Validation plane
Band	5600 MHz
Channels	-
Signal	CW
Frequency (MHz)	5600
Relative permittivity	35.66
Conductivity (S/m)	5.05
Probe	SN 08/21 EPGO352
ConvF	1.21
Crest factor:	1:1





Maximum location: X=6.00, Y=1.00 ; SAR Peak: 5.09 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.618
SAR 1g (W/Kg)	1.740
Horizontal validation criteria: minimum distance (mm)	8.944272
Vertical validation criteria: SAR ratio M2/M1 (%)	54.481674

**E. Z Axis Scan**

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	4.516	2.860	1.558	0.993	0.594	0.356	0.213	0.127	0.076	0.046	0.027	0.016

**F. 3D Image**

**System Performance Check Data (5800MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2026-03-17

Experimental conditions.

Device Position	Validation plane
Band	5800 MHz
Channels	-
Signal	CW
Frequency (MHz)	5800
Relative permittivity	34.88
Conductivity (S/m)	5.27
Probe	SN 08/21 EPGO352
ConvF	1.32
Crest factor:	1:1





Maximum location: X=5.00, Y=6.00 ; SAR Peak: 5.28 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.609
SAR 1g (W/Kg)	1.892
Horizontal validation criteria: minimum distance (mm)	8.944272
Vertical validation criteria: SAR ratio M2/M1 (%)	54.771665

**E. Z Axis Scan**

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	4.924	3.016	1.652	0.881	0.576	0.336	0.196	0.114	0.067	0.039	0.023	0.013


**F. 3D Image**



Appendix B. SAR Test Plots

Plot 1: DUT: W6C Tablet; EUT Model: W6C

Test Date	2026-03-25
ConvF	1.82
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Body
Device Position	Back
Band	2.4GHz WLAN
Signal	802.11b (Crest factor: 1.0)
Frequency (MHz)	2437
Relative permittivity (real part)	39.13
Conductivity (S/m)	1.78





Maximum location: X=6.00, Y=-58.00 ; SAR Peak: 1.96 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.482
SAR 1g (W/Kg)	1.041
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	49.332752

**E. Z Axis Scan**


Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.939	1.147	0.566	0.297	0.152	0.078	0.040

**F. 3D Image**



Plot 2: DUT: W6C Tablet; EUT Model: W6C

Test Date	2026-03-25
ConvF	1.82
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Body
Device Position	Back
Band	BT
Signal	8DPSK(3Mbps)
Frequency (MHz)	2441
Relative permittivity (real part)	39.43
Conductivity (S/m)	1.80




Maximum location: X=5.00, Y=-80.00 ; SAR Peak: 0.87 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.226
SAR 1g (W/Kg)	0.477
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	52.015691

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.848	0.520	0.271	0.144	0.076	0.040	0.021




F. 3D Image





Plot 3: DUT: W6C Tablet; EUT Model: W6C

Test Date	2026-03-25
ConvF	1.37
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Body
Device Position	Back
Band	5.2GHz WLAN
Signal	802.11ac-VHT80(Crest factor: 1.0)
Frequency (MHz)	5210
Relative permittivity (real part)	35.59
Conductivity (S/m)	4.67





Maximum location: X=5.00, Y=-9.00 ; SAR Peak: 1.97 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.297
SAR 1g (W/Kg)	0.734
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.581458

**E. Z Axis Scan**


Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	1.666	1.020	0.403	0.388	0.366	0.383	0.281	0.257	0.217	0.173	0.167	0.116

**F. 3D Image**



Plot 4: DUT: W6C Tablet; EUT Model: W6C

Test Date	2026-03-25
ConvF	1.37
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Body
Device Position	Back
Band	5.3GHz WLAN
Signal	802.11ac-VHT80(Crest factor: 1.0)
Frequency (MHz)	5290
Relative permittivity (real part)	36.66
Conductivity (S/m)	4.75





D. SAR 1g & 10g

SAR 10g (W/Kg)	0.422
SAR 1g (W/Kg)	0.938
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	59.902617

**E. Z Axis Scan**


Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.121	1.261	0.756	2.386	0.643	0.449	0.289	0.231	0.184	0.225	0.179	0.158

**F. 3D Image**



Plot 5: DUT: W6C Tablet; EUT Model: W6C

Test Date	2026-03-25
ConvF	1.21
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Body
Device Position	Back
Band	5.6GHz WLAN
Signal	802.11 n-HT40(Crest factor: 1.0)
Frequency (MHz)	5550
Relative permittivity (real part)	35.84
Conductivity (S/m)	5.01





Maximum location: X=8.00, Y=-15.00 ; SAR Peak: 2.80 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.399
SAR 1g (W/Kg)	0.953
Horizontal validation criteria: minimum distance (mm)	5.656854
Vertical validation criteria: SAR ratio M2/M1 (%)	56.290389

**E. Z Axis Scan**


Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	2.175	1.381	0.777	0.494	0.612	0.500	0.408	0.333	0.272	0.222	0.182	0.148

**F. 3D Image**



Plot 5: DUT: W6C Tablet; EUT Model: W6C

Test Date	2026-03-25
ConvF	1.32
Probe	SN 08/21 EPG0352
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Body
Device Position	Back
Band	5.8GHz WLAN
Signal	802.11 n-HT20(Crest factor: 1.0)
Frequency (MHz)	5785
Relative permittivity (real part)	35.64
Conductivity (S/m)	5.25




D. SAR 1g & 10g

SAR 10g (W/Kg)	0.265
SAR 1g (W/Kg)	0.474
Horizontal validation criteria: minimum distance (mm)	5.656854
Vertical validation criteria: SAR ratio M2/M1 (%)	60.608734




E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	1.044	0.641	0.292	0.258	0.252	0.300	0.216	0.229	0.186	0.176	0.160	0.134



F. 3D Image





Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※END OF THE REPORT※※※※