

FCC Part 15



EMI TEST REPORT

of

E.U.T. : Bluetooth intercom headset
Model No. : R1A
Serial Model : R1+
FCC ID : 2A3C2QR1

for

APPLICA : Taiwan Protect Ltd.
NT
ADDRESS NO. 337-1, Sec.1, Zhongyang Rd., Wuchi Dist.,
Taichung City 43546, Taiwan

Test Performed by

Taiwan Testing and Certification Center

No.34, Dingfu, Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)

NEW TAIPEI CITY, TAIWAN, 24442, R.O.C.

Tel : (02)26023052 Fax : (02)26010910

<http://www.etc.org.tw> ; e-mail: emc@etc.org.tw

Report Number : 20-03-RBF-021-02

TEST REPORT CERTIFICATION

Applicant : Taiwan Protect Ltd.
NO. 337-1, Sec.1, Zhongyang Rd., Wuchi Dist., Taichung City 43546,
Taiwan

Manufacture : Taiwan Protect Ltd.
NO. 337-1, Sec.1, Zhongyang Rd., Wuchi Dist., Taichung City 43546,
Taiwan

Description of Device :

- a) Type of EUT : Bluetooth intercom headset
- b) Trade Name : AiTouch
- c) Model No. : R1A
- d) Serial Model : R1+
- e) Power Supply : DC 3.7V
- f) Frequency Range : BLE 2402~2480 MHz

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.10-2013, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note: 1. The result of the testing report relate only to the item tested.

2. The testing report shall not be reproduced expect in full, without the written approval of
ETC

Summary of Tests

Test	Results
Radiated Emission	Pass
Conducted Emission	Pass
Emission Bandwidth	Pass
Output Power	Pass
100 kHz Bandwidth of Band Edges	Pass
Power Density	Pass
Out-of-Band Conducted Emission	Pass
Duty Cycle	N/A

Date Test Item Received : 3/31/2020

Date Test Campaign Completed : 8/10/2021

Date of Issue : 11/2/2021

Test Engineer :

Brian Huang

(Brian Huang, Engineer)



Approve & Authorized :

Vincent Chang

Vincent Chang, Supervisor

Section Manager of EMC Dept. II

Table of Contents	Page
1 GENERAL INFORMATION.....	6
1.1 Product Description	6
1.2 Characteristics of Device	6
1.3 Test Methodology	6
1.4 Test Facility.....	6
2 PROVISIONS APPLICABLE.....	7
2.1 Definition	7
2.2 Requirement for Compliance	8
2.3 Restricted Bands of Operation	10
2.4 Labeling Requirement.....	10
2.5 User Information	11
2.6 Measurement Uncertainty	12
3. SYSTEM TEST CONFIGURATION.....	13
3.1 Justification.....	13
3.2 Devices for Tested System.....	14
4 RADIATED EMISSION MEASUREMENT	15
4.1 Applicable Standard.....	15
4.2 Measurement Procedure.....	15
4.3 Measuring Instrument	17
4.4 Radiated Emission Data.....	18
4.5 Field Strength Calculation	28
4.6 Photos of Radiation Measuring Setup.....	29
5.1 Description.....	33
5.2 Measurement Procedure.....	33
5.3 Conducted Emission Data.....	34
5.4 Result Data Calculation	36
5.5 Conducted Measurement Equipment.....	36
5.6 Photos of Conduction Measuring Setup	37
6 ANTENNA REQUIREMENT.....	38
6.1 Standard Applicable.....	38
6.2 Antenna Construction and Directional Gain.....	38
7 EMISSION BANDWIDTH MEASUREMENT.....	39
7.1 Standard Applicable.....	39
7.2 Measurement Procedure.....	39

7.3 Measurement Equipment	39
7.4 Measurement Data	40
8 OUTPUT POWER MEASUREMENT.....	43
8.1 Standard Applicable.....	43
8.2 Measurement Procedure.....	43
8.3 Measurement Equipment	43
8.4 Measurement Data	44
9 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT.....	45
9.1 Standard Applicable.....	45
9.2 Measurement Procedure.....	45
9.3 Measurement Equipment	45
9.4 Measurement Data	46
10 POWER DENSITY MEASUREMENT	48
10.1 Standard Applicable.....	48
10.2 Measurement Procedure.....	48
10.3 Measurement Equipment	48
10.4 Measurement Data	49
11. OUT-OF-BAND CONDUCTED EMISSION MEASUREMENT.....	52
11.1 Standard Applicable.....	52
11.2 Measurement Procedure.....	52
11.3 Measurement Equipment	52
11.4 Measurement Data	53
12. DUTY CYCLE.....	57
12.1 Standard Applicable.....	57
12.2 Measurement Equipment	57
12.3 Measurement Data	57

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : Bluetooth intercom headset
- b) Trade Name : AiTouch
- c) Model No. : R1A
- d) Power Supply : R1+
- e)Receiving Frequency : DC 3.7V

1.2 Characteristics of Device

- e)Receiving Frequency : DC 3.7V

1.3 Test Methodology

Both conducted and radiated emissions were performed according to the procedures illustrated in ANSI C63.10-2013. Other required measurements were illustrated in separate sections of this test report for details. For RF test the measurement procedure was referred to FCC KDB 558074 D01 15.247 Meas Guidance v05r02

Measurement Software

Software	Version	Note
e3	Version 6.100618f	Radiated Emission Test
e3	Version 6.100421	Conducted Emission Test

1.4 Test Facility

Location of the Test site: No.34, Lin 5, Dingfu Vil., Linkou Dist., New Taipei City, Taiwan 24442, R.O.C.

Designation Number: TW2628.

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business or industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

* Decreases with the logarithm of the frequency

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

(4) Bandwidth Requirement

For direct sequence system, according to 15.247(a)(2), the minimum 6dB bandwidth shall be at least 500 kHz.

(5) Output Power Requirement

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

(7) Power Density Requirement

According to 15.247(d), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.15
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

In users manual, the Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

2.6 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz ~ 30MHz	$\pm 3.34\text{dB}$ (Mains)(LISN)
Radiated emissions	9kHz ~ 30MHz	$\pm 4.22\text{dB}$
Radiated emissions	30MHz ~ 1GHz	$\pm 4.2\text{dB}$ ($30\text{MHz} \leq f \leq 300\text{MHz}$)
		$\pm 4.44\text{dB}$ ($300\text{MHz} < f \leq 1\text{GHz}$)
	Above 1GHz	$\pm 4.44\text{dB}$ ($1\text{GHz} \leq f \leq 18\text{GHz}$)
		$\pm 3.02\text{dB}$ ($18\text{GHz} \leq f \leq 40\text{GHz}$)
Conducted Measurement	9kHz ~ 40GHz	$\pm 0.88\text{dB}$ ($9\text{kHz} \leq f \leq 30\text{MHz}$)
		$\pm 0.88\text{dB}$ ($30\text{MHz} < f \leq 1\text{GHz}$)
		$\pm 1.04\text{dB}$ ($1\text{GHz} \leq f \leq 18\text{GHz}$)
		$\pm 1.2\text{dB}$ ($18\text{GHz} \leq f \leq 40\text{GHz}$)
Frequencies Tolerance	9kHz ~ 40GHz	$\pm 4.04 \times 10^{-8}$
Occupied Bandwidth	9kHz ~ 40GHz	$\pm 5\%$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

The test result(s) does not consider the uncertainty of measurement when the test standard(s) and/or test method which refer by the labs has the limit or judgments for the test result(s).

3. SYSTEM TEST CONFIGURATION

3.1 Justification

For both radiated and conducted emissions, the system was configured for testing in a typical fashion as a customer would normally use it. The peripherals other than EUT were connected in normally standing by situation. Measurement was performed under the condition that a computer program was exercised to simulate data communication of EUT, and the transmission rate was set to maximum allowed by EUT. Three highest emissions were verified with varying placement of the transmitting antenna connected to EUT (if applicable) to maximize the emission from EUT.

For conducted and radiated emissions, whichever RF channel is operated, the digital circuits' function identically. As the reason, measurement of emissions from digital circuits is performed with the highest, middle and the lowest channel by transmitting mode.

All measurement were intentional to maximum the emissions from EUT by varying the connection cables(if applicable), therefore, the test result is sure to meet the applicable requirement.

For portable device (if applicable), the EUT was pretested in three orthogonal plans: put on table horizontally, stands vertically and side up vertically. The worst case was chosen for final test.

The following mode was investigated and only provided the worst cases (mode 1) was chosen for final test.

1. Bluetooth Low Energy (Bluetooth LE) Data Rate 1 Mbps uses GFSK modulation

3.2 Devices for Tested System

EUT & accessories.

Device	Manufacture	Model	Description
Bluetooth intercom headset*	Taiwan Protect Ltd.	R1A	---
Type-C to USB	Taiwan Protect Ltd.	R1A	1.0m Unshielded Line
Type-C to year phone	Taiwan Protect Ltd.	R1A	1.0m Unshielded Line

Remark “*” means equipment under test.

The EUT connected with the following peripheral devices.

Device	Manufacture	Model	Description
AC/DC Power Adapter	TOPCOM	TC-KPD36WD	--

4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §15.109(a).

For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and direct sequence spread spectrum, and the out band emission shall be comply with §15.247 (d)

4.2 Measurement Procedure

A. Preliminary Measurement For Portable Devices

For portable devices, the following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

B. Final Measurement

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz and above 1 GHz, testing in a 966 RF shielded chamber #2.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables (if any) associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement:

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESU40	2021/3/25	2022/3/24
Bi-Log Antenna	ETC & JYEBAO	MCTD 2786B & FAT- NM5NF5T3G 2W5	2021/7/8	2022/7/7
Amplifier	HP	8447D	2021/07/15	2022/07/14
Horn Antenna (1-18G)	EMCO	3117	2021/03/16	2022/03/15
Amplifier (1G-18G)	HP	8449B	2020/10/06	2021/10/05
Horn Antenna (18-40G)	EMCO	3116	2020/08/19	2021/08/18
Amplifier (1G-40G)	Keysight	83051A	2020/08/27	2021/08/26

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz or $\geq 1/T$ (Note 1)


Note 1:

VBW = 10 Hz, when the duty cycle is no less than 98%.

VBW $\geq 1/T$, when duty cycle is less than 98% where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

4.4 Radiated Emission Data

4.4.1 RF Portion




Site	:Chamber #2	Date	:2020-04-22
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	: Bluetooth intercom headset	Model	:R1A
Power Rating	: Battery 3.7V	Temp.	:20 °C
Engineer	: Brian Huang	Humi.	:68 %
Test Mode	:BLE Mode		
Test Mode	:		

Freq	Reading	Correction	Result	Limits	Over limit	Detector
MHz	dBuV	Factor	dBuV/m	dBuV/m	dB	
4804.0000	41.40	4.07	45.47	74.00	-28.53	Peak
4880.0000	41.54	4.16	45.70	74.00	-28.30	Peak
4960.0000	41.62	4.25	45.87	74.00	-28.13	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.




Site	:Chamber #2	Date	:2020-04-22
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	: Bluetooth intercom headset	Model	:R1A
Power Rating	: Battery 3.7V	Temp.	:20 °C
Engineer	: Brian Huang	Humi.	:68 %
Test Mode	:BLE Mode		
Test Mode	:		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
4804.0000	41.31	4.07	45.38	74.00	-28.62	Peak
4880.0000	41.50	4.16	45.66	74.00	-28.34	Peak
4960.0000	41.63	4.25	45.88	74.00	-28.12	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.

4.4.2 Radiated Emission of Restricted bands




Site	:Chamber #2	Date	:2020-04-22
Limit	:1G TO 40G PEAK	Ant. Pol.	:HORIZONTAL
EUT	: Bluetooth intercom headset	Model	:R1A
Power Rating	: Battery 3.7V	Temp.	:20 °C
Engineer	: Brian Huang	Humi.	:68 %
Test Mode	:BLE Mode		
Test Mode	:		

Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2357.2800	46.03	-0.94	45.09	74.00	-28.91	Peak
2375.7600	45.37	-0.83	44.54	74.00	-29.46	Peak
2506.0800	50.47	-0.55	49.92	74.00	-24.08	Peak
2532.0000	49.70	-0.57	49.13	74.00	-24.87	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.



Site	:Chamber #2	Date	:2020-04-22
Limit	:1G TO 40G PEAK	Ant. Pol.	:VERTICAL
EUT	: Bluetooth intercom headset	Model	:R1A
Power Rating	: Battery 3.7V	Temp.	:20 °C
Engineer	: Brian Huang	Humi.	:68 %
Test Mode	:BLE Mode		
Test Mode	:		


Freq MHz	Reading dBuV	Correction Factor dB	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
2352.7200	46.86	-0.96	45.90	74.00	-28.10	Peak
2373.8400	46.81	-0.84	45.97	74.00	-28.03	Peak
2505.8400	46.75	-0.55	46.20	74.00	-27.80	Peak
2531.0400	45.71	-0.57	45.14	74.00	-28.86	Peak

Note :

1. Result = Reading + Corrected Factor
2. Average Result = Peak Result + Duty Factor ()
3. Corrected Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.

4.4.3 Other Emission

a) Emission frequencies below 1 GHz




Site	:Chamber #2	Date	:2021-08-10
Limit	:FCC CLASS-B	Ant. Pol.	:HORIZONTAL
EUT	: Bluetooth intercom headset	Model	:R1A
Power Rating	: Battery	Temp.	:25°C
Engineer	: Brian Huang	Humi.	:60 %
Test Mode	:BT Mode		

	Freq MHz	Reading dBuV	Correction Factor dB/m	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
	125.0600	29.47	-4.81	24.66	43.50	-18.84	QP
	232.7300	29.91	-7.59	22.32	46.00	-23.68	QP
	341.3700	28.52	-3.73	24.79	46.00	-21.21	QP
	406.3600	28.52	-2.21	26.31	46.00	-19.69	QP
	481.0500	29.16	-1.36	27.80	46.00	-18.20	QP
*	542.1600	29.27	-0.28	28.99	46.00	-17.01	QP

Note :

1. Result = Reading + Correction Factor
2. Average Result = Peak Result + Duty Factor ()
3. Correction Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.
6. " * " mean this data is the worst emission level.




Site	:Chamber #2	Date	: 2021-08-10
Limit	:FCC CLASS-B	Ant. Pol.	:VERTICAL
EUT	: Bluetooth intercom headset	Model	:R1A
Power Rating	: Battery	Temp.	:25°C
Engineer	: Brian Huang	Humi.	:60 %
Test Mode	:BT Mode		

	Freq MHz	Reading dBuV	Correction Factor dB/m	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
	129.9100	28.03	-4.83	23.20	43.50	-20.30	QP
	251.1600	28.43	-6.64	21.79	46.00	-24.21	QP
	334.5800	27.60	-3.98	23.62	46.00	-22.38	QP
	423.8200	28.56	-2.10	26.46	46.00	-19.54	QP
	493.6600	29.23	-1.32	27.91	46.00	-18.09	QP
*	573.2000	28.51	-0.37	28.14	46.00	-17.86	QP

Note :

1. Result = Reading + Correction Factor
2. Average Result = Peak Result + Duty Factor ()
3. Correction Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.
6. " * " mean this data is the worst emission level.




Site	:Chamber #2	Date	:2021-08-10
Limit	:FCC CLASS-B	Ant. Pol.	:HORIZONTAL
EUT	: Bluetooth intercom headset	Model	:R1A
Power Rating	:DC From Adapter	Temp.	:25°C
Engineer	: Brian Huang	Humi.	:60 %
Test Mode	:Charge Mode		

	Freq MHz	Reading dBuV	Correction Factor dB/m	Result dBuV/m	Limits dBuV/m	Over limit Db	Detector
	136.7000	29.77	-5.14	24.63	43.50	-18.87	QP
	249.2200	29.14	-6.76	22.38	46.00	-23.62	QP
	305.4800	29.75	-4.83	24.92	46.00	-21.08	QP
	385.0200	29.41	-2.80	26.61	46.00	-19.39	QP
	445.1600	30.60	-1.59	29.01	46.00	-16.99	QP
*	544.1000	31.46	-0.23	31.23	46.00	-14.77	QP

Note :

1. Result = Reading + Correction Factor
2. Average Result = Peak Result + Duty Factor ()
3. Correction Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.
6. " * " mean this data is the worst emission level.



Site	:Chamber #2	Date	:2021-08-10
Limit	:FCC CLASS-B	Ant. Pol.	:VERTICAL
EUT	: Bluetooth intercom headset	Model	:R1A
Power Rating	:DC Power From Adapter	Temp.	:25 °C
Engineer	:Brian Huang	Humi.	:60 %
Test Mode	:Charge Mode		

	Freq MHz	Reading dBuV	Correction Factor dB/m	Result dBuV/m	Limits dBuV/m	Over limit dB	Detector
	130.8800	29.04	-4.91	24.13	43.50	-19.37	QP
	282.2000	29.76	-5.01	24.75	46.00	-21.25	QP
	352.0400	29.64	-3.67	25.97	46.00	-20.03	QP
	439.3400	29.64	-1.62	28.02	46.00	-17.98	QP
	489.7800	29.74	-1.25	28.49	46.00	-17.51	QP
*	573.2000	29.89	-0.37	29.52	46.00	-16.48	QP

Note :

1. Result = Reading + Correction Factor
2. Average Result = Peak Result + Duty Factor ()
3. Correction Factor = Antenna Factor + Cable Loss - Amplifier Gain (if any)
4. The margin value=Limit - Result
5. Above 1Ghz : Peak measurements are compared to the average limit - as peak measurements are below the average limit, they also comply with the peak limit.
6. " * " mean this data is the worst emission level.

b) Emission frequencies above 1 GHz

According to exploratory test no any obvious emission were detected from above 1 GHz.

c) Emission frequencies below 30MHz (9kHz - 30MHz)

According to exploratory test no any obvious emissions were detected from 9 kHz to 30MHz. All emissions were greater than 20 dB below the limit. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\textbf{Result = Reading + Corrected Factor}$$

where

Corrected Factor = Antenna FACTOR + Cable Loss + High Pass Filter Loss - Amplifier Gain

5 CONDUCTED EMISSION MEASUREMENT


5.1 Description

For unintentional and intentional device, Line Conducted Emission Limits are in accordance to §15.107(a) and §15.207(a) respectively. Both Limits are identical specification.


5.2 Measurement Procedure

1. Setup the configuration per figure 3.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 6 or 8 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.

Figure 3 : Conducted emissions measurement configuration



5.3 Conducted Emission Data




Site	: conducted #1	Date	: 2021-08-10
Condition	: FCC CLASS-B QP	LISN	: NEUTRAL
Tem / Hum	: 24 °C / 65%	Test Mode	: Charge Mode
EUT	: Bluetooth intercom headset		
Power Rating	: DC 5V From Adapter 120Vac60Hz		
Engineer	: Brian Huang	Model	: R1A

	Freq (MHz)	Reading (dBUV)	Factor (dB)	Emission Level (dBUV)	Limit Line (dBUV)	Over Limit (dB)	Remark
*	0.3976	22.80	10.09	32.89	57.90	-25.01	QP
	3.7400	17.78	10.23	28.01	56.00	-27.99	QP
	4.1580	18.52	10.23	28.75	56.00	-27.25	QP
	4.5010	18.57	10.24	28.81	56.00	-27.19	QP
	4.8740	19.20	10.24	29.44	56.00	-26.56	QP
	5.6530	19.65	10.24	29.89	60.00	-30.11	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor
3. " * " mean this data is the worst emission level



Site	: conducted #1	Date	: 2021-08-10
Condition	: FCC CLASS-B QP	LISN	: LINE
Tem / Hum	: 24 °C / 65%	Test Mode	: Charge Mode
EUT	: Bluetooth intercom headset		
Power Rating	: DC 5V From Adapter 120Vac60Hz		
Engineer	: Brian Huang	Model	: R1A

	Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
	0.4468	23.66	10.08	33.74	56.93	-23.19	QP
*	0.5047	24.76	10.08	34.84	56.00	-21.16	QP
	0.6754	21.48	10.09	31.57	56.00	-24.43	QP
	6.4540	26.38	10.23	36.61	60.00	-23.39	QP
	7.2520	27.20	10.25	37.45	60.00	-22.55	QP
	7.6460	26.79	10.25	37.04	60.00	-22.96	QP

Note :

1. Result = Reading + Factor
2. Factor = LISN Factor + Cable Loss+ Pulse Limiter Factor
3. " * " mean this data is the worst emission level

5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$\text{RESULT} = \text{READING} + \text{LISN FACTOR}$$

Assume a receiver reading of 22.5 dB μ V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB μ V.

$$\text{RESULT} = 22.5 + 0.1 = 22.6 \text{ dB } \mu \text{ V}$$

$$\begin{aligned} \text{Level in } \mu \text{ V} &= \text{Common Antilogarithm}[(22.6 \text{ dB } \mu \text{ V})/20] \\ &= 13.48 \mu \text{ V} \end{aligned}$$

5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test .

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESCI	2020/10/14	2021/10/13
LISN	Schwarzbeck	NSLK 8127 PLC	2020/12/22	2021/12/21
PLUSE LIMITER (10dB)	Schwarzbeck	VTSD 9561 F-N	2021/04/29	2022/04/28

6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to §15.247 (b)(4), if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.2 Antenna Construction and Directional Gain

The antenna is permanently mounted on main PCB, no consideration of replacement.
Please see internal photos and the antenna specifications.

7 EMISSION BANDWIDTH MEASUREMENT


7.1 Standard Applicable

According to 15.247(a)(2), for direct sequence system, the minimum 6dB bandwidth shall be at least 500 kHz.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value. The settings of spectrum analyzer is as followings.
 - 1) Set RBW = 100 kHz.
 - 2) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - 3) Detector = Peak.
 - 4) Trace mode = max hold.
 - 5) Sweep = auto couple.
 - 6) Allow the trace to stabilize.
 - 7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
3. Repeat above procedures until all frequencies measured were complete.

Figure 4: Measurement configuration.



7.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2020/01/15	2021/01/14
Attenuator	MINI-CIRCUITS	BW-S10W2+	2019/10/04	2020/10/03


7.4 Measurement Data

Test Date : Apr. 14, 2020 Temperature : 22 °C Humidity : 51 %


Mode: Bluetooth BLE

- a) Channel Low: 6 dB Emission Bandwidth is 0.700 MHz
- b) Channel Mid: 6 dB Emission Bandwidth is 0.700 MHz
- c) Channel High: 6 dB Emission Bandwidth is 0.700 MHz


Note : The expanded uncertainty: $frequency \times 1.65 \times 10^{-6}$ ($1\text{ GHz} < f \leq 18\text{ GHz}$).

Mode: Bluetooth BLE / Channel Low

Date: 14.APR.2020 16:29:59

Mode: Bluetooth BLE / Channel Mid

Date: 14.APR.2020 16:29:59

Mode: Bluetooth BLE / Channel High

Date: 14.APR.2020 16:11:32

8 OUTPUT POWER MEASUREMENT

8.1 Standard Applicable

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


8.2 Measurement Procedure

Measurement Procedure:

9.1.2 PKPM1 Peak power meter method

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable.
3. Record the readings on the instrument and add a compensat factor of the attenuator.
4. Repeat above procedures until all frequencies measured were complete.

Figure 5: Output power and measurement configuration.



8.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
POWER METER +SENSOR	ANRITSU	ML2487A +MA2491A	2019/06/10	2020/06/09
Attenuator	MINI-CIRCUITS	BW-S10W2+	2019/10/04	2020/10/03

8.4 Measurement Data

Test Date : Apr.14 ,2020 Temperature : 22 °C Humidity : 51 %

Measurement Procedure:

9.1.2 PKPM1 Peak power meter method

Output Peak Power		dBm	mW
Bluetooth BLE	Channel Low:2402MHz	3.15	2.065
	Channel Mid:2440MHz	2.89	1.945
	Channel High:2480MHz	1.99	1.581

Note : The expanded uncertainty: 2dB.

9 100 kHz BANDWIDTH OF BAND EDGES MEASUREMENT

9.1 Standard Applicable

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set both RBW of spectrum analyzer to 100kHz and VBW to 1 MHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

9.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2020/01/15	2021/01/14
Attenuator	MINI-CIRCUITS	BW-S10W2+	2019/10/04	2020/10/03


9.4 Measurement Data

Test Date : Apr. 14, 2020 Temperature : 22 °C Humidity : 51 %


Mode: Bluetooth BLE

- a) Lower Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.
- b) Upper Band Edge : All emissions in this 100kHz bandwidth are attenuated more than 20dB from the carrier.

Note : The expanded uncertainty: 2dB.

Bluetooth BLE / Channel Low

Date: 14.APR.2020 16:10:06

Bluetooth BLE / Channel High

Date: 14.APR.2020 16:10:55

10 POWER DENSITY MEASUREMENT

10.1 Standard Applicable

According to 15.247(d), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

10.2 Measurement Procedure

Measurement Method: PKPSD

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 5 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set EUT to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set analyzer center frequency to DTS channel center frequency.
4. Set the span to 1.5 times the DTS bandwidth.
5. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
6. Set the VBW $\geq 3 \times \text{RBW}$.
7. Detector = peak.
8. Sweep time = auto couple.
9. Trace mode = max hold.
10. Allow trace to fully stabilize.
11. Use the peak marker function to determine the maximum amplitude level within the RBW.
12. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
13. Repeat above procedures until all measured frequencies were complete.

10.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2020/01/15	2021/01/14
Attenuator	MINI-CIRCUITS	BW-S10W2+	2019/10/04	2020/10/03


10.4 Measurement Data

Test Date : Apr.14, 2020 Temperature : 22 °C Humidity : 51 %


Mode: Bluetooth BLE

- a) Channel Low: Maximun PSD is -12.46 dBm
- b) Channel Mid: Maximun PSD is -12.69 dBm
- c) Channel High: Maximun PSD is -14.08 dBm


Note : The expanded uncertainty: 2dB.

Bluetooth BLE / Channel Low

Date: 14.APR.2020 16:30:35

Bluetooth BLE / Channel Mid

Date: 14.APR.2020 16:31:16

Bluetooth BLE / Channel High

Date: 14.APR.2020 16:31:38

11. OUT-OF-BAND CONDUCTED EMISSION MEASUREMENT

11.1 Standard Applicable

According to 15.247(c), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

11.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Use the following spectrum analyzer settings:
 Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
 RBW = 100 kHz
 VBW $\geq$ RBW
 Sweep = auto
 Detector function = peak
 Trace = max hold.
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. Plot the result on the screen of spectrum analyzer.
5. Repeat above procedures until all measured frequencies were complete.

11.3 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2020/01/15	2021/01/14
Attenuator	MINI-CIRCUITS	BW-S10W2+	2019/10/04	2020/10/03

11.4 Measurement Data


Test Date : Apr.14 , 2020 Temperature : 22 °C Humidity : 51 %

A. Bluetooth BLE


Mode: Channel Low, Mid, High

- (a) 30 MHz to 1 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.
- (b) 1 GHz to 26.5 GHz frequency band: All emissions are attenuated more than 20dB from the carrier.


Note : The expanded uncertainty: 2dB.

Bluetooth BLE
Channel Low


Date: 14.APR.2020 16:41:16




Date: 14.APR.2020 16:41:06

Bluetooth BLE
Channel Mid


Date: 14.APR.2020 16:40:21



Date: 14.APR.2020 16:40:09

Bluetooth BLE
Channel High

Date: 14.APR.2020 16:42:14



Date: 14.APR.2020 16:42:05

12. DUTY CYCLE

12.1 Standard Applicable

None. Referency only.

12.2 Measurement Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2020/01/15	2021/01/14
Attenuator	MINI-CIRCUITS	BW-S10W2+	2019/10/04	2020/10/03

12.3 Measurement Data

Test Date : Apr. 14, 2020 Temperature : 22 °C Humidity : 51 %

Duty Cycle Calculation


Mode	Period (ms)	Transmission duration (T) (ms)	Duty Cycle (%)	1/T (kHz)	VBW setting (kHz)
BLE	0.62	0.475	76.61	2.105	3

Note:


1. When the duty cycle is less than 98%, for the average measurement of the radiated emission test, the VBW setting is $>1/T$ where the T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Refer to the following page for data plots.

Bluetooth BLE



Date: 14.APR.2020 16:35:24



Date: 14.APR.2020 16:35:10