



MPE Report

Report No.: STS2601310H01

Issued for

Longse Technology Limited

No.18, Dongming 3rd, Huangpu District, Guangzhou,
Guangdong, China

Product Name: PoE NVR

Brand Name: N/A

Model Name: NP08E

Series Model(s): NP08C, NP08D, NP08F, NP08G, NP08K,
NP08L, NP08N, NP08P, LP8ME84D1,
LP8ME84B1, LP8ME88D1, LP8ME88B1,
LP8ME84D2, LP8MC84B2, LP8MC88D2,
LP8MC88B2

FCC ID: 2A3CE-NP08E

Test Standard: FCC 47CFR §2.1091

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the ShenZhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name: Longse Technology Limited
Address: No.18, Dongming 3rd, Huangpu District, Guangzhou, Guangdong, China
Manufacturer's Name: Longse Technology Limited
Address: No.18, Dongming 3rd, Huangpu District, Guangzhou, Guangdong, China

Product Description

Product Name: PoE NVR
Brand Name: N/A
Model Name: NP08E
Series Model(s): NP08C, NP08D, NP08F, NP08G, NP08K, NP08L, NP08N, NP08P, LP8ME84D1, LP8ME84B1, LP8ME88D1, LP8ME88B1, LP8ME84D2, LP8MC84B2, LP8MC88D2, LP8MC88B2
Test Standards: FCC 47CFR §2.1091
447498 D01 Interim General RF Exposure Guidance v06

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the ShenZhen STS Test Services Co., Ltd.

Date of Test

Date of receipt of test item: 23 Dec. 2025
Date (s) of performance of tests: 23 Dec. 2025 to 14 Jan. 2026
Date of Issue: 14 Jan. 2026
Test Result: **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	5
2. FCC 47CFR §2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 TEST RESULT	7

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	14 Jan. 2026	STS2601310H01	ALL	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	PoE NVR	
Brand Name	N/A	
Model Name	NP08E	
Series Model(s)	NP08C, NP08D, NP08F, NP08G, NP08K, NP08L, NP08N, NP08P, LP8ME84D1, LP8ME84B1, LP8ME88D1, LP8ME88B1, LP8ME84D2, LP8MC84B2, LP8MC88D2, LP8MC88B2	
Model Difference	All the model are the same circuit and RF module, except model names and appearance of the color, the test model is NP08E.	
Product Description	The EUT is a PoE NVR	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	GFSK
	Radio Technology:	BLE
	Bluetooth Configuration:	LE(Support 1M PHY, 2M PHY)
	Number Of Channel:	40
	Antenna Type:	Internal antenna
	Antenna Gain (dBi)	2.11
Power Rating	AC 100-240V, 50/60Hz	
Adapter	Model: SA0691-4801360D Input: 100-240V~, 50/60Hz, 1.5A Max Output: DC 48V, 1.36A, 65.28W	
Battery	N/A	
Hardware Version	N/A	
Software Version	N/A	

1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
3.0-30	1842/f	4.89/f	*(900/f ²)
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1.34-30	824/f	2.19/f	*(180f ²)
1500 – 100000	--	--	1.0

F= Frequency in MHz

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.



2.3 TEST RESULT

Tune up

Mode	Detector	Tune up Power
GFSK	Peak	2±1dBm

Protocol	Fre. (GHz)	Separati on distance (cm)	Max Tune up power (dBm)	ANT Gain (dBi)	Max EIRP (dBm)	Max EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/ cm ²)	Ratio	Result
GFSK	2.480	20	3	2.11	5.11	3.243	0.0006	1	0.0006	Pass

Note: 1. The Maximum power is less than the limit, complies with the exemption requirements.

2. ERP = EIRP - 2.15

※※※※※END OF THE REPORT※※※※※