

EUROFINS ELECTRICAL TESTING SERVICE (SHENZHEN) CO., LTD.

RADIO TEST - REPORT

FCC&ISED Compliance Test Report for

Product name: Scout Smart Camera

Model name: PLPC001, PLPCO001

FCC ID: 2A3DE-PLPC001

Test Report Number: EFGX25010255-IE-04-E14-A1

Content

1	General Information	3
1.1	Notes	3
1.2	Testing laboratory	4
1.3	Details of applicant	4
1.4	Details of manufacturer	4
1.5	Application details	5
1.6	Test item	5
1.7	Test standards	7
2	Technical test	8
2.1	Summary of test results	8
2.2	Test environment	8
2.3	Measurement uncertainty	8
2.4	Test mode	9
2.5	Test equipment utilized	10
2.6	Auxiliary equipment used during test	11
2.7	Test software information	11
2.8	Test setup	12
2.9	Test results	14
3	Technical Requirement	15
3.1	Transmitter radiated spurious emissionsr	15

1 General Information

1.1 Notes

The results of this test report relate exclusively to the item tested as specified in chapter "Description of test item" and are not transferable to any other test items.

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd. is not responsible for any generalisations and conclusions drawn from this report. Any modification of the test item can lead to invalidity of test results and this test report may therefore be not applicable to the modified test item.

The test report may only be reproduced or published in full. Reproducing or publishing extracts of the report requires the prior written approval of the Eurofins Electrical Testing Service (Shenzhen) Co., Ltd. This document is subject to the General Terms and Conditions and the Testing and Certification System of Eurofins Electrical Testing Service (Shenzhen) Co., Ltd., available on request or accessible at www.eurofins.com.

Operator:

2026-02-02

Bruce Zheng / Project Engineer



Date

Eurofins-Lab.

Name / Title

Signature

Technical responsibility for area of testing:

2026-02-02

Albert Xu / Lab Manager



Date

Eurofins-Lab.

Name / Title

Signature

1.2 Testing laboratory

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

Room 20 of 2/F., 1/F., Building 2, Spring Block & Room 102, Building 8, Autumn Block, Meishenghuigu Innovation Park, No.83, Dabao Road, Bao'an District, Shenzhen, Guangdong, China

Telephone : +86-755-82911867

Fax : +86-755-82910749

The Laboratory has passed the Accreditation by the American Association for Laboratory Accreditation (A2LA). The Accreditation number is 5376.01

The Laboratory has been listed by industry Canada to perform electromagnetic emission measurements, The CAB identifier is CN0088

1.3 Details of applicant

Name	:	Shenzhen Libro Technology Co., Ltd.
Address	:	Room 501, West Tower, Twin Towers, Galaxy World, No. 8 Yaxing Road, Nankeng Community, Bantian Street, Long-gang District, Shenzhen, China
Telephone	:	./.
Fax	:	./.

1.4 Details of manufacturer

Name	:	Shenzhen Libro Technology Co., Ltd.
Address	:	Room 501, West Tower, Twin Towers, Galaxy World, No. 8 Yaxing Road, Nankeng Community, Bantian Street, Long-gang District, Shenzhen, China
Telephone	:	./.
Fax	:	./.

1.5 Application details

Date of receipt of application	: 2025-12-03
Date of receipt of test item	: 2025-12-03
Date of test	: 2025-12-03 to 2026-01-30
Date of issue	: 2026-02-02

1.6 Test item

Product type	: Scout Smart Camera
Model name	: PLPC001, PLPCO001
Brand	: PETLIBRO
Sample ID	: 250115-11-0014
Serial number	: ./.
Ratings	: Input: DC 5.0V 2.0A
Test voltage	: 120V
Hardware Version	: V0.3
Software / Firmware Version	: V1.5.17
Additional information	: ./.

RadioTechnical data

Radio Tech.	: WLAN (IEEE 802.11 a,n) / UN-III-1, U-NII-3
Frequency Range	: 5 180 MHz ~ 5 240 MHz (U-NII-1 Band) 5 745 MHz ~ 5 825 MHz (U-NII-3 Band)
Modulation	: 802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna type	: FPC antenna
Channel Spacing	: 802.11a/n(HT20)/ac(VHT20): 20MHz 802.11n(HT40)/ac(VHT40): 40MHz
Antenna gain	: 2.07 dBi for 5.2G 1.07 dBi for 5.8G

This report is prepared for FCC class II permissive change.

This report is issued as a supplementary report to original report no. EFGX25010255-IE-04-E14(FCC ID: 2A3DE-PLPC001, Model: PLPC001, PLPCO001). The modification is only concerned with following item:

1. Add optional MCU(Same Manufacturer and serial model)

Original	Add
Manufacturer: Rockchip	Manufacturer: Rockchip
Model: RV1126	Model: RV1126BP
	

In this report, radiated emission tests (worst case) of Scout Smart Camera had been re-tested and only its data was recorded in the following sections.

The above sample(s) and sample information was/were submitted and identified on behalf of the applicant. Eurofins assures objectivity and impartiality of the test, and fulfills the obligation of confidentiality for applicant's commercial information and technical documents.

1.7 Test standards

Test Standards	
FCC Part 15 Subpart E	Subpart E—Unlicensed National Information Infrastructure Devices

Test Method

- 1: ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
- 2: ANSI C63.10-2020, American National Standard for Testing Unlicensed Wireless Devices.
- 3: KDB789033 D02 General UNII Test Procedures New Rules v02r01

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified were ascertained in the course of the tests performed.



2.2 Test environment

Ac line conducted

Environment Parameter	Temperature	Relative Humidity
101.2kPa	23.7 °C	61.3%

RF conducted

Environment Parameter	Temperature	Relative Humidity
101.2kPa	24.7 °C	43.1%

Radiated

Environment Parameter	Temperature	Relative Humidity
101.2kPa	24.3 °C	51.6%

2.3 Measurement uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty in conducted measurements	1.96dB
Uncertainty for Conducted RF test	RF Power Conducted: 1.16dB Frequency test involved: 1.05×10 ⁻⁷ or 1%
Uncertainty for Radiated Spurious Emission 25MHz-3000MHz	Horizontal: 4.46dB; Vertical: 4.54dB;
Uncertainty for Radiated Spurious Emission 3000MHz-18000MHz	Horizontal: 4.42dB; Vertical: 4.41dB;
Uncertainty for Radiated Spurious Emission 18000MHz-40000MHz	Horizontal: 4.63dB; Vertical: 4.62dB;

2.4 Test mode

Frequency band (MHz)		5150~5250	
802.11a / n HT20		802.11n HT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
36	5180	38	5190
40	5200	46	5230
44	5220	--	
48	5240	--	--

Frequency band (MHz)		5725~5850	
802.11a / n HT20		802.11n HT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
149	5745	151	5755
153	5765	159	5795
157	5785	--	
161	5805	--	--
165	5825	--	--

For U-NII-1 Bnad 802.11a/n(HT20 SISO), the lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 36 (5180MHz), 40 (5200MHz) and 48 (5240MHz).

For U-NII-1 Bnad 802.11n(HT40 SISO), the lowest, highest channel numbers of the EUT used and tested in this report are separately 38 (5190MHz) , 46 (5230MHz).

For U-NII-3 Bnad 802.11a/n(HT20 SISO), the lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 149 (5745MHz), 157 (5785MHz) and 165 (5825MHz).

For U-NII-3 Bnad 802.11n(HT40 SISO), the lowest, highest channel numbers of the EUT used and tested in this report are separately 151 (5755MHz) , 159 (5795MHz).

The EUT was set at continuously transmitting mode during the test.

2.5 Test equipment utilized

EQUIPMENT ID	EQUIPMENT NAME	MODEL NO.	CAL. DUE DATE
23-2-13-05	EMI Test Receiver	ESR3	2026-03-25
23-2-13-06	LISN	NNLK 8127 RC	2026-03-25
23-2-10-16	Attenuator	VTSD 9561-F	2026-03-25
23-2-10-63	Temperature & Humidity Meter	COS-03	2026-03-25
23-2-10-65	Barometer	Baro	2026-03-25
23-2-13-12	Signal Analyzer	N9010B-544	2026-03-25
23-2-13-13	BT/WLAN Tester	CMW270	2026-03-25
23-2-13-14	Signal Generator	N5183B-520	2026-03-25
23-2-13-15	Vector Signal Generator	N5182B-506	2026-03-25
23-2-10-43	Switch and Control Unit	ERIT-E-JS0806-2	2026-03-25
23-2-10-44	DC power supply	E3642A	2026-03-25
23-2-10-45	Temperature test chamber	SG-80-CC-2	2026-03-25
23-2-10-50	Temperature & Humidity Meter	COS-03	2026-03-25
23-2-10-66	Barometer	Baro	2026-03-25
23-2-13-01	EMI Test Receiver	ESR7	2026-03-25
23-2-13-02	Signal Analyzer	N9020B-544	2026-03-25
23-2-12-01	Active Loop Antenna	FMZB 1519B	2026-05-29
23-2-12-02	TRILOG Broadband Antenna	VULB9168	2026-05-29
23-2-12-03	Horn Antenna	3117	2026-05-29
23-2-12-04	Horn Antenna	BBHA 9170	2026-05-29
23-2-10-01	Preamplifier	BBV9745	2026-03-25
23-2-10-02	Preamplifier	TAP01018048	2026-03-25
23-2-10-03	Preamplifier	TAP18040048	2026-03-25
23-2-10-62	Temperature & Humidity Meter	COS-03	2026-03-25
23-2-10-64	Barometer	Baro	2026-03-25
23-2-10-14	Switch and Control Unit	ERIT-E-JS0806-SF1	N/A
23-2-13-03	EMI Test Receiver	ESR7	2026-03-25
23-2-13-04	Signal Analyzer	N9020B-526	2026-03-25
23-2-12-06	Active Loop Antenna	FMZB 1519B	2026-03-25
23-2-10-46	Preamplifier	BBV9745	2026-03-25
23-2-10-47	Preamplifier	TAP01018048	2026-03-25
23-2-10-61	Temperature & Humidity Meter	COS-03	2026-03-25
23-2-10-52	Barometer	Baro	2026-03-25
23-2-10-15	Switch and Control Unit	ERIT-E-JS0806-SF1	N/A

2.6 Auxiliary equipment used during test


DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
Laptop	LENOVO	TP00096A	PF-1QH0LV

2.7 Test software information


Test Software&Version	SSCOM	
Mode	Power setting	Rate
802.11a	DEF	6Mbit
802.11n HT20	DEF	MCS0
802.11n HT40	DEF	MCS0

2.8 Test setup


Ac line conducted




RF Conducted tests




Radiated tests below 30MHz



Radiated tests below 1GHz



Radiated tests above 1GHz



2.9 Test results

☒ 1st test

☐ test after modification

☐ production test

Technical Requirements					
FCC Part 15 Subpart E/ IC RSS-247/ RSS-Gen					
Test Condition			Test Result	Verdict	Test Site
§15.207	RSS-GEN 8.8	Conducted emission AC power port	Appendix I	Pass	Site 1
§15.407(a)(1) §15.407(a)(3)	RSS-247 Issue 2 6.2.1.1 RSS-247 Issue 2 6.2.4.1	Maximum Conducted Output Power	Appendix B	Pass	Site 1
§15.407(a)(1) §15.407(a)(3)	RSS-247 Issue 2 6.2.1.1 RSS-247 Issue 2 6.2.4.1	Power spectral density	Appendix C	Pass	Site 1
§15.407(e)	RSS-247 Issue 2 6.2.4.1	6 dB bandwidth	Appendix A3	Pass	Site 1
§15.407(a)	--	26 dB Bandwidth	Appendix A1	N/A	--
--	RSS-GEN 6.7	99% Occupied Bandwidth	Appendix A2	Pass	Site 1
§15.205(a) §15.209(a) §15.407(b)(1) §15.407(b)(4)	RSS-Gen Issue 5 8.9 RSS-Gen Issue 5 8.10 RSS-247 Issue 2 6.2.1.2 RSS-247 Issue 2 6.2.4.2	Unwant Emissions	Appendix E Appendix F Appendix G	Pass	Site 1
--	--	Duty cycle	Appendix D	Pass	Site 1
§15.407(g)	GSS-GEN 6.11	Frequency Stability	Appendix H	Pass	Site 1
§15.203	RSS-GEN 6.8	Antenna requirement	See note 1	Pass	--

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses FPC antenna. According to §15.203/ RSS-GEN 6.8, it is considered sufficiently to comply with the provisions of this section.

3 Technical Requirement

3.1 Transmitter radiated spurious emissions

Test Method:

The test method was referred to the subclause G of KDB 789033 D02 General UNII Test Procedures New Rules v02r01 and ANSI C63.10-2020.

Test Procedures for emission below 30 MHz

The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.

1. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
2. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
3. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

Test Procedures for emission from above 30 MHz

The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meter above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.

1. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
2. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note

All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

- II.G.4. Unwanted emissions measurements below 1 GHz.

Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

- II.G.5. Unwanted maximum emissions measurements above 1GHz.

Peak emission levels are measured by setting the analyzer as follows: Set to RBW = 1 MHz, VBW ≥ 3 MHz, Detector = Peak, Sweep time = auto, Trace mode= Max hold.

- II.G.6. Average unwanted emissions measurements above 1 GHz.

Set to RBW = 1 MHz, VBW ≥ 3 MHz, Detector = power averaging (rms), Averaging type = power averaging (rms), Sweep time = auto, Perform a trace average of at least 100 traces. If the transmission is continuous, If the transmission is not continuous, the number of traces shall be increased by a factor of 1/x, where x is the duty cycle. For example, with 50 % duty cycle, at least 200 traces shall be averaged.

If tests are performed with the EUT transmitting at a duty cycle less than 98 %, a correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle. The correction factor is computed as follows:

- If power averaging (rms) mode was used in II.G.6.c)(iv), the correction factor is $10 \log (1 / x)$, where x is the duty cycle. For example, if the transmit duty cycle was 50 %, then 3 dB must be added to the measured emission levels.

Limit:

FCC § 15.407(b)

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of - 27 dB m/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dB m/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dB m/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dB m/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dB m/MHz at the band edge.

RSS-247 Issue 2

6.2.1.2 Frequency band 5 150-5 250 MHz

For transmitters with operating frequencies in the band 5 150-5 250 MHz, all emissions outside the band 5 150-5 350 MHz shall not exceed -27 dB m/MHz e.i.r.p. Any unwanted emissions that fall into the band 5 250-5 350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5 % of the occupied bandwidth (i.e. 99% bandwidth), above 5 250 MHz. The 26 dB bandwidth may fall into the 5 250-5 350 MHz band; however, if the occupied bandwidth also falls within the 5 250- 5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5 250-5 350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5 250-5 350 MHz band.

6.2.4.2 Frequency band 5 725-5 850 MHz

Devices operating in the band 5 725-5 850 MHz with antenna gain greater than 10 dB i can have unwanted emissions that comply with either the limits in this section or in section 5.5 until six (6) months after the publication date of this standard for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2018.

Devices operating in the band 5 725-5 850 MHz with antenna gain of 10 dB i or less can have unwanted emissions that comply with either the limits in this section or in section 5.5 until April 1, 2018 for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2020.

Devices operating in the band 5 725-5 850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:

- a) 27 dB m/MHz at frequencies from the band edges decreasing linearly to 15.6 dB m/MHz at 5 MHz above or below the band edges;
- b) 15.6 dB m/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dB m/MHz at 25 MHz above or below the band edges;
- c) 10 dB m/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dB m/MHz at 75 MHz above or below the band edges; and
- d) -27 dB m/MHz at frequencies more than 75 MHz above or below the band edges.

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)):

Frequency Range	Field Strength Limit	Field Strength Limit
(MHz)	(uV/m) at 3 m	(dBuV/m) at 3 m
0.009-0.490	2400/F(kHz) @ 300 m	-
0.490-1.705	24000/F(kHz) @ 30 m	-
1.705 - 30	30 @ 30m	-
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54


FCC §15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	


13.36-13.41			
-------------	--	--	--

RSS-GEN 8.10


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	1660 - 1710	9.0 - 9.2
0.495 - 0.505	16.69475 - 16.69525	1718.8 - 1722.2	9.3 - 9.5
2.1735 - 2.1905	25.5 - 25.67	2200 - 2300	10.6 - 12.7
3.020 - 3.026	37.5 - 38.25	2310 - 2390	13.25 - 13.4
4.125 - 4.128	73 - 74.6	2483.5 - 2500	14.47 - 14.5
4.17725 - 4.17775	74.8 - 75.2	2655 - 2900	15.35 - 16.2
4.20725 - 4.20775	108 - 138	3260 - 3267	17.7 - 21.4
5.677 - 5.683	149.9 - 150.05	3332 - 3339	22.01 - 23.12
6.215 - 6.218	156.52475 - 156.52525	3345.8 - 3358	23.6 - 24.0
6.26775 - 6.26825	156.7 - 156.9	3500 - 4400	31.2 - 31.8
6.31175 - 6.31225	162.0125 - 167.17	4500 - 5150	36.43 - 36.5
8.291 - 8.294	167.72 - 173.2	5350 - 5460	Above 38.6
8.362 - 8.366	240 - 285	7250 - 7750	
8.37625 - 8.38675	322 - 335.4	8025 - 8500	
8.41425 - 8.41475	399.9 - 410		
12.29 - 12.293	608 - 614		
12.51975 - 12.52025	960 - 1427		
12.57675 - 12.57725	1435 - 1626.5		
13.36 - 13.41	1645.5 - 1646.5		



QP Final Data List									
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	135.0025	-16.78	17.39	43.50	26.11	100	225	Vertical	PASS
2	198.6588	-19.05	19.07	43.50	24.43	100	194	Vertical	PASS
3	296.9925	-15.93	28.78	46.00	17.22	100	184	Vertical	PASS
4	450.0100	-11.85	28.92	46.00	17.08	100	6	Vertical	PASS
5	540.0988	-10.39	34.09	46.00	11.91	100	177	Vertical	PASS
6	999.0300	-1.21	35.30	54.00	18.70	100	290	Vertical	PASS




QP Final Data List									
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	205.4488	-19.01	15.65	43.50	27.85	100	247	Horizontal	PASS
2	296.9925	-15.93	28.22	46.00	17.78	100	137	Horizontal	PASS
3	450.0100	-11.85	30.21	46.00	15.79	100	204	Horizontal	PASS
4	540.0988	-10.39	31.89	46.00	14.11	200	257	Horizontal	PASS
5	648.0112	-7.66	30.79	46.00	15.21	100	266	Horizontal	PASS
6	999.0300	-1.21	37.86	54.00	16.14	100	280	Horizontal	PASS




Suspected Data List


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1853.80	37.04	1.26	68.23	31.19	150	200	Horizontal	PASS
2	3322.60	41.71	6.90	68.23	26.52	150	170	Horizontal	PASS
3	7238.38	42.91	-9.41	68.23	25.32	150	140	Horizontal	PASS
4	9311.16	44.46	-5.54	74.00	29.54	150	300	Horizontal	PASS
5	10356.7	46.30	-3.94	68.23	21.93	150	110	Horizontal	PASS
6	12478.8	47.11	-1.17	74.00	26.89	150	310	Horizontal	PASS




Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1597.00	35.91	0.33	74.00	38.09	150	170	Vertical	PASS
2	2041.00	37.76	1.93	68.23	30.47	150	290	Vertical	PASS
3	3013.60	40.92	6.04	68.23	27.31	150	100	Vertical	PASS
4	7945.37	43.21	-8.08	68.23	25.02	150	250	Vertical	PASS
5	10360.3	50.76	-3.94	68.23	17.47	150	170	Vertical	PASS
6	11625.5	46.20	-1.93	74.00	27.80	150	130	Vertical	PASS



Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1642.00	36.90	0.31	68.23	31.33	150	240	Horizontal	PASS
2	2278.00	39.07	2.59	74.00	34.93	150	150	Horizontal	PASS
3	3241.60	41.50	6.66	68.23	26.73	150	60	Horizontal	PASS
4	7778.84	42.88	-7.73	68.23	25.35	150	10	Horizontal	PASS
5	9574.68	45.16	-4.28	68.23	23.07	150	60	Horizontal	PASS
6	10397.5	46.86	-3.90	68.23	21.37	150	340	Horizontal	PASS




Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1835.20	37.34	1.28	68.23	30.89	150	180	Vertical	PASS
2	2467.00	39.37	3.68	68.23	28.86	150	320	Vertical	PASS
3	3362.80	41.63	6.78	68.23	26.60	150	40	Vertical	PASS
4	7346.35	42.96	-9.23	74.00	31.04	150	320	Vertical	PASS
5	10403.0	49.48	-3.87	68.23	18.75	150	340	Vertical	PASS
6	13373.7	47.03	0.65	74.00	26.97	150	230	Vertical	PASS




Suspected Data List


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1988.80	36.86	1.84	68.23	31.37	150	10	Horizontal	PASS
2	2516.20	38.75	3.74	68.23	29.48	150	60	Horizontal	PASS
3	3502.00	42.05	6.99	68.23	26.18	150	120	Horizontal	PASS
4	6841.27	42.02	-10.12	68.23	26.21	150	330	Horizontal	PASS
5	10481.7	46.73	-3.73	68.23	21.50	150	310	Horizontal	PASS
6	12558.1	46.98	-1.29	74.00	27.02	150	90	Horizontal	PASS



Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2117.20	37.97	2.16	68.23	30.26	150	50	Vertical	PASS
2	2892.40	39.85	5.13	74.00	34.15	150	100	Vertical	PASS
3	3629.80	42.18	7.75	74.00	31.82	150	290	Vertical	PASS
4	9575.90	45.63	-4.27	68.23	22.60	150	280	Vertical	PASS
5	10479.9	52.37	-3.72	68.23	15.86	150	30	Vertical	PASS
6	11463.8	46.55	-2.31	74.00	27.45	150	90	Vertical	PASS




Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1829.60	37.93	1.21	68.23	30.30	150	240	Horizontal	PASS
2	3054.28	41.37	6.19	68.23	26.86	150	110	Horizontal	PASS
3	4251.76	43.20	10.40	74.00	30.80	150	230	Horizontal	PASS
4	8639.46	44.44	-6.61	68.23	23.79	150	290	Horizontal	PASS
5	10476.4	45.68	-3.70	68.23	22.55	150	170	Horizontal	PASS
6	13298.3	46.84	0.54	74.00	27.16	150	130	Horizontal	PASS




Suspected Data List


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1745.28	37.72	0.78	68.23	30.51	150	290	Vertical	PASS
2	2570.12	38.67	3.88	68.23	29.56	150	230	Vertical	PASS
3	3745.16	42.90	8.65	74.00	31.10	150	320	Vertical	PASS
4	10102.6	45.16	-4.42	68.23	23.07	150	270	Vertical	PASS
5	12190.5	47.48	-1.31	74.00	26.52	150	240	Vertical	PASS
6	14158.1	48.91	1.47	68.23	19.32	150	350	Vertical	PASS




Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2078.48	38.33	2.01	68.23	29.90	150	130	Horizontal	PASS
2	2909.44	40.54	5.68	68.23	27.69	150	150	Horizontal	PASS
3	4056.60	42.90	9.53	74.00	31.10	150	310	Horizontal	PASS
4	9424.86	44.36	-5.13	74.00	29.64	150	190	Horizontal	PASS
5	11085.4	45.93	-2.72	74.00	28.07	150	120	Horizontal	PASS
6	13847.5	48.68	1.42	68.23	19.55	150	220	Horizontal	PASS




Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1988.04	37.51	1.84	68.23	30.72	150	130	Vertical	PASS
2	2619.76	39.81	4.30	68.23	28.42	150	60	Vertical	PASS
3	4189.20	43.13	10.20	74.00	30.87	150	110	Vertical	PASS
4	9828.78	45.21	-3.99	68.23	23.02	150	30	Vertical	PASS
5	11569.4	48.00	-1.91	74.00	26.00	150	250	Vertical	PASS
6	14042.9	49.29	2.05	68.23	18.94	150	50	Vertical	PASS



Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2265.48	37.79	2.78	74.00	36.21	150	300	Horizontal	PASS
2	3083.52	41.08	6.21	68.23	27.15	150	80	Horizontal	PASS
3	4312.28	43.72	10.24	74.00	30.28	150	310	Horizontal	PASS
4	9826.74	45.19	-4.00	68.23	23.04	150	160	Horizontal	PASS
5	11518.9	46.06	-2.27	74.00	27.94	150	300	Horizontal	PASS
6	13861.8	49.36	1.35	68.23	18.87	150	260	Horizontal	PASS




Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1842.52	37.04	1.32	68.23	31.19	150	190	Vertical	PASS
2	2846.20	40.11	5.30	74.00	33.89	150	180	Vertical	PASS
3	3741.76	42.52	8.65	74.00	31.48	150	20	Vertical	PASS
4	9558.99	45.16	-4.91	68.23	23.07	150	100	Vertical	PASS
5	11651.0	47.04	-2.12	74.00	26.96	150	330	Vertical	PASS
6	15320.4	48.99	2.93	68.23	19.24	150	310	Vertical	PASS




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2040.40	37.67	1.94	68.23	30.56	150	60	Horizontal	PASS
2	2684.80	39.95	4.64	68.23	28.28	150	220	Horizontal	PASS
3	3632.80	41.87	7.84	74.00	32.13	150	350	Horizontal	PASS
4	7734.31	43.27	-8.65	74.00	30.73	150	0	Horizontal	PASS
5	10421.3	46.65	-3.60	68.23	21.58	150	110	Horizontal	PASS
6	13623.8	47.61	0.65	68.23	20.62	150	140	Horizontal	PASS




Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2099.80	37.29	2.23	68.23	30.94	150	330	Vertical	PASS
2	2791.60	40.94	5.11	74.00	33.06	150	270	Vertical	PASS
3	3755.80	42.41	8.41	74.00	31.59	150	60	Vertical	PASS
4	8443.13	44.01	-7.06	74.00	29.99	150	150	Vertical	PASS
5	10375.0	47.60	-3.79	68.23	20.63	150	30	Vertical	PASS
6	11449.2	46.29	-2.30	74.00	27.71	150	340	Vertical	PASS




Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2137.60	37.72	2.14	68.23	30.51	150	230	Horizontal	PASS
2	2605.60	40.12	4.07	68.23	28.11	150	240	Horizontal	PASS
3	3695.20	42.59	8.19	74.00	31.41	150	30	Horizontal	PASS
4	7856.92	44.01	-8.51	68.23	24.22	150	130	Horizontal	PASS
5	10273.1	45.46	-3.59	68.23	22.77	150	250	Horizontal	PASS
6	14049.0	49.38	1.84	68.23	18.85	150	70	Horizontal	PASS




Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2199.40	38.35	2.40	68.23	29.88	150	250	Vertical	PASS
2	2707.00	40.30	4.53	74.00	33.70	150	50	Vertical	PASS
3	3219.40	42.17	6.42	68.23	26.06	150	150	Vertical	PASS
4	7781.89	43.42	-7.78	68.23	24.81	150	270	Vertical	PASS
5	10465.2	48.19	-3.75	68.23	20.04	150	270	Vertical	PASS
6	13132.8	46.61	-0.14	68.23	21.62	150	70	Vertical	PASS




Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2152.60	37.18	2.41	68.23	31.05	150	280	Horizontal	PASS
2	2698.64	39.99	4.29	74.00	34.01	150	30	Horizontal	PASS
3	3839.68	42.14	9.17	74.00	31.86	150	30	Horizontal	PASS
4	9000.54	44.74	-6.11	74.00	29.26	150	180	Horizontal	PASS
5	11149.6	45.79	-2.75	74.00	28.21	150	120	Horizontal	PASS
6	14038.8	48.84	2.10	68.23	19.39	150	80	Horizontal	PASS



Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2113.84	37.74	2.13	68.23	30.49	150	240	Vertical	PASS
2	3023.68	40.59	6.06	68.23	27.64	150	60	Vertical	PASS
3	3807.72	43.03	8.89	74.00	30.97	150	100	Vertical	PASS
4	9223.92	44.68	-4.63	68.23	23.55	150	310	Vertical	PASS
5	11805.0	46.52	-1.98	74.00	27.48	150	330	Vertical	PASS
6	13810.3	48.15	1.19	68.23	20.08	150	260	Vertical	PASS



Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2240.32	39.09	2.75	74.00	34.91	150	100	Horizontal	PASS
2	2791.80	40.61	5.12	74.00	33.39	150	260	Horizontal	PASS
3	3603.04	41.83	7.76	74.00	32.17	150	140	Horizontal	PASS
4	9519.72	45.81	-4.53	68.23	22.42	150	270	Horizontal	PASS
5	12212.5	46.07	-1.18	74.00	27.93	150	80	Horizontal	PASS
6	14558.0	48.91	2.64	68.23	19.32	150	110	Horizontal	PASS



Suspected Data List									
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	2402.16	39.30	3.21	68.23	28.93	150	150	Vertical	PASS
2	3332.40	41.68	6.68	74.00	32.32	150	30	Vertical	PASS
3	4365.32	44.11	10.59	74.00	29.89	150	360	Vertical	PASS
4	9502.89	46.53	-4.49	68.23	21.70	150	320	Vertical	PASS
5	11583.1	46.55	-1.92	74.00	27.45	150	140	Vertical	PASS
6	13356.4	47.14	0.64	74.00	26.86	150	160	Vertical	PASS

--End of report--