



RF Exposure Requirements

1 General Information

Client Information

Applicant : Guangdong Chiyang Scent Technology Co.,Ltd.
Address of applicant : 1-9F, Unit A, and 5-9F, Unit B, Building 10,CIMC Center, No.3
Chanxing Road, Xianchong Village, Chencun Town, Shunde
District, Foshan City, Guangdong Province, China, 528313
Manufacturer..... : The same as above
Address of manufacturer..... : The same as above

General Description of E.U.T

FCC ID..... : 2A3DS-AT302
Product Name : Aroma Diffuser
Model No. : A-T302
Model Description : ---
Rated Voltage..... : DC 5V, 2A
Battery Capacity : ---
Power Adapter : GLH50D2000HW
Input: 100-240V~, 50/60Hz, 0.4A; Output: DC 5.0V, 2.0A, 10.0W

Technical Characteristics of EUT

Bluetooth Version..... : Bluetooth LE
Frequency Range : 2402-2480MHz
RF Output Power : 7.153dBm (Conducted)
Modulation : GFSK
Data Rate : 1Mbps
Quantity of Channels : 40
Channel Separation..... : 2MHz
Type of Antenna : PCB Antenna
Antenna Gain : 0dBi



2 Applicable Standard

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

3 Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm), R=20cm.

4 MPE Calculation Result

Frequency (MHz)	Antenna Gain (dBi)	Numeric gain	Conducted Power (dBm)	Maximum Tune-up output power		PD (mW/cm ²)	Limit (mW/cm ²)
				(dBm)	(mW)		
2402-2480	0	1.00	7.153	8.00	6.31	0.00126	1.0

Result: Pass

=====End of Report=====