



RF Exposure Evaluation

FCC ID: 2A3EJ-DCWA01B

1. Client Information

Applicant	:	Deeper Network Inc.
Address	:	5200 Great America pkwy, Santa Clara CA USA 95054
Manufacturer	:	Deeper Network Inc.
Address	:	5200 Great America pkwy, Santa Clara CA USA 95054

2. General Description of EUT

EUT Name	:	Deeper Connect Wi-Fi Adapter	
Model(s) No.	:	DCWA01B	
Model Difference	:	----	
Product Description	:	Operation Frequency:	2.4GWiFi: 2412MHz~2462MHz U-NII-1: 5180MHz~5240MHz U-NII-3: 5745MHz~5825MHz
	:	Antenna Gain:	4.47dBi Dipole Antenna for 2.4G WIFI 1.28dBi Dipole Antenna for U-NII-1 4.44dBi Dipole Antenna for U-NII-3
Power Rating	:	USB Input: DC 5V/1A	
Software Version	:	----	
Hardware Version	:	v1.0	

Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] \cdot [\sqrt{f_{\text{GHz}}]} \leq 3.0 \text{ for 1-g SAR}$$

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] \cdot [\sqrt{f_{\text{GHz}}]} \leq 7.5.0 \text{ for 10-g SAR}$$

2. Summary simultaneous transmission for SAR Exclusion

The SAR exemption limits outlined in clause 4.3.2(b) of KDB 447498 have been derived based on an approximate SAR value of 0.4 W/kg using half-wave dipole antennas Footnote 1. As such, when simultaneous transmitter SAR evaluations include transmitters that have been exempt from routine SAR evaluation, the SAR must be estimating based on the ratio between the maximum tune-up tolerance limit of the transmitter that has been exempt and the exemption limit at the specific distance and frequency for that transmitter. This ratio must be multiplied by 0.4 W/kg(2.0 W/kg for controlled use and 1.0 W/kg for limb worn devices) in order to calculate the estimated SAR level.

The estimate SAR value is calculated based the following equation:

(maximum power level including tune-up tolerance for transmitter A / maximum power level of exemption at the same frequency and distance) * 0.4W/kg

1)
$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{GHz}}/x}]}{0.4 \text{ W/kg}}$$
 W/kg, for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

2) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distance is > 50 mm.³⁷

The $[\Sigma \text{ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg}] + [\Sigma \text{ of MPE ratios}] \leq 1.0$.

The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all ≤ 0.04 , and the $[\Sigma \text{ of MPE ratios}] \leq 1.0$.



3. Calculation:

Test separation: 5mm								
Worst MPE Result								
Test Mode	Antenna	Frequency (MHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.4G b	Ant1	2412	7.14	7±1	8	6.31	1.960	3.0
2.4G g	Ant1	2437	5.14	5±1	6	3.981	1.243	3.0
2.4G n20	Ant1	2462	5.04	5±1	6	3.981	1.249	3.0
2.4G n40	Ant1	2422	3.48	3±1	4	2.512	0.782	3.0
5G a	Ant1	5180	7.70	7±1	8	6.31	2.872	3.0
5G n20	Ant1	5180	7.76	7±1	8	6.31	2.872	3.0
5G n40	Ant1	5230	7.59	7±1	8	6.31	2.886	3.0
5G ac20	Ant1	5200	7.57	7±1	8	6.31	2.878	3.0
5G ac40	Ant1	5230	7.59	7±1	8	6.31	2.886	3.0
5G ac80	Ant1	5210	7.66	7±1	8	6.31	2.881	3.0

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF THE REPORT-----

