

TEST REPORT

Product Name : True Wireless earbuds
Brand Mark : KONNEK STEIN, dyplay
Model No. : ePRO-AE05
ePRO-AE05-BK-KS-US、
ePRO-AE05-WH-KS-US、
ePRO-AE05-TL-KS-US、
Extension model : ePRO-AE05-PK-KS-US, YT1104、
YT1104A、YT1104B、YT1104C、YT1104D、
YT1104E、YT1104F、YT1104G、YT1104H
YT1104I、YT1104J
FCC ID : 2A3HS-EARBUDS
Report Number : BLA-EMC-202110-A4303
Date of Sample Receipt : 2021/10/21
Date of Test : 2021/11/2 to 2021/11/2
Date of Issue : 2021/11/2
Test Standard : 47 CFR Part 1.1307, Part 2.1093, KDB
447498
Test Result : Pass

Prepared for:

Shenzhen yutian digital Co., Ltd.

2208-A13, Block A, union square, 5022 Binhe Avenue, Fushan Community,

Fukuda Street, Futian District, Shenzhen

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

**Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China**

TEL: +86-755-23059481



Compiled by: *Jozu*
Approved by: *Blue Zheng*

Review by: *Sueels*
Date: 2021/11/2



BlueAsia

REPORT REVISE RECORD

Version No.	Date	Description
00	2021/11/2	Original
01	2021/11/10	Model no. from YT1104 to ePRO-AE05

TABLE OF CONTENTS

1	TEST SUMMARY.....	5
2	GENERAL INFORMATION.....	6
3	GENERAL DESCRIPTION OF E.U.T.....	6
4	LABORATORY LOCATION.....	6
5	RF EXPOSURE COMPLIANCE REQUIREMENT.....	7
5.1	STANDARD REQUIREMENT.....	7
5.2	LIMITS.....	7
5.3	EUT RF EXPOSURE.....	7

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	pass

2 GENERAL INFORMATION

Applicant	Shenzhen yutian digital Co., Ltd.
Address	2208 - A13, Block A, union square, 5022 Binhe Avenue, Fushan Community, Fukuda Street, Futian District, Shenzhen
Manufacturer	Shenzhen yutian digital Co., Ltd.
Address	2208 - A13, Block A, union square, 5022 Binhe Avenue, Fushan Community, Fukuda Street, Futian District, Shenzhen
Factory	Shenzhen yutian digital Co., Ltd.
Address	2208 - A13, Block A, union square, 5022 Binhe Avenue, Fushan Community, Fukuda Street, Futian District, Shenzhen
Product Name	True Wireless earbuds
Test Model No.	ePRO-AE05

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	Charging box main board: V1.0 Left earphone motherboard: V1.0 Right earphone motherboard: V1.0
Software Version	N/A
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, p/4DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Chip Antenna
Antenna Gain:	1.8dBi(Provided by applicant)

4 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 STANDARD REQUIREMENT

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.3 EUT RF Exposure

Operational Mode: EDR (8-DPSK worst case)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
2402 MHz	3.489	±1	4.489	2.81	0.87	3.0
2441 MHz	3.061	±1	4.061	2.55	0.80	
2480 MHz	1.408	±1	2.408	1.74	0.55	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.