


Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2422Mhz
Remark:	\	Test_Date	2026/6/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18594.3438	-26.69	63.99	37.30	74.00	36.70	PASS	Vertical	PK
2	19589.5636	-25.59	60.93	35.34	74.00	38.66	PASS	Vertical	PK
3	20858.1543	-25.75	61.37	35.62	74.00	38.38	PASS	Vertical	PK
4	22365.0946	-25.15	59.90	34.75	74.00	39.25	PASS	Vertical	PK
5	23939.6976	-22.05	57.74	35.69	74.00	38.31	PASS	Vertical	PK
6	25651.6661	-20.74	57.33	36.59	74.00	37.41	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2437Mhz
Remark:	\	Test_Date	2026/6/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1132.5422	11.42	36.77	48.19	74.00	25.81	PASS	Horizontal	PK
2	1618.7079	13.71	35.31	49.02	74.00	24.98	PASS	Horizontal	PK
3	2169.678	15.45	35.45	50.90	74.00	23.10	PASS	Horizontal	PK
4	2981.8655	17.88	35.39	53.27	74.00	20.73	PASS	Horizontal	PK
5	13669.7113	7.37	51.24	58.61	74.00	15.39	PASS	Horizontal	PK
6	16289.886	10.86	49.04	59.90	74.00	14.10	PASS	Horizontal	PK
7	13715.7144	7.23	39.46	46.69	54.00	7.31	PASS	Horizontal	AV
8	16341.8895	11.48	36.76	48.24	54.00	5.76	PASS	Horizontal	AV

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2437Mhz
Remark:	\	Test_Date	2026/6/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1470.9647	13.06	35.79	48.85	74.00	25.15	PASS	Vertical	PK
2	2182.4788	15.37	35.62	50.99	74.00	23.01	PASS	Vertical	PK
3	2961.4641	17.78	35.64	53.42	74.00	20.58	PASS	Vertical	PK
4	7988.3326	-1.37	54.29	52.92	74.00	21.08	PASS	Vertical	PK
5	13675.7117	7.35	50.00	57.35	74.00	16.65	PASS	Vertical	PK
6	16276.8851	10.72	49.88	60.60	74.00	13.40	PASS	Vertical	PK
7	13676.7118	7.35	40.41	47.76	54.00	6.24	PASS	Vertical	AV
8	16335.8891	11.41	36.71	48.12	54.00	5.88	PASS	Vertical	AV

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2437Mhz
Remark:	\	Test_Date	2026/6/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18506.6203	-26.69	62.52	35.83	74.00	38.17	PASS	Horizontal	PK
2	19676.9471	-25.45	61.65	36.20	74.00	37.80	PASS	Horizontal	PK
3	21839.7736	-25.58	61.21	35.63	74.00	38.37	PASS	Horizontal	PK
4	23390.2356	-23.59	59.18	35.59	74.00	38.41	PASS	Horizontal	PK
5	24654.4062	-21.89	57.00	35.11	74.00	38.89	PASS	Horizontal	PK
6	26474.499	-21.15	57.98	36.83	74.00	37.17	PASS	Horizontal	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2437Mhz
Remark:	\	Test_Date	2026/6/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18692.2677	-26.51	63.14	36.63	74.00	37.37	PASS	Vertical	PK
2	19525.981	-25.60	60.93	35.33	74.00	38.67	PASS	Vertical	PK
3	20834.6934	-25.71	61.30	35.59	74.00	38.41	PASS	Vertical	PK
4	22085.9434	-25.64	60.07	34.43	74.00	39.57	PASS	Vertical	PK
5	23782.9513	-22.40	58.96	36.56	74.00	37.44	PASS	Vertical	PK
6	25701.9881	-20.77	57.26	36.49	74.00	37.51	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2452Mhz
Remark:	\	Test_Date	2026/6/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBuV]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Result	Polarity	Remark
1	1270.018	11.91	36.44	48.35	74.00	25.65	PASS	Horizontal	PK
2	1851.6568	14.46	35.90	50.36	74.00	23.64	PASS	Horizontal	PK
3	2970.1313	17.94	34.64	52.58	74.00	21.42	PASS	Horizontal	PK
4	9656.4438	1.21	50.33	51.54	74.00	22.46	PASS	Horizontal	PK
5	13690.7127	7.29	50.66	57.95	74.00	16.05	PASS	Horizontal	PK
6	16334.889	11.40	49.40	60.80	74.00	13.20	PASS	Horizontal	PK
7	13760.7174	7.29	39.61	46.90	54.00	7.10	PASS	Horizontal	AV
8	16422.8949	10.43	38.00	48.43	54.00	5.57	PASS	Horizontal	AV

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2452Mhz
Remark:	\	Test_Date	2026/6/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1397.8932	12.78	36.47	49.25	74.00	24.75	PASS	Vertical	PK
2	1861.9241	14.50	35.41	49.91	74.00	24.09	PASS	Vertical	PK
3	2976.9318	17.89	35.56	53.45	74.00	20.55	PASS	Vertical	PK
4	7964.331	-1.39	54.34	52.95	74.00	21.05	PASS	Vertical	PK
5	13672.7115	7.36	49.98	57.34	74.00	16.66	PASS	Vertical	PK
6	16318.8879	11.20	49.53	60.73	74.00	13.27	PASS	Vertical	PK
7	13680.712	7.34	39.54	46.88	54.00	7.12	PASS	Vertical	AV
8	16335.8891	11.41	36.86	48.27	54.00	5.73	PASS	Vertical	AV

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2452Mhz
Remark:	\	Test_Date	2026/6/23


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18627.3251	-26.64	62.89	36.25	74.00	37.75	PASS	Horizontal	PK
2	19712.6485	-25.39	60.88	35.49	74.00	38.51	PASS	Horizontal	PK
3	21805.0922	-25.54	62.14	36.60	74.00	37.40	PASS	Horizontal	PK
4	23245.7298	-24.11	58.96	34.85	74.00	39.15	PASS	Horizontal	PK
5	24648.2859	-21.89	57.32	35.43	74.00	38.57	PASS	Horizontal	PK
6	25588.0835	-20.75	57.10	36.35	74.00	37.65	PASS	Horizontal	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	2452Mhz
Remark:	\	Test_Date	2026/6/23

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18827.9331	-26.29	62.51	36.22	74.00	37.78	PASS	Vertical	PK
2	19893.8758	-24.94	60.62	35.68	74.00	38.32	PASS	Vertical	PK
3	21292.6917	-25.81	61.04	35.23	74.00	38.77	PASS	Vertical	PK
4	22482.0593	-25.06	60.61	35.55	74.00	38.45	PASS	Vertical	PK
5	24277.6711	-22.27	57.81	35.54	74.00	38.46	PASS	Vertical	PK
6	25602.0241	-20.71	56.92	36.21	74.00	37.79	PASS	Vertical	PK

Remark:


- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. The report records the lowest Peak value. If the Peak value is greater than 54dBμV/m, then the Average value at that time is recorded.

Restricted bands:

Test plot as follows:

Test_Mode	802.11 b Transmitting	Test_Frequency	2412Mhz
Remark:	\	Test_Date	2026/6/22


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	34.19	50.15	74.00	23.85	PASS	Horizontal	PK
2	2390	15.96	22.86	38.82	54.00	15.18	PASS	Horizontal	AV

Test_Mode	802.11 b Transmitting	Test_Frequency	2412Mhz
Remark:	\	Test_Date	2026/6/22


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	34.16	50.12	74.00	23.88	PASS	Vertical	PK
2	2390	15.96	22.92	38.88	54.00	15.12	PASS	Vertical	AV

Test_Mode	802.11 b Transmitting	Test_Frequency	2462Mhz
Remark:	\	Test_Date	2026/6/22


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	33.41	49.70	74.00	24.30	PASS	Horizont	PK
2	2483.5	16.29	20.24	36.53	54.00	17.47	PASS	Horizont	AV

Test_Mode	802.11 b Transmitting	Test_Frequency	2462Mhz
Remark:	\	Test_Date	2026/6/22


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2483.5	16.29	33.40	49.69	74.00	24.31	PASS	Vertical	PK
2	2483.5	16.29	19.86	36.15	54.00	17.85	PASS	Vertical	AV

Test_Mode	802.11 g Transmitting	Test_Frequency	2412Mhz
Remark:	\	Test_Date	2026/6/22

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	2390	15.96	34.98	50.94	74.00	23.06	PASS	Horizont	PK
2	2390	15.96	22.22	38.18	54.00	15.82	PASS	Horizont	AV