

RF Exposure Evaluation Statement

Product Name: RGBW STRING LIGHT

Model No.: RE-RGBWA, RE-RGBWB, RE-SOL, RE-DM

FCC ID: 2A3K6JCD2021RE

1 RF EXPOSURE COMPLIANCE REQUIREMENT

1.1 STANDARD REQUIREMENT

According to KDB447498D01 General RF Exposure Guidance v06
Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

1.2 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

1.3 EUT RF EXPOSURE

The EUT H-field strength of the prototype is far less than the evaluation limit of human exposure to radio-frequency (RF) radiation. So no SAR test is required

Note: Refer to project No. BLA-EMC-202109-A9601 for EUT test max H-field strength.