



RF Exposure evaluation

According to 447498 D01 and 47CRF part 2.1093.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Here,

For 433.92MHz

Fre. (GHz)	E (dBuV/m)	EIRP (dBm)	Max ERP (dBm)	Max ERP (mW)	Separation distance (mm)	Calculation Value	Threshold Value
0.43392	85.36	-9.84	-11.99	0.06	5	0.008	3.0

1. $\text{EIRP(dBm)} = \text{E(dBuV/m)} - 95.2 = 85.36 \text{ (dBuV/m)} - 95.2 = -9.84 \text{ dBm}$

2. $\text{ERP} = \text{EIRP(dBm)} - 2.15$

So SAR test is not required