FCC TEST REPORT
FCC ID:2A3NS- BLIX

Report Number..... :	ZKT-240702L7585E
Date of Test.....	Jun. 20, 2024 to Jul. 30, 2024
Date of issue ..... :	Jul. 30, 2024
Total number of pages	75
Test Result ..... :	PASS
Testing Laboratory..... :	**Shenzhen ZKT Technology Co., Ltd.**
Address ..... :	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Applicant's name ..... :	**Sveaverken Svea Agri AB**
Address ..... :	Högmossevägen 11，SE-641 39 Katrineholm，Sweden
Manufacturer's name ..... :	**Sveaverken Svea Agri AB**
Address ..... :	Högmossevägen 11，SE-641 39 Katrineholm，Sweden
Test specification:	
Standard ..... :	FCC CFR Title 47 Part 15 Subpart C Section 15.247 ANSI C63.10:2013
Test procedure..... :	/
Non-standard test method ..... :	N/A
Test Report Form No. ..... :	TRF-EL-110_V0
Test Report Form(s) Originator .... :	ZKT Testing
Master TRF ..... :	Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name ..... :	**Robotic Lawn Mower**
Trademark ..... :	Sveaverken
Model/Type reference ..... :	Blix
Ratings..... :	DC 14.8V

Testing procedure and testing location:

Testing Laboratory.....:	**Shenzhen ZKT Technology Co., Ltd.**
Address.....:	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Tested by (name + signature).....:	Jim.Liu
Reviewer (name + signature).....:	Jackson.Fang
Approved (name + signature).....:	Lake Xie

Table of Contents

	Page
1. VERSION	5
2. SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS	9
4. EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.2.1 RADIATED EMISSION LIMITS	16
4.2.2 TEST PROCEDURE	17
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	17
4.2.5 EUT OPERATING CONDITIONS	18
4.2.6 TEST RESULTS	18
5.RADIATED BAND EMISSIONMEASUREMENT	31
5.1 TEST REQUIREMENT:	31
5.2 TEST PROCEDURE	31
5.3 DEVIATION FROM TEST STANDARD	31
5.4 TEST SETUP	32
5.5 EUT OPERATING CONDITIONS	32
5.6 TEST RESULT	33
6.POWER SPECTRAL DENSITY TEST	36
6.1 APPLIED PROCEDURES / LIMIT	36
6.2 TEST PROCEDURE	36
6.3 DEVIATION FROM STANDARD	36
6.4 TEST SETUP	36
6.5 EUT OPERATION CONDITIONS	36
6.6 TEST RESULT	37

7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH 44
7.1 APPLIED PROCEDURES / LIMIT 44
7.2 TEST PROCEDURE 44
7.3 DEVIATION FROM STANDARD 44
7.4 TEST SETUP 44
7.5 EUT OPERATION CONDITIONS 44
7.6 TEST RESULT 45
8.PEAK OUTPUT POWER TEST 53
8.1 APPLIED PROCEDURES/LIMIT 53
8.2 TEST PROCEDURE 53
8.3 DEVIATION FROM STANDARD 53
8.4 TEST SETUP 53
8.5 EUT OPERATION CONDITIONS 53
8.6 TEST RESULT 54
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 55
9.1 APPLICABLE STANDARD 55
9.2 TEST PROCEDURE 55
9.3 DEVIATION FROM STANDARD 55
9.4 TEST SETUP 55
9.5 EUT OPERATION CONDITIONS 55
9.6 TEST RESULTS 55
10. ANTENNA REQUIREMENT 79
11. TEST SETUP PHOTO 80
12. EUT CONSTRUCTIONAL DETAILS 80

1. VERSION

Report No.	Version	Description	Approved
ZKT-240702L7585E	Rev.01	Initial issue of report	Jul. 30, 2024

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (c)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth& 99% OCB	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033
CAB identifier: CN0110

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	3m camber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m camber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF Band Edge	U=1.68dB
7	RF power conducted	U=1.86dB
8	RF conducted Spurious Emission	U=2.2dB
9	RF Occupied Bandwidth	U=1.8KHz
10	RF Power Spectral Density	U=1.75dB
11	humidity uncertainty	U=5.3%
12	Temperature uncertainty	U=0.59℃

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Robotic Lawn Mower
Model No.:	Blix
Model Different.:	N/A
Serial No.:	N/A
Sample ID	ZKT-240702L7585
Sample(s) Status:	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20):
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum(DSSS) 802.11g/802.11n(HT20): Orthogonal Frequency Division Multiplexing(OFDM)
Antenna Type and Antenna gain:	802.11b/g/n: FPC Antenna Antenna gain: 3.5dBi
Worst Case:	2.4G WIFI 802.11n20
Power supply:	Input:DC 14.8V
SWITCHING POWER ADAPTER:	Input:100-240VAC,50/60Hz,2.5AMAX Output:24VDC,7.5A,180W

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	**Frequency (MHz)**	
	802.11b/802.11g/802.11n(HT20)	/
Lowest channel	2412MHz	/
Middle channel	2437MHz	/
Highest channel	2462MHz	/

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode

Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)
Data rate	1Mbps	6Mbps	6.5Mbps

Test Software	MobaXterm.exe
Power level setup	14

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
PC	Lenovo	Lenovo S14 G2	PF4119QS	/	/

Item	Shielded Type	Ferrite Core	Length	Note
USB Cable	N/A	N/A	0.8m	/

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	N/A	Nov. 14, 2023	Nov. 13, 2024
2	LISN	CYBERTEK	EM5040A	E1850400149	N/A	Nov. 02, 2023	Nov. 01, 2024
3	Test Cable	N/A	C-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
4	Test Cable	N/A	C-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
5	Test Cable	N/A	C-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
6	EMI Test Receiver	R&S	ESCI3	101393	4.42 SP3	Nov. 02, 2023	Nov. 01, 2024
7	Triple-Loop Antenna	N/A	RF300	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
8	Absorbing Clamp	DZ	ZN23201	15034	N/A	Nov. 07, 2023	Nov. 06, 2024
9	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	N/A	\	\

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	A.17.05	Nov. 02, 2023	Nov. 01, 2024
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Nov. 02, 2023	Nov. 01, 2024
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	4.32	Nov. 02, 2023	Nov. 01, 2024
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	N/A	Nov. 13, 2023	Nov. 12, 2024
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Nov. 13, 2023	Nov. 12, 2024
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Nov. 13, 2023	Nov. 12, 2024
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Nov. 16, 2023	Nov. 15, 2024
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	N/A	Nov. 02, 2023	Nov. 01, 2024
9	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	N/A	Nov. 02, 2023	Nov. 01, 2024
10	Amplifier (18GHz -40GHz)	Tonscend	TAP-184050	6214	N/A	Jan. 16, 2024	Jan. 16, 2025
11	Test Cable	N/A	R-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
12	Test Cable	N/A	R-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
13	Test Cable	N/A	R-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
14	Test Cable	N/A	RF-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
15	Test Cable	N/A	RF-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
16	Test Cable	N/A	RF-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
17	ESG Signal Generator	Agilent	E4421B	N/A	B.03.84	Nov. 02, 2023	Nov. 01, 2024
18	Signal Generator	Agilent	N5182A	N/A	A.01.87	Nov. 02, 2023	Nov. 01, 2024

19	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	N/A	Nov. 16, 2023	Nov. 15, 2024
20	Wideband Radio Communication Test	R&S	CMW500	106504	V 3.7.22	Nov. 02, 2023	Nov. 01, 2024
21	MWRF Power Meter Test system	MW	MW100-RF CB	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
22	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	\	\
23	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\
24	RF Software	MW	MTS8310	V2.0.0.0	N/A	\	\
25	Turntable	MF	MF-7802BS	N/A	N/A	\	\
26	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 Test Result

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	L
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2195	17.43	20.00	37.43	52.84	-15.41	AVG
2	0.2220	26.42	20.01	46.43	62.74	-16.31	QP
3	0.4062	26.19	20.14	46.33	57.73	-11.40	QP
4	0.4153	14.91	20.14	35.05	47.54	-12.49	AVG
5	0.5231	24.53	20.09	44.62	56.00	-11.38	QP
6	0.5280	13.99	20.09	34.08	46.00	-11.92	AVG
7	0.6673	23.61	20.08	43.69	56.00	-12.31	QP
8	0.6673	14.62	20.08	34.70	46.00	-11.30	AVG
9	3.2910	16.06	20.04	36.10	46.00	-9.90	AVG
10	3.2955	24.18	20.04	44.22	56.00	-11.78	QP
11	24.3060	26.95	20.38	47.33	60.00	-12.67	QP
12	25.1700	24.94	20.40	45.34	50.00	-4.66	AVG

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
1	0.2195	17.43	20.00	37.43	52.84	-15.41	AVG
2	0.2220	26.42	20.01	46.43	62.74	-16.31	QP
3	0.4062	26.19	20.14	46.33	57.73	-11.40	QP
4	0.4153	14.91	20.14	35.05	47.54	-12.49	AVG
5	0.5231	24.53	20.09	44.62	56.00	-11.38	QP
6	0.5280	13.99	20.09	34.08	46.00	-11.92	AVG
7	0.6673	23.61	20.08	43.69	56.00	-12.31	QP
8	0.6673	14.62	20.08	34.70	46.00	-11.30	AVG
9	3.2910	16.06	20.04	36.10	46.00	-9.90	AVG
10	3.2955	24.18	20.04	44.22	56.00	-11.78	QP
11	24.3060	24.95	20.38	45.33	60.00	-14.67	QP
12	25.1700	24.94	20.40	45.34	50.00	-4.66	AVG

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoiccamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of avariable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum valueof the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned toheights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber andchange form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode	Working



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	129.4677	40.96	-15.53	25.43	43.50	-18.07	QP	199	180	P	
2	143.8295	44.48	-14.84	29.64	43.50	-13.86	QP	199	168	P	
3 *	213.7634	53.43	-17.63	35.80	43.50	-7.70	QP	199	57	P	
4	247.6819	52.59	-16.64	35.95	46.00	-10.05	QP	199	194	P	
5	368.1116	48.24	-13.19	35.05	46.00	-10.95	QP	199	226	P	
6	459.1144	47.28	-10.46	36.82	46.00	-9.18	QP	199	139	P	

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode	Working



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	59.0251	47.43	-16.49	30.94	40.00	-9.06	QP	100	324	P	
2 *	120.0220	51.40	-16.07	35.33	43.50	-8.17	QP	100	2	P	
3	164.9074	45.91	-14.61	31.30	43.50	-12.20	QP	100	280	P	
4	210.0481	52.18	-17.74	34.44	43.50	-9.06	QP	100	358	P	
5	369.4047	50.19	-13.16	37.03	46.00	-8.97	QP	100	266	P	
6	449.1961	47.18	-10.65	36.53	46.00	-9.47	QP	100	35	P	

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case 802.11n20.

1GHz~25GHz
ANT1

802.11b

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	52.66	30.55	5.77	24.66	52.54	74.00	-21.46	PK
V	4824.00	44.27	30.55	5.77	24.66	44.15	54.00	-9.85	AV
V	7236.00	52.03	30.33	6.32	24.55	52.57	74.00	-21.43	PK
V	7236.00	42.97	30.33	6.32	24.55	43.51	54.00	-10.49	AV
V	9648.00	49.85	30.85	7.45	24.69	51.14	74.00	-22.86	PK
V	9648.00	44.35	30.85	7.45	24.69	45.64	54.00	-8.36	AV
V	12060.00	53.08	31.02	8.99	25.57	56.62	74.00	-17.38	PK
V	12060.00	43.84	31.02	8.99	25.57	47.38	54.00	-6.62	AV
H	4824.00	50.50	30.55	5.77	24.66	50.38	74.00	-23.62	PK
H	4824.00	44.34	30.55	5.77	24.66	44.22	54.00	-9.78	AV
H	7236.00	53.51	30.33	6.32	24.55	54.05	74.00	-19.95	PK
H	7236.00	42.95	30.33	6.32	24.55	43.49	54.00	-10.51	AV
H	9648.00	51.86	30.85	7.45	24.69	53.15	74.00	-20.85	PK
H	9648.00	43.61	30.85	7.45	24.69	44.90	54.00	-9.10	AV
H	12060.00	51.51	31.02	8.99	25.57	55.05	74.00	-18.95	PK
H	12060.00	43.49	31.02	8.99	25.57	47.03	54.00	-6.97	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	53.01	30.55	5.77	24.66	52.89	74.00	-21.11	PK
V	4874.00	43.78	30.55	5.77	24.66	43.66	54.00	-10.34	AV
V	7311.00	52.47	30.33	6.32	24.55	53.01	74.00	-20.99	PK
V	7311.00	43.26	30.33	6.32	24.55	43.80	54.00	-10.20	AV
V	9748.00	50.76	30.85	7.45	24.69	52.05	74.00	-21.95	PK
V	9748.00	43.60	30.85	7.45	24.69	44.89	54.00	-9.11	AV
V	12185.00	52.92	31.02	8.99	25.57	56.46	74.00	-17.54	PK
V	12185.00	44.39	31.02	8.99	25.57	47.93	54.00	-6.07	AV
H	4874.00	52.15	30.55	5.77	24.66	52.03	74.00	-21.97	PK
H	4874.00	43.45	30.55	5.77	24.66	43.33	54.00	-10.67	AV
H	7311.00	50.21	30.33	6.32	24.55	50.75	74.00	-23.25	PK
H	7311.00	43.14	30.33	6.32	24.55	43.68	54.00	-10.32	AV
H	9748.00	51.93	30.85	7.45	24.69	53.22	74.00	-20.78	PK
H	9748.00	42.88	30.85	7.45	24.69	44.17	54.00	-9.83	AV
H	12185.00	52.45	31.02	8.99	25.57	55.99	74.00	-18.01	PK
H	12185.00	43.66	31.02	8.99	25.57	47.20	54.00	-6.80	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2462MHz									
V	4924.00	51.56	30.55	5.77	24.66	51.44	74.00	-22.56	PK
V	4924.00	44.00	30.55	5.77	24.66	43.88	54.00	-10.12	AV
V	7386.00	52.09	30.33	6.32	24.55	52.63	74.00	-21.37	PK
V	7386.00	43.46	30.33	6.32	24.55	44.00	54.00	-10.00	AV
V	9848.00	50.75	30.85	7.45	24.69	52.04	74.00	-21.96	PK
V	9848.00	43.46	30.85	7.45	24.69	44.75	54.00	-9.25	AV
V	12310.00	51.90	31.02	8.99	25.57	55.44	74.00	-18.56	PK
V	12310.00	43.43	31.02	8.99	25.57	46.97	54.00	-7.03	AV
H	4924.00	54.40	30.55	5.77	24.66	54.28	74.00	-19.72	PK
H	4924.00	43.68	30.55	5.77	24.66	43.56	54.00	-10.44	AV
H	7386.00	52.87	30.33	6.32	24.55	53.41	74.00	-20.59	PK
H	7386.00	43.46	30.33	6.32	24.55	44.00	54.00	-10.00	AV
H	9848.00	49.80	30.85	7.45	24.69	51.09	74.00	-22.91	PK
H	9848.00	43.54	30.85	7.45	24.69	44.83	54.00	-9.17	AV
H	12310.00	51.75	31.02	8.99	25.57	55.29	74.00	-18.71	PK
H	12310.00	43.70	31.02	8.99	25.57	47.24	54.00	-6.76	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. The test data shows only the worst case.

802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	50.38	30.55	5.77	24.66	50.26	74.00	-23.74	PK
V	4824.00	43.68	30.55	5.77	24.66	43.56	54.00	-10.44	AV
V	7236.00	52.19	30.33	6.32	24.55	52.73	74.00	-21.27	PK
V	7236.00	43.14	30.33	6.32	24.55	43.68	54.00	-10.32	AV
V	9648.00	53.82	30.85	7.45	24.69	55.11	74.00	-18.89	PK
V	9648.00	43.19	30.85	7.45	24.69	44.48	54.00	-9.52	AV
V	12060.00	50.15	31.02	8.99	25.57	53.69	74.00	-20.31	PK
V	12060.00	43.22	31.02	8.99	25.57	46.76	54.00	-7.24	AV
H	4824.00	51.36	30.55	5.77	24.66	51.24	74.00	-22.76	PK
H	4824.00	43.21	30.55	5.77	24.66	43.09	54.00	-10.91	AV
H	7236.00	51.57	30.33	6.32	24.55	52.11	74.00	-21.89	PK
H	7236.00	42.61	30.33	6.32	24.55	43.15	54.00	-10.85	AV
H	9648.00	53.31	30.85	7.45	24.69	54.60	74.00	-19.40	PK
H	9648.00	43.56	30.85	7.45	24.69	44.85	54.00	-9.15	AV
H	12060.00	53.92	31.02	8.99	25.57	57.46	74.00	-16.54	PK
H	12060.00	43.89	31.02	8.99	25.57	47.43	54.00	-6.57	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	51.49	30.55	5.77	24.66	51.37	74.00	-22.63	PK
V	4874.00	44.20	30.55	5.77	24.66	44.08	54.00	-9.92	AV
V	7311.00	52.23	30.33	6.32	24.55	52.77	74.00	-21.23	PK
V	7311.00	43.16	30.33	6.32	24.55	43.70	54.00	-10.30	AV
V	9748.00	50.52	30.85	7.45	24.69	51.81	74.00	-22.19	PK
V	9748.00	43.29	30.85	7.45	24.69	44.58	54.00	-9.42	AV
V	12185.00	54.47	31.02	8.99	25.57	58.01	74.00	-15.99	PK
V	12185.00	42.88	31.02	8.99	25.57	46.42	54.00	-7.58	AV
H	4874.00	54.59	30.55	5.77	24.66	54.47	74.00	-19.53	PK
H	4874.00	43.58	30.55	5.77	24.66	43.46	54.00	-10.54	AV
H	7311.00	51.62	30.33	6.32	24.55	52.16	74.00	-21.84	PK
H	7311.00	43.64	30.33	6.32	24.55	44.18	54.00	-9.82	AV
H	9748.00	52.67	30.85	7.45	24.69	53.96	74.00	-20.04	PK
H	9748.00	43.36	30.85	7.45	24.69	44.65	54.00	-9.35	AV
H	12185.00	54.66	31.02	8.99	25.57	58.20	74.00	-15.80	PK
H	12185.00	44.00	31.02	8.99	25.57	47.54	54.00	-6.46	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2462MHz									
V	4924.00	52.11	30.55	5.77	24.66	51.99	74.00	-22.01	PK
V	4924.00	44.18	30.55	5.77	24.66	44.06	54.00	-9.94	AV
V	7386.00	52.63	30.33	6.32	24.55	53.17	74.00	-20.83	PK
V	7386.00	43.83	30.33	6.32	24.55	44.37	54.00	-9.63	AV
V	9848.00	52.05	30.85	7.45	24.69	53.34	74.00	-20.66	PK
V	9848.00	43.69	30.85	7.45	24.69	44.98	54.00	-9.02	AV
V	12310.00	51.41	31.02	8.99	25.57	54.95	74.00	-19.05	PK
V	12310.00	42.76	31.02	8.99	25.57	46.30	54.00	-7.70	AV
H	4924.00	51.16	30.55	5.77	24.66	51.04	74.00	-22.96	PK
H	4924.00	43.47	30.55	5.77	24.66	43.35	54.00	-10.65	AV
H	7386.00	50.54	30.33	6.32	24.55	51.08	74.00	-22.92	PK
H	7386.00	43.43	30.33	6.32	24.55	43.97	54.00	-10.03	AV
H	9848.00	54.57	30.85	7.45	24.69	55.86	74.00	-18.14	PK
H	9848.00	43.78	30.85	7.45	24.69	45.07	54.00	-8.93	AV
H	12310.00	53.43	31.02	8.99	25.57	56.97	74.00	-17.03	PK
H	12310.00	43.01	31.02	8.99	25.57	46.55	54.00	-7.45	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. The test data shows only the worst case.

1GHz~25GHz
ANT2

802.11b

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	52.52	30.55	5.77	24.66	52.40	74.00	-21.60	PK
V	4824.00	44.18	30.55	5.77	24.66	44.06	54.00	-9.94	AV
V	7236.00	52.51	30.33	6.32	24.55	53.05	74.00	-20.95	PK
V	7236.00	43.04	30.33	6.32	24.55	43.58	54.00	-10.42	AV
V	9648.00	49.66	30.85	7.45	24.69	50.95	74.00	-23.05	PK
V	9648.00	43.88	30.85	7.45	24.69	45.17	54.00	-8.83	AV
V	12060.00	52.75	31.02	8.99	25.57	56.29	74.00	-17.71	PK
V	12060.00	43.48	31.02	8.99	25.57	47.02	54.00	-6.98	AV
H	4824.00	50.59	30.55	5.77	24.66	50.47	74.00	-23.53	PK
H	4824.00	44.30	30.55	5.77	24.66	44.18	54.00	-9.82	AV
H	7236.00	53.15	30.33	6.32	24.55	53.69	74.00	-20.31	PK
H	7236.00	42.47	30.33	6.32	24.55	43.01	54.00	-10.99	AV
H	9648.00	51.55	30.85	7.45	24.69	52.84	74.00	-21.16	PK
H	9648.00	43.84	30.85	7.45	24.69	45.13	54.00	-8.87	AV
H	12060.00	51.39	31.02	8.99	25.57	54.93	74.00	-19.07	PK
H	12060.00	43.97	31.02	8.99	25.57	47.51	54.00	-6.49	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	53.06	30.55	5.77	24.66	52.94	74.00	-21.06	PK
V	4874.00	44.21	30.55	5.77	24.66	44.09	54.00	-9.91	AV
V	7311.00	52.18	30.33	6.32	24.55	52.72	74.00	-21.28	PK
V	7311.00	42.89	30.33	6.32	24.55	43.43	54.00	-10.57	AV
V	9748.00	50.88	30.85	7.45	24.69	52.17	74.00	-21.83	PK
V	9748.00	44.01	30.85	7.45	24.69	45.30	54.00	-8.70	AV
V	12185.00	52.61	31.02	8.99	25.57	56.15	74.00	-17.85	PK
V	12185.00	44.82	31.02	8.99	25.57	48.36	54.00	-5.64	AV
H	4874.00	52.42	30.55	5.77	24.66	52.30	74.00	-21.70	PK
H	4874.00	43.83	30.55	5.77	24.66	43.71	54.00	-10.29	AV
H	7311.00	50.08	30.33	6.32	24.55	50.62	74.00	-23.38	PK
H	7311.00	43.07	30.33	6.32	24.55	43.61	54.00	-10.39	AV
H	9748.00	51.58	30.85	7.45	24.69	52.87	74.00	-21.13	PK
H	9748.00	42.74	30.85	7.45	24.69	44.03	54.00	-9.97	AV
H	12185.00	52.78	31.02	8.99	25.57	56.32	74.00	-17.68	PK
H	12185.00	44.00	31.02	8.99	25.57	47.54	54.00	-6.46	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2462MHz									
V	4924.00	51.59	30.55	5.77	24.66	51.47	74.00	-22.53	PK
V	4924.00	43.82	30.55	5.77	24.66	43.70	54.00	-10.30	AV
V	7386.00	52.10	30.33	6.32	24.55	52.64	74.00	-21.36	PK
V	7386.00	43.88	30.33	6.32	24.55	44.42	54.00	-9.58	AV
V	9848.00	50.29	30.85	7.45	24.69	51.58	74.00	-22.42	PK
V	9848.00	43.84	30.85	7.45	24.69	45.13	54.00	-8.87	AV
V	12310.00	51.49	31.02	8.99	25.57	55.03	74.00	-18.97	PK
V	12310.00	43.22	31.02	8.99	25.57	46.76	54.00	-7.24	AV
H	4924.00	54.16	30.55	5.77	24.66	54.04	74.00	-19.96	PK
H	4924.00	43.86	30.55	5.77	24.66	43.74	54.00	-10.26	AV
H	7386.00	53.26	30.33	6.32	24.55	53.80	74.00	-20.20	PK
H	7386.00	43.73	30.33	6.32	24.55	44.27	54.00	-9.73	AV
H	9848.00	50.26	30.85	7.45	24.69	51.55	74.00	-22.45	PK
H	9848.00	43.88	30.85	7.45	24.69	45.17	54.00	-8.83	AV
H	12310.00	51.93	31.02	8.99	25.57	55.47	74.00	-18.53	PK
H	12310.00	43.54	31.02	8.99	25.57	47.08	54.00	-6.92	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. The test data shows only the worst case.

802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	50.14	30.55	5.77	24.66	50.02	74.00	-23.98	PK
V	4824.00	43.84	30.55	5.77	24.66	43.72	54.00	-10.28	AV
V	7236.00	52.48	30.33	6.32	24.55	53.02	74.00	-20.98	PK
V	7236.00	42.64	30.33	6.32	24.55	43.18	54.00	-10.82	AV
V	9648.00	54.01	30.85	7.45	24.69	55.30	74.00	-18.70	PK
V	9648.00	43.16	30.85	7.45	24.69	44.45	54.00	-9.55	AV
V	12060.00	49.70	31.02	8.99	25.57	53.24	74.00	-20.76	PK
V	12060.00	42.79	31.02	8.99	25.57	46.33	54.00	-7.67	AV
H	4824.00	51.18	30.55	5.77	24.66	51.06	74.00	-22.94	PK
H	4824.00	43.21	30.55	5.77	24.66	43.09	54.00	-10.91	AV
H	7236.00	51.45	30.33	6.32	24.55	51.99	74.00	-22.01	PK
H	7236.00	42.27	30.33	6.32	24.55	42.81	54.00	-11.19	AV
H	9648.00	53.42	30.85	7.45	24.69	54.71	74.00	-19.29	PK
H	9648.00	43.80	30.85	7.45	24.69	45.09	54.00	-8.91	AV
H	12060.00	53.43	31.02	8.99	25.57	56.97	74.00	-17.03	PK
H	12060.00	43.83	31.02	8.99	25.57	47.37	54.00	-6.63	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	51.61	30.55	5.77	24.66	51.49	74.00	-22.51	PK
V	4874.00	44.31	30.55	5.77	24.66	44.19	54.00	-9.81	AV
V	7311.00	51.78	30.33	6.32	24.55	52.32	74.00	-21.68	PK
V	7311.00	43.39	30.33	6.32	24.55	43.93	54.00	-10.07	AV
V	9748.00	50.03	30.85	7.45	24.69	51.32	74.00	-22.68	PK
V	9748.00	43.19	30.85	7.45	24.69	44.48	54.00	-9.52	AV
V	12185.00	54.20	31.02	8.99	25.57	57.74	74.00	-16.26	PK
V	12185.00	43.31	31.02	8.99	25.57	46.85	54.00	-7.15	AV
H	4874.00	55.03	30.55	5.77	24.66	54.91	74.00	-19.09	PK
H	4874.00	43.66	30.55	5.77	24.66	43.54	54.00	-10.46	AV
H	7311.00	51.36	30.33	6.32	24.55	51.90	74.00	-22.10	PK
H	7311.00	43.62	30.33	6.32	24.55	44.16	54.00	-9.84	AV
H	9748.00	52.93	30.85	7.45	24.69	54.22	74.00	-19.78	PK
H	9748.00	43.12	30.85	7.45	24.69	44.41	54.00	-9.59	AV
H	12185.00	55.11	31.02	8.99	25.57	58.65	74.00	-15.35	PK
H	12185.00	43.79	31.02	8.99	25.57	47.33	54.00	-6.67	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2462MHz									
V	4924.00	51.66	30.55	5.77	24.66	51.54	74.00	-22.46	PK
V	4924.00	43.93	30.55	5.77	24.66	43.81	54.00	-10.19	AV
V	7386.00	52.35	30.33	6.32	24.55	52.89	74.00	-21.11	PK
V	7386.00	43.36	30.33	6.32	24.55	43.90	54.00	-10.10	AV
V	9848.00	52.02	30.85	7.45	24.69	53.31	74.00	-20.69	PK
V	9848.00	43.24	30.85	7.45	24.69	44.53	54.00	-9.47	AV
V	12310.00	51.67	31.02	8.99	25.57	55.21	74.00	-18.79	PK
V	12310.00	42.54	31.02	8.99	25.57	46.08	54.00	-7.92	AV
H	4924.00	51.32	30.55	5.77	24.66	51.20	74.00	-22.80	PK
H	4924.00	43.66	30.55	5.77	24.66	43.54	54.00	-10.46	AV
H	7386.00	50.57	30.33	6.32	24.55	51.11	74.00	-22.89	PK
H	7386.00	43.45	30.33	6.32	24.55	43.99	54.00	-10.01	AV
H	9848.00	54.74	30.85	7.45	24.69	56.03	74.00	-17.97	PK
H	9848.00	44.25	30.85	7.45	24.69	45.54	54.00	-8.46	AV
H	12310.00	53.47	31.02	8.99	25.57	57.01	74.00	-16.99	PK
H	12310.00	42.94	31.02	8.99	25.57	46.48	54.00	-7.52	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. The test data shows only the worst case.

802.11n20 （ANT 1+ANT 2）

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	54.27	30.55	5.77	24.66	54.15	74.00	-19.85	PK
V	4824.00	43.99	30.55	5.77	24.66	43.87	54.00	-10.13	AV
V	7236.00	50.83	30.33	6.32	24.55	51.37	74.00	-22.63	PK
V	7236.00	43.64	30.33	6.32	24.55	44.18	54.00	-9.82	AV
V	9648.00	50.08	30.85	7.45	24.69	51.37	74.00	-22.63	PK
V	9648.00	43.66	30.85	7.45	24.69	44.95	54.00	-9.05	AV
V	12060.00	53.17	31.02	8.99	25.57	56.71	74.00	-17.29	PK
V	12060.00	43.18	31.02	8.99	25.57	46.72	54.00	-7.28	AV
H	4824.00	50.06	30.55	5.77	24.66	49.94	74.00	-24.06	PK
H	4824.00	43.26	30.55	5.77	24.66	43.14	54.00	-10.86	AV
H	7236.00	53.69	30.33	6.32	24.55	54.23	74.00	-19.77	PK
H	7236.00	44.11	30.33	6.32	24.55	44.65	54.00	-9.35	AV
H	9648.00	52.24	30.85	7.45	24.69	53.53	74.00	-20.47	PK
H	9648.00	43.88	30.85	7.45	24.69	45.17	54.00	-8.83	AV
H	12060.00	52.82	31.02	8.99	25.57	56.36	74.00	-17.64	PK
H	12060.00	43.76	31.02	8.99	25.57	47.30	54.00	-6.70	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	51.35	30.55	5.77	24.66	51.23	74.00	-22.77	PK
V	4874.00	43.18	30.55	5.77	24.66	43.06	54.00	-10.94	AV
V	7311.00	51.61	30.33	6.32	24.55	52.15	74.00	-21.85	PK
V	7311.00	43.45	30.33	6.32	24.55	43.99	54.00	-10.01	AV
V	9748.00	51.61	30.85	7.45	24.69	52.90	74.00	-21.10	PK
V	9748.00	42.87	30.85	7.45	24.69	44.16	54.00	-9.84	AV
V	12185.00	52.48	31.02	8.99	25.57	56.02	74.00	-17.98	PK
V	12185.00	43.32	31.02	8.99	25.57	46.86	54.00	-7.14	AV
H	4874.00	51.90	30.55	5.77	24.66	51.78	74.00	-22.22	PK
H	4874.00	43.63	30.55	5.77	24.66	43.51	54.00	-10.49	AV
H	7311.00	54.73	30.33	6.32	24.55	55.27	74.00	-18.73	PK
H	7311.00	43.97	30.33	6.32	24.55	44.51	54.00	-9.49	AV
H	9748.00	50.51	30.85	7.45	24.69	51.80	74.00	-22.20	PK
H	9748.00	43.70	30.85	7.45	24.69	44.99	54.00	-9.01	AV
H	12185.00	53.72	31.02	8.99	25.57	57.26	74.00	-16.74	PK
H	12185.00	44.07	31.02	8.99	25.57	47.61	54.00	-6.39	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2462MHz									
V	4924.00	52.62	30.55	5.77	24.66	52.50	74.00	-21.50	PK
V	4924.00	42.89	30.55	5.77	24.66	42.77	54.00	-11.23	AV
V	7386.00	52.67	30.33	6.32	24.55	53.21	74.00	-20.79	PK
V	7386.00	43.93	30.33	6.32	24.55	44.47	54.00	-9.53	AV
V	9848.00	54.38	30.85	7.45	24.69	55.67	74.00	-18.33	PK
V	9848.00	44.02	30.85	7.45	24.69	45.31	54.00	-8.69	AV
V	12310.00	50.88	31.02	8.99	25.57	54.42	74.00	-19.58	PK
V	12310.00	43.07	31.02	8.99	25.57	46.61	54.00	-7.39	AV
H	4924.00	52.66	30.55	5.77	24.66	52.54	74.00	-21.46	PK
H	4924.00	44.04	30.55	5.77	24.66	43.92	54.00	-10.08	AV
H	7386.00	50.02	30.33	6.32	24.55	50.56	74.00	-23.44	PK
H	7386.00	42.62	30.33	6.32	24.55	43.16	54.00	-10.84	AV
H	9848.00	52.23	30.85	7.45	24.69	53.52	74.00	-20.48	PK
H	9848.00	43.24	30.85	7.45	24.69	44.53	54.00	-9.47	AV
H	12310.00	53.90	31.02	8.99	25.57	57.44	74.00	-16.56	PK
H	12310.00	42.87	31.02	8.99	25.57	46.41	54.00	-7.59	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. The test data shows only the worst case.

5.RADIATED BAND EMISSIONMEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

ANT1

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
802.11b	Low Channel 2412MHz									
	H	2390.00	54.24	30.22	4.85	23.98	52.85	74.00	PK	PASS
	H	2390.00	45.09	30.22	4.85	23.98	43.70	54.00	AV	PASS
	H	2400.00	54.93	30.22	4.85	23.98	53.54	74.00	PK	PASS
	H	2400.00	43.57	30.22	4.85	23.98	42.18	54.00	AV	PASS
	V	2390.00	54.05	30.22	4.85	23.98	52.66	74.00	PK	PASS
	V	2390.00	44.69	30.22	4.85	23.98	43.30	54.00	AV	PASS
	V	2400.00	53.46	30.22	4.85	23.98	52.85	74.00	PK	PASS
	V	2400.00	43.86	30.22	4.85	23.98	43.70	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	54.81	30.22	4.85	23.98	53.42	74.00	PK	PASS
	H	2483.50	43.80	30.22	4.85	23.98	42.41	54.00	AV	PASS
	H	2500.00	54.04	30.22	4.85	23.98	52.65	74.00	PK	PASS
	H	2500.00	44.65	30.22	4.85	23.98	43.26	54.00	AV	PASS
	V	2483.50	52.90	30.22	4.85	23.98	51.51	74.00	PK	PASS
	V	2483.50	44.55	30.22	4.85	23.98	43.16	54.00	AV	PASS
	V	2500.00	54.94	30.22	4.85	23.98	53.55	74.00	PK	PASS
	V	2500.00	44.06	30.22	4.85	23.98	42.67	54.00	AV	PASS
802.11g	Low Channel 2412MHz									
	H	2390.00	54.14	30.22	4.85	23.98	52.75	74.00	PK	PASS
	H	2390.00	44.18	30.22	4.85	23.98	42.79	54.00	AV	PASS
	H	2400.00	54.53	30.22	4.85	23.98	53.14	74.00	PK	PASS
	H	2400.00	44.53	30.22	4.85	23.98	43.14	54.00	AV	PASS
	V	2390.00	53.23	30.22	4.85	23.98	51.84	74.00	PK	PASS
	V	2390.00	44.47	30.22	4.85	23.98	43.08	54.00	AV	PASS
	V	2400.00	54.53	30.22	4.85	23.98	53.14	74.00	PK	PASS
	V	2400.00	45.06	30.22	4.85	23.98	43.67	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	54.05	30.22	4.85	23.98	52.66	74.00	PK	PASS
	H	2483.50	44.66	30.22	4.85	23.98	43.27	54.00	AV	PASS
	H	2500.00	54.03	30.22	4.85	23.98	52.64	74.00	PK	PASS
	H	2500.00	44.79	30.22	4.85	23.98	43.40	54.00	AV	PASS
	V	2483.50	54.71	30.22	4.85	23.98	53.32	74.00	PK	PASS
	V	2483.50	44.28	30.22	4.85	23.98	42.89	54.00	AV	PASS
	V	2500.00	53.32	30.22	4.85	23.98	51.93	74.00	PK	PASS
	V	2500.00	44.20	30.22	4.85	23.98	42.81	54.00	AV	PASS

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limi

ANT2

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
802.11b	Low Channel 2412MHz									
	H	2390.00	54.03	30.22	4.85	23.98	52.64	74.00	PK	PASS
	H	2390.00	45.35	30.22	4.85	23.98	43.96	54.00	AV	PASS
	H	2400.00	55.26	30.22	4.85	23.98	53.87	74.00	PK	PASS
	H	2400.00	43.73	30.22	4.85	23.98	42.34	54.00	AV	PASS
	V	2390.00	54.18	30.22	4.85	23.98	52.79	74.00	PK	PASS
	V	2390.00	44.31	30.22	4.85	23.98	42.92	54.00	AV	PASS
	V	2400.00	53.59	30.22	4.85	23.98	52.20	74.00	PK	PASS
	V	2400.00	44.08	30.22	4.85	23.98	42.69	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	54.53	30.22	4.85	23.98	53.14	74.00	PK	PASS
	H	2483.50	43.92	30.22	4.85	23.98	42.53	54.00	AV	PASS
	H	2500.00	54.43	30.22	4.85	23.98	53.04	74.00	PK	PASS
	H	2500.00	44.32	30.22	4.85	23.98	42.93	54.00	AV	PASS
	V	2483.50	52.64	30.22	4.85	23.98	51.25	74.00	PK	PASS
	V	2483.50	44.52	30.22	4.85	23.98	43.13	54.00	AV	PASS
	V	2500.00	55.26	30.22	4.85	23.98	53.87	74.00	PK	PASS
	V	2500.00	44.33	30.22	4.85	23.98	42.94	54.00	AV	PASS
802.11g	Low Channel 2412MHz									
	H	2390.00	54.60	30.22	4.85	23.98	53.21	74.00	PK	PASS
	H	2390.00	43.85	30.22	4.85	23.98	42.46	54.00	AV	PASS
	H	2400.00	54.48	30.22	4.85	23.98	53.09	74.00	PK	PASS
	H	2400.00	44.16	30.22	4.85	23.98	42.77	54.00	AV	PASS
	V	2390.00	53.64	30.22	4.85	23.98	52.25	74.00	PK	PASS
	V	2390.00	44.60	30.22	4.85	23.98	43.21	54.00	AV	PASS
	V	2400.00	54.65	30.22	4.85	23.98	53.26	74.00	PK	PASS
	V	2400.00	45.13	30.22	4.85	23.98	43.74	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	53.90	30.22	4.85	23.98	52.51	74.00	PK	PASS
	H	2483.50	44.46	30.22	4.85	23.98	43.07	54.00	AV	PASS
	H	2500.00	54.34	30.22	4.85	23.98	52.95	74.00	PK	PASS
	H	2500.00	44.82	30.22	4.85	23.98	43.43	54.00	AV	PASS
	V	2483.50	54.76	30.22	4.85	23.98	53.37	74.00	PK	PASS
	V	2483.50	44.46	30.22	4.85	23.98	43.07	54.00	AV	PASS
	V	2500.00	52.89	30.22	4.85	23.98	51.50	74.00	PK	PASS
	V	2500.00	44.05	30.22	4.85	23.98	42.66	54.00	AV	PASS

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limi

802.11n20 MIMO

802.11n20	Low Channel 2412MHz									
	H	2390.00	54.05	30.22	4.85	23.98	52.66	74.00	PK	PASS
	H	2390.00	45.47	30.22	4.85	23.98	44.08	54.00	AV	PASS
	H	2400.00	54.02	30.22	4.85	23.98	52.63	74.00	PK	PASS
	H	2400.SS00	45.07	30.22	4.85	23.98	43.68	54.00	AV	PASS
	V	2390.00	54.03	30.22	4.85	23.98	52.64	74.00	PK	PASS
	V	2390.00	44.55	30.22	4.85	23.98	43.16	54.00	AV	PASS
	V	2400.00	54.00	30.22	4.85	23.98	52.61	74.00	PK	PASS
	V	2400.00	43.97	30.22	4.85	23.98	42.58	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	52.31	30.22	4.85	23.98	50.92	74.00	PK	PASS
	H	2483.50	44.76	30.22	4.85	23.98	43.37	54.00	AV	PASS
	H	2500.00	53.57	30.22	4.85	23.98	52.18	74.00	PK	PASS
	H	2500.00	45.18	30.22	4.85	23.98	43.79	54.00	AV	PASS
	V	2483.50	53.28	30.22	4.85	23.98	51.89	74.00	PK	PASS
	V	2483.50	44.91	30.22	4.85	23.98	43.52	54.00	AV	PASS
	V	2500.00	53.38	30.22	4.85	23.98	51.99	74.00	PK	PASS
	V	2500.00	43.27	30.22	4.85	23.98	41.88	54.00	AV	PASS

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6.POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT

Temperature：	26℃	Relative Humidity：	54%
Pressure：	101kPa	Test Voltage ：	AC 120V/60Hz
Test Mode ：	TX Mode		

TestMode	Antenna	Frequency[MHz]	Result [dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-8.3	≤8.00	PASS
	Ant2	2412	-8.62	≤8.00	PASS
	Ant1	2437	-9.15	≤8.00	PASS
	Ant2	2437	-8.8	≤8.00	PASS
	Ant1	2462	-8.36	≤8.00	PASS
	Ant2	2462	-6.82	≤8.00	PASS
11G	Ant1	2412	-11.26	≤8.00	PASS
	Ant2	2412	-11.95	≤8.00	PASS
	Ant1	2437	-12.18	≤8.00	PASS
	Ant2	2437	-11.3	≤8.00	PASS
	Ant1	2462	-11.53	≤8.00	PASS
	Ant2	2462	-11.73	≤8.00	PASS
11N20MIMO	Ant1	2412	-11.21	≤8.00	PASS
	Ant2	2412	-10.76	≤8.00	PASS
	total	2412	-7.97	≤7.49	PASS
	Ant1	2437	-11.41	≤8.00	PASS
	Ant2	2437	-11.25	≤8.00	PASS
	total	2437	-8.32	≤7.49	PASS
	Ant1	2462	-11.47	≤8.00	PASS
	Ant2	2462	-11.62	≤8.00	PASS
	total	2462	-8.53	≤7.49	PASS

Remark：

Directional gain = GANT + Array Gain=3.5 dBi+3.01 dBi =6.51 dBi；

Array Gain = 10 log(NANT/NSS) dB （NANT=2;NSS=1）

Limit[dBm/3kHz]=8.00-（Directional gain -6dB）when Directional gain ≥6dB

TEST GRAPHS

11B_Ant1_2412

11B_Ant2_2412

11B_Ant1_2437

11B_Ant2_2437

11B_Ant1_2462

11B_Ant2_2462

11G_Ant1_2412



11G_Ant2_2412



11G_Ant1_2437



11G_Ant2_2437



11G_Ant1_2462



11G_Ant2_2462



11N20MIMO_Ant1_2412



11N20MIMO_Ant2_2412



11N20MIMO_Ant1_2437



11N20MIMO_Ant2_2437



11N20MIMO_Ant1_2462



11N20MIMO_Ant2_2462



7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 xRBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULT

Temperature：	26℃	Relative Humidity：	54%
Pressure：	101kPa	Test Voltage ：	AC 120V/60Hz
Test Mode ：	TX b Mode		

TestMode	Antenna	Channel Frequency[MHz]	OCB [MHz]	-6dB Occupy Bandwidth [MHz]
11B	Ant1	2412	11.899	8.078
	Ant2	2412	12.013	7.109
	Ant1	2437	11.954	7.091
	Ant2	2437	12.036	7.159
	Ant1	2462	11.938	7.108
	Ant2	2462	12.032	7.124
11G	Ant1	2412	16.461	16.37
	Ant2	2412	16.484	16.39
	Ant1	2437	16.471	16.37
	Ant2	2437	16.468	16.39
	Ant1	2462	16.463	16.41
	Ant2	2462	16.471	16.37
11N20MIMO	Ant1	2412	17.656	17.56
	Ant2	2412	17.520	16.00
	Ant1	2437	17.657	17.58
	Ant2	2437	17.515	15.13
	Ant1	2462	17.652	17.33
	Ant2	2462	17.495	15.17

Test plot as follows:

11B_Ant1_2412

11B_Ant2_2412

11B_Ant1_2437

11B_Ant2_2437

11B_Ant1_2462

11B_Ant2_2462

11G_Ant1_2412

11G_Ant2_2412

11G_Ant1_2437

11G_Ant2_2437

11G_Ant1_2462

11G_Ant2_2462

11N20MIMO_Ant1_2412

11N20MIMO_Ant2_2412

11N20MIMO_Ant1_2437

11N20MIMO_Ant2_2437

11N20MIMO_Ant1_2462

11N20MIMO_Ant2_2462

Keysight Spectrum Analyzer - Occupied BW
Center Freq 2.462000000 GHz
Center Freq: 2.462000000 GHz
Trig: Free Run
Avg|Hold: 100/100
#Atten: 40 dB
Radio Std: None
Radio Device: BTS
Frequency
Ref Offset 10.61 dB
10 dB/div
Ref 30.00 dBm
Mkr1 2.46448 GHz
3.0457 dBm
Center Freq
2.462000000 GHz
Center 2.462 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 40 MHz
Sweep 3.867 ms
CF Step
4.000000 MHz
Auto
Man
Occupied Bandwidth
17.495 MHz
Total Power 20.2 dBm
Transmit Freq Error -17.049 kHz
% of OBW Power 99.00 %
x dB Bandwidth 14.48 MHz
x dB -6.00 dB
Freq Offset
0 Hz
MSG
STATUS

8.PEAK OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULT

Temperature：	26℃	Relative Humidity：	54%
Pressure：	101kPa	Test Voltage ：	AC 120V/60Hz

Test Mode	Antenna	Frequency[MHz]	Peak Powert[dBm]	Result [dBm]	Limit [dBm]	Eirp [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	14.84	14.84	≤30.00	18.34	≤36.00	PASS
	Ant2	2412	14.66	14.66	≤30.00	18.16	≤36.00	PASS
	Ant1	2437	14.39	14.39	≤30.00	17.89	≤36.00	PASS
	Ant2	2437	14.60	14.60	≤30.00	18.10	≤36.00	PASS
	Ant1	2462	14.57	14.57	≤30.00	18.07	≤36.00	PASS
	Ant2	2462	14.94	14.94	≤30.00	18.44	≤36.00	PASS
11G	Ant1	2412	19.57	19.57	≤30.00	23.07	≤36.00	PASS
	Ant2	2412	19.18	19.18	≤30.00	22.68	≤36.00	PASS
	Ant1	2437	19.03	19.03	≤30.00	22.53	≤36.00	PASS
	Ant2	2437	19.22	19.22	≤30.00	22.72	≤36.00	PASS
	Ant1	2462	19.02	19.02	≤30.00	22.52	≤36.00	PASS
	Ant2	2462	19.24	19.24	≤30.00	22.74	≤36.00	PASS
11N20MIMO	Ant1	2412	17.61	17.61	≤30.00	21.11	≤36.00	PASS
	Ant2	2412	11.98	11.98	≤30.00	15.48	≤36.00	PASS
	total	2412	---	18.66	≤30.00	22.16	≤36.00	PASS
	Ant1	2437	17.28	17.28	≤30.00	20.78	≤36.00	PASS
	Ant2	2437	12.40	12.40	≤30.00	15.90	≤36.00	PASS
	total	2437	---	18.50	≤30.00	22.00	≤36.00	PASS
	Ant1	2462	17.26	17.26	≤30.00	20.76	≤36.00	PASS
	Ant2	2462	13.72	13.72	≤30.00	17.22	≤36.00	PASS
	total	2462	---	18.85	≤30.00	22.35	≤36.00	PASS

Remark：The results obtained include the antenna gain factor.

Directional gain = GANT + Array Gain=3.5 dBi+0 dBi =3.5 dBi；

Array Gain = 0 dB (i.e., no array gain) for NANT ≤4；（NANT=2）

9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01DTS Meas Guidancev05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

A) Set the RBW = 100KHz.
B) Set the VBW = 300KHz.
C) Sweep time = auto couple.
D) Detector function = peak.
E) Trace mode = max hold.
F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

Test plot as follows:

11B_Ant1_Low_2412

11B_Ant2_Low_2412

11B_Ant1_High_2462

11B_Ant2_High_2462



11G_Ant1_Low_2412

11G_Ant2_Low_2412

11G_Ant1_High_2462



11G_Ant2_High_2462

11N20MIMO_Ant1_Low_2412

11N20MIMO_Ant2_Low_2412

11N20MIMO_Ant1_High_2462



11N20MIMO_Ant2_High_2462

Test plot as follows:

11B_Ant1_2412_0~Reference

11B_Ant1_2412_30~1000



11B_Ant1_2412_1000~26500



11B_Ant2_2412_0~Reference

11B_Ant2_2412_30~1000



11B_Ant2_2412_1000~26500



11B_Ant1_2437_0~Reference

11B_Ant1_2437_30~1000



11B_Ant1_2437_1000~26500



11B_Ant2_2437_0~Reference

11B_Ant2_2437_30~1000



11B_Ant2_2437_1000~26500



11B_Ant1_2462_0~Reference

11B_Ant1_2462_30~1000



11B_Ant1_2462_1000~26500



11B_Ant2_2462_0~Reference

11B_Ant2_2462_30~1000



11B_Ant2_2462_1000~26500



11G_Ant1_2412_0~Reference

11G_Ant1_2412_30~1000



11G_Ant1_2412_1000~26500



11G_Ant2_2412_0~Reference

11G_Ant2_2412_30~1000



11G_Ant2_2412_1000~26500



11G_Ant1_2437_0~Reference

11G_Ant1_2437_30~1000



11G_Ant1_2437_1000~26500



11G_Ant2_2437_0~Reference

11G_Ant2_2437_30~1000



11G_Ant2_2437_1000~26500



11G_Ant1_2462_0~Reference

11G_Ant1_2462_30~1000



11G_Ant1_2462_1000~26500



11G_Ant2_2462_0~Reference

11G_Ant2_2462_30~1000



11G_Ant2_2462_1000~26500



11N20MIMO_Ant1_2412_0~Reference

11N20MIMO_Ant1_2412_30~1000



11N20MIMO_Ant1_2412_1000~26500



11N20MIMO_Ant2_2412_0~Reference

11N20MIMO_Ant2_2412_30~1000



11N20MIMO_Ant2_2412_1000~26500



11N20MIMO_Ant1_2437_0~Reference

11N20MIMO_Ant1_2437_30~1000



11N20MIMO_Ant1_2437_1000~26500



11N20MIMO_Ant2_2437_0~Reference

11N20MIMO_Ant2_2437_30~1000



11N20MIMO_Ant2_2437_1000~26500



11N20MIMO_Ant1_2462_0~Reference

11N20MIMO_Ant1_2462_30~1000



11N20MIMO_Ant1_2462_1000~26500



11N20MIMO_Ant2_2462_0~Reference

11N20MIMO_Ant2_2462_30~1000



11N20MIMO_Ant2_2462_1000~26500


Keysight Spectrum Analyzer - Swept SA
Center Freq 13.750000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 20 dB
#Avg Type: RMS
Avg|Hold: 10/10
Ref Offset 10.61 dB
10 dB/div Ref 20.00 dBm
Log
Mkr2 26.006 15 GHz
-48.846 dBm
Start 1.00 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 26.50 GHz
Sweep 2.438 s (30001 pts)
1 N 1 f 2.462 85 GHz -5.260 dBm
2 N 1 f 26.006 15 GHz -48.846 dBm
Frequency
Auto Tune
Center Freq
13.750000000 GHz
Start Freq
1.000000000 GHz
Stop Freq
26.500000000 GHz
CF Step
2.550000000 GHz
Auto Man
Freq Offset
0 Hz
Scale Type
Log Lin

10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi. A transmitter can only be sold or operated with antennas with which it was approved.	
EUT Antenna:	
The antenna is FPC Antenna, the best case gain of the antenna is 3.5dBi, reference to the appendix II for details	

11. TEST SETUP PHOTO

Reference to the appendix I for details.

12. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

※※※※※ END OF REPORT ※※※※※