



**CFR 47 FCC PART 15 SUBPART C,
ISED RSS-247 ISSUE 3 (DSS)**

TEST REPORT

For

Robotic Lawn Mower

MODEL NUMBER: Thor

REPORT NUMBER: E04A25081337F00102

ISSUE DATE: October 30, 2025

FCC ID: 2A3NS-THOR

IC: 33682-THOR

Prepared for

Sveaverken Svea Agri AB

Högmossevägen 11, SE-641 39, Katrineholm, Sweden

Prepared by

Guangdong Global Testing Technology Co., Ltd.

**Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park,
Dongguan city, Guangdong, People's Republic of China, 523808**

This report is based on a single evaluation of the submitted sample(s) of the above mentioned product, it does not imply an assessment of the production of the products.

This report shall not be reproduced, except in full, without the written approval of Guangdong Global Testing Technology Co., Ltd.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	October 30, 2025	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
Conducted Output Power	FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024	FCC Part 15.247 (b)(3) RSS-247 Clause 5.4 (d)	Pass
20 dB Bandwidth and 99% Occupied Bandwidth	FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024	FCC Part 15.247 (a)(2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
Carrier Hopping Channel Separation	FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
Number of Hopping Frequency	FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024	FCC Part 15.247(d) RSS-247 Clause 5.5	Pass
Time of Occupancy (Dwell Time)	FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024	FCC Part 15.247 (d) FCC Part 15.205/15.209 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
Conducted Bandedge and Spurious Emission	FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024	None; for reporting purposes only.	Pass
Radiated Band edge and Spurious Emission	FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
Duty Cycle	FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024	FCC Part 15.207 RSS-GEN Clause 8.8	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C, ISED RSS-247 ISSUE 3 (DSS)> when <Accuracy Method> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY.....	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
5. EQUIPMENT UNDER TEST	8
5.1. <i>DESCRIPTION OF EUT</i>	<i>8</i>
5.2. <i>CHANNEL LIST</i>	<i>8</i>
5.3. <i>MAXIMUM EIRP</i>	<i>9</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>9</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	<i>10</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>10</i>
5.7. <i>EUT ACCESSORY</i>	<i>10</i>
5.8. <i>SUPPORT UNITS FOR SYSTEM TEST.....</i>	<i>11</i>
5.9. <i>SETUP DIAGRAM</i>	<i>11</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	12
7. ANTENNA PORT TEST RESULTS	14
7.1. <i>Conducted Output Power.....</i>	<i>14</i>
7.2. <i>20 dB Bandwidth and 99% Occupied Bandwidth.....</i>	<i>15</i>
7.3. <i>Carrier Hopping Channel Separation</i>	<i>16</i>
7.4. <i>Number of Hopping Frequency</i>	<i>18</i>
7.5. <i>Time of Occupancy (Dwell Time)</i>	<i>19</i>
7.6. <i>Conducted Bandedge and Spurious Emission</i>	<i>21</i>
7.7. <i>Duty Cycle</i>	<i>23</i>
8. RADIATED TEST RESULTS.....	24
8.1. <i>Radiated Band edge and Spurious Emission</i>	<i>31</i>
9. ANTENNA REQUIREMENT	43
10. AC POWER LINE CONDUCTED EMISSION	45
11. TEST DATA - Appendix A.....	48

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Sveaverken Svea Agri AB
Address: Högmossevägen 11, SE-641 39, Katrineholm, Sweden

Manufacturer Information

Company Name: FJ Dynamics Technology (Fujian) Co., Ltd.
Address: Room 305, Unit 5, Huajian Building, No. 12, 16, and 18, East Keji Road, Shangjie Town, Minhou County, Fuzhou City, Fujian Province, China

EUT Information

Product Description: Robotic Lawn Mower
Model: Thor
Series Model: /
Brand: Sveaverken
Sample Received Date: September 02, 2025
Sample Status: Normal
Sample ID: A25081337 001
Date of Tested: September 02, 2025 to October 30, 2025

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C, ISED RSS-247 ISSUE 3 (DSS)	Pass

Prepared By:

Win Huang

Win Huang
Project Engineer

Checked By:

Alan He

Alan He
Laboratory Leader

Approved By:

Shawn Wen

Shawn Wen
Laboratory Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C, ISED RSS-247 ISSUE 3 (DSS)

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 6947.01) Guangdong Global Testing Technology Co., Ltd. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1343) Guangdong Global Testing Technology Co., Ltd. has been recognized to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification rules ISED (Company No.: 30714) Guangdong Global Testing Technology Co., Ltd. has been registered and fully described in a report filed with ISED. The Company Number is 30714 and the test lab Conformity Assessment Body Identifier (CABID) is CN0148.
---------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Items	k	Uncertainty
DTS Bandwidth	1.96	±9.2 PPM
20dB Emission Bandwidth	1.96	±9.2 PPM
Carrier Frequency Separation	1.96	±9.2 PPM
Time of Occupancy	1.96	±0.57%
Conducted Output Power	1.96	±1.5 dB
Power Spectral Density Level	1.96	±1.9 dB
Conducted Spurious Emission	1.96	9 kHz-30 MHz: ± 0.95 dB 30 MHz-1 GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.8 dB 12.75 GHz-26.5 GHz: ± 2.1dB
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.		

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports (AMN)	150 kHz ~ 30 MHz	2	3.37
Radiated emissions	9 kHz ~ 30 MHz	2	4.16
Radiated emissions	30 MHz ~ 1 GHz	2	3.79
Radiated emissions	1 GHz ~ 18 GHz	2	5.62
Radiated emissions	18 GHz ~ 40 GHz	2	5.54
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.			

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name		Robotic Lawn Mower
Model		Thor
Series Model		/
Model Difference		/
Hardware Version		V1.0
Software Version		V1.0
Ratings		Max 58.8V 20ADC
Power Supply	AC	120V 60Hz
	DC	58.8V
	Battery	58.8 VDC, 40A, 2048Wh

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth 5.3
Bluetooth Mode:	Bluetooth BR + EDR
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Type of Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of Channels:	79
Channel Separation:	1 MHz
Maximum Peak Power:	7.51 dBm
Antenna Type:	Integral Antenna
Antenna Gain:	5.2 dBi
Normal Test Voltage:	58.8 Vdc
EUT Test software:	SecureCRT
Note:	The Antenna Gain was provided by customer, and this information may affect the validity of the results, customer should be responsible for this.

5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470

09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	/	/

5.3. MAXIMUM EIRP

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)	Maximum EIRP (dBm)
GFSK	2402 ~ 2480	0-78[79]	6.16	11.36
$\pi/4$ -DQPSK	2402 ~ 2480	0-78[79]	6.95	12.15
8DPSK	2402 ~ 2480	0-78[79]	7.51	12.71

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK	CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402 MHz, 2441 MHz, 2480 MHz
$\pi/4$ -DQPSK	CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402 MHz, 2441 MHz, 2480 MHz
8DPSK	CH 0(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402 MHz, 2441 MHz, 2480 MHz

Note: The hop is hopping mode.

PACKET TYPE CONFIGURATION

Test Mode	Packet Type	Setting (Packet Length)
GFSK	DH1	27
	DH3	183
	DH5	339
$\pi/4$ -DQPSK	2-DH1	54
	2-DH3	367
	2-DH5	679
8DPSK	3-DH1	83
	3-DH3	552
	3-DH5	1021

5.5. THE WORSE CASE POWER SETTING PARAMETER

WORST-CASE CONFIGURATIONS

Bluetooth Mode	Modulation Technology	Modulation Type	Data Rate (Mbps)
BR	FHSS	GFSK	1Mbit/s
EDR	FHSS	$\pi/4$ -DQPSK	2Mbit/s
EDR	FHSS	8DPSK	3Mbit/s

Note: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		SecureCRT		
Modulation Type	Transmit Antenna Number	Test Software setting value		
		CH 00	CH 39	CH 78
GFSK	1	Default	Default	Default
$\pi/4$ -DQPSK	1	Default	Default	Default
8DPSK	1	Default	Default	Default

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	Integral	5.2

Test Mode	Transmit and Receive Mode	Description
GFSK	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
$\pi/4$ -DQPSK	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
8DPSK	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

5.7. EUT ACCESSORY

Adapter	
Model No.:	H80-UP1500C588200-14S
Input:	110-245V AC
Output:	Max 58.8V 20ADC
AC Cable:	1.48 Meter, Shielded without ferrite

DC Cable:	2.50 Meter, Shielded without ferrite
-----------	--------------------------------------

5.8. SUPPORT UNITS FOR SYSTEM TEST

The following support units or accessories were used to form a representative test configuration during the tests.


Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Laptop	Lenovo	Thinkpad T14	PF-3EAKYR	GTG Support
E-2	Serial port board	N/A	N/A	N/A	GTG Support

The following cables were used to form a representative test configuration during the tests.

Item	Type of cable	Shielded Type	Ferrite Core	Length
C-1	DC cable	Unshielded	without ferrite	1.5 m
C-2	USB cable	Shielded	without ferrite	1.0 m
C-3	Dupont thread	Shielded	without ferrite	0.5m

5.9. SETUP DIAGRAM

Radiated emissions & AC Power Line Conducted Emission:



6. MEASURING EQUIPMENT AND SOFTWARE USED

Test Equipment of Conducted RF					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40	102257	2025/08/25	2026/08/24
Spectrum Analyzer	KEYSIGHT	N9020A	MY51285127	2025/08/25	2026/08/24
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61253075	2025/08/25	2026/08/24
Vector Signal Generator	Rohde & Schwarz	SMM100A	101899	2025/08/25	2026/08/24
RF Control box	MWRF-test	MW100-RFCB	MW220926GTG	2025/08/25	2026/08/24
Wideband Radio Communication Tester	Rohde & Schwarz	CMW270	102792	2025/08/25	2026/08/24
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	103235	2025/08/25	2026/08/24
temperature humidity chamber	Espec	SH-241	SH-241-2014	2025/08/25	2026/08/24
RF Test Software	MWRF-test	MTS8310E (Ver. V2/0)	N/A	N/A	N/A

Test Equipment of Radiated emissions below 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2146	2025/08/23	2026/08/22
EMI Test Receiver	Rohde & Schwarz	ESCI3	101144	2025/08/23	2026/08/22
Pre-Amplifier	HzEMC	HPA-9K0130	HYPA21001	2025/08/23	2026/08/22
Biconilog Antenna	Schwarzbeck	VULB 9168	01315	2025/09/20	2028/09/19
Biconilog Antenna	ETS	3142E	00243651	2025/02/22	2028/02/21
Loop Antenna	ETS	6502	00243668	2025/02/22	2028/02/21
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE)	N/A	N/A	N/A

Test Equipment of Radiated emissions above 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2149	2025/08/23	2026/08/22
Spectrum Analyzer	Rohde & Schwarz	FSV40	101413	2025/08/23	2026/08/22
Pre-Amplifier	HzEMC	HPA-1G1850	HYPA21003	2025/08/23	2026/08/22
Horn antenna	ETS	3117	00246069	2025/02/22	2028/02/21
Pre-Amplifier	HzEMC	HPA-184057	HYPA21004	2025/08/23	2026/08/22
Horn antenna	ETS	3116C	00246265	2025/02/22	2028/02/21
RF Filter Bank	HzEMC	HSW-F18	HSWF2218E01	2025/08/23	2026/08/22

RF Filter Bank	HzEMC	HPF18	HPF2218E02	2025/08/23	2026/08/22
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE+)	N/A	N/A	N/A

Test Equipment of Conducted emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Shielded Room	CHENG YU	8m*5m*4m	N/A	2025/08/23	2026/08/22
EMI Test Receiver	Rohde & Schwarz	ESR3	102647	2025/08/23	2026/08/22
LISN/AMN	Rohde & Schwarz	ENV216	102843	2025/08/23	2026/08/22
NNLK 8129 RC	Schwarzbeck	NNLK 8129 RC	5046	2025/08/23	2026/08/22
Test Software	Farad	EZ-EMC (Ver. EMC-con-3A1 1+)	N/A	N/A	N/A

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER


LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor Power sensor and meter or Spectrum analyzer(video bandwidth is greater than the occupied bandwidth). Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	51%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.2. 20 DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1) RSS-247 Clause 5.1 (a)	20 dB Bandwidth	None; for reporting purposes only.	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	None; for reporting purposes only.	2400-2483.5

TEST PROCEDURE


Refer to FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024 clause 6.9.2.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 20 dB Bandwidth: 1 % to 5 % of the 20 dB bandwidth For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 20 dB Bandwidth: approximately 3×RBW For 99 % Occupied Bandwidth: ≥ 3×RBW
Span	Approximately 2 to 3 times the 20dB bandwidth
Trace	Max hold
Sweep	Auto couple

a) Use the occupied bandwidth function of the instrument, allow the trace to stabilize and report the measured 99 % occupied bandwidth and 20 dB Bandwidth.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	51%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.3. CARRIER HOPPING CHANNEL SEPARATION

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISSED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1) ISED RSS-247 Clause 5.1 (b)	Carrier Frequency Separation	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.	2400-2483.5

TEST PROCEDURE

Refer to FCC: ANSI C63.10-2020; ISSED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024 clause 7.8.2.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Span	wide enough to capture the peaks of two adjacent channels
Detector	Peak
RBW	Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
VBW	≥RBW
Trace	Max hold
Sweep time	Auto couple

Allow the trace to stabilize and use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	51%
-------------	--------	-------------------	-----

Atmosphere Pressure	101kPa		
---------------------	--------	--	--

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.4. NUMBER OF HOPPING FREQUENCY

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 3		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d)	Number of Hopping Frequency	at least 15 hopping channels

TEST PROCEDURE


Refer to FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024 clause 7.8.3.

Connect the EUT to the spectrum Analyzer and use the following settings:

Detector	Peak
RBW	To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW	≥RBW
Span	The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
Trace	Max hold
Sweep time	Auto couple

Set EUT to transmit maximum output power and switch on frequency hopping function. then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer, count the quantity of peaks to get the number of hopping channels.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	51%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.5. TIME OF OCCUPANCY (DWELL TIME)

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 3		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 5.1 (d)	Time of Occupancy (Dwell Time)	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed.

TEST PROCEDURE

Refer to FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024 clause 7.8.4.

Connect the EUT to the spectrum Analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1 MHz
VBW	≥RBW
Span	Zero span, centered on a hopping channel
Trace	Max hold
Sweep time	As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel

Use the marker-delta function to determine the transmit time per hop (Burst Width). If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.


For FHSS Mode (79 Channel):

Dwell Time: Pulse Time * Burst Count.

Note:

1. Pulse Time: The time of a single pulse.
2. Burst Count: The number of pulses observed during a 31.6s period.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	51%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.6. CONDUCTED BANDEDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247), Subpart C ISED RSS-247 ISSUE 3		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Spurious Emission	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024 clause 7.8.6 and 7.8.8.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span/RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	51%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.7. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.6°C	Relative Humidity	51%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in FCC: ANSI C63.10-2020; ISSED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in FCC: ANSI C63.10-2020; ISSED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.


X axis, Y axis, Z axis positions:




Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

TEST SETUP





TEST ENVIRONMENT

Temperature	22.2°C	Relative Humidity	51%
Atmosphere Pressure	101kPa		


TEST RESULTS

8.1. RADIATED BAND EDGE AND SPURIOUS EMISSION

Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)

All modes have been tested and the worst result as bellow:


Mode:	3-DH5 2402
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	95.960	51.76	-24.54	27.22	43.50	16.28	PK+	H
2	143.490	55.77	-23.01	32.76	43.50	10.74	PK+	H
3	191.990	54.64	-22.59	32.05	43.50	11.45	PK+	H
4	239.520	53.16	-19.26	33.90	46.00	12.10	PK+	H
5	323.910	51.24	-17.33	33.91	46.00	12.09	PK+	H
6	925.310	31.45	-2.43	29.02	46.00	16.98	PK+	H

Mode:	3-DH5 2402
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	95.960	57.10	-24.54	32.56	43.50	10.94	PK+	V
2	143.490	62.54	-23.01	39.53	43.50	3.97	PK+	V
3	156.100	57.12	-20.71	36.41	43.50	7.09	PK+	V
4	191.990	59.41	-22.59	36.82	43.50	6.68	PK+	V
5	468.440	42.89	-13.15	29.74	46.00	16.26	PK+	V
6	942.770	30.22	-2.18	28.04	46.00	17.96	PK+	V


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

All modes have been tested and the worst result as bellow:


Mode:	3-DH5 2402
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2142.000	54.26	-9.05	45.21	74.00	28.79	PK+	H
2	4803.000	60.41	-11.34	49.07	74.00	24.93	PK+	H
3	7206.000	57.46	-8	49.46	74.00	24.54	PK+	H
4	9609.000	52.39	-7.09	45.30	74.00	28.70	PK+	H
5	17676.000	46.81	0.31	47.12	74.00	26.88	PK+	H


Mode:	3-DH5 2402
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2142.000	54.36	-9.05	45.31	74.00	28.69	PK+	V
2	3372.000	59.06	-14.47	44.59	74.00	29.41	PK+	V
3	6078.000	50.51	-8.11	42.40	74.00	31.60	PK+	V
4	8811.000	50.31	-7.78	42.53	74.00	31.47	PK+	V
5	14541.000	47.55	-3.3	44.25	74.00	29.75	PK+	V
6	17706.000	46.43	0.05	46.48	74.00	27.52	PK+	V


Mode:	3-DH5 2441
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2142.000	55.97	-9.05	46.92	74.00	27.08	PK+	H
2	2696.000	53.02	-8.41	44.61	74.00	29.39	PK+	H
3	4881.000	62.04	-11.14	50.90	74.00	23.10	PK+	H
4	9586.500	50.10	-6.65	43.45	74.00	30.55	PK+	H
5	16257.000	46.96	-0.77	46.19	74.00	27.81	PK+	H
6	17688.000	46.29	0.25	46.54	74.00	27.46	PK+	H


Mode:	3-DH5 2441
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2142.000	56.69	-9.05	47.64	74.00	26.36	PK+	V
2	4882.500	53.66	-11.15	42.51	74.00	31.49	PK+	V
3	5959.500	51.06	-8.63	42.43	74.00	31.57	PK+	V
4	10518.000	48.35	-5.57	42.78	74.00	31.22	PK+	V
5	15367.500	47.62	-2.93	44.69	74.00	29.31	PK+	V
6	17683.500	46.27	0.27	46.54	74.00	27.46	PK+	V


Mode:	3-DH5 2480
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2146.000	56.39	-9.05	47.34	74.00	26.66	PK+	V
2	3385.500	59.22	-14.42	44.80	74.00	29.20	PK+	V
3	4960.500	56.80	-11.34	45.46	74.00	28.54	PK+	V
4	10752.000	47.92	-5.28	42.64	74.00	31.36	PK+	V
5	16690.500	45.58	-0.49	45.09	74.00	28.91	PK+	V
6	17701.500	45.96	0.14	46.10	74.00	27.90	PK+	V

Mode:	3-DH5 2480
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2142.000	54.04	-9.05	44.99	74.00	29.01	PK+	H
2	4959.000	60.67	-11.35	49.32	74.00	24.68	PK+	H
3	9156.000	49.93	-7.29	42.64	74.00	31.36	PK+	H
4	12603.000	47.66	-4.23	43.43	74.00	30.57	PK+	H
5	16696.500	45.55	-0.48	45.07	74.00	28.93	PK+	H
6	17689.500	46.39	0.24	46.63	74.00	27.37	PK+	H


Note:

1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
- For 9KHz to 30MHz and above 18 GHz, a pre-scan was performed, and the result was 20 dB lower than the limit line, the test data was not shown in the report.

Band Edge

All modes have been tested and the worst result as bellow:


Mode:	3-DH5 2402
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2373.180	21.07	22.59	43.66	74.00	30.34	PK+	V
2	2389.820	21.27	22.72	43.99	74.00	30.01	PK+	V


Mode:	3-DH5 2402
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2344.970	21.72	22.69	44.41	74.00	29.59	PK+	H
2	2390.080	20.55	22.72	43.27	74.00	30.73	PK+	H


Mode:	3-DH5 2480
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2483.360	20.40	23.15	43.55	74.00	30.45	PK+	H
2	2496.320	23.02	23.12	46.14	74.00	27.86	PK+	H

Mode:	3-DH5 2480
Power:	DC 58.8V
TE:	Big
Date	2025/09/18
T/A/P	22.2°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2483.500	19.80	23.15	42.95	74.00	31.05	PK+	V
2	2486.240	21.66	23.14	44.80	74.00	29.20	PK+	V

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Standard	Requirement
RSS-Gen issue 5 6.8.	The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list. For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below). When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested. For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location: This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

	Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.
--	---

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


TEST PROCEDURE

Refer to FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024 clause 6.2.

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver is used to test the emissions from the AC line. According to the requirements in Section 6.2 of FCC: ANSI C63.10-2020; ISED: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


Temperature	23.2°C	Relative Humidity	52%
Atmosphere Pressure	101kPa		

TEST RESULTS

Phase: L1

Mode: Charging

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1995	32.36	9.62	41.98	63.63	-21.65	QP
2	0.1995	27.41	9.62	37.03	53.63	-16.60	AVG
3	0.3345	24.09	9.65	33.74	59.34	-25.60	QP
4	0.3345	13.91	9.65	23.56	49.34	-25.78	AVG
5	1.0050	23.53	9.65	33.18	56.00	-22.82	QP
6	1.0050	13.12	9.65	22.77	46.00	-23.23	AVG
7	1.4730	26.66	9.70	36.36	56.00	-19.64	QP
8	1.4730	14.42	9.70	24.12	46.00	-21.88	AVG
9	1.9995	23.07	9.74	32.81	56.00	-23.19	QP
10	1.9995	9.00	9.74	18.74	46.00	-27.26	AVG
11	14.0861	40.68	10.24	50.92	60.00	-9.08	QP
12	14.0861	29.46	10.24	39.70	50.00	-10.30	AVG



Phase: N

Mode: Charging

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1995	30.88	9.67	40.55	63.63	-23.08	QP
2	0.1995	24.17	9.67	33.84	53.63	-19.79	AVG
3	0.3356	24.50	9.61	34.11	59.31	-25.20	QP
4	0.3356	17.08	9.61	26.69	49.31	-22.62	AVG
5	1.2620	25.18	9.68	34.86	56.00	-21.14	QP
6	1.2620	15.97	9.68	25.65	46.00	-20.35	AVG
7	1.4640	25.99	9.68	35.67	56.00	-20.33	QP
8	1.4640	13.82	9.68	23.50	46.00	-22.50	AVG
9	14.2126	41.09	10.23	51.32	60.00	-8.68	QP
10	14.2126	29.11	10.23	39.34	50.00	-10.66	AVG
11	24.5290	35.71	10.52	46.23	60.00	-13.77	QP
12	24.5290	24.28	10.52	34.80	50.00	-15.20	AVG

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.


11. TEST DATA - Appendix A


Maximum Conducted Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	E.I.R.P. Limit (dBm)	Verdict
NVNT	1-DH5	2402	Ant1	5.85	21	11.05	<=36.02	Pass
NVNT	1-DH5	2441	Ant1	6.01	21	11.21	<=36.02	Pass
NVNT	1-DH5	2480	Ant1	6.16	21	11.36	<=36.02	Pass
NVNT	2-DH5	2402	Ant1	5.91	21	11.11	<=36.02	Pass
NVNT	2-DH5	2441	Ant1	6.57	21	11.77	<=36.02	Pass
NVNT	2-DH5	2480	Ant1	6.95	21	12.15	<=36.02	Pass
NVNT	3-DH5	2402	Ant1	6.62	21	11.82	<=36.02	Pass
NVNT	3-DH5	2441	Ant1	7.19	21	12.39	<=36.02	Pass
NVNT	3-DH5	2480	Ant1	7.51	21	12.71	<=36.02	Pass


Note1: Antenna Gain: 5.2dBi;


Note2: E.I.R.P = Total Power + Antenna Gain













-20dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH5	2402	Ant1	1.04	N/A	N/A
NVNT	1-DH5	2441	Ant1	1	N/A	N/A
NVNT	1-DH5	2480	Ant1	1.01	N/A	N/A
NVNT	2-DH5	2402	Ant1	1.34	N/A	N/A
NVNT	2-DH5	2441	Ant1	1.34	N/A	N/A
NVNT	2-DH5	2480	Ant1	1.34	N/A	N/A
NVNT	3-DH5	2402	Ant1	1.3	N/A	N/A
NVNT	3-DH5	2441	Ant1	1.33	N/A	N/A
NVNT	3-DH5	2480	Ant1	1.29	N/A	N/A












Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH5	2402	Ant1	0.887
NVNT	1-DH5	2441	Ant1	0.893
NVNT	1-DH5	2480	Ant1	0.897
NVNT	2-DH5	2402	Ant1	1.211
NVNT	2-DH5	2441	Ant1	1.201
NVNT	2-DH5	2480	Ant1	1.211
NVNT	3-DH5	2402	Ant1	1.211
NVNT	3-DH5	2441	Ant1	1.206
NVNT	3-DH5	2480	Ant1	1.206









OBW NVNT 3-DH5 2441MHz Ant1

Keysight Spectrum Analyzer - Occupied BW

03:56:40 PM Sep 03, 2025

Center Freq 2.441000000 GHz

Center Freq: 2.441000000 GHz

Trig: Free Run

Avg|Hold: 100/100

Radio Std: None

#FGain:Low

#Atten: 30 dB

Radio Device: BTS

10 dB/div

Log

Ref Offset 0.78 dB

Ref 20.78 dBm

Mkr1 2.4411365 GHz

2.1680 dBm

1

Center 2.441 GHz

#Res BW 30 kHz

#VBW 91 kHz

Span 3 MHz

Sweep 3.333 ms

Occupied Bandwidth

1.2061 MHz

Total Power

10.8 dBm

Transmit Freq Error

-14.994 kHz

% of OBW Power

99.00 %

x dB Bandwidth

1.281 MHz

x dB

-20.00 dB

MSG

STATUS

Frequency

Center Freq

2.441000000 GHz

CF Step


300.000 kHz

Auto

Man


Freq Offset


0 Hz





Carrier Frequencies Separation


Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	Ant1	2402.146	2403.15	1.004	0.693	Pass
NVNT	1-DH5	Ant1	2441.142	2442.154	1.012	0.667	Pass
NVNT	1-DH5	Ant1	2479.14	2480.138	0.998	0.673	Pass
NVNT	2-DH5	Ant1	2402.006	2402.998	0.992	0.893	Pass
NVNT	2-DH5	Ant1	2440.998	2441.99	0.992	0.893	Pass
NVNT	2-DH5	Ant1	2478.986	2479.982	0.996	0.893	Pass
NVNT	3-DH5	Ant1	2402.146	2403.152	1.006	0.867	Pass
NVNT	3-DH5	Ant1	2441.142	2442.138	0.996	0.887	Pass
NVNT	3-DH5	Ant1	2479.138	2480.14	1.002	0.86	Pass













Number of Hopping Channel


Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH5	Ant1	79	15	Pass
NVNT	2-DH5	Ant1	79	15	Pass
NVNT	3-DH5	Ant1	79	15	Pass









Dwell Time


Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH5	2402	Ant1	2.886	349.206	121	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.886	352.092	122	31600	400	Pass
NVNT	1-DH5	2480	Ant1	2.887	334.892	116	31600	400	Pass
NVNT	2-DH5	2402	Ant1	2.889	283.122	98	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.888	323.456	112	31600	400	Pass
NVNT	2-DH5	2480	Ant1	2.888	300.352	104	31600	400	Pass
NVNT	3-DH5	2402	Ant1	2.889	297.567	103	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.89	367.03	127	31600	400	Pass
NVNT	3-DH5	2480	Ant1	2.891	329.574	114	31600	400	Pass



























Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	No-Hopping	-62.06	-20	Pass
NVNT	1-DH5	2480	Ant1	No-Hopping	-64.16	-20	Pass
NVNT	2-DH5	2402	Ant1	No-Hopping	-60.05	-20	Pass
NVNT	2-DH5	2480	Ant1	No-Hopping	-63.21	-20	Pass
NVNT	3-DH5	2402	Ant1	No-Hopping	-61.65	-20	Pass
NVNT	3-DH5	2480	Ant1	No-Hopping	-63.14	-20	Pass


















Band Edge(Hopping)


Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	Hopping	-60.97	-20	Pass
NVNT	1-DH5	2480	Ant1	Hopping	-59.44	-20	Pass
NVNT	2-DH5	2402	Ant1	Hopping	-59.87	-20	Pass
NVNT	2-DH5	2480	Ant1	Hopping	-59.83	-20	Pass
NVNT	3-DH5	2402	Ant1	Hopping	-55.34	-20	Pass
NVNT	3-DH5	2480	Ant1	Hopping	-60.98	-20	Pass

















Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH5	2402	Ant1	-48.35	-20	Pass
NVNT	1-DH5	2441	Ant1	-48.77	-20	Pass
NVNT	1-DH5	2480	Ant1	-47.62	-20	Pass
NVNT	2-DH5	2402	Ant1	-45.16	-20	Pass
NVNT	2-DH5	2441	Ant1	-46.08	-20	Pass
NVNT	2-DH5	2480	Ant1	-47.59	-20	Pass
NVNT	3-DH5	2402	Ant1	-46.23	-20	Pass
NVNT	3-DH5	2441	Ant1	-47.31	-20	Pass
NVNT	3-DH5	2480	Ant1	-47.67	-20	Pass























END OF REPORT